







2023 PRODUCT CATALOG



QUI	CK INDEX
3-57	Feed Systems

Poultry Nests & Egg Handling

75-102 Swine Steel Equipment & Flooring

103-108 Swine Feeders

109-119 Poultry Watering

120-124 Swine Watering

125-136 Plumbing

137-150 Medicators

151-164 Ventilation Controls

165-195 Ventilation Fans

196-231 Curtains and Inlets

232-259 Heating

260-272 Building Materials


273-286 Lighting & Electrical

287-298 Animal & Manure Handling

300-325 Supplies

GrowerSELECT®, Georgia Poultry Equipment Co.® are trademarks owned by Hog Slat Inc. Replacement parts listed with these marks are designed to fit and function in place of original equipment manufacturers replacement parts. Chore-Time® and Roxell® are the registered trademarks of CTB INC., a company not affiliated with Hog Slat Inc. AP®, Cumberland® & Hired Hand® are registered trademarks of The GSI Group, LLC, a company not affiliated with Hog Slat Inc. AcmeFan® is the registered trademark of Acme Engineering & Mfg. Corp. INC., a company not affiliated with Hog Slat Inc. Aerotech Ventilation Systems® is a registered trademark of Munter Corporation, a company not affiliated with Hog Slat Inc.





Model	Tube Dia (OD)	Capacity Lbs /Min	Motor Sizing/Hp	Max System Length	Max Extension Length
MODEL 55	2-1/4"	15	1/3	150′	185′
			1/2	250′	285′
MODEL 75	3"	50	1/2	80′	125′
			3/4	150′	185′
			1	200′	245′
MODEL 90	3-1/2"	100	1/2	30′	65'
			3/4	90′	125'
			1	150′	185′
MODEL HR	3-1/2"	50	1/2	30′	55′
			3/4	90′	105′
			1	150′	185′

1) Upper Boots

- Fits 16" bin openings. Available in three different material types.
- Clear polycarbonate, Translucent polyethylene or black polyethylene.
- Black double straight boot has a 14" diameter.

• Black double straight boot has a 14 diameter.			
Item #	Description	Chore-Time®	AP®
HS524	Clear 30°	4347C	FLX-2194C
HS793T	Translucent 30°	-	FLX-2194T
HS793	Black 30°	4347	FLX-2194
HS525	Clear straight	6093C	FLX-2195C
HS794T	Translucent straight	-	FLX-2195T
HS794	Black straight	-	FLX-2195
HS662	Black double boot	_	FLX-4869





Hardware Package

Includes:


18) $5/16" \times 3/4"$ zinc plated bolts, washers & nylon nuts.

#HS530Hardware pkg. upper boot

APFLX-2196

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov






2) Single Unloader Kits

⚠WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Quad Unloader w/ Anchor Bearings and Transfer Plate

#HS522KIT......Model 55

⚠WARNING:




A) Single Unloader with Anchor Bearings and Transfer Plate

#HS556KIT	Model 55
#HS520KIT	Model 75
#HS520PKIT	Model 75 (Pellet)
#HS557KIT	Model 90
#HS557HRKIT	Model HR
#HS554KIT	Model 108
#HS220SOKIT	Model 220
#HS300SOKIT	Model 300
#HS350SOKIT	Model 350

↑ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




C) Twin Unloader with Anchor Bearing, Transfer Plate & Baffles

#HS555KIT	Model 55
#HS521KIT	Model 75
#HS521PKIT	Model 75 (Pellet)
#HS558KIT	Model 90
#HS558HRKIT	Model HR
#HS220TOKIT	Model 220
#HS300TOKIT	Model 300
#HS350TOKIT	Model 350

MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



E) Twin Unloader with Anchor Bearing & Double Transfer Plate

#HS555KITDT	Model 55
#HS521KITDT	Model 75
#HS521PKIT	Model 75 (Pellet)
#HS558KITDT	Model 90
#HS558HRKITDT	Model HR
#HS220TOKITDT	Model 220
#HS300TOKITDT	Model 300
#HS350TOKITDT	Model 350

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




B) Single Tandem Unloader with Transfer Plate

#HS556TKIT	Model 55
#HS520TKIT	
#HS520PTKIT	
#HS557TKIT	Model 90
#HS557HRTKIT	Model HR
#HS220SOKIT	Model 220
#HS300STKIT	Model 300
#HS350STKIT	Model 350

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




D) Twin Tandem Unloader with Transfer Plate

#HS555TKIT	Model 55
#HS521TKIT	Model 75
#HS558TKIT	Model 90
#HS558HRTKIT	Model HR
#HS220TTKIT	Model 220
#HS300TTKIT	Model 300
#HS350TTKIT	Model 350

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



F) Twin Tandem Unloader with Double Transfer Plate

#HS555TKITDT	Model 55
#HS521TKITDT	Model 75
#HS558TKITDT	Model 90
#HS558HRTKITDT	Model HR
#HS220TTKITDT	Model 220
#HS300TTKITDT	Model 300
#HS350TTKITDT	Model 350

⚠WARNING:



Anchor Bearing Assembly

	•		
Item #	Description	Chore-Time®	AP ®
HSAB45UP	Feedline	6817	07098932
HSAB55C	Model 55	39405	FLX-4879
HSAB55	Model 55	-	FLX-4646
HSAB55CF	Model 55 - flag	39408	-
HSAB75C	Model 75	37346	FLX-4648C
HSAB300	Model 300	-	FLX-4648
HSAB350	Model 350	-	FLX-4650
HSAB75-OS	Model 300 (old style)	-	FLX-2227

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Item #	Description	Chore-Time®	$\mathbf{AP}^{\scriptscriptstyle{(\!\!R\!\!\!)}}$
HSAB75CP	M75 / pellet	-	_
HSAB75C-1	Replacement Hub Mdl 75	-	-
HSAB90U-1	Replacement Hub Mdl 90	-	-
HSAB90U	Model 90	35343	-
HSAB90U-HR	High Roughage (M90 Boot & M75 Auger)	-	FLX-4648HR
HSAB90S	Model 90 - Screener	35345	-
HSAB108	Model 108 - Unrestricted	35766	-
HSAB108E	Model 108 - Restricted	35767	-



WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Boot Body Weldments

Item #	Description	Chore-Time®	AP®
SINGLE			
HS220S	Single Model 220	-	FLX-4331
HS556A	Single Model 55	7999	-
HS556SS	Single Model 55 - SS	7999SS	-
HS300S	Single Model 300	-	FLX-4669
HS300S-SS	Single Model 300 - SS	-	-
HS520	Single Model 75	36588	-
HS520SS	Single Model 75 - SS	36588SS	-
HS350S	Single Model 350	-	FLX-2053
HS557	Single Model 90	8873	FLX-2053
HS554	Single Model 108	30386	-
TWIN	_		
HS220T	Twin Model 220	_	FLX-3938
HS555A	Twin Model 55	7998	-
HS300T	Twin Model 300	-	FLX-4761
HS300T-SS	Twin Model 300 - SS	_	-
HS300TB	Twin Model 300 w/ baffles	_	FLX-4761E
HS300TBSS	Twin Model 300 w/ baffles - SS	_	-
HS521	Twin Model 75	36350	-
HS350T	Twin Model 350	-	FLX-2116
HS558	Twin Model 90	36354	-
HS735	Twin Model 108	35617	-
QUAD			
HS522	Quad Model 55	7980	-

3) 10' Straight PVC Tube

Item #	Description	Chore-Time®	AP®
HSAT55-S	Model 55, 2-1/4" OD	7955	PVC-1004
HSAT75-S	Model 75, 3" OD	6516	PVC-1005
HSAT90-S	Model 90, 3-1/2" OD	6293	PVC-1006
HSAT108-S	Model 108, 4-1/2" OD	34547	-





4) PVC Tube Coupler

Item #	Description	Chore-Time®	AP®
HSAT55-C	Model 55	8029	FLX-2537
HSAT75-C	Model 75	7084	FLX-2538
HSAT90-C	Model 90	7085	FLX-2539
HSAT108-C	Model 108	34557	-
HSAT125-C	Model 125	-	FLX-2540

5) 45° PVC Elbows, 5' radius

Item #	Description	Chore-Time®	AP®
HSAT55-45	Model 55	34855	PVC-1101
HSAT75-45	Model 75	7285	PVC-1001
HSAT90-45	Model 90	7357	PVC-1002
HSAT108-45	Model 108	34546	_
HSAT125-45	Model 125	-	PVC-1003



6) Grow-Flex™ Auger



Our innovative manufacturing process forges a stronger, more durable auger with superior flexing and breaking strength that outperforms standard augers.

Item #	Description	Chore-Time®	AP®
HSFA-44	Model 44	6820	FLXA-14375
HSFA-44D	Model 44 drag auger	-	FLXA-1520
HSFA-55	Model 55	7961	FLXA-1520
HSFA-75	Model 75	4744	FLXA-2390
HSFA-75P	Model 75 (pellet)	-	FLXA-2206
HSFA-90	Model 90	6942	FLXA-2710
HSFA-108	Model 108	30108	-
HSFA-125	Model 125	-	HSFA-125



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



	4
#60665	1/4" x 3-1/2" galvanized
#606655	
#60673	
#606733	
#60678	#2/0 twin loop chain, zinc
#60399	

MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





9) Drop Adaptors

- 100% Feed Drop Out
- Secure hose clamp connections with overlapping seams to prevent water entry.
- Fits existing brands of feed tubes.


Item #	Description	Chore-Time®	AP®
HS655	M55/220	43455C	GAPCD-109
HS675	M75/300	43475C	AP-2276 &
HS690	M90/350	43490C	FLX-2433 FLX-2434




9) Plastic Wye Drop Adaptor

• 3" x 3" x 3"

#HS39187 Plastic wye drop adaptor





🗘 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov






3" Agitator Ball

Item #	Description	Chore-Time®	AP®
HS527	3" agitator ball	3531	00404238

⚠ WARNING:



10) Drop Tube

Drop tube part number combinations that make up the telescoping drops.

- A Drop Tube Adaptor
- B Top Tube
- C Bottom Tube
- D Clips

MODEL	A	В	С	D	SINGLE TUBE
55	HS655	HSDT005	HSDT003	60638	HSDT005
75	HS675	HSDT005	HSDT003	60638	HSDT005
90	HS690	HSDT001	HSDT006	60638	HSDT001
HR	HS690	HSDT001	HSDT006	60638	HSDT001
Control Unit		HSDT001	HSDT006	60638	HSDT001

Item #	Description	Chore-Time®	AP®
HSDT001	3.937" ID x 4.125" OD x 12'	-	AP-1766
HSDT002	3" ID x 3.188" OD x 12'	1932	FLX-2425
HSDT003	3.562" ID x 3.750" OD x 12'	6381	FLX-2427
HSDT004	3.937" ID x 4.125" OD x 6'	-	FLX-2428
HSDT005	3.313" ID x 3.5" OD x 6'	-	FLX-2426
HSDT006	4.187" ID x 4.375" OD x 12'	-	FLX-2429



13) Control Unit

Item #	Description	Chore-Time®	AP®
HS693	Complete w/ relay	-	FLX-4496
HS593	Control unit W/O relay	6560 & 24482	
HS591KIT	Power head drop cone	-	FLX-2017
HS589	Switch Assy. w/o Relay	30953	_
HS689	Switch Assy. w/ Relay	-	FLX-4512

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



11) Wire Pin

Item #	Description	Chore-Time®	AP®
60638	4" for attaching drop tubes	41657	FLX-4278

🚹 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



12) Direct Drive & Tube Anchor

Item #	Description	Chore-Time®	AP®
HS536	Model 55	24102-8	FLX-2699
HS531	Model 75	24102-2	FLX-2696
HS531P	Model 75 /pellet	-	FLX-5210
HS537	Model 90	24102-3	FLX-2697
HS540	Model HR	-	FLX-2737

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



14) Direct Drive Power Units, 256 RPM

Complete with motor, gear heads, pinion, 36" pigtail cord and 15 oz. bottle of gear oil. All units are 115/208-230 Volts.

	Item #	Description	Chore-Time®	AP®
		1/2 Hp Model 75 & 90	3259-50	FLX-2673
i	HS9022D8	3/4 Hp Model 75 & 90	3259-136	FLX-2674
:	HS9023D8	1 Hp Model 75 & 90	-	FLX-3629

15) Direct Drive Power Unit, 352 RPM

Item #	Description	Chore-Time®	AP®
HS9020D1	1/3 Hp Model 55	3259-34	FLX-2458
HS9021D1	1/2 Hp Model 55	3259-39	FLX-2459
HS9022D2	3/4 Hp Model 75 & 90	3259-52	FLX-2460
HS9023D2	1 Hp Model 75 & 90	3259-49	FLX-2461

♠ WARNING:



16) Extension Unloader Kits Single Unloader Kits w/ Anchor Bearings and Control Unit Adaptor

#HS556KITA	Model 55
#HS520KITA	Model 75
#HS557KITA	Model 90
#HS520PKITA	Model 75 Pellet
#HS220SOKITA	Model 220
#HS350SOKITA	Model 350

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Single Unloader w/ Anchor Bearings and Drop Adaptor 2.9"

#HS556KITB	Model 55
#HS520KITB	Model 75
#HS520PKITB	Model 75 Pellet
#HS220SOKITB	Model 220

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



STAINLESS STEEL Single Unloader Kit w/ Anchor Bearings & Galvanized Adaptor

Unloader weldment and access cover constructed of 16 gauge, 304 stainless steel. Adaptor and clamps are

#HS520SSKITA....Model 75, Control Unit Adaptor #HS520SSKITB...... Model 75, 2.9" Drop Adaptor

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Body Only Control Unit without **Electrical Box**

Use with extension unloader kits with control unit adaptor.



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Formulated to work with GrowerSELECT auger gear head unit to provide excellent lubrication properties. Oil contains extreme pressure (EP), anti-corrosion and anti-oxidation additives for prolonged gear life and smoother operation. 15 oz bottle. SAE 80W-90.

Item #	Description	Chore-Time®	AP®
HS450	Gear Head Oil	-	FLX-447



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Auger Gear Heads

Item #	Description	Chore-Time®	AP^{\otimes}	Big Dutchman®	Valco®
HSGR001	352 RPM, Mdl 55	3261-5	-	-	-
HSGR002	352 RPM, Mdl 75/90	3261-7	-	-	-
HSGR003	358 RPM, Poultry w/ clamp	-	0040408	-	-
HSGR004	358 RPM	-	FLX-4277	-	-
HSGR005	216 RPM	-	-	-	-
HSGR009	358/296 RPM at 60/50 Hz - 58	-	-	11-00-1005A	-
HSGR010	693/573 RPM at 60/50 Hz	3261-17	-	-	-
HSGR011	266/222 RPM at 60/50 Hz - 58	-	-	86-00-2667	-
HSGR012	266/222 RPM at 60/50 Hz	-	FLX-4403	-	-
HSGR014	441/364 RPM at 60/50 Hz - 78	-	FLX-4405	-	-
HSGR015	256/213 RPM at 60/50 Hz - 58	-	-	_	-
HSGR016	216/179 RPM at 60/50 Hz - 58	3261-1	-	-	-
HSGR017	156/130 PRM at 60/50 Hz - 78	-	_	-	-
HSGR021	62/52 RPM at 60/50 Hz- 78	3261-9	-	-	_
HSGR022	657/542 RPM At 60/50 Hz 3/4"	-	-	-	450369





⚠WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Pinion Gears

Item #	Description	Chore-Time®	AP®	Big Dutchman®	Valco*
HSP01	Straight pinion, 1/2" ID	-	FLX-4275	-	-
HSP02	Straight pinion, 5/8" ID	-	FLX-4276	11-00-9364	-
HSP03	Helical pinion, 1/2" ID	5046	_	-	-
HSP04	Helical pinion, 5/8" ID	6104	-	-	-
HSP05	Straight pinion, 1/2" ID	3249	-	-	-
HSP06	Straight, 1.812" long, 1/2" ID	-	FLX-2983	11-00-9151	-
HSP07	Straight, 14 tooth x 2.25" long, 5/8" II) –	FLX-2973	86-00-0205	-
HSP08	Straight, 14 tooth x 3" long, 5/8" ID	-	FLX-4542	-	-
HSP09	Straight 14 teeth 1/2" bore 2.170" long	r -	-	10-00-9613	450366



Transfer Plate and Slide Assembly

Item #	Description	Chore-Time®	AP®
HS523	Single transfer plate assembly	6284	BLK-11137
HS523SS	Stainless steel single assembly	-	-

MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





NOW AVAILABLE IN STAINLESS STEEL OR CLEAR PLASTIC

Access Cover for Boot Weldments

Flexible Drop Tube

Item #	Description	Chore-Time®	AP®
HS526	Galv. access cover	6197	FLX-4239
HS526C	Clear access cover	=	FLX-5127
HS526SS	Stainless steel cover	-	_

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



	-		
Item #	Description	Chore-Time®	AP®
HSFLX-2563F	3" ID, galv. (25' roll)	7497	FLX-2563
HSFLX-2564F	3-1/2" ID galy (25' roll)	6383	FI.X-2564

MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Extended Anchor Bearing

Eliminate problems with auger breaking and plugging when feeding out of the front bin of a tandem system. With the extended anchor bearing you can open the slide gate and remove restrictor baffles that cause bridging.

The standard anchor bearing features a restrictor tube to prevent the core of the auger from overfilling. The extended anchor simply extends the restrictor tube forward to the front bin.

Remove the existing anchor bearing on the back bin. Cut the 14' galvanized tube to length extending 2'' past the front unloader. Slip the cut tube inside the auger core and attach the new bearing to the rear bin unloader.



Double Transfer Plate Assembly

Item #	Description	Chore-Time®	AP®
HS541	Double transfer plate assembly	36683	FLX-4234
HS541SS	Stainless steel double assembly	-	-

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Slide Gate

Item #	Description	Chore-Time®	AP®
HS523-12	Single, 11.31" x 6.6"	4357	_
HS523SS-12	Single stainless steel	-	-
HS523-17	Double, 11.31" x 3.125"	_	-
HS523SS-17	Double stainless steel	-	-
HS523-25	Single, 11.91" x 6.1"	-	FLX-4782
HS451	Double, 11.25" x 3.25"	-	FLX-4320


⚠ WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Clear Flexible Drop Tube

#52776	3" ID, 3.35 OD flexible tube, clear
#52777	3-1/2 ID, flexible tube, clear
#527773	5" ID, 5.63 OD flexible tube, clear





With Extended Anchor





GrowerSELECTDirect Drive Auger Motors

Superior engineering makes GrowerSELECT $^{\mathbb{R}}$ the best replacement motor for any operation.

- Features stress-proof 1144 steel shaft to prevent breakage
- · Permanently lubricated ball bearings provide extended service
- · Shielded centrifugal starting switch protects against over spin conditions
- · Manual overload protection
- · Higher Service Factor
- 1725 RPM, 50/60 Hertz



HP: 1/3 Shaft Size: 1/2" F.L. Amps: 5.4/2.7-2.7 Volts: 115/208-230 Frame: 48Y



HS9021C

HP: 1/2 Shaft Size: 1/2" F.L. Amps 8.7/ 4.3-4.4 Volts: 115/208-230 Frame: 56Y





HS9022A

HP: 3/4 Shaft Size: 1/2" F.L. Amps 10.4/5.0-5.2 Volts: 115/208-230 Frame: 56Y



HS9023C

HP: 1 Shaft Size: 5/8" F.L. Amps 8.8/4.4-4.4 Volts: 115/208-230 Frame: 56HY



HS9024A

HP: 1-1/2 Shaft Size: 5/8" F.L. Amps 15.7/7.8-7.8 Volts: 115/208-230 Frame: 56HY

Replacement OEM Part Numbers*

Item #	AP/Cumberland®	Chore-Time®	Valco®
HS9020A	FLX-4763	4229	735390
HS9021C	FLX-4764	5050C	735391
HS9022A	FLX-4765	5051	736392
HS9023C	FLX-4766	6857	735393
HS9024A	FLX-2473	8782C	-



- · Totally Enclosed Fan Cooled
- · Class B Insulation
- · Manual Reset Thermal Overload Protector
- · ODE Shaft Extension for Hand Crank
- · Ball Bearings
- · Reversible Rotation
- · 1-Year Warranty



Shaft Size: 1/2" F.L. Amps: 5.9/2.6 Volts: 115/230 Frame: 56Y



N9021

HP: 1/2 Shaft Size: 1/2" F.L. Amps: 8.6/4.3 Volts: 115/230 Frame: 56Y



HP: 3/4 Shaft Size: 1/2" F.L. Amps: 10.6/5.3 Volts: 115/230 Frame: 56Y



HP: 1

Shaft Size: 5/8" F.L. Amps: 12.89/6.5-6.4 Volts: 115/208-230

Frame: 56Y



HP: 1-1/2 Shaft Size: 5/8" F.L. Amps: 16.2/8.1 Volts: 115/230 Frame: 56Y



Leeson Motors

- · Totally Enclosed Fan Cooled
- · Class B Insulation
- · Manual Reset Thermal Overload Protector
- · ODE Shaft Extension for Hand Crank
- · Ball Bearings
- · Reversible Rotation
- · 2 Year Warranty



HP: 1/3 Shaft Size: 1/2" F.L. Amps: 5.9/2.6 Volts: 115/230 Frame: 56Y



LE9022

Frame: 56Y

HP: 1/2 Shaft Size: 1/2" F.L. Amps: 8.6/4.3 Volts: 115/230



LE9023

HP: 3/4 Shaft Size: 1/2" F.L. Amps: 10.6/5.3 Volts: 115/230 Frame: 56Y




LE9024

HP: 1

Shaft Size: 5/8" F.L. Amps: 12.89/6.5-6.4 Volts: 115/208-230 Frame: 56Y







SAVE	
WHEN YOU	
BUY 500 OR	
MORE!	



Pan w/ shallow cone

HS8000-1 Pan w/ standard cone



HS8000-4 Support cone for standard fin



Support cone for extended fin

-	
	þ

HS8000





HS8000A







HS8000B







HS8000C







HS8000D







HS8000F







HS8000G







Classic Flood Pan Feeder Modei For Big Dutchman 45mm Smooth Pipe

#HS8000I.....8 spoke grill, standard fin, shallow pan, 2 piece, 45mm drop tube #HS8000M...... 14 spoke grill, standard fin, shallow pan, 2 piece, 45mm drop tube #HS80000 14 spoke grill, extended fin, shallow pan, 2 piece, 45mm drop tube

⚠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Support Cones for Big Dutchman 45mm Smooth Pipe

A) #HS8000-10......Removable Top B) #HS8000-9Support Cone


HS8000-5R Support cone w/ removable top	HS8000-6R Removable top	HS8000-3F Adjuster for extended fin	HS8000-3 Adjuster for standard fin	HS8000-8 8-spoke grill	HS8000-2 14-spoke grill
			√		√
			√	√	
		√			√
		√		√	
✓	√		✓		√
√	√	√			√
√	√	√		√	





G-Logic Control Pan

G-Logic Control Pan features a non-mechanical sensor to detect feed levels for increased reliability. Complete with a IO' pigtail cord, 18" cord protector, watertight connections and 8 spoke grill. 115/ 230 volt. Available as eight spoke grill only.


#HS8501 G-Logic Control Pan







Qty	Item#	Description
1	HS8500-16	Bracket Complete, Bottom - Eol Control
1	HS8500-12	Housing Complete, Main - Eol Unit
1	HS8500-24	Inlet, Complete – Eol Control
19	60930	Shw #10-24 X .375 Zp
1	HS8500-7	Assy - Paddle Shield - Eol Control
1	HS8500-14	Paddle, Eol Control
1	HS8500-15	Brkt, Retainer - Eol Control Paddle
1	HS8500-10	Brkt Complete, Control Module - Eol Control
2	5289024	Screw, 6-20 X .250 Pan Head Tapping
1	HS8500-31	Brkt Complete, Hopper Divider - Eol Control
1	HS8250-4	Assy- Control Housing
1	HS8500-19	Brkt, Drive End - Eol Control
1	HS8500-34	Cover Assy, Hopper - Eol Control
1	HS8500-18	Rear Shield, Hopper - Eol Control
1	HS8000-2	Grill, 14 Spoke Chicken Feeder
1	HS8000-3	Cone, Adjustment Chicken Feeder
4	60596	Washer, Lock, Helical, 1/4 Zp
4	60500	Hhc, 1/4-20 X .50 Lg Zp
1	1121010500	Nut, Hex, Nyloc #10-32 Unf
2	60911	Nut, Hex, #10-32, Zinc
1	HS8500-37	Cone, Support Modified - Eol Control
3	60925	Screw, 10-16 X .75 Hex Type B
1	WNY25-1	Wire Nut, Yellow - Csa Certified
	1 1 1 19 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 HS8500-16 1 HS8500-12 1 HS8500-24 19 60930 1 HS8500-7 1 HS8500-14 1 HS8500-15 1 HS8500-10 2 5289024 1 HS8500-31 1 HS8500-31 1 HS8500-19 1 HS8500-18 1 HS8500-18 1 HS8000-2 1 HS8000-3 4 60596 4 60500 1 1121010500 2 60911 1 HS8500-37 3 60925



HS8250 Mid-Line Control Pan

Key	Qty	Item#	Description
1	1	HS8250-6	Bracket Mounting Assembly
2	6	60930	Screw 10-24 X .375 Hex Head Washer Unslotted Zinc
3	1	HS8500-14	Paddle Control
4	1	HS8500-15	Control Paddle Bracket Retainer
5	2	5289024	Screw, 6-20 x .250
6	1	HS8250-4	Assembly, Control Housing
7	1	HS8000-2	Grill, 14 Spoke Chicken Feeder
8	1	HS8000-3	Cone Adjuster-Classic Flood Feeder
9	4	60596	Washer Lock 1/4"
10	4	60500	Bolt 1/4-20 X 1/2" Zinc
11	1	1121010500	Nut Nylok SS 10-32
12	2	60911	Nut, Hex, 10-32 Zinc
13	1	HS8250-13	Bracket Housing Assembly
14	1	HS8250-11	Bracket Shield Mount Assembly
15	1	HS8250-8	Bracket Flapper Assembly
16	1	HS8500-28	Paddle Shield
17	1	HS8500-27	Plate Retainer
18	2	609210	Screw 6-32 X 5/16" Zinc
19	2	60912	Nut Hex Machine Screw #6-32 Zinc
20	1	HS8250-10	Cover, Mount
21	2	10C175MUH2	Hex Head Unslotted 10-24 X 1-3/4" Zinc
22	4	10CNMAZ	Nut 10-24 Hex Zinc
23	1	HS8500-37	Cone Support EOL Control
24	3	60925	Screw 10-16 x .75 Hex Head Zinc





With heavy plastic construction to handle aggressive pullets, the Classic Flood feeder can be customized for any operation.

- \bullet Shallow pan for increased accessibly with raised ridges separating the bottom to maintain uniform feed distribution.

 • Flood window for increased feed availability for young chicks.
- Choose from optional features such as slide shutoff, restriction cone, and an anti-rotation device.

Optional Part # HS8000-24, Flood Lockout Collar also available for all models

#HS8000-24 Flood Lockout Collar



CLASSIC PULLET FEEDER PARTS MATRIX	HS8010A	HS8010B	HS8010C	HS8010D
Pan HS8000-		✓	√	√
Shutoff Si HS8000-	lide -17	✓		
Restrict HS8000-		✓		√
Cone Bott HS8000-		HS8000-19B	HS8000-19C	HS8000-19D
Cone To	op -20	✓	√	√
Adjuste HS-8000	er -21	✓	√	√
Anti-Rota HS8000-		✓	√	√
8-Spoke 0 HS8000-	Grill -14	✓	√	√





Choose from multiple options to customize your operation's rooster pans. Heavy duty injected molded plastic stands up to the most aggressive roosters.

- 4-spoke grill minimizes "hang-ups".
- Anti-Rotation Device to prevent swinging and keep pans steady.
- Raised ridge pan bottom maintains uniform feed distribution.
- Molded locking collar to prevent manipulation of feed level.
- Optional Restrictor Tube to further reduce amount of feed per pan.
- Optional pan shut off slide to allow selective feeding.

		·	•	3
CLASSIC ROOSTER				
FEEDER PARTS M.	ATRIX	HS8020B	HS8020C	HS8020D
	Pan HS8000-16	✓	✓	✓
	Shutoff Slide HS8000-17	✓		
*	Restrictor HS8000-18	✓		✓
	Cone Bottom HS8000-19*	HS8000-19B	HS8000-19C	HS8000-19D
	Cone Top HS8000-20	\checkmark	✓	✓
	Adjuster HS-8000-21	\checkmark	✓	✓
	Anti-Rotation HS8000-22	\checkmark	✓	✓
	Flood Lockout Collar HS8000-24	✓	✓	✓
	4-Spoke Grill HS8000-25	✓	✓	✓


Poultry Feed Systems



See page 48

For winches, pulleys, cable and rod winching components go to page 207

Ø



20 ga. galvanized feed hopper with Dual Point suspension. Can also be mounted with top single point suspension. Ships unassembled.

#HS569A-120	120 lb
#HS569A-200	200 lb
#HS456	Lid for 200 lb hopper
#UCECOX 200	200 lb

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- A) Electromechanical switch with adjustable arm to set feed levels.
- B) Proximity Hopper Switch eliminates problems with paddles and fabric diaphragms.
- C) Isolator switch serves as a master relay connecting up to four proxy or electromechanical hopper switches to the auger control unit.

#HS597	
#HS597-PROX	
#HS765	

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



3) Unloader Kits

Unloader kits for feed line hoppers, complete with cannonballs, anchor bearings, and hardware.

#HS532KIT	Single Unloader Kit
#HS533KIT	Double Unloader Kit

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



4) Feed Line Tube

Constructed of G90, rolled-formed galvanized steel, the GrowerSELECT® feedline tube is a standard 1.75" diameter. The seam features additional crimps per inch for additional strength and a deep 2" long wedged bell mouth.

#HSPFT175-409	1.75 4 On 9
#HSPFT175-410	1.75 4 On 10
#HSPFT175-809	1.75 8 On 9
#HSPFT175-810	1.75 8 On 10

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HSH022	Hanger Bracket
#HSH022-1	Strap only for HSH022
#HSH023	Hanger Bracket
#HS671	Rooster Hanger Bracket
#HS449	Scissor Hanger w/ S-hook

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GROW-FLEX

7) Grow-Flex™ Auger

Our innovative manufacturing process forges a stronger, more durable auger with superior flexing and breaking strength that outperforms standard augers.

#HSFA-44Flexible Auger 44mm

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



8) Intermediate Control Pan

Mid line control pan complete with 10' pigtail cord, 18" cord protector and 8 spoke grill. 115/230 volts with 20 amp micro switch, CSA Certified. Available as eight spoke grill only.

#HS8250......Intermediate Control Pan

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



9) Hanger Clamp for 1.75" Feed Pipe

#HSH024 Hanger Clamp

WARNING:



Rugged, trouble-free design utilizes a simple paddle switch to control feed lines. Complete with 10' piqtail cord, 18" cord protector, water tight connections and 8 spoke grill. 115/230 Volts with 20 amp micro switch. CSA Certified. Available as eight spoke grill only.

#HS8500 End Control Pan

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Complete with 115/230v motor, 352-rpm gear head, pinion, driver connection kit, gear oil and hardware. Includes 36" pigtail cord.

#HS9020D1-P	1/3	Нр
#HS9021D1-P	1/2	Ηр

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Direct Drive Auger Motors

These rugged, reliable motors have been designed from the "ground up" to meet the demanding duty cycle of feed motors.

#HS9020A	1/3 Hp Standard (CT,BD, GSI, Valco)
#HS9021C	1/2 Hp Standard (CT,BD, GSI, Valco)
#HS9025A	

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Light Kit

Light kit for any Classic Flood end control pan. Six powerful, long-lasting LED lights illuminate the control pan attracting birds. This leads to increased feed line run times, resulting in fuller pans. The light kit mounts under the control unit to reduce shading and shadows. Includes light plate and integrated wiring assembly.

#HS8500LA Light Kit



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Auger Gear Head

Quality cast aluminum housing with precision cut internal gears.

#HSGR001 352 RPM Gear Head

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Shocker Cable

1/16" 1x7 galvanized cable

#52260-500	500' roll
#52260-1000	1000' roll
#HS17016	Shocker Spring 5" long

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Cable & Rope

Adjusters

#HS532-15 Insulator Kit

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Auger Lock & Drive Kit

#HS538 Auger Lock and Drive Kit

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Cord Cleaner

The Cord Cleaner installs over existing pulleys to remove dirt and dust when the equipment is raised.

#ISCC-10......Cord Cleaner



#HSH076



#617315



#HSH018








#HSH019









#HSCA-3Heavy Duty Cord Adjuster **MARNING:**


#HSCA-1Plastic Cord Adjuster


#HSH018 3-1/2" - w/ lock

rowerselect Adult Turkey Feeder

▲WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Adult Turkey Feeders HST1000 - Standard Profile HST1000S - Low Profile

Key	Qty	Item#	Description
1	1	HST1000-1	Pan
2	1	HST1000-10	Adjustment Flue Support
3	3	HST1000-8	Feeder Shield Support Leg
ЗА	3	HST1000S-8	Feeder Shield Support Leg, Low Profile
4	1	HST1000-14	Swinging Support Leg
4A	1	HST1000S-14	Swinging Support Leg, Low Profile
5	1	HST1000-7	Feed Tube
5A	1	HST1000S-7	Feed Tube, Low Profile
6	1	HST1000-4	Drop Tube Top
7	1	HST1000-13	Shield
8	2	HST1000-9	Locking Bar
9	1	HST1000-16	Flue ring adjustment
10	4	13664-00200	Screw #10-24 x 3/8" Hex Slot Washer
			Zinc w/ Nylon Patch
11	4	6070900	Carriage Bolt 1/4-20 X 5/8" Zinc
12	4	60680	Lock Nut Hex Nylon Insert 1/4-20 Zn
13	1	HST1000-15	Centering Clip



HST1500 G-Logic End of Line Control Pan - Turkey


Key	Qty	Item#	Description
1	1	HST1500-24	Inlet, Complete, EOL Control, 2 In
2	1	HST1500-12	EOL Control Unit, Body
3	1	HST1500-38	U-Bracket, Control Unit
4	1	HST1500-34	Cover, Hopper, EOL Unit, Complete
5	1	HST1500-44	Cover Asy, Hopper - EOL Control
6	1	HS8500-19	Eol Control Unit, Brkt, Drive End
7	1	HST1500-5	Bracket, Control Box, EOL Control Unit - Complete
8	1	HST1500-8	Control Box Assy, G-Logic
9	1	HST1500-18	Rear Shield, Hopper - EOL Control
10	3	HST1000-8	Leg, Support, Feeder, Shield
11	1	HST1500-1	Eol Shield, Turkey Feeder
12	1	HST1000-14	Leg, Support, Swinging
13	1	HST1500-9	Support, Sensor, EOL Unit
14	1	HST1500-46	Tube, Assy, Drop
15	1	HST1000-16	Ring, Adjustment, Flue
16	1	HST1000-10	Support, Adjustment Flue
17	1	HST1000-1	Pan, Turkey Feeder



HST1100 Mechanical End of Line Control Pan - Turkey

Key	Qty	Item#	Description
1	1	HST1100-2	Tube, Assy, Drop-Mechanical
2	1	HST1100-3	EOL Shield, Turkey Feeder-Mechanical
3	1	HST1000-10	Support, Adjustment Flue
4	1	HST1000-1	Pan, Turkey Feeder
5	1	HST1000-16	Ring, Adjustment, Flue
6	3	HST1000-8	Leg, Support, Feeder Shield
7	1	HST1000-14	Leg, Support, Swinging
8	1	88023NMF	Conduit Flexible 1/2" X 100' Rolls Sold Per Foot
9	1	8802093	Elbow, Metallic, 1/2 Liquid Tight
10	1	8802092	Hub,Conduit,Liquid Tight, 1/2 Gray St
11	1	HST1100-5	Housing Complete, Main EOL Unit Mechanical
12	1	HST1100-10	Inlet, Complete-Mechanical EOL Control 2"
13	1	HS8500-7	Assy- Paddle Shield - EOL Control
14	1	HST1100-15	Paddle, EOL Control
15	1	HS8500-15	Brkt, Retainer - EOL Control Paddle
16	1	HS8500-10	Brkt Complete, Control Module - EOL Control
17	1	HS8500-31	Brkt Complete, Hopper Divider - EOL Control
18	1	HS8250-4	Assy-Hopper Level Control
19	1	HS8500-19	Brkt, Drive End - Eol Control
20	1	HST1100-12	Cover Asy, Hopper EOL Control Mechanical
21	1	HST1100-9	Rear Shield, Hopper EOL Control Mechanical
22	1	HST1100-7	Brkt Complete, Bottom-EOL Control-Mechanical

Turkey Feed Systems



1) Feed Line **Hoppers**

20 ga. galvanized feed hopper with Dual Point suspension. Can also be mounted with top single point suspension. Ships unassembled



#HS569A-200	200 1	b
#HS569A-300	300 1	b

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

2) Hopper Level **Control Switch**

Fully enclosed "normally closed" switch eliminates shock hazard. Switch features adjustable arm to set feed depth and removable feed shield to adapt to different applications. Prewired "Normally Closed" 110/220 Volt, 20 Amps max.

#HS597..... Hopper Level Control Switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





3) Unloader Kits

#HST1610KIT Single Unloader Kit #HST 1600KIT Twin Unloader Kit

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



4) Turkey Tube

#HSPFT200-110	2",	1	on	10'	(80"	spacing)
#HSPFT200-210	2",	2	on	10'	(60"	spacing)
#HSPFT200-210L	2",	2	on	10'	(80"	spacing)
#HSPFT200-310	2",	3	on	10'	(40"	spacing)

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



5) Winch Kit

#HST1733 winch for feed level adjustment

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



6) Grow-Flex™ Auger

Our innovative manufacturing process forges a stronger, more durable auger with superior flexing and breaking strength that outperforms standard augers.

#HSFA-44Flexible Auger 44mm

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Complete with 115/230v motor, 352-rpm gear head, pinion, driver connection kit, gear oil and hardware.

#HS9020D1-P.....1/3 Hp

#HS9021D1-P.....1/2 Hp

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



7) Feed Line Clamp

#HST500 2" Feed line clamp

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Boot Weldments

#HST1610Single Boot Weldment #HST1600......Double Boot Weldment

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



8) End Control Pan

#HST1500 Proximity switch model #HST1100 Mechanical switch model

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HST1734

Insulator Kit & Feed Line

9) Drive Units

Includes 36" pigtail cord.

#HST1001

Hanger

#HST1734Insulator Kit, Turkey #HST1001 Feed Line Hanger

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Anchor Bearing

#HSTAB45.....Turkey Anchor Bearing

♠ WARNING:

Growerselect

The Sow Drop's molded UV stable polypropylene body resists damage from sunlight and cold temperatures. Available in large 12 pound capacity or 8 pound model with integrated card clip.





Positive open/close shut off slide on top. Adjustable feed slide features fade-resistance, stamped lettering versus surface printed symbols.



The GrowerSELECT Sow Drop utilizes a longlasting, stainless steel cable instead of a nylon cord to control the shut off ball. Cable runs through replaceable wear grommets.

The open-top design allows installation of the unit directly on feed lines. Features large side access plug.

weight. Lifter cable can be replaced without disassembling the ball.

Constructed of high

density plastic,

the one-piece

shut off ball does

not require filler

#HSSD55......Model 55/Model 236, 12 lb #HSSD75......Model 75, 12 lb #HSSD90......Model 90, 12 lb #HSSD558 Model 55/Model 236, 8 lb

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Center drop design hangs straight under the feed pipe. Molded from UV stable polypropylene to prevent damage from sunlight and cold temperatures.



#HSSD55C	55mm,	8 lb
#HSSD60C	60mm,	8 lb



Positive open/close shutoff lever.



Open-top design permits installation directly on feed pipe. Features large access plug.



Adjustable dial controls feed settings from 1 to 8 pounds.



Nylon wheel to prevent excess wear on lifter cord with weighted ball for positive feed shutoff.

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



12 pound capacity control drop for all models with Proxy Plus sensor, 220 Volt.

#HSSD-CUSow Drop Control Unit

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HS76000......Complete drop assembly - 2"

#HS76001 ... Complete drop assembly - 3", blue collar #76000-2..... Replacement collar - 2"

#HS76000-3 Replacement collar - 3"



- · Operates up to 30 feed drops.
- · Includes hardware
- (3) 1 3/4" split red fiberglass pulleys
- (1) 1/8" glavanized cable clamp
- (2) 2 1/2" x 3/8" lag bolts
- (3) 3 1/2" x 5/16" screw hooks

#76003.....Trip lever



Center Drop Feeder with Control

8-pound capacity for all Center Drop models with Proxy Plus sensor, 220 volt.

#HSSD2-CU...... Center Drop Feeder w/Control

⚠WARNING:



Offering the most flexible range of feeding systems available.

Fewer Motors

In many layouts, a Grow-Disk system will only require two motors instead of four. All motors can be located by electrical service entrance, reducing wiring and electrical costs.

Flexible Pig Management

Since the system isn't controlled by a switch in the end feeder, pigs can be sorted out of any pen without affecting it's operation.

Flexible Feeding


Offering the capability to feed multiple farrowing rooms or rows of gestation stalls with a single system.



GET A

E-ZCLEAN

2) E-Z Clean **Corner Wheel**



- · Door flips open to remove feed buildups
- · Cast wheel with encapsulated bearings
- · Rugged reinforced polymer housing with sealed gaskets
- · Includes hanging kit

.....E-Z Clean complete

#HSCD505

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1) Fill System Unloader

Stainless steel construction with nominal 7.20" x 7.20" flanged opening. Includes clear feed tube couplers and four pipe clamps.

#HSCD304-4

.....Fill System Unloader

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



3) 44mm Grow-Disk™

Chain

Manufactured with harden chain to minimize stretch to reduce the need for adjustments. Grow-Disk chain features longer-lasting nylon disks instead of poly. Grow-Disk is multi-directional with disks spaced at 71.5mm intervals.

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




4) Galvanized **Tube**

Heavy, 18 ga. galvanized feed tube eliminates installation problems associated with PVC pipe systems. 20' long steel sections don't sag, reducing low spots in the system that cause premature wear on the disks. Tube has an OD of 2.375 inches.

#HSFT2375Galvanized Tube

🔔 WARNING:

GrowerSELECT - D-CD-HOESLAT



- · 304 Stainless steel construction
- Maximum effective length 1,800 feet
- 1-1/2 HP motor
- · Dual safety switches

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Control Unit

Simple Control Based on a Touch Screen Menu

- · Timed or continuous feeding
- · Manual or automatic operation
- · Controls fill auger, chain disk and feed drops
- · USB port for importing settings
- · Stores historical info for up to 60 days

#HSCD200 Control Unit



6) Chain Coupler

#HSCD600-C.....Chain Coupler

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



7) Tube Coupler

7-7/8" long with four bolts for a secure connection.

#HSCD-01Galvanized #HSCD-01SSStainless Steel

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



8) Drop Adaptor

Wear resistance nylon body with secure hose clamp connections.

#HS660S......Drop Adaptor

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



9) Proxy Switch Kit

Includes HS11 proxy switch, clear tube and mounting hardware.

#HSCD-900Proxy Switch Kit #HS11 Proxy switch only, 220v, no hardware

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



10) Drive Motor

#HS9032A 1-1/2 Hp, 208-230 V

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




HOR GLAST. **Chain Disk Soft**

Starter System

Recommended for use with chain systems over 1,000 ft. Reduces start up impact on system components by starting chain disk drive motor slower over a period of approximately 3 seconds.

#HSCD-100-SSChain Disk Soft Starter

⚠WARNING:




Chain Disk Corner Assembly

Key	Qty	Item#	Description
1	1	HSCD505-6	Bottom, Corner, Chain Disk
2	1	HSCD505-19	Top, Corner, Chain Disk
3	1	HSCD505-20	End, Clear, Corner, Chain Disk
4	2	HSCD505-11	Clamp, Tube-Chain Disk Corner
5	2	HSCD505-8	Gasket, Bottom-Left
6	12	HS724	Nut, 3/8-16 Hex Serrated Flange
7	2	HSCD505-9	Gasket, Bottom-Right
8	3	HSCD505-18	Retainer Clip
9	1	HSCD505-17	Rod, L-Shaped-Chain Disk Corner Hinge
10	2	605832	Washer, 1/2", Neoprene Bonded Seal 18-8 SS
11	10	605161	Bolt, Hex Cap, 3/8"-16 x 1 1/4" SS
12	2	6068015	Nut, Acorn-1/2"-13 SS
13	39"	HSCD505-24	Gasket, Chain Disk Corner
14	15"	HSCD505-25	Gasket, Access Door
15	1	HSCD505-30	Wheel, Chain Disk Corner
16	1	HSCD505-1	Shaft, Chain Disk Corner
17	2	HSCD505-23	Bearing, Chain Disk Corner
18	1	60686	Hex Bolt - 1/4-20 X 1 SS
19	1	0129150	Nut, Hex, Serrated 1/4"-20 SS
20	2	607092	Bolt, J, 3/8"-16 X 3-1/2" SS
21	2	60606	Nut, Hex, Finish 3/8"-16 SS
N/S	1	HSCD505-28	Kit, Hardware - HSCD505
22	1	HSLABEL-251	Label, Warning, Chain Disk Corner
23	1	HSLABEL-252	Label, Warning, Chain Disk Corner-Spanish

⚠ WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



HSCD401-SUB.ASY

Key	Qty	Item#	Description
1	1	HSCD401-3	Plate, Guide Pulley
2	1	HSCD401-9	Shaft, Idle Pulley
3	1	HSCD401-5-1	Pulley, Idle-Asy
4	3	605842	Washer, Flat 1.19" OD x 0.64" ID x 0.0585 THK SS
5	2	605523	Nut, Zinc 5/8" Jam-Chain Disk
6	4	1EMG3	Bushing, Chain Disk Carriage
7	4		60881 Cross Recessed Pan Head
			Machine Screw - Type I 8-32 x 3/4" SS
8	2	HSCD401-11	Spring, Tension
9	4	60883	Nut, 8-32, Nyloc-Ss

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



HSCD401 MOTOR-GEARBOX SUB

Key	Qty	Item#	Description
1	1	HSCD401-7	Weldment, Housing
2	1	HSCD-303	Plate, Mount
3	4	73834	Screw, 1/2"-13 X 1" Socket Button Cap SS
4	4	60616	Washer, Lock - Ss 1/2"
5	4	606061	Nut, Hex, 1/2-13 - SS
6	1	HSCD-301	Gearbox Transtecno 39.26:1 Nema 56C-14OTC
7	8	61914	Bolt, M8 X 1.25 x 14mm SS
8	1	HS9032A	Motor 1.5 Hp 1ph 60 Hz 208-230v
9	1	HSCD-311	Shaft, Output
10	1	HSCD313	Wheel, Drive, Cast-Assembly
11	2	HSCD-308	Washer, Op Shaft To Drive-Cd
12	3	61913	Bolt, M8 x 1.25 x 20mm SS
13	1	HSCD-306	Guard, Gearbox
14	1	HSLABEL-213	Label, Warning, Moving Parts-Eng./Spanish
15	1	HSCD-507	Key, 8mm x 10mm x 1.7in
16	2	HSCD-501	Key, 8mm x 10mm x 2.5in
17	1	HSCD-311-01	Spacer, HSCD-311 Rev A3 Shaft
18	2	60589	Washer, Lock 5/16 SS

GrowerSELECT

Infrared Feed Control

Control uses advanced infrared light technology to detect feed levels and the control feed system. Intuitive multicolor function display shows controller status at a glance. Functions include max run time monitoring, FEED NOW to bypass feed delay, continuous run, and timed disable mode. Includes relays for direct connection to the auger motor and alarm output.



#HS820	Infrared Feed Control
#HS820-4	Clear protective cover

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

GrowerSELECT

Hopper Level Control Switch

Fully enclosed switch eliminates shock hazard. Switch features adjustable arm to set feed depth and removable feed shield to adapt to different applications. Prewired "Normally Closed" 110/220 Volt, 20 Amps max.

#HS597	Hopper Level Control Switch
#EL1052M	Replacement Micro Switch
#HS597-4	Replacement Blue Cloth Switch Cover

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

GrowerSELECT

Hopper Level Proximity Control Switch

This hopper level control switch utilizes a proxy switch to eliminate problems with paddles and fabric diaphragms. Easy height adjustment to control feed level. Designed to work with HS765 Multi-Hopper Isolation Switch. The HS597-PROX is a low current device (220mA max) and can only be used to operate a relay or other low current loads



#HS597-PROX	Hopper Level Prox Control Switch
#EL1213	Replacement Proximity Switch for HS597-PROX

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

GrowerSELECT

Feed Level Control

Controls feed motor to regulate the feed level in hoppers and feeders. Circuit is normally closed (motor runs) when there is no feed present against the paddle. The circuit is open (motor stops) when feed is against the paddle. The single pole, double throw switch is rated at 20 amps or approximately 1 HP.



#HS529	Inside Mount Hopper Control Level
#EL1052M	Replacement Micro Switch
	Replacement Blue Cloth Switch Cover

<u>^</u> WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

GrowerSELECT

Multi-Hopper Isolator Switch

The HS765 Multi-Hopper Switch Isolator allows for the connection of up to four hopper level switches to one location providing a single Normally Closed (N/C) output. The output can be connected to an auger control unit to control the operation of the auger motor. The four hopper level switches are isolated so that



electromechanical or two wire proximity switches can be used in any combination. With the HS765, any of the four switches can call for feed causing the auger motor to power on. Relay Output Contact Rating: 1-1/2 HP @ 220-240VAC 50/60 Hz.

#HS765......Multi-Hopper Isolator Switch

🚹 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECT

Delay Relay Kit

Prevents auger motor from "short cycling" & causing premature motor failure.

#HS598 Switch w/ internal relay, adjusts from 1-100 sec #HS617Switch w/o internal relay, adjusts from 1-1000 sec

<u> (</u> WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

GrowerSELECT

Proximity Drop Tube Control

An updated drop tube control featuring a proximity for increased reliability. Assembly includes a 16" long molded plastic housing with non-adjustable proxy switch. Complete with watertight control box and 36" pigtail cord. 110/220 volt, 20 amp, rated for 1-1/2 motor.



🔔 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Max Run Timer

Help prevent a spill by controlling your maximum motor run times.

#GE100-A1047AP Maximum run

⚠ WARNING:

HaloJrMax

The HaloJrMax accurately detects feed flow with infrared light beams to control new or existing feed systems. This compact model features Max Run and Delay Start Timers with the electronics sealed in a plastic enclosure.



Specifications:

Universal Power Supply: 85-300 VAC Motor Contact: 20 Amp dry contact/1.5HP Max Alarm Contact: 1 Amp dry contact Dimensions: 9.7" H x 7.3" W x 6.7" D Inlet: 3.5" ID Outlet: 3.5" ID or 4" OD

#HALOJRMAX......w/ Delay/Max Run #HALOJRMAXA.....w/ Delay/Max Run/Alarm



SmartIR & IR Plus

The SmartIR Feed System Sensor utilizes infrared sensing technology to detect the level of feed and control all functions of a Flex-Flo feed delivery system. SmartIR requires no sensitivity adjustment and is not affected by changes in temperature, humidity or feed type. This sensor adapts to most new and existing flexible auger feed systems.

#GFLX-4951	SmartIR feed sensor, 230V
#HSAP-4738	
#GFLY-5262	IR Plus Feed Sensor



SMARTflex Flex-flo Control Unit from AP incorporates all of the timers, switches and sensors required to efficiently and effectively operate your feed delivery


and the timers, switches and sensors required to efficiently and effectively operate your feed delivery system in one compact pre-wired unit. A Retrofit Kit is available to update your existing AP Flex-Flo or other flexible auger feed delivery system to a SMARTflex.

#GAP-2984	Sensor for SMARTflex
#GFLX-4799	SmartFlex top board
#GFI.X-4801	SmartFlex hottom hoard



Hired Hand Hopper Switch

No longer do you have to contend with mechanical switches. SENS-0-MATIC, Hired-Hand's Electronic Feed Hopper Switch, eliminates the problems that have always been associated with hopper switches. No more replacing mechanical switches. No more adjusting hopper switches. No more dry hoppers!



A) #C14550...... Chore-Time Level Control
B) #HS589CR Replaces Chore-Time #8789
C) #HS529-7 Replacement Diaphragm only

D) #HS582 Replacement Diaphragm Assembly

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Simple, effective hanging switch to control feed levels in feedline hoppers.

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#GAP-0990......110V or 220V #GFLX-3489......Micro switch assy. (red plastic)



Flat Proxy

Replacement sensor for G-Logic Control Pan.

- 20-240V
- · Normally Closed
- 30-sec delay
- Fixed sensitivity

#EL1230Flat Proxy



30mm Proxv

Replacement for chain disk feed systems and Turkey Control Pan.

- 20-250 VAC/ DC
- No time delay
- Switchable between Normally Open (NO)
- to Normally Closed (NC)
- 6' cord

#HS11Blue Prox



Proximity Sensor Mounting Kit

Constructed of of corrosive resistant plastic, this component kit securely mounts proximity switches to plastic tubes and hoppers. Does not include mounting screws or proximity switch.

#HS10-2Proximity Sensor Mounting Kit



Proxy Plus

- · Isolated wiring provides superior circuit protection
- · Can be used with any voltage
- The best replacement proximity switch on the market!
- Push-button control eliminates screw drivers!

#HS10Proxy Plus



Proxy Classic

• Replaces Chore-Time® OEM Part #34255.

#HS09.....Proxy Classic



FEED BINS Bulk Feed Solutions


Capacity based on 40 lbs./Cubic Feet (641 Kg./Cubic Meter)

- The heaviest grade of feed bins available on the market today. Longer lasting feed bins built with 5-10% more steel, by weight, than competitive brands. Built entirely of high tensile Structural Steel Grade 55 with a G100 galvanized finish. G100 bins have a galvanized coating that is 10% thicker than competitor brands, resulting in a longer lifespan.
- Manufactured in-house for complete control of raw material purchasing and manufacturing operations. State-of-the-art rolling, stamping and finishing operations ensure precise fit and finish of feed bin components. Available in 6', 7', 9' and 12' diameter sizes.
- In many locations, a local store offers assembly and delivery to your farm or building project.

Item#	Rings	Tons	Metric Tons	Cubic Feet	Cubic Meters	Bushels	Fill Height (Ft./In.)	Fill Height (Meters)	Ladder Kit	Ladder/ Safety Cage Kit
6-FOOT BIN										
GST-616016K	1	3	2.7	150	4.2	120	11'6"	3.5	GST-LD616040	GST-LDSC616040
GST-626016K	2	4.5	4.1	225	6.4	180	14'2"	4.3	GST-LD626040	GST-LDSC626040
GST-636016K	3	6	5.4	300	8.5	240	16′10″	5.1	GST-LD636040	GST-LDSC636040
GST-646016K	4	7.5	6.8	375	10.6	300	19'6"	5.9	GST-LD646040	GST-LDSC646040
7-FOOT BIN										
GST-716716K	1	4.9	4.4	245	6.9	196	14'9"	4.5	GST-LD716740	GST-LDSC716740
GST-726716K	2	6.9	6.3	345	9.8	276	17′5″	5.3	GST-LD726740	GST-LDSC726740
GST-736716K	3	9	8.2	450	12.7	360	20′1″	6.1	GST-LD736740	GST-LDSC736740
GST-746716K	4	11	10	550	15.6	440	22′9″	6.9	GST-LD746740	GST-LDSC746740
GST-756716K	5	13	11.8	650	18.4	520	25'5"	7.7	GST-LD756740	GST-LDSC756740
GST-766716K	6	15	13.6	750	21.2	600	28'1"	8.3	GST-LD766740	GST-LDSC766740
9-FOOT BIN										
GST-916016K	1	8.5	7.7	425	12	340	15'7"	4.7	GST-LD916040	GST-LDSC916040
GST-926016K	2	12	10.9	600	17	480	18'3"	5.6	GST-LD926040	GST-LDSC926040
GST-936016K	3	15	13.6	750	21.2	600	20'11"	6.4	GST-LD936040	GST-LDSC936040
GST-946016K	4	18.5	16.8	925	26.2	740	23′7″	7.2	GST-LD946040	GST-LDSC946040
GST-956016K	5	22	20	1100	31.1	880	26′3″	8	GST-LD956040	GST-LDSC956040
GST-966016K	6	25.5	23.1	1278	36.2	1020	28'11"	8.8	GST-LD966040	GST-LDSC966040
GST-967016K	7	29	26.3	1450	41	1160	31′6″	9.6	GST-LD976040	GST-LDSC976040
12-FOOT BIN										
GST-1216016K	1	17.5	15.9	875	24.8	700	19'5"	5.9	GST-LD121040	GST-LDSC121040
GST-1226016K	2	23.5	21.3	1175	33.3	940	22′1″	6.7	GST-LD122040	GST-LDSC122040
GST-1236016K	3	29.5	26.8	1475	41.8	1180	24'9"	7.5	GST-LD123040	GST-LDSC123040
GST-1246016K	4	35.5	32.2	1775	50.3	1420	27′5″	8.4	GST-LD124040	GST-LDSC124040
GST-1256016K	5	41.5	37.6	2075	58.8	1660	30′1″	9.2	_	GST-LDSC125040
GST-1266016K	6	47.5	43.1	2375	67.3	1900	32'9"	10	-	GST-LDSC126040
									1111 O	иоппъи I 20

Feed Bins





G100 Galvanized Coating

Built entirely of high tensile Structural Steel Grade 55 with a G100 galvanized finish.



Poly Feed Bin Lid

Durable lid constructed of high-density polyethylene. Unique stainless steel locking spring holds the lid in place preventing rain and snow from entering. The lid opens on a stainless steel pivot rod and slides down the side of the bin protecting it from fill auger damage.



Weather Edge™

Improved Weather EdgeTM design, with its extended 1-1/4" leg directs water away from the bin's hopper and boot.



40 Degree Roof

Laser cut roof sheets are rolled for precise fit. 40 Degree angle slope allows for maximum filling capacity.





Precision Stamped Ladder

Precision stamped ladder assembly with adjustable standard brackets. Rounded trapezoid ladder rung provides secure footing with a larger surface area. Design exceeds OSHA standards.



Bottom Cone Sheets

Thicker and stronger bottom cone sheets resist dents and dings from mallets and hammers.



Stamped 16" Bin Collar

Reduces variation in dimensions compared to rolled or spun collars. Constructed of 10 gauge metal, as much as 4 gauges heavier than competitive brands.



Strong Base

10 & 12 gauge roll-formed legs provide a strong base.





Sliding design eliminates the accumulation of snow and rain when lid is open and prevents damage from feed truck augers.



Pivots on stainless steel rod with powerful spring to hold the lid shut in gusty weather. Safety mechanism locks in place for servicing. Locking tab will automatically disengage when the lid is actuated from the ground.



Installs on existing bins with a single bolt ring. Roller wheel slides lid down the roofline. Complete with ground control cable.









YouTube: EZ Slide Feed Bin **Transfer Plate Opener**



EZ Slide Opener For Feed Bin


Transfer Plates





Gate valve mounts to feed bin hopper cones providing access to

#GST-AC3001 Feed Bin Hopper Valve






BINTRAC **Bin Weighing System**

From a single bin to a multi-site system with remote monitoring, BinTrac can be configured to meet your needs now and in the future.

BinTrac Features:

- Easy installation on existing and loaded bins using patented load cell bracket assembly
- Real-time bin inventory by weight
- ≥ 24-hour feed use for each of the past 4 days
- Feed delivery validation
- One-year warranty covers lightning damage to load cells - 2-year extended warranty available
- Requires no calibration



Load Cell Assembly & Mounting Bracket

- For "W" style legs
- · Easily installs on existing & loaded bins
- The bracket is the lifting mechanism • Requires less than 1/2" bin lift
- · Simplifies equal loading
- No shimming or blocking
- · Field calibration is not required
- · Temperature compensated load cell

Item#	Description
MLB-200000	10K Load
MLB-300000	15K Load



Item#	Description
ASY-000127 ASY-000129	5K Load Cell 10k Load Cell
ASY-000159	15k Load Cell



Load Cell Tester

Item#	Description		
LCTO01 A	Load Cell Tester		

BinTrac Indicator

Indicator connects up to 4 bins and can be located up to 250 feet from bins.



Item#	Description
MCA-000001	w/standard pro software

BinTrac Indicator, Large Screen

Indicator connects up to 4 bins and can be located up to 250 feet from bins. Features large 0.56 inch digits for ease of viewing. New 6 digit display for bin applications exceeding 99,999 lbs.



Item#	Description
MCA-000301	Large Screen

BinTrac Breeder Control

With user programmable batching weight and scheduled batching.



Item#	Description
MCA-000201	w/ standard software

Digital Summing Box

Converts analog signal to digital for measuring and averaging load cell output.




Item#	Description
MSA-004000	4 load cell
MSA-006000	6 load cell
MSA-008000	8 load cell



PS17 Power Supply

Item#	Description
ASY-000237	1115/230VAC to 12.6 VDC



Item#	Description
CAB-000009	Interface Cable, 22AWG 4 Conductor Shielded/ft.
DS22204	Sensor wire 22/4 Shielded/ft.
DS21804-1000	Sensor wire 18/4 1000 ft. roll (for runs over 250')



Feed Level Indicator

Eliminate dangerous climbing up slippery, icy ladders to check feed levels in any weather. Installing Bin Flag indicators will let you know the levels in your bins at a glance from over 200 feet away. You can even set up your existing ALARM SYSTEM to notify you on your phone when low feed levels occur.

- · Install the Magnetic Sensor on Bin Flag
- · Connect to alarm system with inexpensive telephone wiring, NO NEED TO RUN A 120 VOLT LINE TO THE BIN.
- · Alarm dialer alerts you by phone when feed level drops below a critical level. You can even program the dialer to tell you which bin is low.

#HDL540 Bin Flag Feed Level Indicator #HDL59065-952 Magnetic Sensor for Bin Flag





Transfer plate T-Handle

Bolts to unloader slide plate to assist in opening and closing. Slots placed every 1-1/2" hold slide in place at the desired amount of opening. 13-1/4 inches long.

#HS1113T-Handle



Bin Anchors

5/8" diameter center pin anchor bolts used to secure feed bins to concrete pads. Each anchor bolt includes a serrated, flanged nut and will not require a washer.

Do not use 4" anchor bolt on concrete pads known or expected to be less than 6" in depth. Do not install new feed bins on concrete pads that are known or suspected to be less than 6" deep.

#60705 5/8" x 4" use on pads 6" thick #607051 5/8" x 6" use on pads 8" thick

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- Size #8
- 75 pound max load
- #HSBINCHN.....Sold per ft.

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Rubber Mallets

#59900	16 02
#M52651	32 oz
#95083	16oz W/Fiberglass Handle



#GBLK-13080 30 Degree Peak Ring & Hardware #GBLK-1310140 Degree Peak Ring & Hardware #GBLK-13102 BFT Without Peak Ring Retro for GSI Bins #GBLK-13216.....for Brock, Roxell, & Chore-Time without Peak Ring for Retro




- · Reduces bin bridging by redirecting feed flow away from the cone center.
- · Reduces feed particle separation and promotes even material feed out.
- · Heavy polyethylene agitator cone installs on the bottom collar of new or existing bins.

#FF 1000Feedfas Bin Agitator

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



JitterBall Anti-Bridge Agitator

- · Uses the motion of the auger to agitate the feed.
- · Designed to reduce feed bridging and sticking to the sides of the bin.
- · Helps feed flow freely and reduces separation.
- Simple installation: slides in through the service plate.
- · Stays upright and in one place.

#8070840000 JitterBall feed bin agitator

⚠WARNING:

Bin Stik

The lightweight aluminum telescoping pole and HDPE ball tip allows you to tap and rub the side of each feed bin from the ground to monitor feed content levels. The distinct noise difference between dead air space in the empty part of a bin, and the part of the bin with feed remaining inside quickly reveals internal bin content levels.







Rugged, heavyweight model for the most demanding use.

Extended Length: 11' 10" Storage Length: 6' 6" Dia: 1-1/4" Weight: 2.5 lbs.

#HS792.....Hog Slat Bin Stik

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bin Stik Jr.

Lighter weight. Longer Reach. Stores easily behind a pickup seat!

Extended Length: 15' 1" Storage Length: 3'8" Dia: 7/8" Weight: 1.4 lbs.

#HS818Hog Slat Bin Stik Jr.

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov







Bin Stik Pole Holder

Easy to use snap lock Bin Stik pole holder can be mounted to feed truck trailers, feed bin legs, barn walls or any other location that secure, easy to access storage for your Bin Stik is needed. Use with Bin Stik only, will not hold Bin Stik Jr.

#HS816Hog Slat Bin Stik Pole Holder



4" and 6" Rigid Auger **Systems**

How to order...

1) Boots For 16" bin opening #HS52430° Clear #HS525 Straight Clear #H\$793......30" Black #HS793T30° Translucent #HS794.....Straight Black #HS794T Straight Translucent

Replacement V-Belts

#HSA38	.4-inch,	1/2"x	40'
#GK1308	6-inch.	5/8"x	46'

2) 15° Wedge Adapter

Add to change auger angle to 45° if desired

#HS441 Wedge Adapter 15°



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

3) Rigid Auger Unloader With stub shaft & bearing



	•	0	
#HS445KIT		get de la company de la co	4-inch
#HS444KIT			6-inch
#HS445		4-inch	unloader only
#HS444		6-inch	unloader only

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

6) Motor

Size motor for total auger length

4-inch

#GMF12E1 15' Max Length, 1/2 Hp, 5/8" shaft #5330014......20' Max Length, 3/4 Hp, 5/8" shaft #533002127' Max Length, 1 Hp, 5/8" shaft

6-inch

#5330014...... 11' Max Length, 3/4 Hp, 5/8" shaft #5330021 16' Max Length, 1 Hp, 5/8" shaft #N9034 18' Max Length, 1-1/2 Hp, 5/8" shaft #N903221' Max Length, 2 Hp, 7/8" shaft #N9031 27' Max Length, 3 Hp, 1-1/8" shaft

WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

9) Connecting **Band**

(connect auger tube)



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



4) Auger


Choose length and diameter (includes tube, auger, auger pulley, V-belt, connectors and hardware)

4-inch #GGBF41100......4" x 11 #GGBF415004" x 15" #GGBF42000......4" x 20'

6-inch **#GGBF6111A**......6" x 11 #GGBF6161A6" x 16" #GGBF6211A6" x 21'

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



4-inch	-11
#PAK2558	5/8" bore x 2.5" OD Pulley
PAK3058	5/8" bore x 3.0" OD Pulley

6-inch **#PBK2578**......7/8" bore x 2.5" OD Pulley

#PBK2878......7/8" bore x 2.8" OD Pulley **#PBK36-118** 1-1/8" bore x 3.5" OD Pulley **#PBK3058**......5/8" bore x 3.0" OD Pulley #GC2000249......1-1/8" bore x (2.6" A to 3.0" B) OD Double Groove Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

10) Support Clamps

Does not include cables or chain.



▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

5) Auger Extensions


4-inch	
#GCE45000	4" x 5' extension
#GCE41000	4" x 10' extension
#GCE42000	4" x 20' extension

6-inch	
#GCE65001	6" x 5' extension
#GCE61001	6" x 10' extension
#GCE61501	6" x 15' extension
#GCE62001	6" x 21' extension

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

8) Discharge Spout



4-incn	
#GGK2574	90° spout only
	90° spout w/ 2' flex tube
#GGK2578	45° spout
6 inch	

0-IIICII	
	90° spout only
#GGK3407	90° spout w/ 3' flex tube
#GGK7181	45° spout

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

11) Rigid Supports

Includes lower half band clamp & hardware (not shown).

#GGK1459......4" Auger **#GGK4540**6" Auger



Highcroft Co. Feed Carts

Heavy poly construction pneumatic wheels with semi-pneumatic casters



• 39-1/4" L x 18-1/4" W x 35" H (6 cu. ft.)

#109022......240 lb. feed cart

Model 610 Replacement Wheels

#06-1018.....Semi-Pneumatic fixed #06-1023.....Semi-Pneumatic 8" caster

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Model 800

• 44-1/4" L x 20-1/4" W x 37" H (8 cu. ft.)

Model 800 Replacement Wheels

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Model 9-50FF

• 53-1/2" L x 19-1/2" W x 34-1/2" H (9 cu. ft.)

• Large flat floor area to hold pigs or approx. 360 lbs.

Model 9-50FF Replacement Wheels

#09-1018.....Semi-Pneumatic fixed #08-1009....Semi-Pneumatic swivel

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Poly-Tuf® Feed Cart

- · Polyethylene Tub
- 11 bushel or 600 lbs.
- 44" L x 27" W x 35" H • 8 x 2.5" semi-pneumatic tires

• 6 x 2.5 semi-pheumancine

#RMP11-4WPoly-Tuf® Feed Cart

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- Durable plastic cart with sturdy metal frame
- 4-1/2 bushel capacity or 180 lbs.
- 18-1/2" W x 37" L

MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Feed Scoops

#9203 3 qt. galvanized, L 7" x W 7" x H 8-3/4" #9204 4 qt. galvanized, L 7" x W 7" x H 11-3/4" #9206 6 qt. galvanized, L 7" x W 7" x H 12-3/4" #150415 4 qt. plastic

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Check us out on Facebook and "Like" us!

https://www.facebook.com/HogSlatInc






Utility Cart

This narrow-profile cart maneuvers through alleys and around tight corners. Great for various chores, including hauling feed, moving pigs, or packing tools for a repair job.



- Plastic corrosion resistance tub
- Heavy galvanized frame
- Top slot with stop permits adding a plywood platform
- Capacity 4-1/2 bushels or 180 pounds
- 18" wide x 37" long x 35" high





#HS813-5......Axle MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Chore Cart Heavy Duty

The CHORE CART HD is built to last! All of the features that are important to the producer are addressed in the no-nonsense design.

This Extra Thick, Durable plastic tub has a huge capacity! The smooth texture and rounded design make it easy to scoop feed, easy to wash out and sanitize, and provide longevity beyond compare! It's also balanced to ride level when you grab it by the handles and balanced to take the load off your arms by putting it on the wheels.

- Durability
- Maneuverability
- Cleanability
- Capacity (Holds 6 Bushels or 240 lbs!)
- Function and Value!

#8320301100	
#8321000000	16" Wheel (blue and green cart)
	Frame for Cart (blue and green cart)
	4" Swivel Wheel (blue cart only)
#5Q51 <i>A</i>	6" Small Wheel Jareen cart only)

⚠ WARNING:





Chain Disk



Chain Disk Controls

#GAPCD-500	
#GAPCD-600	





Control Boards

#GAPCD-500B	Bottom board for GAPCD-500
#GAPCD-500B-S.	Bottom board for GAPCD-500-S
#GAPCD-600B	Bottom board for GAPCD-600
#GAPCD-500T	Top board for GAPCD-500
#GAPCD-500T-S	Top board for GAPCD-500-S
#GAPCD-600T	Top board for GAPCD-600



Relay

• for GAPCD-500 & GAPCD-600

#EL1153..... Relay, DP, 240V, 30A



Includes HS11 proxy switch, clear tube and mounting hardware.

#HSCD-900Proxy Switch Kit

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Kwik Attach Drop Kit

#GAPCD-109 Kwik Attach Drop Kit





#HSCD600-C

44mm Grow-Disk™ Chain

GrowerSELECT

#HSCD600 ... GrowerSELECT chain disk 160'/bag

#HSCD600-C...... GrowerSELECT Chain Coupler

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Proximity Sensor

Replacement proximity sensor for chain disk feed systems. Replacement part for AP® part number FLX-4256

- · Normally Open (N.O) 2-Wire AC/DC
- 20V-250V AC/DC
- 6.5' cable
- 15mm Dia.
- 3mm- 15mm sensing range

#EL1222Proximity Sensor




PVC Plastic Tube & Coupler

#HSAT60C-S	2.36" OD GrowerSELECT®
	Clear PVC tubing, 10'
#GAPCD-112	2.36" OD White PVC tubing, 10'
#GAPCD-105	Clear PVC coupler
#GAPCD-113	White PVC coupler



Power Units

:	#HSCD-307	Drive Unit Replacement with Spocket
	#HS9032A	
	#HSCD995	
	#GAPCD770S	
9		<u> </u>




WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Replacement Parts

#HS693Control Unit w/ Relay for Proximity Switches

	Assembly Hopper
2) #HS590-11	Access Gate
3) #9705090500	# 10-16 x 3/4" Hex Self Drilling Screw
4) #HS591	Drop Cone - Clarified Plastic
6) #60927	#10-16 x 1" Hex Washer Self Drilling Screw
7) #HS582	Diaphragm Assembly
8) #HS589-8	Switch Assembly Mount Plate
9) #6068014	#10-32 Hex Machine Nut
	Plunger Seal
11) #1121010500	#10-32 Nylon Lock Nut
•	Legend Plate, On/Off
15) #E11083	Toggle Switch Boot Cover
	Switch Actuator Pin
	Indicator Lamp, Red, 250V
	Switch Mount Bracket
	#6-32 x 1", Phillips Pan Head Machine Screw
	Insulating Film
21) #EL1052M	Snap Action 20A @ 250V
22) #609160	#6-20 x 3/8" Tapping Screw Type Bt
23) #HS589-4	Switch Assembly Component Mount Plate
	#10 x 3/8" Thread Forming - Grounding Screw
	#6-32 x 1" Phillips Pan Head Tapping Screw
	#6-32 Hex Machine Nut
	Switch Housing Cover
30) #60932	Shoulder Screw #10-16 x 1.375" Hex Washer Head
	#6-32 x 1/4" Screw
32) #9705090500	#10-16 x 3/4" Hex Washer Self Drilling Screw




GrowerSELECT

HS531 Direct Drive Kit M75

1) #HS531-2	Weldment Adapter
2) #HS531-5	Weldment Coupling
3) #HS531-8	Clamp Auger
4) #CLAMP325	Clamp U-Bolt 3.125" ZP
5) #91251A578	SHC Screw 5/16-18 x 1/2"
6) #91251A592	SHC Screw 5/16-18 x 2 1/4"
7) #60508	Bolt Hex 5/16-18 3/4" ZN
8) #605800	
9) #60571	Nut Hex 5/16-18 ZP STL

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECT

HS537 Direct Drive Kit M90

119991 Diffect 1	HOOOL DIECE DIIAG IZIF MOO	
1) #HS537-2		
2) #HS537-5	Weldment Coupling	
3) #HS531-8	Clamp Auger	
4) #CLAMP400	Clamp U-Bolt 4IN	
5) #91251A578	SHC Screw 5/16-18 x 1/2"	
6) #91251A592	SHC Screw 5/16-18 x 2-1/4"	
7) #60508	Bolt Hex 5/16-18 3/4" ZN	
8) #605800		

9) #60571......Nut Hex 5/16-18 ZP STL

Roxell Replacement Parts



Roxell Feed Line Motors

Item#	OEM#		Description
HS9025A	10105716, 1	0109148	1/2 Hp Feed Line
HS9026A	10203693,	13107081	3/4 Hp Fill System or Feed Line
HS9027A	13106810		1 Hp Fill System
Itom#	OEM#	Doggrintion	Pomoining Stock

Item# OEM# Description Remaining Stock AGL00102020 00102020 1/2 Hp Feed Line Power Unit 365 RPM

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hopper Switch

#AGL03102314..... Hopper switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#AGL13104567Level switch #AGL05100532Feed Switch Kit, Yellow

#V7-1V19E9 Switch Micro 2 Hp for Paddle Switch





ELO Anchor Weldment

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Shield for **Hopper Switch**



#AGL10105641......Black



#AGL10111441.....Anchor Bearing "New Style"

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Bearing

For Roxell M75 & M90 Anchor Bearing

#BRB6003-2RS Bearing Only Replacement

⚠ WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



AGL00103028 1) #HSH024..... Tube Clamp Ass'y Dia. 2) #AGL10107597 Reinforcement Hook 3) #HS849 Boot Body Weldment 4) #AGL20100442 Set Screw M8x16 5) AGL10107522 (Discontinued) Bearing Holder Half 6) #BRB6003-2RS Bearing 17x35x10 - 60 9) #AGL20100111Bolt M5x10 Din 933 11) #AGL10111441 Anchor & Bearing Ass'y (New Style) 12) #AGL13106596 Decal - Hands Warning

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Roxell Double Intake Feedline Boot AGL00102053C

1) #AGL00102921	(Discontinued) Tube Clamp Ass'y Dia.
2) #AGL20101333	Seeger Ring 17x1 Din
	Bearing 17x35x10 - 60
4) #AGL10107522	Bearing Holder Half
5) #AGL10107639	Shaft F Weldment Dia 19. (+5')
6) #AGL10111441	Anchor & Bearing Ass'y (New Style)
7) #AGL00106518Dot	able Boot Weldment w/ Anchor Bearings
8) #AGL13106596	Decal - Hands Warning

<u>⚠</u> WARNING:

Feed Line Tube



GrowerSELECT

Feed Line Tube

Constructed of G90, rolled-formed galvanized steel, the GrowerSELECT® feed line tube is a standard 1.75" diameter. The seam features additional crimps per inch for additional strength and a deep, 2" long swedged bell mouth.

#HSPFT175-309#HSPFT175-409#HSPFT175-609SR#HSPFT175-610SR	Poultry feed tube 2 hole on 9' Poultry feed tube 3 hole on 9' Poultry feed tube 4 hole on 9' Poultry feed tube 6 hole on 9' (4 feeder & 2 starter) Poultry feed tube 6 hole on 10' (4 feeder & 2 starter) Poultry feed tube 8 hole on 9'
#HSPFT175-310#HSPFT175-410	Poultry feed tube 2 hole on 10' Poultry feed tube 3 hole on 10' Poultry feed tube 4 hole on 10' Poultry feed tube 6 hole on 10'
	Poultry feed tube 8 hole on 10'

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Cumberland

Width	Holes
9 ft.	4-hole
9 ft.	8-hole
12 ft.	5-hole
12 ft.	10-hole
12 ft.	3-hole
	9 ft. 9 ft. 12 ft. 12 ft.

Valco

Item#	Width	Holes
#V450910	10 ft.	4-hole
#V460102	10 ft.	2-hole

Big Dutchman

Item#	Width	Holes
#BD11-00-1921	9 ft.	4-hole
#BD11-00-1927	9 ft.	8-hole
#BD11-00-1938	9 ft.	2-hole
#BD11-00-1925	9 ft.	3-hole
#BD11-00-1911	10 ft.	4-hole
#BD11-00-1926	10 ft.	8-hole
#BD11-00-1914	10 ft.	2-hole
#BD11-00-1912	10 ft.	3-hole

Chore-Time/Roxell

Item#	Width	Holes
#RXA6854-4	10 ft.	4-hole



Cumberland i-plus3 Control Pan

The i-plus3 Control Pan senses and detects the level of feed in the control pan for proper and reliable operation. Infrared technology requires no moving parts or sensitivity adjustments.


#GC2000532	Hi-Lo i-plus3 End Control Pan, 220V, 1phase
#GC2000560	Hi-Lo i-plus3 Center House Control Pan, 220V, 1phase

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Cumberland HI-LO Pan


Features Include:

- · Collapsible bottom for easy chick entry to ensure great start.
- Unique center level section allows flood feed effect while eliminating overfilling and waste.
- · Fits on most standard feed tube for easy retro fit or new house applications.
- · Costs less than most alternatives.




HI-LO Pan Feeder 14 Spoke (1 & 2 Piece Options)

#G07098851.... Pan Complete, 1 Piece Drop Tube #G07100960.... Pan Complete, 2 Piece Drop Tube 1) #G07098856...... Hi-Lo Grill /14 Spoke 2) #G07100782Hi-Lo Drop Tube, 1 piece 3) #GC2000215... Hi-Lo Drop Tube Assembly 2 piece 4) #G07098854 Hi-Lo Feed Level 5) #G07098855 Hi-Lo Feed Level Stand 6) #G07098857Hi-Lo Pan



HI-LO VIII Pan Feeder 8 Spoke (1 & 2 Piece Options)


#G07101255..... Pan Complete, 1 Piece Drop Tube #G07101450..... Pan Complete, 2 Piece Drop Tube 1) #G07101254 Hi-Lo Grill /8 Spoke 2) #G07100782Hi-Lo Drop Tube, 1 Piece 3) #GC2000215......Hi-Lo Drop Tube Assembly 4) #G07098854 Hi-Lo Feed Level 5) #G07098855 Hi-Lo Feed Level Stand 6) #G07098857Hi-Lo Pan



#GC2000532 Hi-Lo i-Plus3 End Control Pan


Key	OEM#	Description
	G C2000532	Hi-Lo i-Plus3 End Control Pan (220V, 1 PH)
1	GC2000431	Housing Assembly, End Control (Prox, Plunger)
2	G C2000552	Control Pan Drop Tube
3	G 7101254	Hi-Lo Grill (8 Spoke)
4	G 7098857	Pan, Hi-Lo
5	G 7098855	Hi-Lo Feed Level Stand
6	G 7098854	Hi-Lo Feed Level
7	G C2000534	Sensor Assembly, i-Plus3
8	G C2000441	Overflow Bypass Funnel
9	G 7097341	Grilled Feeder Control Unit
10	G S-280	Screw, SDS #10-16 x 5/8" HWH ZN
11	G C2000535	End Control Box, i-Plus3
12	G S-1102	Hex Nut 1/4"-20 ZN Grade 2
13	G S-10209	Threaded Stud, 8"-32 x 2", Zinc Plated
14	G S-6551	Split Lock Washer #8 Med ZN
15	G S-6525	Hex Nut #8-32 ZN Grade 2
16	G FLX-2690	Gasket, 4" x 4" x 3/16" PVC Lid
17	G FLX-2689	Electrical Box Lid
18	G S-7377	Screw, MS #10-24 x 1" RHP ZN Grade
19	G S-849	Hex Nut #10-24 Grade 2
20	G DC-851	Decal, CE Electrical Hazard
21	G DC-889	Decal, Danger High Voltage
N/S	G 7098556	Shroud, for 16" Motor Cord
N/S	G 7098247	Drive Mount Hardware Package
N/S	G PNEG-1864	Instruction, Wiring Diagram, IR Sensor
N/S	G BX-116	Box, 14-1/4" X 14-1/4" x 11-7/8" 200 C, RSC for Pan Control Unit

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#GC2000560 Hi-Lo i-Plus3 Center House Control Pan


Key	OEM#	Description
	G C2000560	Hi-Lo i-Plus3 Center House Control Pan (220V, 1 PH)
1	G C2000526	Housing Assembly, Center Control (Prox, Plunger)
2	G C2000552	Control Pan Drop Tube
3	G 7101254	Hi-Lo Grill (8 Spoke)
4	G 7098857	Pan, Hi-Lo
5	G 7098855	Hi-Lo Feed Level Stand
6	G 7098854	Hi-Lo Feed Level
7	G C2000534	Sensor Assembly, i-Plus3
8	G C2000563	Center Control Box, i-Plus3
9	G S-1102	Hex Nut 1/4"-20 ZN Grade 2
10	G S-10209	Threaded Stud, 8"-32 x 2", Zinc Plated
11	G S-6551	Split Lock Washer #8 Med ZN
12	G S-6525	Hex Nut #8-32 ZN Grade 2
13	GFLX-4561	Gasket, Electrical Box 4" x 6"
14	GFLX-4560	Cover, Electrical Box Lid 4" x 6"
15	G S-7377	Screw, MS #10-24 x 1" RHP ZN Grade 2
16	G S-849	Hex Nut #10-24 Grade 2
17	G DC-851	Decal, CE Electrical Hazard
18	G DC-889	Decal, Danger High Voltage
N/S	G 7098556	Shroud, for 16" Motor Cord
N/S	G 7099545	Hi-Lo Center House Control Clamp Package
N/S	G PNEG-1864	Instruction, Wiring Diagram, IR Sensor
N/S	G BX-116	Box, 14-1/4" X 14-1/4" x 11-7/8" 200 C, RSC for Pan
		Control Unit



Cumberland HI-LO Center Control Pan with Micro Switch #G07101534

With Micro Switch #G0710155) '1
1) #GFLX-2689	Electrical Box Lid
2) #EL1052	Switch, 20 AMP Unimax
3) #GAP-2289	Switch Bracket
4) #GS-8298	Rivet, Solid - 1/8" x 1" Long
5) #GFH-1309	
6) #GFH-1310	
7) #G07100348	Cord 12" Long, 16/3 SJT
8) #G07101541	Electrical Box, Drilled
9) #EL1000	Toggle Switch, SPST 15A w/ on/off
10) #GAP-2329	Foam Gasket
11) #G52-0170	Spring
12) #G07101537	Body Assembly
13) #G07101535	Paddle Rest and Shield Assembly
14) #G07101350	Paddle
15) #G07101348	Paddle Clip
16) #G07101346	Retainer plate
17) #G07101347	Paddle Cover
18) #G07101536	Inner Plate Assembly
19) #GC2000552	Control Pan Drop Tube Assembly
20) #G07101539	Base Plate Assembly
21) #G07101538	Lid Assembly
22) #G07099376	Switch Guard
23) #GC2200010	Anti-Spin Bracket
24) #G07101254	Hi-Lo Grill / 8 spoke
25) #G07098854	Hi-Lo Feed Level
26) #G07098855	Hi-Lo Feed Level Stand
27) #G07098857	Hi-Lo Pan
N/S) #GS-4322	Pin Cotter 3/32x1 Zn Gr 2

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Cumberland HI-LO End Control Pan with Micro Switch #G07101482

	~ -
1) #G07097341	Anti-Roost Guard
2) #G07101493	Top Plate Assembly
3) #G07101489	Paddle Guard Plate Assy.
4) #G07101347	Paddle Cover
5) #G07101346	Retainer Plate
6) #G07101348	Paddle Clip
7) #G07101488	Slope Plate
8) #G07101350	Paddle
9) #G07091666	Anchor Plate
10) #G07101487	Mount Plate
11) #GAP-2329	Foam Gasket
12) #GFH-1310	
13) #G07100348	Cord 120" Long, 16/3 SJT
14) #G07100350	Cord 28" Long, 16/3 SJT
15) #EL1052	Switch, 20AMP Unimax
16) #GFLX-2690	Electrical Box Gasket
17) #GFLX-2689	Electrical Box Lid
18) #GAP-2289	Switch Bracket
19) #G07101490	Drilled Electrical Box
20) #G52-0170	Spring
21) #G07101485	Body Assembly
22) #G07100314	Inlet Tube Bracket Weldment
	Drive Mount Hardware pkg
	Bottom Plate
	Overflow Bypass Funnel (New Style)
25) #G07101491	Base Plate Assembly
26) #G07100353	
27) #G07098854	Hi-Lo Feed Level
	Hi-Lo Feed Level Stand
•	Hi-Lo Pan
•	Anti-Spin Bracket
	Hi-Lo Grill / 8 spoke
	Shroud for 16" Motor Cord
	Lock Nut, 1/2 Inch w/ Pipe Threads
A 100	



Cumberland Pro-1 Flood Pan

Culliberialia Pro-1 Proou Pali	
1) #G07101254	Hi-Lo Grill (8 Spoke)
2) #GC2000215	Two-Piece Drop Tube
3) #GC2000209	Drop Tube Extension
4) #GC2000212	Locking Collar
5) #GC2000210	Lower Drop Tube
6) #GC2000307	Clear Window Guard
7) #GC2000211	Feed Level Adjustor
8) #G07098857	



Grower SELECT Control Pan Light Kit

The GrowerSELECT® feed pan light encourages the birds to eat from the end control pan to increase feed line run times.



- Six powerful LED lights rated at 10,000-hour life
- Attaches directly to the pan; surrounds pan with a light
- · No heat build-up
- · Corrosion resistant
- 115 volt 1/2 Hp, 230 volt 1 Hp
- Easily retrofits to GrowerSELECT® or Chore-Time® control pans.

#HS8500LAEnd of Line Control Pan Light Kit

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- 120 or 220 Volts
- · IP65 waterproof

#ISP3W227K.....Life Lamp pan light



GC2000530 **Power Supply Only**

GC2000531 **Light & Cord Only**

Cumberland Control Pan LED Light

• Kit can be operated on 115VAC or 230VAC.

A) #GC2000531	Control Pan Light Assembly
B) #GC2000536	Light and Cord Only
C) #GC2000530	Power Supply






Once® AgriShift FL

The AgriShift Feeder Light is an easy-to-install system that mounts with an electrical junction box to most existing control pans.

- 3 Watt LED emitting poultry-specific wavelengths.
- 230 Volts
- Rated life of 50,000 hours

#OIFL-FSWR-DE Feeder Light Kit



Roxell System Feed Pans

A) Roxell Vitoo Pullet Feeder Upper Cone 1) #AGL00800540 Upper Cone 2) #AGL00800557 Adjuster Ring 3) #AGL00800086 Slide (Optional) 4) #AGL00800581 Anti-Swing Piece 5) #AGL00800565 Top Support

C) Roxell Kixoo Adjustable Breeder Feeder


#AGL00800001	Kixoo Feeder Complete
1) #AGL00800540	Upper Cone
2) #AGL00800524	Inside Grill
3) #AGL00800508	Outside Grill
4) #AGL00800573	Adjustment Knob
5) #AGL00800557	
6) #AGL00800581	Anti-Swing Piece
7) #AGL00800565	Top Support

B) Roxell Haikoo Broiler Feeder

#AGL00900282	
1) #AGL009000502) #AGL00900019	
3) #AGL009000684) #AGL00900035	
5) #AGL00900027	

D) Roxell Minimax Broiler Feeder

•	
1) #AGL00104281	Feeder Pan Minimax Line - Low
2) #AGL00101196	Feeder Pan Minimax Line - Classic
3) #AGL00101246	14 Strut Grill
4) #AGL00103135	10 Strut Grill
5) #AGL00101212	Support Cone Minimax Line
6) #AGL00101204	Short Adjuster Ring Minimax Line
7) #AGL00101220	Top Support Minimax Line
8) #AGL20101937	Square Neck Bolt M6X16
9) #AGL00600312	Anti-Swing Clamp
10) #AGL20104105	Flange Nut M6



Roxell Feedline End Control Unit #AGL00104901

1) #AGL20100681	Nut M4 - Din 934
2) #AGL20100566	
3) #AGL15000037	Handy Box Obo A8
4) #AGL13600598	Roxell Decal - 42x10
5) #AGL15001472	Cable Ring
6) #AGL10102978	Cable Ring Nut

7) #801 10100100	(1 Ot Ot Ot
7) #AGL10103109	
8) #AGL 10106870	
9) #AGL10105690	
10) #38563	
12) #AGL20100210	
13) #HS685	Tube Bracket Assy
14) #AGL10107209	
15) #11511019	
16) #AGL20103081	
17) #AGL20100806	
18) #AGL10107423	
19) #AGL10107183	
20) #AGL10107191	
21) #AGL20101713	Socket Cap Screw M6x10
22) #AGL10107381	
23) #AGL10107373	
24) #AGL20100756	
25) #AGL20100335	Wingnut M6 - Dub 315
26) #AGL10106847	
27) #AGL00102392	Agitator - Poultry
28) #AGL00101477	Feeder Pan - Max C
30) #AGL10107860	Anti Roost Guard
31) #AGL10107431	
32) #AGL20100400	Connecting Wire
33) #AGL10100782	
34) #AGL20100483	
35) #AGL20102307	
36) #AGL20104196	Sock. But. Hd Cap Scr. M8x1
37) #AGL05000013	
38) #AGL10107449	
39) #AGL10203156	

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Roxell Minimum Hopper Switch

This switch is used to keep your feed lines charged full of feed for more uniform feeding.

#AGL00205559Minimum Hopper Switch



Control Pan Switch Assembly

#AGL10105690	Switch Assembly
#AGL10105732	Switch Only
#AGL05100532	Feed Switch Kit, Yellow
#177 11710F0	Craritah Miana OIID for Doddla Craritah





#AGL00104901C.....End Control Pan #AGL00104919...... Intermediate Control Pan

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1) #C25052.....Support Cap 2) #C25053 Locking Insert 3) #C25280 Model C2 Grill 4) #C25283 Support Cone w/2 Piece Top






A) Model C2 Breakdown

5) #C34538	Support & Adjustment Cone	
6) #C30730	Adjustment Cone	
7) #C25281	Model C2 Feeder Pan	
B) Model C2 Pl	us Pan	
1) #HS8000-6R	Removable Top	
2) #HS8000-2	C2 Plus Grill	
3) #HS8000-3	Adjustment Cone	
4) #C41188	Packed Cones	
5) #C38602	Support Cone, Removable Top	
6) #HS8000-1	Feeder Pan	
C) Model C Breakdown		
1) #C25052	Support Cap	
2) #C25053	Locking Insert	

3) #V450261 Model C Grill 4) #C25051 Grill Support w/2 Piece Top 5) #C2508.....Feed Tube 6) #C8171Feed Ring 7) #G07097220.....Feeder Pan


Chore-Time Model C2® PLUS Standard End Control Unit: C40943 Model C2® PLUS Shallow End Control Unit: C42012


Woder 62° PLOS Shallow End Control Offic. 642012			
Key	#C40943	#C42012	Description
1	#C14434	#C14434	Control Body
2	#C41363	#C41363	Deflector Panel
3	#C25045	#C25045	Paddle Retainer
4	#HS8500-34	#HS8500-34	Control Cover Assy
6	#C5083-8	#C5083-8	1/4-20 1.5 Cap Screw
7	#HS536-1	#HS536-1	Driver Block
8	#HS8500-21	#C44794	Drive Tube Wldt
9	#HS8500-18	#HS8500-18	Bottom Cover
10	#C25495	#C25495	Control Cord Assy
11	#61646	#61646	1/2" Liquid Tight Conn
12	#C247O2	#C24702	Switch Box
13	#C46122	#C46122	Switch Bracket
14	#HS529-50	#HS529-50	Switch Insulation
15	#EL1052M	#EL1052M	Actuator Switch
16	#C23810	#C23810	1/2" Liquid Tight Conn
17	#C26982-1	#C26982-1	14" Flexible Conduit
18	#C26980	#C26980	Straight Liquid Tight Conn
19	#C43110	#C43110	Cut Sleeve
20	#HS8500-19	#HS8500-19	Anchor Plate
21	#C40947	#C37371	Center Support Assy
22	#HS8000-2	#HS8000-2	Feeder Grill
23	#C25318	#C25318	Mylar Assembly
24	#C41501	#C41500	Feeder Pan
25	#HS8000-3	#HS8000-3	Adjustment Cone
26	#HS529-48	#HS529-48	Switch Box Cover
27	#HS529-49	#HS529-49	Switch Box Gasket
29	#HS8500-24	#HS8500-24	Support Bracket
30	#HS529-46	#HS529-46	Plunger
31	#HS529-45	#HS529-45	Gasket
32	#C6972	#C6972	Paddle
33	#C6963	#C6963	#10-32 Lock Nut
34	#C46123	#C46123	Actuator Pin




Key	#C40943	#C42012	Description
35	#C25084	#C25084	Switch Box Mount
36	#C25433	#C25433	Stop Panel
37	#C40749	#C40749	Switch Bracket
NS	#C2798	#C2798	Anti-Roost Guard

⚠ WARNING:








- · Angled Cord
- Replaces Chore-Time® OEM # 56077









Cumberland HI-LO VIII Rooster Feeder #G07101562

#G07101562	Hi-Lo VIII Complete
	Anti-Rotation Clip for Hi-Lo
2) #G07101254	Hi-Lo Grill / 8 Spoke
3) #GC2000215	Hi-Lo Drop Tube, 2 pc Assy
4) #G07101604	Funnel Restrictor
5) #GC2000009	Hold Down Clip
6) #G07098854	Hi-Lo Feed Level
7) #G07098855	Hi-Lo Feed Level Stand
8) #G07101606	Hi-Lo Pan / Low Volume



Roxell Cockrel Feeder

1) #AGL00101204	Adjuster Ring
2) #AGL00400564	Pan Support
3) #AGL00101220	Top Support
4) #AGL00101212	Short Support Cone
5) #AGL00600320	Feeder Pan Fidimat
6) #AGL10401230	Support Lock (option)
7) #AGL20101937	Square Neck Bold M6x16
8) #AGL00600312	Anti Swinging Clamp
9) #AGL20104105	Flange Nut M6
10) #AGL00602037	Sledge
11) #AGL00602045	Short Support Cone w/Sledge



Cyclone 12" Pan Assembly

#BD86-00-2119	12" Pan Assy Complete
1) #BD11-03-1007	12" Pan
2) #BD86-00-2120	Grill Assembly
3) #BD11-14-1130	Cone/Feed Drop Combo
NS) #BD11-14-1150	Parts Bag
4) #BD11-AT-1460	Top Clamp Assy
5) #CY99-10-1068	.Hex Bolt, 1/4-20 x 1-1/4"
6) #CY99-20-1014	Weld Nut, 1/4-20





Clamp **Anti Swing Kit**

• Old style pan anti swing lock

#HS672.....Clamp Anti Swing Kit (2 Hose Clamps & Bar)

Plasson Male Feeder Pan

Plasson's male feeder pan was developed for males in breeder houses with separate feeding for males and females.



- · Small feed capacity
- · No restriction access • 7-9 males per pan
- No swinging panUniform feed distribution
- Plasson renown plastic quality
- Grill-less pan
- Improve mortality
- Eliminate male hangups
- · Increase potential fertility and hatchability



#DI2310570	Feeder Pan for Males Com
1) #DI2310122	Feeder Pan Body w/Level "O" Maroon
2) #DI2310092	Feeder Pan Regulator 0-5 Gray
3) #DI2310121	Feeder Pan Upper Locking Maroon
4) #DI2310125	High Cone for Males Pan Maroon
5) #DI2310895	Feeder Pan Anti-Rotation Bracket Set

Turbogrow Low Profile

Low profile model for use with pan feeders having lower working heights.

Measurements

Total height: 6.7" Pan diameter: 9.85" Total capacity: 9 lbs.

Recommend density: 1 Feeder per 50-100 chicks



#355900LP Turbogrow Low Profile

Turbogrow 2

Turbogrow 2 is a rectangular rounded chick feeder designed to be filled automatically for broiler and breeders from 1 to 15 days of age. Eight segmented distribution windows help in prevent feed wastage.

Measurements:

Height: 7.5" Weight: 1-1/3 lbs. Length: 11" **Total Capacity:**

Width: 6-1/4" 11 lbs

#355903INTurbogrow 2

Hi-Grow Feeder

HI-GROW is a rounded plastic chick feeder designed to feed baby chicks from 1 to up to 15 days of age. It has been shown to reduce feed wastage compared to using standard feed trays and provides a more sanitary feed source for chicks compared to basic trays.

Measurements:

Total Capacity:

Total Height: 7.5" 9.92 lbs.

Pan diameter: 11"

Recommended density:

Weight: 1 lb. 1 Feeder per 50-100 chicks.

#355900EHi-Grow Feeder

TurboMate

Unique design incorporates the feeder, drop and hanger into one simple-to-use product. Simply rotate unit 180° above feed pipe to store. Individual trough dividers limited feed wastage.

Measurements:

Height: 6"

Length: 13-3/4" Width: 6-1/4" Weight: 1 lb.

Total Capacity:

2.65 lbs

Recommended density:

1 Feeder per 75-100 chicks.



TurboMate II

Automatic bi-directional feeder that incorporates feeder and rotating hanger. Features double cone, open windows and trough dividers.

Measurements:

Length: 14" Width: 6.6"

Total Capacity:


Recommended density:

1 Feeder per 50-100 chicks.

#020202-034-US......Short, 1.77" throat #020202-035-US.....Long, 2.75" throat



Manufactured from high quality NYLON to prevent breakage. Sleeves are constructed of chemical resistant polypropylene. Installs easily on existing feed lines.



Note clearance between the cone sleeve and feed line. This clearance allows the drop tube to come to a complete right angle assuring complete feed shutoff. Drops will not loosen and fall down over time. When installing any chick starter be sure to install it so that the drop folds up towards the fan end of the house.

#HS577	Kwik Start Chick Feeder
1) #HS578L	Cone Sleeve w/ Lock
2) #HS577-325	
3) #HS577-600	6" Sleeve
•	

*Sleeves are excluded from GrowerSELECT 2 Year warranty.

Max Fill

- Swivels 360° to shut off feed flow
- · Fits both smooth and ribbed tubes
- · Short tube increases feed level in chick feeders

#8660-B-US......Chick Filler



TurboTwist Filler

Automates the filling of turbo grow feeders from feed line.

- · Plastic construction
- · Central position indicator
- · Extended fin to avoid finger injuries
- · Simple manual rotation

#SG-357000 TurboTwist Filler




Cord Locks

Labor saving storage method attaching TurboGrows to feedline with a cord.

#HSH107 plastic/each


Cumberland Adult Turkey Control Unit

Turkey control (71111
1) #G07097736	Turkey Pan
1) #G00404108	Intermediate Turkey Pan
1) #G07099174	Plastic Turkey Pan
2) #HST1000-10	Feed Level Ring Assy.
3) #HST1000-16	Feed Level Tube
	Turkey Control Pan Shield
6) #GS-7235	Pop Rivet 3/16" x 1/4"
7) #GC2000267-HR	DPivot Pan Support
8) #G07097831	Pan Support
9) #G00402600	Box Cover
	Electrical Box
	90 Deg. Connector
	Flex Cable
	Straight Connector
	Drop Tube Body Weldment
	Body Weldment Assy.
	Bottom Plate Assy.
	Anchor Plate
19) #G07097341	Anti-Roost Guard
20) #G07091678	Safety Closure Assy.
21) #G07091698	Cover Assy.
	Turkey Insulator Pkg.
	Switch Brkt. Assy.
24) #G07091670	Diaphragm Assy.
25) #G07091673	Spacer Plate
	Diaphragm Housing
	Paddle Guard
	Switch Cover
	Micro Switch
32) #GS-721410-	32 x 7/8" Pan HD Nylon M/S
33) #G07091699	Switch Bracket Assy.




	U Bolt #10-24 x1 3/8"
N/S) #GS-2010	# 10-24 NY Loc Nut
34) #G07097816	Drop Tube Insulator
35) #G07097728	Pan Shield Support
36) #GC2000288	Drop Tube Square

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




	•
#G0798257	Single Boot
#G07098258	Double Boot
1) #HS732	
2) #HST1620	Double Body Weldment
3) #GC1000013	3/4 Bearing w/Roll Pin Hole
5) #1635-2RS	=
7) #G00401906	Idler U-Bolt
8) #G07097980	Idler Shaft
9) #GS-2010	#10-24 Hex NY-Loc Nut
10) #HSAB45UP	Boot Shaft & Bearing Assembly
11) #CLAMP200	Clamp 2"
12) #G07097946	-
13) #GS-2086	-
14) #G07097371	•
•	

16) #60598	3/8" Lock Washer
17) #GS-456	3/8"-16 Hex Nut
18) #GS-4275	5/16"-18 x 3/4" Hex Head Bolt
N/S) #GS-1147	5/16" Lock Washer
N/S) #GS-396	5/16"-18 Hex Nut
N/S) #GS-7277	#10-32 Hex Lock Nut
20) #G07098109	Latch Chain
21) #GS-6994	Latch Cotter Pin
22) #HS527	Cannon Ball, Agitator 3"



Cumberland 350 Top Mount Screener


-	
1) #GFLX-2459	1/2 Hp Direct Drive Power Unit
2) #G07099849	TMS Hood Mounting Bracket
3) #G07099850	TMS Power Unit Hood
4) #G07098580	
5) #G07098581	
6) #G07100112	
7) #GFLX-3861	DD Screener Spindle
8) #GS-9163	3/16" x 1-1/4" Roll Pin
9) #GS-6482	5/16" Cap Screw
10) #GFLX-2947	Clamp Pin
11) #GS-4312	5/16" x 1/2" Sq. HD Setscrew
12) #GFLX-3864	Agitation Paddle
13) #HSDTFLX	3.406" Galv. Flexible Tubing
14) #HSDT003	12' Tube Drop 3.562" ID x 3.750"0D
15) #G07098647	TMS Body Assembly
16) #G07099986	Double Tube Weldment
17, 20) #GC1000005	300-350 Screener Tube Weldment
18) #GC1000001	Top Half 350 Screener
19) #G07098573	TMS Cover Lid
21) #CLAMP400	Tube Clamp 4"
22) #GFLX-2318	Tube Anchor Plate Weldment
24) #GS-4276	5/16" x 1-1/4" F. Thread Bolt
25) #GFLX-3512	Fill Cover Sealer Strip
26) #GFLX-2718	Spacer



Top Fill Kit for Mdl 90 Auger #GST-AC510-90

- Fits Roxell, Chore-Time and Hog Slat feed bins
- Replacement for Chore-Time #25806

Item	Qty	Part #	Description
1	-	GST-AC515	Fill Cover Assembly
2	1	GST-AC506	Top Fill Assembly, Access Cover Assembly
3	1	GST-AC505	Top Fill Assembly, Motor Shield
4	1	HS537-2	Weldm't - Adapter, Direct Drive-M90
5	8	HS712	Bolt, 5/16 - 18 x 1 Hex Head Bin Bolt
			w/PE Washer, Gr 8.2 JS1000
6	8	HS724	Nut, 3/8-16 Hex Serrated Flange,
			Grade 5, JS500
7	1	HS537-5	Weldm't - Coupling, Direct Dirve
8	1	HS531-8	Clamp Auger
9	1	91251A578	SHC Screw 5/16-18 x 1/2"
10	1	91251A592	SHC Screw 5/16-18 x 2-1/4"
11	1	CLAMP400	CLAMP,UBOLT,4IN
12	1	GST-PNF1011	Weather-Resistant EPDM Edge-Grip
			with Seal 69.125" long





#IS203015Boot Adaptor for Chore-Time/Cumberland/GrowerSELECT

*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Spinks Scale Systems



#IS005500......5,000 lb. Platform Scale for 6' Bin

Bin Scale Parts



#IS005150 Whisker Switch



#005151..... Green Push Button Assy.



• See page 50 for complete parts listing

#GST-AC510-90......Top Fill System Complete

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#ISTWC-10Push Button



#IS203014 ...

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#I-SA1Micro Switch Assy

Rooster Scale Parts



#ISO60148 Pressure Switch

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#IS0031330-350 Lb. Decal



#ISO00201 Control w/Mag Cutoff



#LE016B02M..... Spring for switch assy.




GrowerSELECT

Replacement Feed Chain

#HSFC-1.....50' rolls only

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





...6' long. 1-5/8" spacing

High Profile Medium Wide (4-3/4")

Medium Wide (4-3/4")

#G07098846

**WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


GrowerSELEC 90° Corner

Replacement corner for chain systems complete with suspension kit and clear plastic cover. Features a cast iron wheel and roller bearing pivot pin for longer life.

#HSFC2C GrowerSELECT® 90° Corner


⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HS618-12 Medium wide. 12' long for hens #G07097269 10' pullet #V410300 10' medium wide hen (Pax)

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




GrowerSELECT Corner Stand

14" wide x 16-1/2" high.

#HSFC4Corner Stand

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HSH031 Medium Wide #G07097633Hanger for Pullet Trough #HSFC310-1/4" wide x 4" high

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HSFC14

End Caps

#HSFC9 Hen, Medium Wide, Hi Profile #HSFC10 Pullet 3.25 (L) x 2.75 (W) x 3.75 (H)

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Cumberland Corner

#G07097574C ... 90° corner w/o cover and hanger #G07097523C ... 90° corner w/ cover and hanger

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pivot Pin Assembly

· Pivot pin kit for chain corner

#G07098281.....Pivot Pin Assembly #HS07099370......Grease Zerk Only

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Trough Couplers

#HS6568" Medium wide #G07097570......12" Trough Coupler

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Power Shoes

#G07097731Cumberland #V410419Valco/Pax #BD10-00-0337Big Dutchman

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Chain Breaker

#HSFC8Chain Breaker

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Shear Pins #G07099513.....Shear pin hard grade #G01060124Shear pin soft grade #G07099512.....Shear pin medium grade #V410999 Valco/Pax shear pin (10 pk) #G07099518.....Pkg 50 Hard #G07099517Pkg 50 Medium #BD10-00-0034Big Dutchman 3/16" x 1-1/4" (10 pk.)

⚠ WARNING:





#HSFC2C-1R Wheel Assy



#HSFC2C-2R Shaft Assy



#HSFC2C-3RBall Bearing



#HSFC2C-4RShaft Seal



#HSFC2C-6RClear Cover



#HSFC2-2Composite wheel and shaft kit for original 90° Corner

*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


GrowerSELECT Direct Drive Chain Feeder Motor

- 1750 RPM
- 230 Volts

#HS9036.....



*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



1) #HS07099370	Bolt w/ Grease Zerk
•	Plastic Cover
	Pivot Pin Assembly
4) #G07101494	Corner wheel with Bushing
•	Corner Weldment
6) #G07097697	Corner Suspension Hanger

⚠ WARNING:

*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Item#	•	y needed per VF1938) Stand	
#HWF1938	HWF1938 Leg stand for chain feeder support 19.5" tall w/o hardware 1		
#60580	Washer flat commercial 5/16 x 3/4 SS	4	
#97337304SS	Bolt U Round 5/16-18 x 1-7/16" x 2.73" 304SS	3	
#9731240503	Bolt U 5/16" x 1-3/8" ID x 2-1/2"	3	
#605071	Bolt hex cap 5/16-18 x 1/2" Grade 5 zinc	10	
#60681	Nut lock hex nylon insert 5/16-18 zinc	4	
#617202	Pipe tube 1.315" OD x 10' 16ga galv w/crimp-perching roos	t varies on length	
#6172024	Pipe tube 1.315" OD x 24' 12ga galv w/crimp-perching roos	t varies on length	

Belt Drive Chain Feeder Motor


- 1750 RPM
- 115/230 • 56 Frame
- · Manual Reset

#N90341-1/2 HP Motor




Big Dutchman Champion® Floor Chain Feeding Systems


1) #BD10-BJ-0004	Guard, Belt Sprocket
2) #BD99-10-0096	Bolt, 3/8-16 x 1.0"
3) #BD10-00-0008	Strap, Rack Hanger
4) #BD10-00-0068	Shear Pin
5) #BD10-00-0625	Baffle, Feed Guard
6) #BD99-50-0091	Eye Bolt
7) #BD99-50-0150	Allen Wrench, 1/8"
8) #BD99-50-0152	Allen Wrench, 5/32
9) #BD10-00-0063	Cover, Cleanout
10) #BD99-10-0110	Bolt, 1/4-20 x 1/2"
11) #BD99-10-1139	Bolt, 5/16-18 x .38"
12) #BD10-00-9576	Wire Belt Guard, Bottom
13) #BD99-10-0283	Bolt, 5/16-18 x 1.0"
14) #BD99-10-0733	Bolt, 1/2-13 x 2.0"
15) #BD10-00-9578	Bracket, Bottom Belt
16) #BD99-10-0373	Machine screw, 1/4-20 x 1/2"
17) #BD99-20-0111	Washer, 5/16"
18) #BD99-21-0006	Washer, 1/4 x 1.0" O.D.
19) #BD10-00-1025	Stripper, Chain, Universal
20) #BD99-20-0100	Kep Nut, 5/16-18
21) #BD99-20-0047	Kep Nut, 1/4-20




Description	22* Belt	23* .625" Bore Motor Sheave	23* .87" Bore Motor Sheave	23* 1.12" Bore Motor Sheave
20 FPM/60 HZ	BD99-50-0145	BD10-20-0004	NA	NA
20/40 FPM/60 HZ	BD99-54-0001	BD99-53-0004	NA	NA
60 FPM/60 HZ	BD99-54-0006	BD99-53-0010	NA	NA
60 FPM/50 HZ	BD99-54-0005	BD99-53-0101	BD99-53-0102	NA
120 FPM/60 HZ	BD99-54-0044	BD99-53-0084	NA	NA
120 FPM/50 HZ	BD99-50-1005	BD99-53-0121	BD99-53-0122	BD99-53-0123

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov







1) #BD99-20-0090	Washer, Split-Lock 1/2"
2) #BD99-20-0105	Hex Nut, 1/2-13
3) #BD99-50-0019	Square Key, 1/4" x 1-7/8"
4) #BD10-03-2027	Sprocket, Drive Assembly
5) #BD10-00-9543	Sprocket-Power-3/4 in. Rev.
6) #BD10-00-9544	
7) #BD10-00-9061	Collar, F/Eccentric Hub
8) #BD10-00-9600	Hub, Shear Pin Sprocket
9) #BD10-00-0376	Reducer
10) #BD10-00-9662	Coupling, Spider
11) #BD10-00-9661	Coupling Body, Gear Reducer
12) #BD10-00-9661	Square Key, 3/16" x 3/4"

1) #BD10-00-0135Chain Guide
2) #BD10-00-0197Feed Return Wheel
3) #BD10-00-0337Power Shoe
4) #BD10-04-1005 Feed Return Wheel Slide
5) #BD10-04-1010 Feeder Body
6) #BD10-22-0006Shaft
7) #BD10-BK-6007 Feed Gate
8) #BD99-10-0206 Bolt, 1/4-20 x 1/2"
9) #BD99-10-0261 Bolt, 3/8-16 x 5/8"
10) #BD99-10-1133 Screw, 1/4-20 x .63" Flat Head Allen
11) #BD99-20-0041 Wing Nut, 5/16-18
12) #BD99-20-0111 Washer, 5/16"
13) #BD99-20-0134Hex Nut, 1/4-20
14) #BD99-21-0003Washer, 1/4"
15) #BD99-50-0868 Cotter Pin, 1/8" x 1 1/4"
16) #BD99-20-0047 Kep Nut, 1/4-20
17) #BD99-10-1520 Crg. Bolt, 5/16-18 x 3/4"
18) #BD10-00-0621 Shim Plate, Power Shoe, 10 Ga.
18) #BD10-00-0622 Shim Plate, Power Shoe, 14 Ga.
18) #BD10-00-0623 Shim Plate, Power Shoe, 18 Ga.


18) #BD10-00-0624... Shim Plate, Power Shoe, 22 Ga.

1) #BD99-20-0090	Washer, Split-Lock 1/2"
2) #BD99-20-0105	Hex Nut, 1/2-13
3) #BD99-50-0019	
4) #BD99-50-0020	Square Key, .187" x 1 1/4"
5) #BD10-00-0380	Sprocket, Drive Assembly
6) #BD10-00-9543	Sprocket, Power, 3/4" Rev.
7) #BD86-00-2098	Hub, F/Eccentric Sprocket
8) #BD83-00-2095	Collar, F/Eccentric Hub
9) #BD10-00-9600	Hub, Shear Pin Sprocket

Description	12* Reducer	13 Sheave
20 fpm/60 Hz	BD10-00-0262	BD10-20-0004
20/40 fpm/60 Hz	BD10-00-0266	BD99-53-0005
60 fpm/60 Hz	BD10-00-0284	BD99-53-0007
60 fpm/50 Hz	BD10-00-0284	BD99-53-0007
120 fpm/60 Hz	BD10-00-0371	BD99-53-0042
120 fpm/50 Hz	BD10-00-0371	BD99-53-0042

Big Dutchman Champion Chain 90° BD15-10-5057


1) #BD83-00-4430	Corner Cover
2) #BD15-00-9004	Snap Ring
3) #BD15-00-9010	
4) #BD99-20-0093	Fiber Washer
5) #BD15-10-5167	
5) #BD15-00-0069	Corner Wheel w/Bronze Bushing
6) #BD15-00-9011	
7) #BD15-10-9206	
8) #BD15-10-9106	
9) #BD15-00-0204	Leg Clip F/Floor Feeding
10) #BD99-20-0128	
11) #BD99-20-0090	
12) #BD99-20-0105	
13) #BD15-10-9109	
#BD15-10-5053	
#BD15-20-5009	Trough 10' Medium Wide
#PP17514	Feed Chain Drive Sprocket



WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Big Dutchman 2-Line Chain Feeder

big butchman z	
1) #BD10-BJ-00003	Plate, motor mount
	Guard, belt and sprocket
3) #BD10-02-1060	Body, hopper
	Ring, eccentric w/grease fitting
5) #BD10-00-0047	Ring, retaining
6) #BD10-00-0060	Bearing, flange
7) #BD10-00-0069	Pin, drive, 3/8" x 2"
8) #BD10-00-0074	Spacer, .125" x 1.062" ID x 1.75" OD
9) #BD10-00-0116	Spacer, .031" x 1.062" ID x 1.75" OD
10) #BD10-00-0135	Guide, chain
· ·	
	Slide, feed return
	Wick, felt oil
	Bushing
	Shoe, power
	Yoke, shear pin
-	Shaft, power
•	Gear, power
•	Gear, power
	Coupler, power assembly
	Coupler, long power
	Coupler, short power
	Chain, double
-	
•	Link, connector
	Screw, 1/4-20 x 5/8", FHMS, ZP
	Screw, 3/8-16 x 1-1/4", HHCS, ZP
	Screw, 3/8-16 x 1", HHCS, ZP
	Screw, 3/8-16 x 3/4", HHCS, ZP
	crew, 5/16-18 x 3/4", CRG SH neck, ZP
	Screw, 1/2-13 x 1-3/4", HHCS, ZP
	Screw, 3/8-16 x 4", HHTB, ZP
	Nut, wing, 5/16-18, ZP
აგ) #RD99-20-0090	




	5) ²²
39) #BD99-20-0097	Nut, kep, 3/8-16, ZP
40) #BD99-20-0105	Nut, hex, 1/2-13, ZP
41) #BD99-20-0111	Washer, flat, 5/16", ZP
42) #BD99-20-0336	Washer, flat, 1/4", ZP
43) #BD99-20-0338	
	Cotter Pin, 1/8" x 1-1/4"
45) #BD10-00-0068	Shear Pin, 3/16" x 1-1/4"
46) #BD99-10-0026	Screw, set 1/4-20 x 1/4"
47) #BD10-00-9576	Guard, bottom belt, wire
48) #BD99-50-9316	Cap, rubber
49) #BD10-00-0284	Reducer, 52.5-1 ratio (10CC5600)
49) #BD10-00-0266	
50) #BD99-10-0373	Screw, 1/4-20 x 1/2", THMS, ZP
51) #BD99-10-0370	Screw, 1/4-20 x 3/4", RHMS, ZP
52) #BD99-21-0006	Washer, flat, 1/4", ZP

Cumberland Chain Feeding Systems

1 Line, 60fpm Hopper - Complete #GC492000	92000	#GC49	Complete	Hopper -	60fpm	Line,	1
---	-------	-------	----------	----------	-------	-------	---


i Line, 60ipm Hopper - Comp	lete #GC4920000
1) #G07097737	Gear Reducer 10-00-0284 RH
2) #G07099141	Reversible Drive Sprocket
3)#G07099142	Drive Sprocket Hub
4) #G07097510	
5) #G07097514	Feed Return Wheel Slide
6) #G07097515	Power Shoe Shim Plate
7) #G07098901	Feed Level Plate
8) #G07097522	
9) #G07097535	Gearbox Drive Sprocket Cover
10) #G07097579	
11) #G07097598	Hopper Chain Guide
12) #G07097609	Intake Wheel Weldment
13) #G07097717	Clean-Out Cover-Trough
14) #G07097730	
15) #G07097731	Power Shoe Wear Plate Assy.
16) #G07097654	Pulley Shield Lower
17) #G07098283	3/16" x 1-1/4" Key
18) #G01060124	Shear Pin (Soft Grade)
18) #G07099512	Shear Pin (Medium Grade)
18) #G07099513	Shear Pin (Hard Grade)
19) #G07098225	Belt Guard Back Plate
20) #G07098224	Belt Guard Front Plate



*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

2 Line, 60fpm Mini Hopper - Complete #GC4920001-60


1) #G07097737	Gear Reducer 10-00-0284 RH
2) #G07097506	Chain Stripper Weldment
3) #G07099362	Feed Return Wheel Slide
4) #G0709751	Power Shoe Shim Plate
	Motor Mount Support Angle
	Motor Mount
	Sheave .750 Bore x 3" O.D. Double Groove
	Hopper Chain Guide
	Intake Wheel Weldment
	Belt Guard Front Plate
	Coupler #40 Chain 18 Tooth Assembly
12) #G07097652	Bearing 1" Flange 4-Hole
13) #G07097654	Pulley Shield Lower
	Feed Level Plate
	Drive Guard Assembly
· · · · · · · · · · · · · · · · · · ·	Intake Wheel Shaft
· · · · · · · · · · · · · · · · · · ·	Drive Shaft
	Yoke Assembly
•	Belt Guard Back Plate
	Clean-Out Cover-Trough
	2-Line Hopper-Drive Unit Weld Assembly
	Power Shoe Wear Plate Assembly
	Drive Sprocket Hub
24) #G07097637	Oil Impregnated Bushing
	Shear Pin (Soft Grade)
20, " 20100012 1	



1-Line Hopper (fill only) Replacement Parts

#G07097525D	One-Line Mini-Hopper (FILL ONLY) Complete
	One-Line (FILL ONLY) Wrapper Weldment
2) #G07098901	Feed Level Plate
	Feed Return Wheel Shaft
	Hopper Chain Guide
	Intake Wheel Weldment
6) #G07097514	Feed Return Wheel Slide
•	







Growerselect Nest Systems

Maximize breeder flock production with a comfortable, secure nesting system from GrowerSELECT. Choose from center or side belt models with 8 or 10 holes per side (16 or 20 total). Side-belt (5") and center-belt (8") egg collection options available. Either nest accepts cloth or poly belts. Heavy galvanized metal construction.



Choose from manual nest closure or integrated tube closure for automated systems.



Open grill polypropylene nest bottom permits trash to fall through and improves air circulation. Choose from turf style or rubber finger pads.



Includes poly Comfort Perch ergonomically designed to increase bird comfort. Mushroom shape fits bird paw promoting better balance.



Two nest width sizes of 9.5 and 12 inches are available. Open top design allows hens easy access to the nests.




Growerselection Tables

Simplify egg gathering with GrowerSELECT collection tables. Innovative pinch roller design maintains belt tension to reduce slippage. Top shelf adjusts height without tools. Preprogrammed controller features "soft start/stop" to reduce egg damage while PVC guide rail safety directs eggs to the collection point.

- · Available in Center-belt and side-belt models
- Table height is adjustable from 27" to 42"
- Magnetic vinyl coated table tops are easily removed for cleaning.
- Self-regulating tensioning device permits greater range of adjustment.
- Pre-wired NEMA4X controller requires no programming with "Soft start and stop"
- Belt speed of 17 to 27 fpm.
- Large collection trays under table collect dirt and debris.





GrowerSELECT Center Belt Nest Breakdown

Key	16-hole #	20-hole #	Description	Key	16-hole #	20-hole
1	GSN-2109	GSN-2209	CB Back, 16 Hole	12	GSN-2120	
2	GSN-2004	GSN-1604	Stringer, 16 Hole	13	GSN-2019	
3	GSN-2107	GSN-2207	CB Front, 16 Hole	14	GSN-2114	
4	GSN-2102S	GSN-2007S	CB Top, 16 Hole	15	GSN-2115	
5	GSN-2005GS		Partition, Universal	16	GSN-2124	
6	GSN-2111		CB Egg Belt Curtain	17	GSN-2311	
7	GSN-2006		Wire, Bottom Support, Galv #5 95.125", Universal	18	GSN-2210	
8	GSN-2310		Perch, Extruded	19	GSN-2122	
9	GSN-2101		CB Conveyor Cover	20	606940	
10	GSN-2009		Flipper, 8ft Universal	21	GSN-2103	GSN-220
11	GSN-2017		Perch Support Bracket, Universal	22	GSN-2110	


Key	16-hole #	20-hole #	Description
12	GSN-2120		Rivet Pop 3/16" Aluminum
13	GSN-2019		Grommet Heyco-2514 Black
14	GSN-2114		Black Nylon Insulation Retainer
15	GSN-2115		CB Front Brace, Universal
16	GSN-2124		Hinge Front Lid, 1.97" X 3.5" SS
17	GSN-2311		Perch Retainer Bracket
18	GSN-2210		Splice Plate
19	GSN-2122		CB Egg Tray Brace
20	606940		Pin Cotter 3/32" X 1" Extended Prong Zinc
21	GSN-2103	GSN-2203	CB Egg Tray
22	GSN-2110		CB End



Growerselect

GrowerSELECT Side Belt Nest Breakdown

Key	16-hole #	20-hole #	Description
1	GSN-1604	GSN-2004	Stringer
2	GSN-2002		SB Egg Tray Cover
3	GSN-2003A	GSN-1603A	SB Egg Tray Assembly
4	GSN-2005GS		Partition, Univ
5	GSN-2102S	GSN-2007S	Top 9.6" With Decal
6	GSN-2008	GSN-1608	SB Back
7	GSN-2009		Flipper, 8 Ft Univ.
8	GSN-2123		Closure, Front Lid
9	GSN-2310		Perch, Extruded
10	GSN-2006		Support Rod
11	616517		Screw Machine 10-24 X 1/2" Hex Unslotted Zinc




Key	16-hole #	20-hole #	Description
12	606940		Pin Cotter 3/32" X 1" Extended Prong Zinc
13	GSN-2012		SB Egg Tray Connector
14	GSN-2013		SB Egg Tray Brace
15	GSN-2014		SB Suspension Bracket
16	GSN-2017		Brkt: Perch/Rod Support Univ.
17	GSN-2120		Rivet, Pop 3/16 ALAM #62
18	GSN-2124		hinge, front lid
19	GSN-2311		Perch Hanger
20	1137014		Nut Hex Nyloc 10-24 Zinc
21	GSN-2011		SB Center Flipper Brkt



Cumberland **Side Belt Nest** Breakdown

GFRN16, GFRN20 Nest Assembly

Key	#GFRN 16	#GFRN 20	Description
1	#G07101221	#G07101221	Nest Panel
2	#GC5000028	#G07101219	Back Panel
3	#GC5000031	#G07101218	Stringer
4	#G07101206	#G07101206	Center Tray Brace
5	#GC5000034	#G07101223	Egg Tray
6	#G07101229	#G07101229	Egg Belt Guide
7	#GC5000032	#G07101222	Egg Tray Front Plate
8	#GC5000029	#G07101217	Nest Top
9	#G07101355	#G07101355	Winch Bracket
10	#G07101403	#G07101403	Connecting Winch Bracket
11	#GC5000043	#GC5100000	Swing Top with Decals
12	#GC5000026	#GC5000026	Support Rod
13	#GC5000033	#G07101215	Egg Tray Cover
14	#G07101211	#G07101211	Nest Panel
15	#G07101292	#G07101292	Perch Board
16	#GC5000023	#G07101296	Blinder
17	#G07101247	#G07101247	Splice Plate
18	#GC5000022	#G07101293	Nest Bottom
19	#G30-0221	#G30-0221	Hinge 2" x 3.5" SS
21	#GC5000056	#GC5000056	Flipper
22	#G07101297	#G07101297	Clamp Tubing .375"
NS	#GS-1101	#GS-1101	Bolt 1/4-20 x 1/2 HHCS
NS	#GS-1102	#GS-1102	Nut Hex 1/4-20
NS	#GS-8302	#GS-8302	Screw MS 10-24 x 2-1/4" RHS
NS	#GS-2010	#GS-2010	Nut Nylock 10-24




WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


Key	#GFRN 16	#GFRN 20	Description
NS	#GS-4322	#GS-4322	Pin Cotter 3/32" x 1.00"
NS	#GS-7222	#GS-7222	Rivet Alum. 3/16" x 3/8"
NS	#GS-7235	#GS-7235	Rivet Steel 3/16" x 1/2"
NS	#GS-7236	#GS-7236	Rivet Steel 3/16" x 3/4"



GAN12 Cumberland Center Belt Nest Breakdown


1) #G07097732	Egg Tray
	Back Panel
	Nest Panel
	Top Panel
5) #G07097662	Top Cover
6) #G07097943	Web Retainer Assembly
7) #G07097664	Short Center End Plate
8) #G07097665	Long Center End Plate
9) #G07097666	Front Bottom Strap
10) #G07097668	Flipper
11) #G07097670	Egg Belt Guide
12) #G07097671	Egg Tray Splice Plate
13) #G07099166	Gray Nest Pad (12 Hole)
	Coated Wire Nest Bottom
	Perch Bracket Assembly
16) #G07097986	Perch Board - AN12
17) #GC5000027	Nest Bottom Support Rod
18) #G07100688	Top Cover Retainer





Cumberland Center Belt

Drive Assembly
1) #G07099243 40-1 Ratio Gearbox
2) #WW9D21 1/2 Hp C-Face DC Motor (90 Volt)
3) #GS-6290#40 Roller Chain
4) #GD02-0031 Connecting Link - #40 Chain
5) #G07099244 1" Bore 4016 Chain Sprocket
6) #G07098656 3/4" Bore 4016 Chain Sprocket
7) #G07097778Bearing w/ Collar
9) #G070977685/16" x 5-3/4" Adjustment Rod
10) #G07097780Compression Spring
11) #G07097836 Extension Spring (Idler)
12) #G07098667 Idler Roller Bracket
12) #G07098682 Spring Tensioner Bracket
13) #G07097763Intermediate Roller Shaft
14) #G071016A7 Belt Rollers
15) #G07097766
16) #G07097782Switch Mounting Bracket
17) #G0401064Micro Switch #BA-2RV178-A2
18) #GBLK-10164
19) #G07098696 Roller Shaft - Pinch Roller
20) #G07098707 Drive Roller Weldment
21) #G07100226Brush and PVC Bracket
N/S) #G07097769Adjusting Tab
N/S) #GS-396 Hex Nut 5/16"-18 Zinc YDP Grade 2
25) # GS-5220
N/S) #G07099955Link Offset #40 Chain-Half Link
,,





#G07099043:

Complete Return Idler Assembly for Center Belt Systems

Cumberland Center Belt Return Idler Assembly

3) #G07101312	End Roll Axle
5) #G07101311	
6) #G07101304	
7) #G07101339	
9) #GS-7086	
11) #G07099615	Hinge
N/S) #G07101358	
N/S) #GDC-887	
N/S) #GS-396	
N/S) #GS-4303	Bolt 5/16" - 18 x 3/4"
N/S) #GS-7499	

⚠ WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Cumberland Side Belt Power Unit Assembly


1) #WW9D21	1/2 Hp Motor
	Gearbox - 40:1
	Spider Coupler
	Drive Shaft
5) #G50-0008	
	Drive Roller Assy.
•	,

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



1) #G07097778	 3/4" Bearing Assy.
2) #G07097767	
3) #G07097766	 Idler Arm
4) #G07097782	 Switch Mounting Bkt.
5) #G07097836	
6) #G07098667	 Idler Roller Bkt.
7) #G07101412	 Internal Roller Shaft
9) #GBLK-10164	 Plastic Pulley
10) #G00401064	 Micro Switch
11) #G07101413	 Pinch Roller Shaft
12) #G07100226	 Belt Brush




Shenandoah SEGS T/98 **Collection Table**

Wear Plate
Lower Leg
Swing Arm Assembly
Side Guard Panel
Shaft
Electric Box Complete
Vulcanized Drum Pulley
Pillow Block
50:1 Gear Reducer
.60:1 New Style Gear Reducer w/ Coupler
1/2 Hp Motor
Alignment Pad
Metal Litter Pan
Pinch Roll Kit T/98

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Shenandoah Belt **Idler Roll Assembly**




Nest Bottom Options & Pads

#AGL16-37352 Black Bottom w/ Clean Out Grill #AGL16-37206Blue Finger Nest Pad (left) #AGL16-37197 Grey Astro Style Nest Pad (right)


New Style Shenandoah Collection Table Drive Unit

1) #HSBHN-0008 Roller, Plastic 1.5 OD x .64 ID x 8.0
2) #AGL16-103703 Shaft: Return Roll
3) #AGL16-63702Nut: Hex 3/8-16 - Plate
4) #AGL16-5031 Rod: Tie Thrd Segs-T/200
5) #AGL16-37039Spring: Compression 3"
6) #AGL16-103702 Shaft: Pinch Roll
7) #AGL16-103621 Adjuster: Belt Drum
8) #AGL 16-101498 Screw: Hex Tap 3/8-16 x 3-1/2"
9) #AGL 16-101483 Pulley: Drive 5 Dia x 5, 3/4" Bore
10) #AGL16-101482Bearing: Flange 3/4" Dia
11) #2NPA1Isolator: Vibration
12) #AGL16560240 60:1 Gear Reducer w/ Coupler
12A) #AGL16060098 Motor 1 Hp 180VDC 3450 RPM
13) #AGL16-13191700 Washer: Nylon Shoulder
14) #AGL16-13200550 Nut: Hex Flg Lck 3/8-16
15) #AGL16-101158 Clip: Hitch Pin 1/8 D. x 2-1/2"
16) #AGI.16560005 Take Un Assy 4" Egg Belt




17) #AGL16-103931 Cordset: Male Graham Cmplt 18) #AGL16-101485......Spring: Extension 5/8 X 4-1/2" 19) #AGL16500052 Guard, Belt Tensioning

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



1) #AGL16-8222	Brush Mount Bracket
2) #AGL16-34678	Dust Cover
	Roll Retainer Bracket
	Brush
	Hex Shaft
6) #AGL16-37051	PVC Roll Assembly
7) #AGL16-37699	Push Nut Retainer Bracket New Style
	Retainer Bracket Old Style
•	

MARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



-	
1) #AGL16-560061	Dust cover
2) #HSBHN-0025	Roller
3) #AGL16-35629	Serrated flange nut #20 x 1/4"
4) #AGL16-63702	Hex nut
5) #AGL16-005182	
6) #AGL16-102977	Shaft for roller
7) #HSBHN-0003	Brush for roller
8) #AGL16-560060	Brush mounting bracket
9) #AGL16-63700	Hex screw
10) #AGL16-13200550	Flange lock nut #16 x 3/8"
11) #AGL16-560064	




5" Dual Belt Nests

- 60" long
 Includes nest pads
 Heavy galvanized construction
- Plastic dividers

#W5220504 Dual Belt Nest



WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Parts List

Item	Qty	Part #	Description	Item	Qty	Part #	Description
1	14	W2001934	Partition Plastic For Wadeken Side Belt Nest	13	12	DP202112PB	Pad Nest 11 5/8" X 12 5/8" Blue Gray For Center Belt
2	1	W3002747	Back Strip [5" Nest]	14	4	W2001914	3/16 X 60" L Bottom Support Rod
3	2	W3002835	Egg Tray For 5Ft Dbl Belt Nest [Side Belt]	15	2	W300002	3/4 Metal Conduit 62"
4	2	W4001519	Egg Roll-Out Skirt Frame [5In Nests]	16	4	W2001936	5" Nest Closure Plastic Red Conduit Cap
5	2	W3002836	Tray Cover For 5Ft Dbl Belt Nest [Side Belt]	17	21	W2001940	#6 X 1-1/4 Phil Head Screw
6	1	W3002746	5In Dbl Nest Top Cover	18	60	W2001939	#8-32 X 1/2 Phillp Pan Head Screw
7	1	W3002765	Dbl Hanger [5In Nests]	19	16	GSN-2120	Rivet, Pop 3/16 Alam #62
8	1	W3002764	End Hanger [5In Dbl Nests]	20	2	60500	1/4" X 1/2" Bolt
9	1	W3002749	5In Dbl. Nest Flipper	21	2	W2000730	1/4In Star Lock Washer
10	2	W3002839	Spice Plate 5In Nests	22	2	60570	1/4" Hex Nut
11	4	W3002837	Egg-Tray Belt Guide For 5In Nests	23	3	W2000233	Cotter Pin 1/8 X 1
12	12	W2001946	Plastic Bottom For Side Belt Nests	24	4	W2001937	Plastic Grommet For 5" Nest




8" Center Belt Nests


- 60" long
- Includes nest pads
- Heavy galvanized construction

#W5220105......Center belt nest $\mbox{\bf \#W5220105LP}......\mbox{Center belt nest without pads}$ #DPREDRAMP...... 10" x 29" red ramp, 4 per nest






Item	Qty	Part #	Description
1	4	W3002722	End Partition With Stiff Rib
2	10	W3002723	Inner Partition With Stiff Rib
3	2	W3002491	Back Bottom Strip [8" Nest]
4	1	W3002492	8In Ctr Nest Tray 60In Long
5	2	W3002490	Front Bottom Strip W/ Lovers
6	1	W3002501	Long - Center End
7	1	W3002502	Short - Center End
8	2	W4001478	8In Ctr Nest Egg Rollout Skirt Assem
9	2	W3002503	Belt Guide For 8In Ctr. Nests
10	2	W3002489	8In Ctr Nest Top
11	1	W3002488	8In Ctr Nest Top Cover
12	2	W3002507	Spice Plate Ctr Nests
13	2	W2001914	3/16 X 60" L Bottom Support Rod
14	1	W3002493	8In Ctr. Nest Flipper
15	12	W3002508	Wire Nest Bottom
16	12	DP202112PB	Pad Nest 11 5/8" X 12 5/8" Blue Gray For Center Belt
17	126	GSN-2120	Rivet, Pop 3/16 Alam #62
18	8	60500	1/4" X 1/2" Bolt
19	8	W2000730	1/4In Star Lock Washer
20	8	60570	1/4" Hex Nut
21	24	W2001954	Pad Retainer Clips Ratchet Fasteners
22	3	W2000233	Cotter Pin 1/8 X 1






WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



5" Dual Nest

Key	Item#	Description	# of Guides
1	W3002861	12" Egg Tray	
	W3002863	18" Egg Tray	
	W3002865	24" Egg Tray	1
	W3002867	30" Egg Tray	1
	W3002869	36" Egg Tray	1
	W3002871	42" Egg Tray	1
	W3002873	48" Egg Tray	1
	W3002875	60" Egg Tray	2
	W3002877	72" Egg Tray	2
	W3002879	84" Egg Tray	
	W3002881	96" Egg Tray	
2	W3002862	12" Tray Cover	
	W3002864	18" Tray Cover	
	W3002866	24" Tray Cover	
	W3002868	30" Tray Cover	
	W3002870	36" Tray Cover	
	W3002872	42" Tray Cover	
	W3002874	48" Tray Cover	
	W3002876	60" Tray Cover	
	W3002878	72" Tray Cover	
	W3002880	84" Tray Cover	
	W3002882	96" Tray Cover	
3	W3002838	Belt Guide	
4	W3002839	Splice Plate	
5	GSN-2120	3/16 ALAM #62 Pop Rivet	



8" Center Nest

Key	Item#	Description	# of Guides
1	W3002812	12" Egg Tray	
	W3002681	18" Egg Tray	
	W3002494	24" Egg Tray	1
	W3002495	30" Egg Tray	1
	W3002496	36" Egg Tray	1
	W3002682	42" Egg Tray	1
	W3002684	60" Egg Tray	2
	W3002685	72" Egg Tray	2
	W3002686	84" Egg Tray	2
	W3002687	96" Egg Tray	2
2	W3002813	12" Tray Cover	
	W3002688	18" Tray Cover	
	W3002498	24" Tray Cover	
	W3002499	30" Tray Cover	
	W3002500	36" Tray Cover	
	W3002689	42" Tray Cover	
	W3002690	48" Tray Cover	
	W3002691	60" Tray Cover	
	W3002692	72" Tray Cover	
	W3002693	84" Tray Cover	
	W3002694	96" Tray Cover	
3	W3002503	Belt Guide	
4	W3002507	Splice Plate	
5	GSN-2120	3/16 ALAM #62 Pop Rivet	



5" Dual Belt Table


#W5220501R..... with Reversing Switch

(20) (14) (10) (11)

(54)


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Parts List

Item	Qty	Part #	Description	Item	Qty	Part #	Description
1	1	W3002847	Table Top Assem. [5" Dbl]	30	4	W3002649	Collect. Table Take-Up Arm
2	1	W4001539	18" Florescent Light Fixture (Discontinued)	31	4	W3002647	Front Roller Supt Angle [ModC]
3	2	W4001538	Dual Belt Safety Switch Assy.	32	2	W3002640	Collector Table Side Plate R.h.
4	1	W4001533	5" Dbl Belt Front Leg Asy[8811533100]	33	2	W3002639	Collector Table Side Plate L.h.
5	1	W4001534	5" Dbl Belt Rear Leg [8811534100]	34	2	W3002516	Brush Plate 8" [Egg Collect]
6	4	W4001505	Adj Leg 18-7/8" [8811505100]	35	2	W3002515	Brush Holder 5" And 8" [Egg Collect]
7	1	W4001535	5" Dbl. Collector Table Supt Assy.[8811535100]	36	1	W2001988	Idler End Shaft
8	2	W4001529	Rod Adj. Drive Roller	37	1	W2001908	Gear Reducer Almrb46 / 20:1 Ratio Bxsize 66C
9	2	W4001528	Trash Tray Assem For Dbl Belt Collector	38	4	W2001961	Coupling Chain Half
10	2	W4001511	Two Direct. Egg Diverter Weld [5" Table]	39	2	W2001960	Chain For Coupling W2001961
11	2	W4001514	5" Collect Single Egg Diver. w/ Bumper Assem.	40	1	W2001952	Motor 3/4Hp 90V 1800Rpm
12	2	W4001504	Rear Lifting Handle 9-3/4 [8811504100]				Model #WPMDC34-18-90V-56CB
13	4	W4001506	Pinch Roller Adj. Rod	41	2	W2001920	4" Drive Roller
14	2	W4001508	Flip -Up Bar 26-5/16 [8811508100]	42	3	W2001879	Rubber Bummer 1/8 X 3/4 Wide
15	1	W3002848	Top Front Roller Suppt. (5" Dbl Table)	43	4	616421	3/16 X 3/16 X 1-1/4"L Key Stock
16	2	W3002839	Spice Plate 5In Nests	44	1	W2001865	3/16 X 3/16 X 3"L Key Stock
17	1	W3002803	Brace Brkt. (5" Dbl Table)	45	4	W2001863	Pinch Roller Spring
18	4	W3002802	Shelf Supt Brkt [5" Dbl Table]	46	2	W2001857	Brush Holder Spring
19	1	W3002801	5" Dbl Belt Ss Shelf	47	4	W2001856	Adj. Foot 1/2-13 Thread Vib. Damp.
20	2	W3002783	Roller Cover (5" Dbl. Table)	48	4	W2001848	Take Up Shaft
21	2	W3002781	Trash Deflector (5" Dbl Table)	49	2	W2001847	Pinch Roller Shaft
22	2	W3002780	Roller Cover Hinge [6" Table]	50	2	W2001844	3/4 X 1-7/8 X 9Inl Base 2In Belt Brush
23	1	W3002667	Dart Control Mtg. Brkt.	51	4	W2001843	Take-Up Arm Spring
24	1	W3002666	Motor Support Clip	52	26	W2001834	#10-24 Keps Lock Nut
25	1	W3002663R	Front Lifting Lug Right	53	30	W2001833	#10-24 X 1/2 Pan Head Screw
26	1	W3002663L	Front Lifting Lug Left	54	1	W2001832	Dart Speed Controler W/ Three Hole Base
27	6	W3002652	Take-Up Arm Spring Clip	55	6	W2001824A	PVC Roller 9-3/8"
28	6	W3002651	Pinch Roller Adj. Clip [ModC]	56	1	W2001760	3/4" Set Screw Collar
29	.2	W3002650	Safety Switch Mtg. Brkt.	57	4	GSN-5234	Bearing




Parts List

Item	Qty	Part #	Description	Item	Qty	Part #	Description
1	1	W4001538	Dual Belt Safety Switch Assy.	28	2	W3002647	Front Roller Supt Angle [ModC]
2	1	W4001529	Rod Adj. Drive Roller	29	1	W3002646	Collect. Table Front Panel 8" Cb.
3	1	W4001510	Two Direct. Egg Diverter Welded [8In Table]	30	1	W3002640	Collector Table Side Plate R.h.
4	1	W4001509	8" Collect Single Egg Diver. w/ Bumper Assem.	31	1	W3002639	Collector Table Side Plate L.h.
5	1	W4001503	8" Collector Table Supt Assy.[8811503100]	32	1	W3002516	Brush Plate 8" [Egg Collect]
6	1	W4001507	Table Top Assem. [8" Cb.]	33	1	W3002515	Brush Holder 5" And 8" [Egg Collect]
7	2	W4001506	Pinch Roller Adj. Rod	34	1	W3002507	Spice Plate Ctr Nests
8	1	W4001501	Front Leg Assy 8" Table [8811501100]	35	1	W2001908	Gear Reducer Almrb46 / 20:1 Ratio Bxsize 66C
9	1	W4001502	Rear Leg Assy [8811502100]	36	1	W2001952	Motor 3/4Hp 90V 1800Rpm Model
10	4	W4001505	Adj Leg 18-7/8" [8811505100]				#WPMDC34-18-90V-56CB
11	2	W4001508	Flip -Up Bar 26-5/16 [8811508100]	37	1	W2001920	4" Drive Roller
12	1	W4001504	Rear Lifting Handle 9-3/4 [8811504100]	38	4	W2001879	Rubber Bummer 1/8 X 3/4 Wide
13	1	W3002669	Hinged Shelf Supt Brkt Coll. Table	39	1	W2001865	3/16 X 3/16 X 3"L Key Stock
14	1	W3002668	Shelf Short Hinged Brkt [8" Dbl Table]	40	2	W2001863	Pinch Roller Spring
15	1	W3002667	Dart Control Mtg. Brkt.	41	1	W2001857	Brush Holder Spring
16	1	W3002666	Motor Support Clip	42	4	W2001856	Adj. Foot 1/2-13 Thread Vib. Damp.
17	1	W3002665	Collect. Table L.h. Leg Brace	43	2	W2001848	Take Up Shaft
18	1	W3002664	Collect. Table R.h. Long Leg Brace	44	1	W2001847	Pinch Roller Shaft
19	1	W3002663R	Front Lifting Lug Right	45	1	W2001844	3/4 X 1-7/8 X 9Inl Base 2In Belt Brush
20	1	W3002663L	Front Lifting Lug Left	46	2	W2001843	Take-Up Arm Spring
21	1	W3002662	Roller Cover Hinge [8" Table]	47	12	W2001834	#10-24 Keps Lock Nut
22	1	W3002654	Trash Chute For 8In Cb Table	48	14	W2001833	#10-24 X 1/2 Pan Head Screw
23	1	W3002653	Roller Cover (8" Cb. Table)	49	1	W2001832	Dart Speed Controler W/ Three Hole Base
24	3	W3002652	Take-Up Arm Spring Clip	50	3	W2001824A	PVC Roller 9-3/8"
25	3	W3002651	Pinch Roller Adj. Clip [ModC]	51	1	W2001760	3/4" Set Screw Collar
26	1	W3002650	Safety Switch Mtg. Brkt.	52	2	GSN-5234	Bearing
27	2	W3002649	Collect. Table Take-Up Arm				




Idler Assembly



W5220502 - 5" Dual Belt (two per nest required)

1 1 1 1 1	W3002844 W3002842 W3002841 W3002840 W3002780	5In Idler End Scraper 5In Idler End Support Strap 5In Idler Support Brkt 5In Idler Cover W/ Brush Beller Cover Hinge Id." Tobled
1 1 1	W3002841 W3002840	5In Idler Support Brkt 5In Idler Cover W/ Brush
1	W3002840	5In Idler Cover W/ Brush
1		
1	W3002780	Poller Correr Linga [6" Toble]
_		Roller Cover Hinge [6" Table]
1	W3002770	Idler Side Plate Left [5" Nest]
1	W3002769	Idler Side Plate Right [5" Nest]
2	W2001978	Idler Roller 2–3/8 X 6–1/4
1	W2001977	Idler End Shaft
1	W2001976	5In Idler Guide Shaft
1	W2001947	3/4 X 1-7/8 X 6Inl Base 2In Belt Brush
2	W2001853	Hex Bolt 5/16-18 X 3 Full Thread
8	W2001834	#10-24 Keps Lock Nut
8	W2001833	#10-24 X 1/2 Pan Head Screw
2	GSN-2120	Rivet, Pop 3/16 Alam #62
2	60597	Lock Washer 5/16 Zinc
6	60571	5/16" Hex Nut
2	60508	5/16" X 3/4" Bolt
2 2 6		GSN-2120 60597 60571


WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




W5220103 - 8" Center Belt (one per nest required)

• Direct replacement for Big Dutchman #BD37-03-0025

Item	Qty	Part #	Description
1	1	W3002558-R	Idler Side Plate Right [8" Nest]
2	1	W3002558-L	Idler Side Plate Left [8" Nest]
3	1	W3002546	8In Idler Support Brkt
4	1	W3001491	Idler Belt Guide Bar 1" Conduit [8811491100]
5	1	W3002547	8In Idler End Support Strap
6	1	W3002598	8In Idler End Scraper
7	1	W3002544	8In Idler Cover W/ Brush (Long)
8	1	W3002550	Idler Cover Hinge
9	1	W2001846	Idler End Shaft
10	1	W2001824A	PVC Roller 9-3/8"
11	1	W2001844	3/4 X 1-7/8 X 9Inl Base 2In Belt Brush
12	2	W2001853	Hex Bolt 5/16-18 X 3 Full Thread
13	6	60571	5/16" Hex Nut
14	4	W2001833	#10-24 X 1/2 Pan Head Screw
15	4	W2001834	#10-24 Keps Lock Nut
16	2	GSN-2120	Rivet, Pop 3/16 Alam #62
17	2	W2000165	1/4" X 1/2" Bolt
18	2	W2000166	Hex Head Bolt 1/4-20 X 3/4 L
19	4	60680	1/4" Locknut [9602502501]








17% to 28% more open area

Rectangle slots create 58.5% of total opening to reduce manure buildup resulting in a cleaner floor.



Stronger, Heavier Panels

Each 2' x 4' panel weighs 6.7 pounds...over 3/4 of a pound more than competitive brands. 21 longitudinal ribs compared to others with only 17 ribs provides a level slat surface with only three support runners.



Interlocking tabs

Multiple interlocking edge tabs reduce flexing to promote a flat, stable walking surface. Arch latitudinal ribs furnish greater support to the longitudinal ribs.

Choose from three different UV stable Polypropylene formulations in 24-inch wide by 48-inch long sections.

#PF-P24X48	Prime white "virgin" poly
#PF-P24X48RP	Reprocessed white poly
#PF-P24X48RPB	Reprocessed black poly






Egg Belting

Pre-Stretched Polypropylene Belt resists moisture absorption to inhibit the growth of bacteria and fungus. Herringbone weave keeps eggs in place.

Ask about quantity discounts!













ITEM #	LENGTH	COLOR
2" WIDE		
HSEB800A-1270W	1270′	White/Blue Stripe
3.5" WIDE		·
HSEB801A-1040W	1040'	White/Red Stripes
HSEB801A-1240W	1240'	White/Red Stripes
HSEB801A-1509W	1509'	White/Blue Stripes
3.75" WIDE		
HSEB802A-840	840'	Gray/Blue Stripes
HSEB802A-1040	1040'	Gray/Blue Stripes
HSEB802A-1240	1240'	Gray/Blue Stripes
HSEB802A-1240W	1240'	White/Blue Stripes
HSEB802A-1509W	1509'	White/Blue Stripes
HSEB802A-1600W	1600′	White/Blue Stripes
4" WIDE		
HSEB803A-840	840′	Dark Gray/Blue Stripes
HSEB803A-1040	1040'	Dark Gray/Blue Stripes
HSEB803A-1240	1240′	Dark Gray/Blue Stripes

ITEM #	LENGTH	COLOR
4.5" WIDE		
HSEB805A-1050W	1050′	White/Red Stripes
5" WIDE		
HSEB807-840	840′	Dark Gray/ Blue Stripes
HSEB807-1040	1040′	Dark Gray/ Blue Stripes
HSEB807-1240	1240′	Dark Gray/ Blue Stripes
145 MM WIDE		
HSEB809A-294MW	294m	White/Green Stripes
8" WIDE		
HSEB808-1020	1020′	Dark Gray/Blue Stripes
HSEB808-1220	1220′	Dark Gray/Blue Stripes
HSEB810A-820W	820′	Feather Glide White/Black Stripe
HSEB810A-1020W	1020′	Feather Glide White/Black Stripe
HSEB810A-1220W	1220′	Feather Glide White/Black Stripe

Nest Pads



Rubber fingers cushion and support eggs. Open design allows debris to fall through resulting in a cleaner nest.



The original AstroTurf® nesting pad.



AstroTurf® NXT pads are the next generation of turf pads. Rounded tips and straighter blades mean cleaner eggs. New plastic formulation and thicker, stronger base extends pad life.

Item#	Description	Size	OEM#
#HS601	Finger Style	12.75" x 11.65"	GC5000078
#HS602A	Finger Style	5.63" x 9.75"	GC5000079
#HS603-1	Turf Style, Grey	5.6" x 9.6"	G07101294
#HS603-2	NXT Style, Grey	5.6" x 9.6"	AGL16-37197, DPPB5X9
#HS604-1	Turf Style, Grey	11.75" x 12.875"	G07099166, AGL16-37193
#HS604-2	NXT Style, Grey	11.5" x 12.875"	-

Breeder House Replacement Parts











Egg Table Replacement Controls & Boards

1) #AGL16-500062	
	Dart control box, with on/ off toggle, no wires
	Dart control box , with on/ off/ reverse toggle, no wires
#W4001524	
3) #G07099510	
4) #125DV-C	
5) #253G-200C	
6) #HSBHN-0017	
N/A) #HSBHN-0023	



Roller for Egg Table

#AGL16-101483.....Roller for Egg Table #AGL16-37067 Roller Pulley Head Drum Vulcanized for Older Shenandoah Nests



Solid Belt Rollers

• 1-1/2" x 8" Plastic

1) #HSBHN-0008Replaces OEM#16-101468 2) #HS07101647OBCO, 9.375"L alternate for Cumberland # 7101647

#BD37-01-2035... 2.05" x 8.31" for Gather All Tables



Dart Controls Potentiometer Kit

• for Egg Table Control

#SA-STOK-WO.....Potentiometer Kit



Wooden Cannonballs

• Replaces metal cannonball to reduce noise

#BD11-00-1012......Standard 3-5/16" #BD11-00-1023...... Hard Wood 3"



Nest Clip

· for back of nest

#W5220130 Galvanized Center Belt Nest Clip

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Sewing Kit



#66500	1 lb. Spool
#AGL16-37179 .	Kit for Twill Egg Belt
#66501	Small Waxed Thread Spool 27yd
#W2001849	Wadeken Waxed Thread
#66600	3" Bent needle for egg belt

Breeder House Replacement Parts







Egg Table Motors

- · Permanent magnet DC
- Variable speed
- · C-face with removable base

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Item#	Нр	RPM	Shaft Length	Shaft Size	Voltage	OEM Reference #
WW9D21	1/2	1750	2.06"	5/8"	90	LE098000, G07097895, 2M168D, JD4132, MMZ606, W2001830
WW9D22	3/4	1750	2.06"	5/8"	90	2M169, W2001952
WW9D23	1	1750	2.44"	5/8"	90	LE108022
WW9D24	1	3600	2.44"	5/8"	180	AGL16060098



• For the 1/2 & 1/3 Hp Lesson motor

A) #EIS900163-11	Motor Brush MMZ606 Motor
B) #EIS900115-01	Motor Spring MMZ606 Motor
#2ZB83	Brush For 2M168 Motor Pax Nest
#2ZB84	Brush & Spring For 2M168 Motor Pax Nest
#EIS900015-18	Brush Replacement for Lesson Motor



Gearhead


· Gear reducer for NEW STYLE egg table

#HSGRET001......1:60 alternate for Shenandoah #16560240 #AGL16060107Coupling Kit Only KG3 Hp NO56 for AGL16560240

🔔 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Double Pulley Options



♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Mastercraft Big Red Handheld Turbo Air Blower

The Big Red industrial quality hand held blower is designed for heavy duty. The unique shape of the hand blower enhances the vortex and directs a large volume of air at a high velocity through the molded 3/4" nozzle in hard to reach places, speeding cleaning, reducing maintenance and drying time.

• Model: B650 · Current: 11 AMPS


• CFM: 94 Motor: 1 HP, 120 V






Litter Pans

A) #HSL128Metal, replacement for OEM#16-85834 B) #T9A239473RDPlastic







Item#	OEM#	Description
#LOV11091	16-35617	Lovejoy Hub Coupler LO95 1" Bore 1/4" Keyway
#LOV11087	16-35618	Lovejoy Hub Coupler LO95 3/4" Bore 3/16" Keyway
#LOV11075	16-35616	Lovejoy Spider Gear Spacer Hollow Blue L090/L095




White Brush



Trion Humidifier Model 707 Parts List

#520280	Complete 115V
1) #520240	Discharge Dome
2) #5202001	Motor Cover
3) #520219	Retainer Clip
4) #52031	Motor Base
5) #520245	Diffusing Screen
6 & 8) #52030	. Impeller & Impeller Pump (kit)
7) #52032	Screw, Set Cup



9) #520294	Vibration Damper
10) #5208201	Center Pan
11) #52029	Center Pan Support
12) #52802827	Drip Tube
13) #520292	Float & Valve Assembly
15) #520296-001	Motor 115V
16) #5202186	Mounting Bracket

Hurricane Ultra II

The Hurricane Ultra II ULV mister is an electric portable aerosol applicator that dispenses both oil and water-based products. Features solid state metering device, low profile one-gallon tank to resist tipping and controllable droplet sizes. Adjustable flow rate of 0-4.5 gph and 5.50 particle size. 12" L x 12" W x 14" H.



#CD62150-1 Hurricane Ultra II Fogger

TRI-JET

Chemical fogger or humidity control is simple with the Commander "Tri-Jet" Fogger. The combination of adjustable valve and the tornado action nozzle allows you to maximize mist up to 30 feet directionally. Three counter rotating vortex nozzles dispense an adjustable particle



size of 15-30 microns from either oil- or water-based chemical solutions. 1 gallon tank capacity. Aluminum construction with chemical resistant vinyl tubing.

#TRIJET110Tri-Jet Fogger

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Float Valve Assembly

For Trion 707 Humidifier

#520292Brass



Replacement	Ų
Compressors	4
#525839	

#525639	101 13000-136
#A608	for 6000-10E
#40006E	for 4000-6E
#G900015ECOMP	for 9000



Blades		
#525833.	12" pusher for	9000-15e
#525836.	14" sucker for 18000-27e &	13000-20e

#525834 12" sucker for 9000-15e **#525831**......11" for 6000

#525833 ... 12" pusher for 9000-15e & 6000-10e

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





#G900015ECAP

Burch Cooler Capacitors

#35370 for 6000 Burch Cooler #G900015ECAP..... for 900015E Cooler

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Float Valve Assembly

For Burch Egg Cooler



Humidifier Pan Only

#525852	.for	6000-1	0e
#520281	.for	9000-1	5e





#52586...... 50W Model 6000 Inside Fan Motor & 9000 Inside & Outside

#52585.....35W Model 6000 Outside Fan Motor & Model 4000 Inside & Outside #525851..1/4 HP Fan Motor for Models 13K,18K,& 24K

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hi Lo Thermometer

Records the high and low temperature day and night. Also great for use in egg coolers

#59630..... Hi Lo Thermometer



Heater Elements

#52587	500 Watt
#525157	1000 Watt for 13000 cooler
#525853	for 9000-15e

Burch Egg Room Coolers

Burch manufactures packaged cooling units which can be equipped with 2 stage room heating to control a desired temperature in egg holding rooms all year long.

A humidification system is also available to protect egg shells from losing moisture in the egg holding room. Hatching egg units are able to cool down as low as 55 degrees F while table eggs units cool as low as 40 degrees F.

Manufactured using tough, durable powder coated steel cabinets, these self contained, through the wall, units require little maintenance and are simply built to enable easy service in the field. Shipped fully charged, installation is very quick and conditioning of eggs can begin in a matter of minutes.

Additional options available including custom painted exterior housing. Call for details.

MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Hatching Egg Coolers




Table Egg Coolers

DESCRIPTION	MODEL	OPTIONS	VOLTS	BTU	MIN TEMP	EGG HOLDING ROOM CU FT	WALL ROUGH OPENING (H x W)
BURCH Table Egg Cooler	3000-5TE	Room Heater, Humidifier	115	5800	40 F	800	22.25 x 22.25
BURCH Table Egg Cooler	4000-6TE	Room Heater, Humidifier	220	8300	40 F	1,000	22.25 x 22.25
BURCH Table Egg Cooler	6000-10TE	Room Heater, Humidifier	220	15200	40 F	1,500	22.25 x 22.25
BURCH Table Egg Cooler	9000-15TE	Room Heater, Humidifier	220	16300	40 F	2,500	24.25 x 30.25
BURCH Table Egg Cooler	13000-20TE	Room Heater, Humidifier	220	21800	40 F	3,300	32.25 x 36.25
BURCH Table Egg Cooler	18000-27TE	Room Heater, Humidifier	220	28000	40 F	4,900	32.25 x 36.25
BURCH Table Egg Cooler	24000-32TE	Room Heater, Humidifier	220	28900	40 F	5,800	32.25 x 36.25
BURCH Table Egg Cooler	50000-62TE	Room Heater, Humidifier	220	61000	40 F	13,800	45.25 x 48.25

Burch Egg Cooler Room Doors

Burch Insulated Cooler Room Doors feature a wood jointed torsion frame to insure strength and long lasting performance. These engineered doors feature ample

fiberglass insulation and an 18 gauge metal frame with a 22-gauge metal face, all powder coated for protection in harsh environments.

Each door includes heavy galvanized hinges, door handle, striker, safety pushrod and hex mounting lag screws. Standard and custom sizes available in Left or Right hand.



Note: With Left Hand Doors, the hinges are on the left and the door handle is on the right. With Right Hand Doors, the hinges are on the right and the door handle is on the left.

#3680	36" x 80" RH Swing/Opens to Outside
#52589	
#5284884	
	Sweep for Egg Cooler Room Door (Sold Per Foot)
#525881	Latch Only For Burch Egg Cooler Door

MARNING:





Hog Slat's integrated stanchion system features solid rod construction with a powder epoxy paint or hot-dipped galvanized finish.

Let us show you why more producers are choosing stanchions as their group housing option. Hog Slat is the industry leader in group housing with over 600,000 stanchion conversions or new projects completed. Stanchions offer these advantages over ESF and free access stalls.

- · Well-suited to current U.S. producton practices. Farm staff can more easily make the transition to a stanchion system because it utilizes the same feed delivery system and penning. Does not require a staff highly trained in maintaining complicated electronics.
- This design lends itself to a wide range of group sizes with a lot of flexibility in pen and building dimensions - an important consideration with remodel projects.
- Lower initial equipment costs than either ESF systems or free access stalls and less equipment to maintain and repair. Stanchion systems require over 14% less floor space than floor plans utilizing free access stalls.
- · More control over feeding compared to floor-fed pen systems. Feeding stanchions may also be used with total slats simplifying manure handling and pen management.




Optional double or single-sided stainless steel trough completes the installation.



Complete with illustrated pictures of equipment and diagrams of building layouts, this 16-page handbook contains practical details needed to build new sow housing or convert existing stalls to group housing.

Download your free copy at www.hogslat.com







Free Access Stall

In combination with Hog Slat's stanchion equipment, our Free Access Stall gives producers a management-friendly group housing system that meets welfare concerns without complex maintenance and communication issues found with electronic sow feeding.

- Balanced gate system does not require springs or weights for activation.
- Rear individual locks retain an animal when releasing the rest of a row.
- No weld installation with pre-punched top spacing bars.
- Heavy galvanized construction with 5/8" rod and 12 ga. structural pipe.
- All pivot points have stainless steel sleeve bushings.
- · Stainless steel hardware.





Top locking lever

shuts down or opens a row of stalls for breeding or treatment.



Stainless steel legs

adjust to fit slat openings and height differences for secure anchoring.



Feed pipe

and double water bracket bolt on stall.




Step through rear gate for breeding.

Gestation Stalls Parts


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



A) #5301080101	48" painted feed pipe - slope front
B) #5301110101	48" painted feed pipe - straight front
C) #5330080001	15-1/2" pipe, weld on replacement
D) #5301130000	Feeder pipe door clips
E) #5161040000	Gestation stall door clip







#59404..... Chase Gate Kit #2000150100 Chase Gate Hinge Only



A) #2040850100	Backup plate, ptd
B) #2040850200	Backup plate, galv.
#5330030100	Feed pipe clamp, ptd
C) #5330030200	Feed pipe clamp, galv.

U-Bolts

	5/16" x 2-1/2", zinc
#5331370001	.5/16" x 2-1/2" x 3-9/16" legs, zinc
	5/16" locknut, zinc
#5331370500	5/16" x 2-1/2" x 3-1/16" legs, s.s.
#5331370501	5/16" x 2-1/2" x 3-9/16" legs, s.s.
#60692	5/16" locknut, s.s.




Chase Gate

hook, bolts and nuts.

Top Spacers Pre-punched

#5010100100	114-3/4"x.23" o.c., painted
#5010200100	119-3/4"x 24" o.c., painted
#5010300100	129-3/4"x 26" o.c., painted
#5010100200	114-3/4" x.23" o.c., galvanized
#5010200200	119-3/4" x 24" o.c., galvanized
#5010300200	. 129-3/4" x 26" o.c., galvanized



Gestation Top Spacers Connectors

Used at end of top spacers for gestation stalls. Six needed per row of gestation stalls.

#5000920100	Connector painted
	Connector galvanized
#60647	1/4" V-bolt
	1/4" Lock Nuts

Gate Rods



- A) #5000100100 Standard 1/2" gestation gate rod (long door) 24-5/8" below bend
- #1000100200.......1/2" farrowing crate gate rod 19-1/4" below bend, galvanized

 B) #1000100100.......1/2" farrowing crate gate rod 19-1/4" below bend (Also used for short rear gestation door)
- C) #5000170100.......1/2" gestation gate rod 24-5/8" below bend, washer welded flush beneath bend (Used on long front door when washer is desired to prevent rod from falling through slats (long rear door w/ez clips) #5000100200 1/2" rod for stall door
- D) #1000090100......1/2" gate rod w/ bend 16-1/2" below washer (Used mainly on short rear gestation doors w/ez clips) #1000090200 1/2" gate rod w/bend 16-1/2" below washer, galvanized
- E) #50002602003/8" candy cane style rod 19-1/2" overall length (Used mainly as a replacement for solid rod gestation rear door)
- F) #5000120100.......3/8" gate rod w/ bend 19-3/8" below washer (Used mainly as a replacement for solid rod gestation rear door)



Weld-On Gestation Replacement Legs

#5000060100	Front Leg, 8 -5/8
#500000100	Rear Lea 9-5/8






Gestation Stalls

Hog Slat's unique bolt-together design requires no welding to install. Galvanized floor spacers along with bolt on top spacers ensure a straight installation with even stall spacing. Available in 7'0" or 7'6" lengths and widths of 22", 23", 24", 25", 26", 28".

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Other trough profiles available!

Gestation Trough

· Single sided bolt down

#8950590505....304 SS trough, single side bolt down, 8' long, 31 lbs #8000140500304 SS solid end plate, 2.2 lbs




Gestation Trough

• Double sided bolt down


#8950590511..... 304 SS trough, double sided bolt down, 8' long, 39 lbs #8000150500304 SS solid end plate, 2.5 lbs


#8000340500......304 SS end plate with 2" nipples, 2.5 lbs



Gestation Trough

Doubled sided bolt down









The AIP

The AIP is an improved model featuring an injection molded saddle that also provides a tighter fit. IT'S VIRTUALLY INDESTRUCTIBLE!

#1051102......AIP, injected molded



A.I. Buddy

A rugged "hands-free" insemination device with a solid plastic saddle and aluminum rods. Choose from two different rods; one for bottles and tubes and the other for bags. Designed without velcro or fabric that can deteriorate with use

. •	
1) #AIB	Saddle only
2) #AIBR	
3) #AIRT	Rod for tubes & bottles



Most Efficient Sow Stimulation, Heat Detection and Insemination System on the Market!

The Magic of Pheromones and Snout-to-Snout Contact!

Remote-Controlled, Self-Guided and Articulated Boar Cart... Designed by Pig Breeders for Breeders

WORLD-WIDE REPUTATION

Successfully proven and unique state-of-the-art heat detection tool. Renowned and adopted by the worldwide community of pig producers. Has revolutionized the productivity of the swine industry since 1997.

MAXIMUM STIMULATION

Genuine futuristic technology based on natural mating ritual of pigs. Contact-O-Max exposes boar to sows for optimal sustained snout-to-snout contact; optimizes sow fertility and makes work easier. Rigorous, precise, reliable and efficient heat detection system; requires only 15 seconds per sow twice a day to stimulate and heat check. Drastically decreases number of heat returns and late weaners. Guarantee of maximum stimulation and successful insemination.

OUICK PAYBACK

One of the most cost-effective pieces of equipment in a sow barn. Fastest and best return on investment; payback less than 2 months for 1000 sows. Yields farrowing rates up to 95%. Only one worker is needed.

#HSCJ20SXX	Coitact-O-Max Jr. 20" Wide Stainless Stee
#UCCC22VVV	Contact O May Cr Stainless Stoc





Handy Remote Self-Guiding System



Optimized Snout-To-Snout Contact



One-Worker Operation





Contact-O-Max Replacement Parts





 Internal Control box (for old SR model only) 	
#HSRMACX4003	4 button, freq. #4
#HSRMACX5003	4 button, freq. #5
#HSRMACX6003	4 button, freq. #6
#HSRMACX7003	4 button, freq. #7
External Control Roy (for IR & SR models)	

- External control box (for the dist inoders)			
#HSRMACX4001	4 button, freq. #4		
#HSRMACX5001	4 button, freq. #5		
#HSRMACX6001	4 button, freg. #6		
#HSRMACX7001			







Remote Controls & Batteries

#HSSEE1000005X	. Remote Control 1, White Label,	Freq #1,	Two :	Button
#HSSEE2000005X	Remote Control 2, Purple Label,	Freq #2,	Two:	Button
#HSSEE4000006X	Green Light,	Freq #4,	Four :	Button
#HSSEE5000006X	Blue Light,	Freq #5,	Four :	Button
#HSSEE6000006X	Yellow Light,	Freq #6,	Four :	Button
#HSSEE7000006X	Red Light,	Freq #7,	Four :	Button
#HSSEEP000006R	Touch Pad Membrane for 4	& 5 Boar	Cart F	≀emote
#8902260000	Battery for 4 Button Rem	ote Contr	ol - C	R2016



Battery

DCS-50u, 50 amp, for Contact-O-Max JR/SR

#HSSEB0000001P Battery



Battery Charger

Interior mount, for Contact-O-Max JR/SR

#HSSEE0000004X..... Battery Charger





Switches

For Contact-O-Max JR/SR

#HSSES0000006P.... Green Manual Forward Switch #HSSES0000005P Yellow Manual Backward Switch



ON/OFF Switch

For Contact-O-Max JR/SR

#HSSES0000008P ON/OFF Switch #HSSES0000018P.....Key Switch On-OFF



#HSSEM0000002A.....for new style JR & SR #HSSEM000004A..... for old style SR

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Axle Differential

#HSCJACX0012 #HSCSADX0001-A SR

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Axle Differential

for old style Contact-O-Max SR

#HSCSADX000224"

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Sprocket Axle

For Contact-O-Max SR

#HSSAG0000002A Sprocket Axle

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



3/4", for Contact-O-Max SR

#HSSAX000004S..... Steel Support Bearing



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bearing 1"

With steel support for old Contact-O-Max JR

#HSSAB0000006A1" Bearing

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Brake Handle

For Contact-O-Max JR/SR

#HSSAX0000002S..... Brake Handle



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Drive Gear Sprocket 40-30, for Contact-O-Max JR

#HSCJASX0049 Drive Gear Sprocket

⚠WARNING:



Nylon Rollers

#HSCJPAM0013	4" x 4" (front corner)
#HSCJPAM0003 3" x 4	4" (front corner old model)
#HSCJPAM00145" x 5"	(lateral rear roller OPTIONAL)
#HSCJPAM0077	5" x 4" (rear corner)
#HSCJPAM0078 4" x 5	" (lateral rear & front corner)
#HSCSPAR00295" x 5"	" (front & rear corner / for SR



Attachment Roller

For Contact-O-Max JR

#HSCJACX0008Attachment Roller



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Roller Bracket

L-shaped, for Contact-O-Max JR

#HSCJASX0038Roller Bracket



Gel Filled Wheel

For Contact-O-Max SR (use with hub transition)

#HSSAW000009AGel Filled Wheel



Air Filled Wheel

Plastic hub, for Contact-O-Max SR

#HSSAW000005A Air Filled Wheel



Hub Kit

#HSSAW1000005PPlastic Hub

Gel Filled Wheel

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hub Transition

For Contact-O-Max SR foam filled tire.

#HSCSASX0017 Hub Transition



Tire

For Contact-O-Max JR/SR

#HSSAW0000008A Tire



Casters

For Contact-O-Max JR/SR

#HSSAW000002A Caster for SR #HSAW000001 A Caster for JR



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Handle Assembly

#HSCJASX0041......JR

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Side Wheel Cover

For Contact-O-Max SR

#HSCSPAP0006.....Side Wheel Cover



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Collar Set

Metric, for Contact-O-Max JR

#HSCJPAM0066......Collar Set

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



J-Latch

For rear door, Contact-O-Max JR

#HSCJPAC0001 J-Latch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Top & Bottom Swivel Bolts

For Contact-O-Max JR

#HSCJPAM0006......Top Swivel Bolt #HSCJASX0042Bottom Swivel Bolt

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Transmission Release Handle

For Contact-O-Max JR

#HSCJPAC0012Transmission Release Handle

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Motor Mount

For Contact-O-Max JR

#HSCJPAP0019Motor Mount

⚠WARNING:




Advantage Farrowing Crate

The Advantage crate is our most versatile crate design.



Advantage Farrowing Crates are available with these options:



SEVERAL SIDE BAR OPTIONS. Allows you to build the crate that works the best for you. Options include: finger bar, finger bar with anti-crush bar, bow bar and bow bar with anti-crush bar.

MULTIPLE FEED AND WATERING OPTIONS.


Choose the feeder and water option that fits your needs: large or small bowl feeder, ad lib feeder or keep the feeder you have. Water with nipples or cups. It's your choice.




Advantage Crate Parts List - (Tubular)

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Key	Part#	Qty.	Description
1	1250500002	2	Side 7'-0"
1	1250542001	2	Side 7'-6"
2	1250420000	1	Finger Bar 7'-0"
2	1250460000	1	Finger Bar 7'-6" Right [85"]
3	125042000	1	Finger Bar 7'-0"
3	1250470000	1	Finger Bar 7'-6" Left [85"]
4	1250410000	2	Bolt-On Bar 7'-0"
4	1250380000	2	Bolt-On Bar 7'-6"
5	1250400000	2	Bow Bar 7'-0"
5	1250370000	2	Bow Bar 7'-6"
6	1260370000	2	Solid Anti-Crush Bar 40-3/4"
7	1250780500	2	Anti-Crush Bar Stop
8	1250050000	1	Water Bracket Bent
9	8150620500	1	Sampson Waterer SS [Large Bowl Door &
			Small Bowl Centered Door]
10	8150600700	1	European Waterer [Small Bowl Offset Door]
11	1250790500	4	U-Channel
12	1250850000	2	Top Strap 23-7/16
13	1250810000	1	Top Center Strap 40-1/2"
14	1000970700	1	Chart Plate 10"
15	1000160000	1	Heat Lamp Arm
16	1260101100	1	Front Door Offset [Small Bowl] Assembly
17	1250261100	1	Front Door [Small Bowl] Assembly
18	1250281101	1	Front Door [Large Bowl] Assembly
19	7150040500	1	Sow Feeder [Small Bowl] 304 SS



Key	Part#	Qty.	Description
20	7150070500	1	Sow Feeder [Large Bowl] 304 SS
21	1230050000	1	Retainer Rod [Small Bowl Offset]
21	5150020000	1	Retainer Rod [Large Bowl & Small Bowl Centered]
22	1231160000	1	Pivot Rod [Small Bowl Offset]
22	5150010000	1	Pivot Rod [Large Bowl & Small Bowl Centered]
23	9900020000	2	Hair Clip Pin (60635)
24	1250200020	1	Rear Door
25	1250900700	1	Rear Door (Sheet Metal)
25	1250890000	1	Rear Door (Polyboard)
26	1250310000	1	Bolt-On Rump Rail
27	1000100000	4	1/2" X 19-3/4" Crate Rod



Advantage Crate Parts List - (Solid Rod))


Key	Part#	Qty.	Description
1	1260600000	1	7' Side Bow Bar [Right]
1	1260600001	1	7' Side Finger Bar [Right]
1	1260610004	1	7'-6" Side Finger Bar [Right]
2	1260500000	1	7' Side Bow Bar [Left]
2	1260500001	1	7' Side Finger Bar [Left]
2	1260510004	1	7'-6" Side Finger Bar [Left]
3	1260420000	1	7' Solid Finger Bar
3	1260430000	1	7'-6" Solid Finger Bar [Right]
4	1260420000	1	7' Solid Finger Bar
4	1260440000	1	7'-6" Solid Finger Bar [Left]
5	1260400000	2	7' Solid Bolt-On Bar
6	1260450000	2	Finger/Bolt-On Bar Brace
7	1260460000	2	7' Solid Bow Bar
8	1260470000	2	Bow Bar Brace
9	1260370000	2	Anti-Crush Bar
10	8150620500	1	Sampson Waterer Ss
11	1260890000	2	Waterer Backup Plate


Key	Part#	Qty.	Description
12	1260800000	2	Top Strap
13	1250810000	1	Top Center Strap
14	1000970700	1	Chart Plate 10"
15	1000120000	1	7' Heat Lamp Arm
15	1000160000	1	7'-6" Heat Lamp Arm
16	1250261100	1	Front Door [Small Bowl] Assembly
17	1250281101	1	Front Door [Large Bowl] Assembly
18	7150040500	1	Sow Feeder [Small Bowl] 304 Ss
19	7150070500	1	Sow Feeder [Large Bowl] 304 Ss
20	5150020100	1	Retainer Rod
21	5150010000	1	Pivot Rod
22	9900020000	2	Hair Clip Pin (60635)
23	1260200000	1	Rear Door
24	1250900700	1	Rear Door Punch
25	1250310000	1	Bolt-On Rump Rail
26	1000100000	4	1/2" X 19-3/4" Crate Rod

Swing Side Farrowing Crate

Hog Slat's Swing Side provides maximum flexibility in crate design when undertaking complex remodeling or state-of-art new construction. Choose from multiple options to build the best farrowing crate for your next project.

Base model with stationary head gate mounts against wall or head-to-head layouts. SowMAX feed dispenser eliminates need for front alley.





The crates sides swing open to aid sow handling when filling or unloading crates.

Choose a Walk-Thru gate for floor plans with a front alley. Shown with small bowl feeder, SowMax and bow bar sides. All models are available in tubular or solid rod construction.






Anti-crush bar slows sow ascent to limit pig losses.




Simple height adjustment of bottom rail.

Customize the Swing Side crate with finger bar sides, large capacity feeder with either a galvanized or painted finish.









Options include several styles of rear gates.



ATT® Ultimate Farrowing Crate



Rear Door

Solid plastic door with double vertical rump rails.





Welfare-friendly loop style fingers precisely placed for excellent teat access and pig protection. Standard anti-crush bars slow sow's descent to save pigs and flip up when sow stands.

Large Wet/Dry Bowl Feeder

Optional large Wet/ Dry sow feeder features pivot-inplace, tip-out easy cleaning. 16" width provides maximum head room for sow comfort.






Ultimate Crate Parts List

1) #1700100100Ultimate Crate Front Door (small feeder)
#1700110100 Ultimate Crate Front Door (large feeder)
2) #1700800100Ultimate Crate Top 51"
3) #1700650100 Ultimate Crate Side Right (7'6")
#1700600100 Ultimate Crate Side Right (7'0")
4) #1170550100 Ultimate Crate Side Left (7'6")
#1700500100 Ultimate Crate Side Left (7'0")
5) #1700900000 Ultimate Crate Rear Door PVC Panel
6) #1700010100 Ultimate Crate Rear Gate Rod
7) #1700300100Ultimate Crate Rump Rail
8) #1700200100Ultimate Crate Rear Door
9) #1240400100 Ultimate Crate Anti-Crush Bar
10) See Page 89 for Feeder Options
11) #1000970700Chart Plate 10"
12) #8150620700 Sampson Waterer (56612)
13) #7150890500 SowMAX Feeder
14) #60539 1/2" x 3" Bolt
15) #606831/2" Locknut
16) #9403752102 3/8" x 1-1/2" Bolt
17) #9623750310
18) #605813/8" Flatwasher
19) #60682
20) #60702U-bolt 5/16" x 1-3/8" x 1-13/16"
21) #60681 5/16" Locknut
22) #60531 1/4" x 3/4" Bolt
23) #60680 1/4" Locknut
24) #9623130511 1/4" x 1-3/4" U-bolt

⚠WARNING:




Sampson Crate Parts List - Painted

Inis product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov		
1) #1010640111	Sampson Side 7'0" Rt.	
#1010650111	Sampson Side 7'6" Rt.	
#1010640100	Sampson Side 7'0" Rt. (Old Style 1994-95)	
#1010650100	Sampson Side 7'6" Lt. (Old Style 1994-95)	
2) #1050200100	Rear Door (Standard)	
#1010230100	Rear Door (Bolt-On Rump Rail)	

⚠ WARNING:


3) #1010540111	Sampson Side 7'0" Lt.
#1010550111	Sampson Side 7'6" Lt.
#1010540100	Sampson Side 7'0" Lt. (Old Style 1994-95)
#1010550100	Sampson Side 7'6" Rt. (Old Style 1994-95)
4) #1000100100	19-3/4" Gate Rod
5) #1010810102	Short Top
6) #1010830100	Side Top
7) #1010850100	Front Top
	Long Top #3
	Front Door (Small Bowl Ass'y)
	Front Door (Large Bowl Ass'y)
	Rump Rail, Hanging
	Rump Rail Murphy Style, Bolt-On
	Rump Rail
12) #1010350100	Rump Rail Rod
,	Feeder (Small Platinum) 304 SS
	Feeder (Large Platinum) 304 SS
,	Retainer Rod
	Pivot Rod
16) #1010400100	Pivot Bar 57-1/2" for 7'0"
	Pivot Bar 63-1/2" for 7'6"
	Bow Bar 7'0"
	Bow Bar 7′6″
	Bow Bar 7'0" (1994-95)
	Bow Bar 7'6" (1994-95)
	Heat Lamp Arm
•	Hair Clip Pin
,	Sampson Water
	Rubber Sleeve
,	
	Sheet Metal Rear Door (Bolt-On Rump Rail)
#1050880000	Polyboard (Standard)



European Crate Parts List


1) #1230140101	
2) #1230500100 #1230510100	
3) #1230600100	Right Side 7'0"
#1230610100	Right Side 7'6"
4) #1230360100	Left Side Finger Bar 7'0"
#1230370100	Left Side Finger Bar 7'6"
5) #1230380100	Right Side Finger Bar 7'0"
#1230390100	
6) #1230810100	
7) #1230820100	
8) #1230800100	
9) #1230300100	
10) #7150040500	
11) #1000100100	
12) #1231160100	
13) #1230050100	

14) #1230310100	Rump Rail Rod
	Hair Clip Pin
16) # 8150600700	Nipple Water Assy
NA) #1232600200	Water Assy Bracket, 1-1/2" x 4", Galv.
	See page 78 for U-Bolts
17) #1000120100	Heat Lamp Brkt Arm
18) #1230400100	Bow Bar 7'0" (Regular)
#1230410100	Bow Bar 7'6" (Regular)
19) #1230440100	Bow Bar 7'0" (Straight)
#1230450100	Bow Bar 7'6" (Straight)
21) #1230100100	Euro Front Door (Flat Bottom Feeder)
22) #7150070500	Large Feeder 304 SS
23) #1231320100	European Latch Rod
24) #1230200100	Rear Door
25) #1230900700	Galv. Sheet Metal for Rear Door
	PVC for Rear Door 16" x 19-1/2"
26) #1000970700	Chart Plate
	Bolt on Bar 7′0″
	Bolt on Bar 7'6"



Bow Bars, Painted

A) #1010420100	80-1/4" (7' for old style crates 1994-1995)
•	
•	84-1/2" Current 7'6" (For Current Sampson Crate Produced 1995 to Present)



Creep Panel Starter Angle

Secure end creep panel in place with this stainless steel clip. Mounting hardware not included, suggested hardware for mounting to TriDEK:


(1) 3/8" x 1-1/2" SS bolt (60610) (2) 3/8" SS washer (60670)

(1) 3/8' SS locknut (60612)

#1000200500 SS starter angle

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#1000750100	2-way, left, painted
#1000750200	2-way, left, galvanized
#1000740100	2-way, right, painted
#1000740200	2-way, right, galvanized
#1000650100	3-way, front creep, painted

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Bow Bar for Euro Crate

#1230400100 7	(regular bend
#1230410100 7'6'	' (regular bend

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Finger Bars for Euro Crate

#1230380200	Right Galvanized Euro 7'
#1230360200	Left Galvanized Euro 7'
#1230380100	Right Painted Euro 7'
#1230360100	Left Painted Euro 7'
#1230390200	Right Galvanized Euro 7'6"
#1230370200	Left Galvanized Euro 7'6"
#1230390100	Right Painted Euro 7'6"
#1230370100	Left Painted Euro 7'6"

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Crate Replacements Legs, Painted

#1010960100	Universal Sampson, Right 7"
#1010920100	Universal Sampson, Left 7"
#1230930101	Euro, Left Side, 12"
#1230930111	Euro, Right Side, 12"

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Galvanized and Stainless Steel **Creep Panels**

Rugged creep panels are constructed of 16 ga. steel in your choice of galvanized or

lengths to match your crates and flooring configuration.



Call us for details and a quote on specific panel lengths.

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Poly & Galvanized Rear Door Panel

... 19" x 19-1/2", Galv. (Euro)

#1050900700 19-1/8" x 21", Galv. (Humboldt and Sampson)

#1010900700 21" x 25-3/8", Galv. (bolt-on rump rail)

#1231840000 ... 1/8" x 19" x 19-1/2" Poly Replacement Door (panel only)

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



10-inch wide plate with 2 bends.

#1000970700......Chart plate **#1097**.....3" bulldog clip

⚠WARNING:





AdLib Sow Feeder

With SowMAX you'll do a better job of feeding lactating sows and you'll do it with less labor. Fill the hopper in the morning and fresh feed is always available... day or night. Reduce labor. Reduce feed waste. Feed sows better.

SowMAX offers these advantages:

100% Stainless Steel construction.

There are no plastic parts to wear or go out of adjustment.

No motors or electronics.

Many systems use a metering motor to dispense the feed and ear tags to start the motor. SowMAX uses the simple action of the sow activating a lever - no motors to replace or ear tags to lose.

Adapts to existing feeders and delivery systems.

Choose from a 16 lb. hopper for hand filling or install with a feed system to automatically fill the dispensers. Adapts to most existing farrowing feeders with simple brackets.

Positive actuation and adjustment.

Other systems utilize a bumper ball or bar that can vary in the amount of feed delivered. With SowMAX, you adjust the amount, and the trigger mechanism dispenses that exact amount every time the sow activates the lever







SowMAX Dispenser

#7150890500...... SowMAX dispenser (439 SS) Mounting Hardware Requires Two Each

1) #60501 1/4" x 3/4" zinc bolt 1) #60680 1/4" lock nut




SowMAX Hopper


#HS535Plastic 16 lb. hopper

SowMAX eBook

Illustrated SowMAX manual with instructions for feeding lactating sows. Download your free copy at www.hogslat.com

Learn more about the advantages of SowMAX dispensers feeding weaned sows in breeding. Go to www.hogslat.com and search for SowMAX. You'll find blogs and videos with more information.





Feed Hoppers w/ Grain Gate

Heavy galvanized steel hopper available in 200 and 400-pound sizes. Painted grain gate with 8" x 20" opening fills feed carts fast. Mounts from the ceiling with four 36" long painted brackets. Unassembled.

#7060611700	24" x 36" x 32" Unassembled
#7060621700	
#7000360000	

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Farrowing Drop Feeder

- Flexible sleeve for full range of movement
- · Spring-loaded stainless steel discharge cup
- 3" x 36" drop tube with volume markings and slide band

#HS738..... Farrowing drop feeder





WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Hand crank adjusts tube height with indexed markings for repeatable settings.

Sow Feeder with PVC tube

#7160250500..... 16" wide, Left (pictured above) #716025150016" wide, Right

Longer Lasting Slats that Are Easier on Feet and Joints

Many methods used for producing concrete slats consist of placing wet cast concrete into multiple steel forms and hand troweling to finish. It is harder to build slats with a consistently flat surface by hand finishing methods. We produce slats with a different process that eliminates the uneven surface found on hand cast slats. Automated Rotoscreeds "strike off" the mold creating a level, uniformly flat top that is easier for pigs to move across.

After placing the concrete, spinning ROTOSCREEDS strike off the mold. This machine process enables us to work the ZERO slump mixture. It's not possible to work ZERO slump concrete by hand troweling. Our automated process eliminates the variation caused by hand troweling. One of the key features of our slats is the uniform FLAT top which is easier on your pigs' feet. There are no humps on the slats caused by hand troweling the edges.

Steam Curing Reduces Variation

After casting, each slat is STEAM CURED in climate-controlled tents. Steam provides the heat necessary for accelerated curing and the moisture to prevent stress cracks and shrinkage. In only a



Machined Slat (cross-section)



few hours, we are able to harden slats that exceed 28-day strengths of normally cured concrete. Hot, dry weather or cold, wet conditions don't affect the quality of the slats delivered to your farm. It is very important proper steam curing procedures are followed to ensure long-term durability of the slats. The rate of temperature gain and the maximum temperature in the curing chamber must be controlled and monitored using accepted industry guidelines and practices. Failure to do this can result in a shortened life span of the concrete slats due to delayed ettringite formation (DEF), a condition that leads to early deterioration of the concrete when exposed to an environment similar to that found in a hog barn.



Low Cement-Water Ratio Yields Longer Lasting Slats

The water-cement ratio refers to the ratio of the water weight to the cement weight used in a concrete mix. A lower ratio leads to higher strength and durability but makes the mix difficult to work with and form. For this reason, most slats are produced with wet cast concrete using a water-cement ratio of 0.5. Hog Slat manufactures slats



from dry cast concrete with a water-cement ratio of less than .39. A cubic yard of wet cast concrete formulated with 500 pounds of cement contains 250 pounds of water, while a dry cast mix only contains 195 pounds. As the excess water leaves during the curing process, it creates microscopic pores that reduce the final strength of a slat.



Dry Cast Concrete

23.4 GALLONS WATER

.38 Cement-Water Ratio 500 lbs. Cement

Wet Cast Concrete

30 GALLONS WATER

.50 Cement-Water Ratio 500 lbs. Cement



Hog Slats

Hog Slat is the world leader in the production of high quality concrete slats. Machine manufactured with a strong, dry cast concrete mix and reinforced with high tensile steel mats.



Standard sizes include 4' width and either 8' or 10' lengths. A special 2' width is available for remodeling. Choose 1" openings for wean to finish or 1-1/2" slots for gestation and breeding. All concrete gang slats are 4" in depth with broom finished 5" top.

#1214	2'x 8'x 1" slot
#1218	4' x 8' x 1" slot
#1222	4'x 8' x 1-1/2" slot
#1213	4' x 8' solid (no slot openings)
#1231	2' x 10 x 1" slot
#1228	4' x 10' x 1" slot
#1236	4' x 10' x 1-1/2" slot
#1230	4' x 10' solid (no slot openings)

T Slats

Single T Slats are great choice for replacing slats in older facilities. Self-spacing design maintains accurate 1" slot spacing while allowing the opposite end to be cut to length. Slats are 4" in depth with 6" broom finished top.



#1314T	4′
#1316T	5′
#1318T	6′
#1320T	7′
#1322T	8′
#1324T	9°
#1326T	10′

Lintels

High strength concrete lintels are key to providing solid support for concrete flooring systems. Manufactured with the same dry cast process as our slats to hold up under the harshest conditions.



:1440	8	3′ 2	k 8"	Х	10'	long
1442	8	"x	10"	Х	10'	long
1444	8"	X	10"	Х	12′	long



We are the leading Slat Replacement Professionals in the U.S.



When our team of professionals starts a project they commit themselves to get it done in the timeliest manner possible.

We use the latest tools, techniques and equipment. By doing our own site work, we have better control of the project schedule and can expedite the project which helps cut our clients downtime and saves them money as well!

Every customer is unique, every situation is different. People turn to us for many reasons, but the #1 reason is Trust!

Working with Hog Slat to provide the best slat replacement in the US.

- Inspections
- Slat and beam replacement
- Barn conversions
- Post Repair
- Equipment removal and installations





1-888-435-2210

www.altenburgconstruction.com

office@altenburgconstruction.com

221 PV Street N. • Lewisville, MN 56060

É ÉLAT® Feed Bunks

- High-strength steel reinforcement
- Minimum of 5,000 psi concrete
- Pre-formed front holes for mounting accessories and posts
- · High back wall to prevent feed waste
- · Chamfered front and rear wall top to prevent injury
- · Smooth interior to promote complete clean up and improved sanitation
- Front and rear 2" chamfers in the trough to eliminate corners feed could accumulate.
- *10' Long x 23" Wide x 16" Deep (Trough Measurements)
- · Weight: 4,000 pounds.

10' MEGA Slope-Back Bunk Mold



75° 2" long chamfers

2" long chamfers

10' MEGA Straight-Back Bunk Mold




Cattle Slats

Cattle gang slats are 4' wide and are available in either 8', 10', 12' lengths. Cattle slats are 6" deep with 6-1/2" slat tops and 1-1/2"openings. Slats come standard with a broom finish. Lintels feature extra steel support and stirrups.

#1334	4′ x 8′
#1336	4′ x 10′
#1338	4′ x 12′
#1330	4' x 8' solid
#1332	4' x10' solid
	0" v 10" v12' long gottle lintel









CATTLE BARN CONSTRUCTION SERVICES

With extensive resources of each phase of the construction project, you can be assured Hog Slat has you covered. Our unique position as a national turn-key construction contractor allows us to control and ensure the finished quality of all project phases and installation of equipment including our pre-cast cattle feeding bunks, pre-cast cattle slats (deep pit systems), and other required systems.

Backed by innovative engineering, technology, and more than 50 years of industry experience we strive to deliver quality products and services to agricultural producers.

With extensive resources for each phase and design of your project, you can be assured Hog Slat has you covered.

Included in all of our projects:

- Consultation
- Blueprints

- Building design
- Compete building construction
- · Site supervision of all construction phases







Floor Frames

- · Heavy-duty Hog Slat farrowing frames are constructed from 3/8" x 2" bar stock.
- · Nursery frames are constructed from 1/4" x 2" or 3/8" x 2" bar stock.
- · After fabrication, they are cleaned and powder coated to produce a high quality, baked-on enamel finish
- · Many sizes available



Painted	Galvanized	Description
#3110680100		4' x 8' - Nursery frame
#3110660100		4' x 10' - Nursery frame
#3110600100		5' x 10' - Nursery frame
#3120180101	#3120180201	4' 6" x 7' - Farrowing frame
#3120040100		4' 6" x 7' 6" - Farrowing frame
#3120100102	#3120100202	5' x 7' - Farrowing frame
#3120140101	#3120140201	5' x 7' 6" - Farrowing frame
#3120280100		5' 6" x 7' 6" - Farrowing frame

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



5	#3100730100	#3100 1 30100	#3100120100
#31007201	.00	Angle leg,	5-3/4" , Left, Painted
#31007202	200	Angle leg, 5-3	/4", Left , Galvanized
#31007301	.00	Angle leg, 5	-3/4", Right, Painted
#31007302	200	Angle leg, 5-3/	4", Right, Galvanized
#31004301	00	Angle leg,	4", Straight, Painted
#31004302	200	Angle leg, 4",	Straight, Galvanized

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Woven Wire Flooring

- · Wire flooring is unequaled for thorough flushing and self-cleaning.
- Available in any size in either 3 gauge or 5/16"

Standard Farrowing sizes:

• 5' x 7'

Floor


Leas

Frame

• 5' x 7'6"

Standard Nursery sizes:

- 4' x 8'
- 4' x 10'





This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Plastic Flooring

High-tech injection molding from virgin quality Polypropylene Copolymer creates durable, long-lasting plastic flooring. Available in multiple grid configurations and sizes, Hog Slat's plastic flooring adapts to any building scheme.





Self-cleaning, 3/8" slots arranged in a multidirection pattern give nursery pigs optimum traction. Sturdy design supports wider spans, reducing support beam costs. Suitable for pigs up to 130 lbs.

#MK00337-HS	24" x 23-5/8"
#MK00112-HS	24" x 3-15/16"



DUO Support Beams

Composite fiberglass beam ensures a stable and durable flooring support. End cap protects and supports beams.

#MK22000 L, 4.75"	high
#MK20000 XL, 6"	high



DUO Support Leg Set


Provides intermediate support for longer beam installations

#MK24100	Upper & lower bracket, no pipe
#MK25201	Green, fiberglass support tube, 72" long




Modular Plastic Farrowing Floors

Modular components are configured to match almost any size of farrowing layout. Choose from durable cast iron or Swing plastic center sections paired with interlocking creep sections.








Triangular surface bars make it the cleanest floor!

- It stays cleaner easiest to clean between groups
- Cleaner than the other floors on the market



All TRIDEK Flooring is RESISTANCE WELDED for superior strength.



Multiple surface options

- Smooth or No-Slip Dimpled surface to provide your preferred level of traction.
- Standard flat deck or optional traction breaks.



Great for nursery and farrowing remodels!

- · Hot-dipped galvanized for longevity
- 30" standard width
- Available in custom sizes up to 144" long.

Cast and TRIDek Combo

This unique combo offers producers a distinctive option. Self supporting galvanized TRIDEK creep sections lock the two-piece cast into a stable farrowing platform. The two-piece cast center section eliminates multiple joints.

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



TRIDEN Floor Patch



1. Cut out the section of damaged wire along floor frame supports





2. Insert TRIDEK patch in floor catching the Z Hooks under the support in the front of the cut out



4. Crate anchors hold the TRIDEK patch in place



MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Custom sizes are available to match your floor!

- The TRIDEK Patch allows a producer to cut out the worn wire flooring, then replace it by dropping the TRIDEK Patch in.
- ullet Dropping in the TRIDEK Patch is easier installation than other patches. TRIDEK also stays cleaner than wire or cast.



TRIDEK Floor Patch (24-5/16" x 84")

• For replacing the entire center of the floor

#318081020024-5/16" x 84"





- Finish plank For animals 120 lbs. and up
- Nursery plank For animals 30 lbs. to 120 lbs.
- Creep plank For animals up to 30 lbs.
- · Field cut to fit

#HSCP-1016	
#HSCP-1013	
#HSPN-15020	1-1/2" x 30" x 20' Nursery plank
#HSPN-15024	
#HSPC-07821	
	,






SINGLE POST 1-1/2": AP-3238 2": AP-3234




DOUBLE LOOP POST 1-1/2": AP-3239 2": AP-3235



POST BACK TO BACK 1-1/2": AP-3246 2": AP-3232



SINGLE LOOP POST 1-1/2": AP-3240



POST WALL BRKT 1-1/2": AP-3309 2": AP-3308

#GAP-3238	
	Post, 2" x 39" - U-Channel single
#GAP-3246	
#GAP-3232	Post, 2" x 39" - Back to Back U-Channel
#GAP-3240	Post, 1-1/2" x 31" - Single Loop
#GAP-3236	Post, 2" x 39" - Single Loop
#GAP-3239	Post, 1-1/2" x 31" - Double Loop
	Post, 2" x 39" - Double Loop
#GAP-3309	
#GAP-3308	Wall Bracket - 2" Single Loop



End Cap

• Install with PVC glue to seal ends

#GCP78EC-1P......7/8" x 10'



Drop Rod End

#GNP15DRE-1P1-1/2" x 20' #GFP2DRE-1P......2" x 20'



#GFP34DR-1P3/4" x 20'



U-Channel

#GCP78UC-1P	7/8" x 20'
#GCP118UC-1P	
#GNP15UC-1P	1-1/2" x 20'
#HSPU-20020	2" x 20'






Tongue & Groove Plank (Locking)

#HSPTG-20020	2"	Х	8"	Х	20'
#HSPTG-20024	2"	х	8"	х	24'



Stainless Steel Hardware

· Available for nursery & finish



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

PVC Posts

• Posts are sized for 1.5" x 30" and 2" x 38" PVC plank

• Slots in the base plates are 3/8" x .750"

• Channels are pre-punched with 5/16" holes





Hog Penning Equipment

Hog Slat offers a complete line of economical hog penning equipment in your choice of powder epoxy paint or hot-dipped galvanized.

Features Include:

- Top angle: 1/8" x 1-1/2" Horizontal rods: Solid 1/2" with 3/4" bottom rail
- Uprights: 1/4"x 2"
- AVAILABLE OPTIONS:
- 3/8" end uprights.
- 3/16" top angle
- 1/4" top angle - 1-1/2" uprights

Standard Sizes include

31.5" - 7 rod	Nursery, wean/finish and finishing
36"- 8 rod	Special wean/finish
40"- 6 rod	Standard Gestation/Breeding
40"- 9 rod	Special Gestation for wean/gilt grow-out



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

DIY Cut & **Weld Panels**



See It In Action! Scan for YouTube Cut & Weld **Hog Panels video**

#4470108160 Panel: 31-1/2", 6-9 #4470144160 Panel: 31-1/2", 9-12




1. Knock loose tack welded upright and slide along rod to correct length.



2. Cut off excess rod and weld to upright.



3. Attach clips and/or pipe fitting to each end. Spray welds with matching paint to complete the panels.



#2002010000 2" x 2" x 30" Post Tube #2002000000...... 2" x 2" x 40" Post Tube #201170000030" Upright w/ 7 holes #2011610000...... 40" Upright w/ extra holes #203101000031.5" Upright w/ 7 holes

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Rodded Door Clip

• Use for farrowing crates up to 1" OD pipe.

#5101100000 Rodded door clip

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Crate Door Clip

• Use for farrowing crates up to 1.315" or 1.66" OD tube.

#1275250000 Crate door clip

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




8" x 16" Base Plate

#2001450000 1/4" thick #89612800001/2" thick

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Double Hole Aisle Clip

#5301140000 Double Hole

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Post Gusset

#5001800000 Post Gusset


♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Plastic Post Cap

#8221200000Plastic Post Cap



Single Hole Aisle Clip

#2011000000 Single Hole

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Angle Divider Clips

#8954300000......Angle Divider clips

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Flat Bar Clip

#1274060000Flat Bar Clip

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Divider Clip Pipes

A) #9101000511 1" x 3" Pipe (below divide clip) **B)** #91010005021" x 19-1/2" Pipe C) #2030630000....Gate Clip w/ Pipe Between Clips

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Flipper Latch

- #2050980200... Flipper Latch, Heavy Duty 3-3/8" Galv **#8951860101** Flipper Latch #60682......3/8" lock nut

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Latch Clips

#2011060000......3" Top latch clip

#2011070000 3-1/2" Bottom latch clip

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hog Slat Blue Spray Paint (New Blue)

#59722 New Blue spray paint

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


Galva Zinc Spray-On Galvanizing

Galva Zinc is cold galvanizing spray that protects galvanized metal after welding, cutting or drilling. This 90% pure zinc, epoxy-based formula drvs to the touch in as little as ten minutes and can be recoated in one hour.



▲WARNING:

Δ	G M.
Λ.	G. M.
В.	H. N.
C.	
0.	I0.
D	J
Cato E.	P
Gate E.	Q.
Poda E	L
Rods F.	R.
4) #2000100100 1/2" gate rod w/ bend	36" below washer (Used on front gates w/ 30", 31-1/2", 36" & 40" equipment)
#2000100200	36" helow washer galvanized
B) #2000340100 1/2" gate rod w/ bend	28" below washer (Used on front gates w/ 30", 31-1/2", 36" & 40" equipment)
#2000340200	
	23-1/2" below washer (Used on front gates w/ 30", 311/2", 36" & 40" equipment)
#2000060200	
D) #2000300100	
(Used for gates, any location, wall brackets & feeders w/ 30",	
#2000300200	
E) #2020100100	tht handle 23-1/2" below washer
(Used for gates, any location, wall brackets & feeders w/ 30",	
#2020100200	
F) #5000100100 Standard 1/2" gestation	n gate rod (long door) 24-5/8" below bend
#1000100200	
G) #1000100100	ate rod 19-1/4" below bend (Also used for short rear gestation door)
H) #5000170100	1 24-5/8" below bend, washer welded flush beneath bend
(Used on long front door when washer is desired to prevent ro	
#5000100200	
	16-1/2" below washer (Used mainly on short rear gestation doors w/ez clips)
#1000090200 1/2" gate rod w/bend	16-1/2" below washer, galvanized
	rod 19-1/2" overall length (Used mainly as a replacement for solid rod gestation rear door)
#5000260200 3/8" candy cane style	
K) #50001201003/8" gate rod w/ bend	19-3/8" below washer (Used mainly as a replacement for solid rod gestation rear door)
L) #1010350100 5/8" Sampson rump ra	ıil rod
#1010350200 5/8" Sampson rump ra	
M) #1100050100 5/8" Sampson feeder in	
#1100050200 5/8" Sampson feeder i	
N) #11011601003/4" Sampson feeder p	
#1101160200 3/4" Sampson feeder p	
0) #1230310100	
#1230310200 5/8" European rump ra	
P) #1230050100 5/8" European feeder	
#1230050200	
Q) #1231160100	·
#1231160200	ptvot rod, gatvanized This product can expose you to chemicals, including nickel, which is
R) #1100370100	
#1100370200 5/8" adjustable crate r	ump raii rod, galvanized




Wall Brackets

	A
#2020950200	30" universal, w/pipe inside, galvanized
	30" universal, w/pipe inside
#2020760200	30" universal, w/3" pipe, galvanized
D) #2020760100	30" universal, w/3" pipe
#2020750200	28-1/2" universal, galvanized
C) #2020750100	28-1/2″ universal
	30" w/flipper bar, galvanized
B) #8950930100	30" w/flipper bar
	30" w/flat bar, galvanized
•	30" w/flat bar

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#7000540500.....SS Feeder Bracket for 4" block wall **#7000490700**......Galv. Feeder Bracket for 6" wall, 10" long #7000640700 Galv. Feeder Bracket for 6" wall, 5" flange



A) #2020290203 29" Flat bar, 2"x 17" foot

Bolt-On Legs

- B) #2000830200 29" Flat bar, 8"x16" plate
- C) #2020520202 29" Flat bar, w/ 2"x17" foot, gate clip w/ inside pipe one side
- D) #2040050201 29" Flat bar post, 2"x19" foot, with divider clips



The tabbed design allows installation from above the floor without extra tools. Slide the encased nut assembly through the flooring slots and the winged tabs hold it in place until the bolt is tightened. After securing equipment the wings can be cut off. Package of 4.

#HS652-50......M8-1.25 x 50mm long bolt #HS652-90......M8-1.25 x 90mm long bolt

- · Mounts on any brand of angle bottom penning
- · Hot Dipped Galvanized
- Use where bottom angle has rusted preventing the use of a standard angle leg
- 2" x 17" Foot

• 1/4" Stainless Steel construction


EIP style gating

· Use for mid gate leg for

• Height -12" • Wt -6.9 lbs

#5000641200 Angle Bottom, Bolt-On Leg Pkg

- Hot Dipped Galvanized or Stainless Steel
- · Adapts to Any Horizontal Fencing
- · Complete with bolts, nut, washers and back-up plate





- · Heavy Stainless Steel Leg for Angle Penning
- · Mounts to Any Brand Angle Bottom Gate
- #5000841500 for angle bottom penning #5000850500..... bolt-on top bracket



#5000870500 For middle of panel (EIP style)

- 1/4" Stainless Steel Construction
 - · Mounts on the end of EIP style penning or at a feeder
 - #5000880500...... For end of panel (EIP style)



#8250730208 8"x 13" Plate w/ 6" x 1-3/4" solid shaft

· Comes with Stainless Steel bolt

" #3090451000	1/2" x 4-1/2" - Cast Iron
#3090451002	1/2" x 5-1/2" - Cast Iron
#60583	1/2" flat SS washer
#60831	SS Bolt 1/2" x 4-1/2"
#60828	SS Bolt 1/2" x 5-1/2"
#3090700000	Cast Iron tee only



T-Bolt and Nut Package

• Includes hex nut & washer

#3090401500	3/8" x 1-1/2" - Stainless
#3090421500	3/8" x 5-1/2" - Stainless
#3090601500	1/2" x 5" - Stainless
#3090441500	1/2" x 5-1/2" - Stainless
#3090521500	1/2" x 6-1/2" - Stainless

STOP DROPPING T-BOLTS INTO THE PIT!!!

T-Bolt Wrench

- Holds T-bolts in place while you tighten the nut.
- · Allows you to replace T-bolts from the top of the slats.
- · Makes installing T-Bolts simple!






#3090910100 T-bolt wrench



Hog Slat feeders are the benchmark for efficient feed conversion. Choose from multiple options in width, length, and feed adjustments to fit your feed management style.

• Magnum Series





Choose our Magnum option, in either Finish or Wean/Finish models for an additional 2" of head room.

• Feeder Adjustments

Lever Loc

- Powerful, smooth operating lever with 25 positive locking stops
- Indexed plate provides visual, repeatable confirmation of settings
- Increased leverage eases adjustments even with a full feed pan
- Precise 1/16" of adjustment per stop



AccuCrankTh

- Screw adjustment moves the feed gate 1/16 of an inch per revolution, allowing finetuned feed gate positioning.
- Positive lock slots prevents pigs from wiggling the slide gate out of adjustment.



Trough Dividers




Wean/Finish

Our **HyVis Divider** provides separation without restricting operator's view of the trough. Rugged four-bolt attachment stays in place.



Wean/Finish

Solid panel dividers limit pig contact and reduce aggression.



Finisher

5/16" stainless steel rodded dividers.



Nursery

Full depth dividers prevent pigs from lying in the trough.





Easy Clean Feeder Handle

The Easy Clean Feeder Handle eases the hassle of cleaning feeders. The top leverage handle adjusts to fit any feeder length. One person can easily tip any size feeder without removing it from the fence line. The Easy Clean Feeder Handle also reduces feeder damage caused during clean-out.

#7000721200	Galvanized For finish feeder
#7000721100	Painted For finish feeder
#7000811100	Painted For nursery feeder

♠ WARNING:



Her GLAT Wean to Finish - Magnum Series

🗘 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

· Wider width provides 2" more headspace

Trough Depth

• 304 stainless steel • 36" high Single side - 17-1/2" Double side - 29" · 18 gauge construction 11" for the Magnum

Length	# Holes	Adjustment	Trough Divider	Capacity	Shipping WT	Double Sided Item #	Single Sided Item #
40	3	ACCUCrank	HyVis	364	120	FDRZ4036D3CRCB	FDRZ4036S3CRCB
42	3	ACCUCrank	HyVis	382	122	FDRZ4236D3CRCB	FDRZ4236S3CRCB
45	3	ACCUCrank	HyVis	410	131	FDRZ4536D3CRCB	FDRZ4536S3CRCB
50	3	ACCUCrank	HyVis	455	145	FDRZ5036D3CRCB	FDRZ5036S3CRCB
56	4	ACCUCrank	HyVis	510	157	FDRZ5636D4CRCB	FDRZ5636S4CRCB
60	4	ACCUCrank	HyVis	546	164	FDRZ6036D4CRCB	FDRZ6036S4CRCB
70	5	ACCUCrank	HyVis	637	188	FDRZ7036D5CRCB	FDRZ7036S5CRCB
75	5	ACCUCrank	HyVis	683	204	FDRZ7536D5CRCB	FDRZ7536S5CRCB
40	3	ACCUCrank	Solid	364	123	FDRZ4036D3CSCB	FDRZ4036S3CSCB
42	3	ACCUCrank	Solid	382	124	FDRZ4236D3CSCB	FDRZ4236S3CSCB
45	3	ACCUCrank	Solid	410	133	FDRZ4536D3CSCB	FDRZ4536S3CSCB
50	3	ACCUCrank	Solid	455	148	FDRZ5036D3CSCB	FDRZ5036S3CSCB
56	4	ACCUCrank	Solid	510	159	FDRZ5636D4CSCB	FDRZ5636S4CSCB
60	4	ACCUCrank	Solid	546	166	FDRZ6036D4CSCB	FDRZ6036S4CSCB
70	5	ACCUCrank	Solid	637	190	FDRZ7036D5CSCB	FDRZ7036S5CSCB
75	5	ACCUCrank	Solid	683	206	FDRZ7536D5CSCB	FDRZ7536S5CSCB
40	3	Lever Lock	HyVis	364	120	FDRZ4036D3LRCB	FDRZ4036S3LRCB
42	3	Lever Lock	HyVis	382	122	FDRZ4236D3LRCB	FDRZ4236S3LRCB
45	3	Lever Lock	HyVis	410	131	FDRZ4536D3LRCB	FDRZ4536S3LRCB
50	3	Lever Lock	HyVis	455	145	FDRZ5036D3LRCB	FDRZ5036S3LRCB
56	4	Lever Lock	HyVis	510	157	FDRZ5636D4LRCB	FDRZ5636S4LRCB
60	4	Lever Lock	HyVis	546	164	FDRZ6036D4LRCB	FDRZ6036S4LRCB
70	5	Lever Lock	HyVis	637	188	FDRZ7036D5LRCB	FDRZ7036S5LRCB
75	5	Lever Lock	HyVis	683	204	FDRZ7536D5LRCB	FDRZ7536S5LRCB
40	3	Lever Lock	Solid	364	123	FDRZ4036D3LSCB	FDRZ4036S3LSCB
42	3	Lever Lock	Solid	382	124	FDRZ4236D3LSCB	FDRZ4236S3LSCB
45	3	Lever Lock	Solid	410	133	FDRZ4536D3LSCB	FDRZ4536S3LSCB
50	3	Lever Lock	Solid	455	148	FDRZ5036D3LSCB	FDRZ5036S3LSCB
56	4	Lever Lock	Solid	510	159	FDRZ5636D4LSCB	FDRZ5636S4LSCB
60	4	Lever Lock	Solid	546	166	FDRZ6036D4LSCB	FDRZ6036S4LSCB
70	5	Lever Lock	Solid	637	190	FDRZ7036D5LSCB	FDRZ7036S5LSCB
75	5	Lever Lock	Solid	683	206	FDRZ7536D5LSCB	FDRZ7536S5LSCB





· 18 gauge construction

• 36" high

HIE GLAT Wean to Finish - Original Series

• 304 stainless

steel

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov • Width:

Double side - 24-1/4"

· Trough Depth

9-1/2" for the Original

⚠ WARNING:

Length # Holes Adjustment **Trough Divider Shipping WT** Double Sided Item # Single Sided Item # Capacity FDRZ4036D3CRBB 40 3 **ACCUCrank** FDRZ4036S3CRBB HyVis 418 120 42 3 **ACCUCrank** HyVis 439 122 FDRZ4236D3CRBB FDRZ4236S3CRBB 3 FDRZ4536S3CRBB 45 **ACCUCrank** FDRZ4536D3CRBB HyVis 471 131 3 50 **ACCUCrank** HyVis 523 145 FDRZ5036D3CRBB FDRZ5036S3CRBB 56 4 **ACCUCrank** HyVis 157 FDRZ5636D4CRBB FDRZ5636S4CRBB 586 60 4 **ACCUCrank** HyVis 628 164 FDRZ6036D4CRBB FDRZ6036S4CRBB 5 70 **ACCUCrank** HyVis 732 188 FDRZ7036D5CRBB FDRZ7036S5CRBB 75 5 **ACCUCrank** HyVis 785 204 FDRZ7536D5CRBB FDRZ7536S5CRBB 40 3 **ACCUCrank** 418 123 FDRZ4036D3CSBB FDRZ4036S3CSBB Solid 42 3 **ACCUCrank** Solid 439 124 FDRZ4236D3CSBB FDRZ4236S3CSBB 3 45 **ACCUCrank** Solid FDRZ4536S3CSBB 471 133 FDRZ4536D3CSBB 50 3 **ACCUCrank** Solid 523 148 FDRZ5036D3CSBB FDRZ5036S3CSBB 56 4 **ACCUCrank** 586 159 Solid FDRZ5636D4CSBB FDRZ5636S4CSBB 4 60 **ACCUCrank** Solid 628 166 FDRZ6036D4CSBB FDRZ6036S4CSBB 5 70 **ACCUCrank** 190 Solid 732 FDRZ7036D5CSBB FDRZ7036S5CSBB 75 5 **ACCUCrank** Solid 785 206 FDRZ7536D5CSBB FDRZ7536S5CSBB 40 3 Lever Lock HyVis 418 120 FDRZ4036D3LRBB FDRZ4036S3LRBB 3 42 Lever Lock HvVis 439 122 FDRZ4236D3LRBB FDRZ4236S3LRBB 3 45 Lever Lock HyVis 471 131 FDRZ4536D3LRBB FDRZ4536S3LRBB 50 3 Lever Lock HyVis 523 145 FDRZ5036D3LRBB FDRZ5036S3LRBB 56 4 157 Lever Lock HyVis 586 FDRZ5636D4LRBB FDRZ5636S4LRBB 4 HyVis 60 Lever Lock 628 164 FDRZ6036D4LRBB FDRZ6036S4LRBB 5 70 Lever Lock HyVis 732 188 FDRZ7036D5LRBB FDRZ7036S5LRBB 5 75 Lever Lock HyVis 785 204 FDRZ7536D5LRBB FDRZ7536S5LRBB 3 40 Lever Lock Solid 418 123 FDRZ4036D3LSBB FDRZ4036S3LSBB 3 42 Lever Lock Solid 439 124 FDRZ4236D3LSBB FDRZ4236S3LSBB 45 3 Lever Lock Solid 471 133 FDRZ4536D3LSBB FDRZ4536S3LSBB 3 50 Lever Lock Solid 523 148 FDRZ5036D3LSBB FDRZ5036S3LSBB 56 4 Lever Lock Solid 586 159 FDRZ5636D4LSBB FDRZ5636S4LSBB 60 4 Lever Lock Solid 628 166 FDRZ6036D4LSBB FDRZ6036S4LSBB 70 5 Lever Lock Solid 732 190 FDRZ7036D5LSBB FDRZ7036S5LSBB 75 785 206 Lever Lock Solid FDRZ7536D5LSBB FDRZ7536S5LSBB

Single side - 15-1/4"



Finishing - Magnum and Original

· Magnum width:

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

• 36" high

• 18 gauge construction

Single side - 17-1/2" • 304 stainless steel Double side - 29"

· Original width: Single side - 15-1/4" Double side - 24-1/4" · Trough Depth 11" for the Magnum 9-1/2" for the Original

Finish - Magnum Series

Length	# Holes	Adjustment	Trough Divider	Capacity	Shipping WT	Double Sided Item #	Single Sided Item #
40	3	ACCUCrank	Rod	364	110	FDRF4036D3CRCB	FDRF4036S3CRCB
42	3	ACCUCrank	Rod	382	112	FDRF4236D3CRCB	FDRF4236S3CRCB
45	3	ACCUCrank	Rod	410	120	FDRF4536D3CRCB	FDRF4536S3CRCB
50	3	ACCUCrank	Rod	455	133	FDRF5036D3CRCB	FDRF5036S3CRCB
56	4	ACCUCrank	Rod	510	144	FDRF5636D4CRCB	FDRF5636S4CRCB
60	4	ACCUCrank	Rod	546	157	FDRF6036D4CRCB	FDRF6036S4CRCB
70	5	ACCUCrank	Rod	637	177	FDRF7036D5CRCB	FDRF7036S5CRCB
75	5	ACCUCrank	Rod	683	190	FDRF7536D5CRCB	FDRF7536S5CRCB
40	3	Lever Lock	Rod	364	110	FDRF4036D3LRCB	FDRF4036S3LRCB
42	3	Lever Lock	Rod	382	111	FDRF4236D3LRCB	FDRF4236S3LRCB
45	3	Lever Lock	Rod	409	120	FDRF4536D3LRCB	FDRF4536S3LRCB
50	3	Lever Lock	Rod	455	133	FDRF5036D3LRCB	FDRF5036S3LRCB
56	4	Lever Lock	Rod	509	143	FDRF5636D4LRCB	FDRF5636S4LRCB
60	4	Lever Lock	Rod	546	156	FDRF6036D4LRCB	FDRF6036S4LRCB
70	5	Lever Lock	Rod	637	176	FDRF7036D5LRCB	FDRF7036S5LRCB
75	5	Lever Lock	Rod	682	189	FDRF7536D5LRCB	FDRF7536S5LRCB

Finish - Original Series

	original borros						
Length	# Holes	Adjustment	Trough Divider	Capacity	Shipping WT	Double Sided Item #	Single Sided Item #
40	3	ACCUCrank	Rod	418	110	FDRF4036D3CRBB	FDRF4036S3CRBB
42	3	ACCUCrank	Rod	439	112	FDRF4236D3CRBB	FDRF4236S3CRBB
45	3	ACCUCrank	Rod	471	120	FDRF4536D3CRBB	FDRF4536S3CRBB
50	3	ACCUCrank	Rod	523	133	FDRF5036D3CRBB	FDRF5036S3CRBB
56	4	ACCUCrank	Rod	586	144	FDRF5636D4CRBB	FDRF5636S4CRBB
60	4	ACCUCrank	Rod	628	157	FDRF6036D4CRBB	FDRF6036S4CRBB
70	5	ACCUCrank	Rod	732	177	FDRF7036D5CRBB	FDRF7036S5CRBB
75	5	ACCUCrank	Rod	785	190	FDRF7536D5CRBB	FDRF7536S5CRBB
40	3	Lever Lock	Rod	418	110	FDRF4036D3LRBB	FDRF4036S3LRBB
42	3	Lever Lock	Rod	439	112	FDRF4236D3LRBB	FDRF4236S3LRBB
45	3	Lever Lock	Rod	471	120	FDRF4536D3LRBB	FDRF4536S3LRBB
50	3	Lever Lock	Rod	523	133	FDRF5036D3LRBB	FDRF5036S3LRBB
56	4	Lever Lock	Rod	586	144	FDRF5636D4LRBB	FDRF5636S4LRBB
60	4	Lever Lock	Rod	628	157	FDRF6036D4LRBB	FDRF6036S4LRBB
70	5	Lever Lock	Rod	732	177	FDRF7036D5LRBB	FDRF7036S5LRBB
75	5	Lever Lock	Rod	785	190	FDRF7536D5LRBB	FDRF7536S5LRBB





• 31" high

• 20 gauge construction

• 304 stainless steel

• Magnum

Single Width - 13-1/2" Double Width - 22-3/4"

Trough Depth - 8-3/4"

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

• Orginal

Single Width - 10-1/2"

Double Width - 17-1/4"

Trough Depth - 6"

Nursery	- Magnum	Series

Length	# Holes	Adjustment	Trough Divider	Capacity	Shipping WT	Double Sided Item #	Single Sided Item #
32	4	ACCUCrank	Rod	234	64	FDRN3231D4CRCD	FDRN3231S4CRCD
40	5	ACCUCrank	Rod	292	76	FDRN4031D5CRCD	FDRN4031S5CRCD
48	6	ACCUCrank	Rod	351	88	FDRN4831D6CRCD	FDRN4831S6CRCD
56	7	ACCUCrank	Rod	409	100	FDRN5631D7CRCD	FDRN5631S7CRCD
32	4	Lever Lock	Rod	234	64	FDRN3231D4LRCD	FDRN3231S4LRCD
40	5	Lever Lock	Rod	292	76	FDRN4031D5LRCD	FDRN4031S5LRCD
48	6	Lever Lock	Rod	351	88	FDRN4831D6LRCD	FDRN4831S6LRCD
56	7	Lever Lock	Rod	409	100	FDRN5631D7LRCD	FDRN5631S7LRCD

Nursery - Original Series

Length	# Holes	Adjustment	Trough Divider	Capacity	Shipping WT	Double Sided Item #	Single Sided Item #
30	5	ACCUCrank	Rod	219	60	FDRN3031D5CRBD	FDRN3031S5CRBD
36	6	ACCUCrank	Rod	263	64	FDRN3631D6CRBD	FDRN3631S6CRBD
42	7	ACCUCrank	Rod	307	70	FDRN4231D7CRBD	FDRN4231S7CRBD
48	8	ACCUCrank	Rod	351	76	FDRN4831D8CRBD	FDRN4831S8CRBD
60	10	ACCUCrank	Rod	439	98	FDRN6031D10CRBD	FDRN6031S10CRBD
30	5	Lever Lock	Rod	219	60	FDRN3031D5LRBD	FDRN3031S5LRBD
36	6	Lever Lock	Rod	263	64	FDRN3631D6LRBD	FDRN3631S6LRBD
42	7	Lever Lock	Rod	307	70	FDRN4231D7LRBD	FDRN4231S7LRBD
48	8	Lever Lock	Rod	351	76	FDRN4831D8LRBD	FDRN4831S8LRBD
60	10	Lever Lock	Rod	439	98	FDRN6031D10LRBD	FDRN6031S10LRBD



Wet/Dry Feeder

You can now choose a Wet/Dry feeder option with the confidence from the industry leader, Hog Slat. Based on a time tested-design, our Wet/ Dry series of feeders are welded of 16 ga. 304 Stainless Steel. The adjustment mechanism is constructed of 14 ga. with 12 ga. blocking panels. Precise management of the feed shelf is provided by a special version of our proven Select-A-Flow adjustment. The innovative Cam Action provides close incremental adjustments to fine tune feed delivery on the shelf.

- Choice of heights 31", 36" & 41"
- 16 ga. construction
- 12 ga. blocking panels

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov







Two-piece water bar aids maintenance. Vertical pipe is easily removed from horizontal bar.

Unbolt side plate and slide the entire interior water bar assembly out the cutout.

				1997		
Length	# Holes	# Nipples	Height	Capacity	Item # Lever Adjustment	Item # AccuCrank
15	1	1	31"	84	FDRW1531D1LSWA	FDRW1531D1CSWA
30	2	2	31"	168	FDRW3031D2LSWA	FDRW3031D2CSWA
45	3	3	31"	252	FDRW4531D3LSWA	FDRW4531D3CSWA
48	3	3	31"	269	FDRW4831D3LSWA	FDRW4831D3CSWA
60	4	4	31"	336	FDRW6031D4LSWA	FDRW6031D4CSWA
72	5	5	31"	403	FDRW7231D5LSWA	FDRW7231D5CSWA
84	6	6	31"	470	FDRW8431D6LSWA	FDRW8431D6CSWA
15	1	1	36"	120	FDRW1536D1LSWA	FDRW1536D1CSWA
30	2	2	36"	240	FDRW3036D2LSWA	FDRW3036D2CSWA
45	3	3	36"	360	FDRW4536D3LSWA	FDRW4536D3CSWA
48	3	3	36"	384	FDRW4836D3LSWA	FDRW4836D3CSWA
60	4	4	36"	480	FDRW6036D4LSWA	FDRW6036D4CSWA
72	5	5	36"	576	FDRW7236D5LSWA	FDRW7236D5CSWA
84	6	6	36"	672	FDRW8436D6LSWA	FDRW8436D6CSWA
15	1	1	41"	153	FDRW1541D1LSWA	FDRW1541D1CSWA
30	2	2	41"	306	FDRW3041D2LSWA	FDRW3041D2CSWA
45	3	3	41"	459	FDRW4541D3LSWA	FDRW4541D3CSWA
48	3	3	41"	490	FDRW4841D3LSWA	FDRW4841D3CSWA
60	4	4	41"	612	FDRW6041D4LSWA	FDRW6041D4CSWA
72	5	5	41"	734	FDRW7241D5LSWA	FDRW7241D5CSWA
84	6	6	41"	857	FDRW8441D6LSWA	FDRW8441D6CSWA



Round Feeder

- One-piece fiberglass hopper vs. two-piece hopper
- · Reinforced spindle axle is mounted through the bottom of the pan to prevent breakage
- · Heavier weight metal fixtures with powder coated paint finish
- 4.5 bushel capacity (213 lbs. of feed)
- Multiple lengths of panel dividers are available as optional equipment (shown with dividers, not included)

#792000000	Round Feeder / 8 openings
#7920200100	Panel Blocker
#7920220100	40" Panel Adapter
#7920210100	50" Panel Adapter
#7920170100	56" Fence Line Panel

⚠WARNING:





Top angle band prevents damage when feeder is turned over for cleaning.



Select-A-Flow adjustment allows for precise regulation of feed flow.



Internal bump bars prevent feed from bridging.

Boar Feeder

Single Hole

- · Allows you to maximize the accuracy and tailor your nutritional program.
- · Bracket allows for adjustment from floor level to 16" off the floor.
- · Feeder is constructed of heavy duty 18 gauge Stainless Steel for years of reliable use.
- · Large capacity holds 158 pounds of feed.
- 14-3/4" wide x 46" tall.
- 400 series stainless steel

Adjustment Bracket

#7800901100 Includes:

- Cage
- 17-1/2" Adjustable Rod
- · Hairpin Clip
- (4) Wall Brackets





#7809715511Boar Feeders

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Single Sided Feeders

Single sided feeders designed to feed show pigs and smaller groups of pigs. Constructed of heavy 20 gauge galvanized steel with an adjustable feed gate at the trough. Top cover raises from the back to allow filling without disturbing the hogs. Weathertight trough lids are removable by sliding out a pin. Ships knocked down... assembly required.

Single Door **Hog Feeder**

- · Designed to feed up to FOUR hogs to market weight.
- Holds approximately 1-1/2 bushels of feed.
- 12" Wide x 20" Deep x 29-1/2" Tall



Double Door Hog Feeder

- · Designed to feed up to EIGHT hogs to market weight.
- Holds approximately 3.7 bushels of feed.
- 23" Wide x 20" Deep x 36" Tall



#FS400 Single Door #FS401 Double Door

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Poly Feed Pan

Build your own feed pan with our durable 8" high

polypropylene trough, available in 16", 18", and 20" lengths. Drill mounting holes and attach to gates or

a portable clip-on feeder to use at home or at shows.

· Clips can be added for custom mounting needs

· Great for temporary feeding during travel or at

dividers. Order snap clips (#10385, not included) to build

#BUCP0820B-BK20-inch

#BUCP0818B-BK......18-inch

#BUCP0816B-BK......16-inch

Hold Freeder Clean-out Rod

34" aluminum clean-out rod makes easy work of removing leftover feed from hoppers and clearing trough openings. Features 7" foam cushioned handle and 2" bent hook on the bottom end.



#2090561900 Feeder Clean-out rod

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#8130690500 feeder handle clip

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other

reproductive harm. For more information, go to www.P65Warnings.ca.gov

Feed Pipe Holder

#74083115005" tall

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Old Style **Crank Handles**



· Stainless steel inside & outside • 3/8" thread

#7306850500 old style crank handles

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#103855/16" Spring Snap, zinc Feeder **Cross Brace**

livestock shows

Portable

· 2 crank fin SS

• 16-1/2" u-handle

#7407600500.



...... feeder cross brace

♠ WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Adjustment Handle

Feeder Parts

Feeder Handle Clip

- Finish
- 3/8" thread

• Finishing

Adjustment Rod

· 6" tail nib z-bend



#HSAP-2075 3/8" adjustment handle

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#7406480500.....adjustment rod z-bend right #7406470500 adjustment rod z-bend left

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other

reproductive harm. For more information, go to www.P65Warnings.ca.gov

Adjustment Handle

• 5/16" thread

#HSAP-20745/16" adjustment handle

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other

reproductive harm. For more information, go to www.P65Warnings.ca.gov

Nursery Divider Rod

• 5/16" rod only, no



nuts or washers

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Adjustment Rod

· for AP feeders

#HSAP-1220......3/8" adjustment rod #HSAP-0553 5/16" adjustment rod

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Finishing Feeder Divider Rod

• 5/16" rod only, no nuts or washers

#7406900500......11-1/4" long for 40" & 50" **#7606910500**.......10" long for 60" & 70"

↑ WARNING:





Maxi Pan

Maxi Pan is ideal feeder for newly weaned pigs.

- · Stainless steel, 10 hole grid
- 20 30 animals per feeders
- 16-3/4" diameter x 3" trough
- · Overall height 25"

#18004000w/ T-bolt



Maxi Pan Hopper Package

Add a hopper to Increase feed capacity of Maxi Pan.

- · Adjustable collar to regulate feed
- 18" high x 15" diameter cone
- · 30 pound capacity



- Hooks into many types of crate flooring.
- Place in the farrowing crate corner to keep it away from the sow.
- · Avoid expensive feed waste.
- 3 compartment bowl means feed contamination from urine and feces will be minimized.
- · The stainless steel floor hook fastener design accommodates most types of crate flooring.
- · A handy arrow on top of the hook latch lets you know which way the hook is pointing.

#SG-545200......MaxiGro 3000®



MaxiFlow 3000 Milk Replacement Feeder

Uniquely designed feeder reduces waste when feeding high priced milk replacement diets.

Features Include:

- · Separate double feeding compartments reduces contamination
- · SS floor hook snaps in place on most farrowing floors
- · 1 gal plastic bottle
- · Triangular profile allows feeder to fit in creep corner away from sow

#SG-545400......MaxiFlow 3000

Stainless Steel **Piglet Feeder**

- 304 stainless steel
- · Universal J clamp
- · 20 gauge construction
- · Fits all standard slat floors

#1095.....Stainless Steel Piglet Feeder

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel Feeder, Plastic Divider

#10954SS feeder, plastic divider


♠ WARNING:

#18000010 Hopper pkg.

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Hopper Creep Feeder

- Non-corrosive polyethylene
- Adjustable feed gate
- · Mounted bracket included
- 12" W x 6" D x 15" H



#10950 Plastic piglet feeder

Feeder Adjustment Repair Kits

Select-A-Flow

Includes

- (1) 1/4" Locknut
- (1) 1/4"x 5/16"x 3/4" L shoulder bolt
- (1) Spring (1) Bent lever
- (1) Label
- (1) Adjustment plate

#7408911500



.Select-A-Flow

Lever Loc

Includes

- (2) 1/4"x 5/16"x 3/4" L shoulder bolt
- (2) Spring
- (2) 3/4" washer
- (3) 1/4" Locknut
- (1) Adjustment plate
- (1) Adjustment
- (1) Adjustment -offset
- (1) 5/16" x 3/8 shoulder bolt

#7408401500.....Lever Loc





GrowerSELECT

Poultry Water Line Pressure Regulator

- · Provides high water volume at the low pressures needed.
- Large diameter flush valve for better flushing of biofilm and sediment.
- · Mesh reinforced rubber diaphragm for better resistance to stretching.
- Longer adjustment knob for ease of adjustment while low to the ground.
- · Standpipe sold separately

Available Water Line Adapters

HS822-50W 7/8" OD Round Pipe Ziggity	HS822-51 22MM Square Pipe Lubing	60179 1.05" OD Pipe Valco, Choretime, & Cumberland	DIP2205212 & 60026 1" OD Pipe Plasson
		.0	
= Regulator end, slip fit. Do not glue.			
= Water line end, slip fit. Do not glue.			
	$lue{}$ = Water line end, must use PVC glue.		

#HS822Water pressure regulator

Flexible Standpipe Assy

- for HS822 regulator
- Hi-visibility yellow float ball

#HS822-FSA24	24"	High
#HS822-FSA18	.18"	High



Manual Flush Assy

• Replaces Ziggity # 1374

#HS822-40.....for HS822 regulator



Aluminum Rail Bracket Kit

support rail to HS822 regulator

#HS822-PB.....for HS822 regulator



Replacement Standpipe Tubing

#TIP1101996100	Plasson/ per ft / 100' roll
	Lubing / per ft / 164' roll
	Cumberland / precut 24" length
#AP15006501	Chore-Time / per ft
#AP189053	Ziggity / 100' roll
#AP189053-FT	Ziggity / per ft.
	GrowerSELECT/ precut 24"
#HS822-FT18	GrowerSELECT/ precut 18"



Float Balls

#600-015	Cumberland & Impex 7/16" Blue
#C37142	Chore-Time Blue
#DIP2205411	Plasson Small Orange
#L0013701900	Lubing Large 10mm Red
#HS822-33Y	GrowerSELECT 3/8" Yellow
#L0013701903	Lubing 8mm Red
#VRP03	Val Large Blue
#VRP03F	Val Small Blue
#Z147	Ziggity Blue
	00 ,



C-Sticks

#C-Stick-SM-B

Easily observe water pressure in your stand pipe with bright C-Sticks. As the water pressure goes up and down, the C-Stick moves with it. SM & Med- 16/ bottle LG- 8/


Dizion Din D	
#C-Stick-SM-O	Orange
#C-Stick-SM-R	Red
#C-Stick-SM-Y	Yellow
#C-Stick-MD*	Orange Only
#C-Stick-LG*	Orange Only



Cover Bags for Sight Tubes

• 4 Mil poly bags protect sight tubes from dust and grime.


#S-1787	4"	Х	24"
#S-6343	3"	х	26"




Riser Brush

#Z748	Ziggity, 28"
#GCW-5006	Cumberland/Chore-Time, 24" Long
	Plasson
#LBB4227	Lubing
	Val Rigid
#VB151F	Val Flex

*Use of manufacturer part number for reference purposes only







#GCW-10233..... J-Lock Purple Cap #GCW-10233TTwin-Lock Purple Cap #GCW-9440.... J-Lock Orange Pin Dual Stage Hi Flow



#61726......1/8" cable #HSH052 1/16" adjustable cable clamp for shocker wire

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HSH004Nylon swivel pulley 1-7/8"

9. Cup Hook

#60665......1/4" cup hook **⚠WARNING:**

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

10. Aluminum Sleeve

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



11. Cable & Cord Adiusters



1. #HSH076	3" - no lock
2. #617315	2" - no lock
3. #HSH018	3-1/2" - w/ lock
4. #HSH019	flat
5. #HSCA-1	Plastic Cord Adjuster
6. #HSCA-3	Heavy Duty Cord Adjuster

⚠WARNING:




12. Winch #HSW01 #HSW01Split Reel Worm Gear 2000 lb. #HSW02.....Single Reel Worm Gear 2000 lb.

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Shocker Springs



#HB8020

#61394...... 4" long x 7/16" dia. #HSH0613-1/4" long x 1/2" dia.

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Shut Off Assembly

#GCW-5065...... Shut Off Assembly



Hanger Clip for Aluminum Support

Folding Hanger

#GCW-10008.....

...... Hanger Folding

#GCW-9227

▲ WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Wrench for Nipple #GCW-2064...... Wrench for Nipple




Float Ball #600-015Float Ball




Cumberland GCW-3030 Regulator w/ Accessories

Cumberland

1) #GCW-3025	Regulator
2) #GCW-10050	Flush Cap Assembly
3) #600-015	
4) #GCW-3019	Mount Bracket
5) #GCW-9051	
6) #GCW-9052	Spring 22" for Sight Tube
7) #HSCA-1	Cord Adjuster
8) #0708878	Hose Clamp Nylon
9) #GCW-10013	Female Hose Repair 3/4"
10) #GS-4614	Bolt HHCS 1/4"-20 x 1/2" SS
11) #GS-7359	Bolt HHCS 1/4"-20 x 1" SS
12) #GS-7307	Nut Nylock 1/4"-20 SS
13) #GS-9244	S-Hook #1
14) #GCW-2032	Garden Hose (Sold Separately)
13) #GCW-5031	Spring 3" OALx.418 OD



	Name of the last o
w/Accessories	6 (1) (1)
1) #GCW-10050	Flush Cap Assembly
2) #GCW-9051	Flex Sight Tube 24"
3) #0708878	3/4"-7/8" Hose Clamp Nylon
4) #600-015	Float Ball - 7/16" Plastic
	S-Hook #1 0.080 x 1-1/16"
	Garden Hose Washer
7) #GS-9222	Elbow 90° PVC 3/4" MPT x 3/4" Barb
7) #GCW-10073	(Optional) 90° Elbow 3/4" MPT x 3/4" Barb
8) #G60-0272	Swivel Adapter FGH x 3/4" FPT
9) #GCW-10054	End Kit Housing
10) #GS-8910	Nut Square 1/4"-20 Plated
11) #GCW-5020	Coupler Assembly
12) #HSCA-1	Cord Adjuster
13) #GCW-3019	Water Line Mounting Bracket
14) #GS-8789	Screw MS 1/4"-20 x 3/4" RHP
15) #GCW-9052	Spring 22" for Sight Tube




Cumberland

GCW-3025

Regulator

Assembly	A L L L
1) #GCW-3023	Top Assembly
2) #GCW-3011	Internal Plunger Retainer
3) #GCW-3028	Internal Plunger
4) #GCW-3024	Inlet Assembly
	Flush Lever
6) #GS-7656	Screw SMSAB #12 x 3/4" PHP SS
7) #GCW-3026	Diaphragm Assembly
7) #GCW-3001	Diaphragm (Only)
8) #GCW-3003	Pressure Spring
9) #GCW-3005	Bottom
	Adjustment Assembly
11) #GCW-5027	Water Line O-Ring
12) #GCW-3018	End Cap
13) #GS-8668	Screw TRS #8 x 1/2" PHP SS
14) #GS-9249	Flat Washer 3.5 mm Wide
15) #GS-7662	Screw MS #6-32 x 1/4" PHP SS



1) #GCW-10050	Flush Can Assembly
2) #GCW-9051	
•	•
3) #0708878	Hose Clamp Nylon
4) #600-015	Float Ball
5) #GS-9244	
6) #GS-8910	Nut Square 1/4"-20 Plated
7) #GCW-5020	
8) #HSCA-1	Cord Adjuster
9) #GCW-3019	Mounting Bracket
10) #GS-8789	Screw MS 1/4"-20 x 3/4" RHP
11) #GCW-9052	
12) #GCW-10055	
13) #GCW-5031	



with Plastic Adaptor

#L4060C......Drinker Mini w/ Plastic Adaptor #L4060-SO Drinker Mini w/ SS Nipple Adaptor



Snap Cup and Extension

#L4017 Snap Cup and Extension



Regulator

See Parts Diagram page 113

#L3201-00 Flush Regulator Kit w/ sight tube **#L3317-00**..... Breather unit 450mm (18")



Shut-off Midline 22mm

#L302-4-22-01... Shut-off Midline 22mm Pipe Aluminum



Midline Breather

#L302-4-22.... Breather Inline 18" for 22mm Pipe



Shut-off Midline 24"

#L302-6-28-02for 28mm Pipe w/ Flush



Breather Unit

#L4255-6-00 Breather Unit w/ 24" standpipe



Shut-off Midline (New Style)

#L302N.....Shut Off Midline New Style



Drinker Pipe

#L109512......10' drinker pipe w/ 12-4095 nipples w/ rail #L109515......10' drinker pipe w/ 15-4095 nipples w/ rail


⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



LitterGard™ Drip Cup

#L4617	Large
#L4612	•
#1.4622_01	Littergard 1 Arm Red



#117207	I tout assembly
#L0013900902	Ball
#L0013902525	. Pivot Arm Assembly w/o Ball



Float Ball

Float aggombly

#L0013701900Large Red Float Ball, 10 mm #L0013701903Small Red Float Ball, 8 mm



Expansion Connectors

#L4363Expansion connectors w/ crimp



Crimping Tool

#L4414.....Crimping Tool



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Crimp Ring

#L286-7RD

#L316-3BR **#L316-3BR**.....for L4363 **#L286-7RD** for L4367

⚠ WARNING:



Feather Soft 360° Action

.....High flow - broiler #L4023 #L4077 Regular flow- broiler/pullet

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel **Vertical Action**

#L4071 Medium flow - breeder

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Combi **Vertical Action**

#L4005High flow, red/yellow - broilers

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



OptiGROW 360° Action

#L4050 Hi flow, red - broiler #L4090-01 Regular flow, red - pullets

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Combi 360° Action

#L4078-01 Regular flow, red - broiler #L4078-00..... Regular flow, yellow - broiler


⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Ball Tank with Flush System #L4221

1) #L0013800300	Tank
2) #L4212 Rubber W	Vasher 3/4" Male Thread
3) #L0013801300	Outlet with Holder
4) #L0013701800	Washer 3/4"
5) #L0013702901	Male Plug 3/4" Red
6) #L0013801601	
7) #L4367	Tube Connector
11) #L4254	Ball Valve
12) #L4215	Washer 1/2" Inside
13) #L4313 Angle Hose Co	
14) #L0013802000	Form O-Ring
15) #L0013800400	Cover
16) #L0013801100	Flush Knob
18) #L2707041 Cylinde:	r Screw 3mm x 16 DIN 7
19) #L0013801200	Guide Piece
20) #L2384052 Raised Ch	eese Screw M5 x 30 DIN 7985
22) #L3002480	0-Ring 12 x 3



Black Tank without Flush System #L4210

1) #L4201-2Water Tank Cover
2) #L4251-1Tank Shell with Plug & Sticker
3) #L0302000200Tank Bracket (4210)
4) #L4204Float Assembly Complete
5) #L4215 Rubber Washer 3/4" Male Thread
7) #L00138016013/4" Flat Nut
9) #L42161/2" Tank Plug
10) #L4212 Rubber Washer 3/4" Male Thread
12) #L3002 Supply Tube Complete (Includes #'s 11, 12, 13)
13) #L4210As Shown Complete




essure Regulator #I.3201-00

Pressure Regulator #L3201-00	
1) #L4311-00	Hose Connector
5) #L0302402200	Adjustment Wheel
6) #L0302402300	Adjustment Nut
7) #L0302402800	Diaphragm
8) #L0302402500	Lever Operation
	Valve Lever
11) #L0302402400	Diaphragm Plate
12) #L3301-00	Hanger for Regulator
14) #L0302403300	Pressure Spring
15) #L302002900	Flush Bordering
16) #L0302403601	Adjusting Mechanism
17) #L0302403701	Holder Nut
18) #L0302403800	Toggle
25) #L3006203	0-Ring 20 x 2.5
26) #L3303-00	Transition Piece Complete
27) #L4215	Washer 1/2" Inside

UPGRADE YOUR EXISTING SYSTEM WITH THE LUBING ADVANTAGE

The Lubing modular design makes it easy to retrofit the Lubing Advantage to your existing watering system without replacing railings, regulators and end assemblies.



• Add the Hanger Brackets according the type of existing support rail. (5) brackets for every 10' section, except with a Chore-Time® system where (6) clips are required.




Add LitterGard[™] Cups


• Square to Round Transition to attach square Lubing pipe to existing regulators.



#L4617	Two Arm Large
#L4612	
#L4622-01	Single Arm




A) #L43810	Square to Round Adapter 22mm x 3/4" PVC
	Square to Round Adapter 28mm to 3/4" PVC
C) #L3304-00	Transition Adapter 28mm to 22mm
D) #L3303-00	Transition for 22mm Regulator
E) #L3305-00	



World Class Poultry Systems To order go to www.hogslat.com

The unique feature of the Plasson Drinker is the ballast bottle, which acts independently of the bell and eliminates wear on the valve mechanism. The bell design ensures a constant water level and a dry floor. Once a bird drinks as little as 10 grams (0.3 oz.) of water, this highly sensitive and maintenance-free system is activated. The Bell drinker incorporates a bayonet - based bell, a special handle hook and an efficient stacking design. Combine all of these factors and you have a system that is easy to ship and install. Approximately 8- 10 Plasson Drinkers are needed per 1000 adult birds. Working pressure: (6 - 12 psi) for optimum efficiency. The pressure can be regulated by means of a pressure regulator or via a head tank. The ballast bottle should be completely filled with water up to the water level line. In frost-prone areas, add antifreeze to the water Adjust drinkers to the proper drinking height, always keeping the drinker lip a little higher than the bird's back. Keep water level in the bell trough as low as possible.





Plasson® Broiler Drinker

Flasson Broner Diniker	
#DIP2140000	Broiler Drinker Complete
#DI52821	Clip
#61724D	1/8" nylon cord
#HSCA-1	Cord Adjuster
#DI2140018	Handle Hook
#DI2140009	Water Level Adjuster
#DIP2140012	Mechanism Top
#DI2140011	
#DIP2140016	Stainless Steel Spring
#DI2140017	
#DI2140015	Washer Support
#DI2140013	Mechanism Body
#DI2140014	
#DI2140004	
#DI2140007	Hanger Rod
#DI2140008	
#DI2140002	Ballast Bottle
#SDBV22	Inline Shut-off
#DI52832	
#DIP2100039	1/4" Union

Plasson® Breeder Drinker

i iasson Dieedei Dinikei	
#DI52800	Breeder Drinker Complete
#DI52821	Clip
#61724D	1/8" nylon cord
#HSCA-1	Cord Adjuster
#DIP2100039	1/4" Union
#DI52832	
#DI2102035	Mechanism Cap
#DI52840	
#DI52835	
#DI52826	Mechanism Pipe
#DI52823	Water Level Adjuster Nut
#DI52822	Lock-nut
#DI52825	Mechanism Spring
#DI52824	Valve Assembly Complete
#DI52829	Bell
#DI2102041	Bottle Hanger Support
#DI52834	Ballast Bottle
#DI52844	Valve Spring
#DI52842	Plunger
#DI52828	Washer
#DI52841	0-Ring
#DIP2100016	Valve Housing




World Class Poultry Systems




Nipple Line Head Kit #DI220507AMK2

1) #DIP2205701 2) #DI2205702 3) #DI2205720 4) #DI2205703 5) #DI2205704 6) #DI2205713	Bottom Shell Screw Knob Nut Spring
	Spring Hex Nut Backing Plate



10) #DI2205489	Auto Flush Valve
11) #02205680 (NSU)	Cap
12) #DI2205707	
13) #DIP2205717	
14) #DI2205706	Upper Spool
15) #DIP2205716	
16) #DI2205708	Washer
17) #DI2205714	M6 Screw
18) #DI2205709	Cap



Replacement Parts for Nipple Line Head Kit #DI220507AMK2

B) #DIP2205122	Plasson Drinker Line Coupling Connector
E) #60600	Bolt 1/4" x 1/2"
F) #60600	Bolt 1/4" x 1/2"
G) #60602	
H) #DI3016055	
I) #DIP220507S	Sight Tube Complete
NS) #DIP2205410	Cap for Sight Tube Drinker
NS) #DIP2205413	
NS) #DIP2205429	
•	



Drinker Nipples

#DIP2205202	Yellow nipple only
#DIP2205009	Orange nipple only
#DI2205007	Gray nipple only



PVC Drinker Pipe

#DIP2205130-10......10' w/ 10 holes



Aluminum Support Rail

#DI2205162......10' long




This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Aluminum Connectors

#DI2209023.....Short connector #DI2209024.....Long connector (14")

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



MK2 Retro Kit

Converts new regulator to older drinker lines.



#DI2205035	External connector
#DI2205985	PVC sleeve
#DIP2205122	Insert fitting, 25mm
	complete kit

Sight Tube Kit

complete
riser tube
spring
car
ll, orange

Plasson Water on Demand System

By simply upgrading every nipple line to the patented Plasson pressure reducers you allow the WOD system to operate. Plasson regulators can be upgraded using an easy-to-use Retrofit Kit. The water pressure in all drinker lines can be managed from a single location by using 2 pre-set pressure regulators (one regulator for low to medium pressures and a second regulator for medium to high pressures). Additional pre-set regulators are available if desired, giving you more stages for your program.

The patent pending Water on Demand (WOD) ensures uniform pressure in all drinker lines and supplies water according to your birds' changing demands. This takes the labor out of constantly changing individual regulator pressures as birds age and adjusting water levels in riser tubes. Water on Demand does not require additional expensive infrastructure for installation. It fits every Plasson watering system and can fit other brands of drinking systems using a Retrofit Kit. Water on Demand maximizes bird performance with optimal water supply, maintains drier litter, and cuts labor costs.

The WOD system enables immediate transition between different preset pressures of all nipple lines in a

house by closing and opening solenoid or manual valves at a central control point. With the solenoid model, you can control automated valves through your controller or a standard electrical timer. These immediate, uniform pressure transitions at specific ages and peak drinking times aid in bird performance and lead to simplified management of your watering system.

PRESSURE REQUIREMENT:

Inlet pressure to the Water on Demand Control Unit requires a minimum of 43 psi. Operating the WOD panel between 8-43 psi will allow the Plasson Pressure Reducers to regulate line pressure between 4 to 24 column inches. This allows whole house pressure management at one central location depending on bird requirements and floor conditions.

#DI220507WMK2	WOD MK2 Header Kit
#DI22050WDB	WOD Basic Unit
#DI22050WDE	WOD Extension
#DI22050WDBEWOD	Basic Unit w/ Extension





Includes: • Pump and motor

- · Frequency drive
- · Pressure sensor

#DI2205389K





Pump

#DI2209029.....

MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pressure Sensor

#DI2205279WOD sensor bar



Frequency Drive

#DI2350007 WOD drive module



Regulator

#DI2205950 Pressure Regulator




Water Pressure Gauge


#DI22050WODGAUGE.....0 to 60 psi

♠ WARNING:



EasyLine The recipe for success is Easy. Just Add Water.





B) Finishing - Toms With Aluminum Rail

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Starter Ball

#L4636-01 Starter ball 30mm (Red)



#L4633Pendulum



Drive Socket 1/4"

#L7600600200... 1/4" for lubing adult turkey nipples

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Nipple

FeatherSoft Turkey Nipple 360° stainless steel desisgned for EasyLine Drinking System.

#L4070360° SS nipple

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#L4631-1-01 Rearing Cup w/ SS insert



#L4630-1-01......Tom Finishing Cup w/ SS insert



#L4632-01 Pendulum holder, red



Aluminum Profile - Turkey

#L0301101600.....Aluminum Profile - Turkey #L0301201100.......Coupling for Aluminum Profile

▲WARNING:



Plasson® Compact Turkey Drinker

#DI2104005	Compact Turkey Drinker Complete
#DI52821	Clip
#61724D	
#HSCA-1	Cord Adjuster
#DI2140018	Handle Hook
#DI2140009	Water Level Adjuster
#DIP2140012	
	Mechanism Lock Collar
#DIP2140016	Stainless Steel Spring
#DI2140017	Washer
#DI2140015	
#DI2140013	Mechanism Body
	Down Spout
#DI2104033	Bell
#DI2140007	
#DI2140008	Hanger Ballast Nut
#DI2140002	
#SDBV22	Inline Shut-off
#DI52832	1/4" Flexible Tube
#DIP2100039	1/4" Union

Plasson* Turkey Drinker	
#DI21050WB	Turkey Drinker Complete
#DI52821	Clip
#61724D	1/8" nylon cord
#HSCA-1	Cord Adjuster
#P2100039	
#DI2102035	Mechanism Cap
#DI52840	0-Ring
#DI52835	
#DI52826	Mechanism Pipe
#DI52823	Water Level Adjuster
#DI52822	
#DI52837	Mechanism Spring
#DI52824	Valve Assembly Complete
#DI2104033	Bell
#DI52833	Bottle Hanger
#DI52834	
#DI52832	
#DI52838	<u> </u>
#DI52844	
#DI52842	3
#DI52828	
#DI52841	3
#DIP2100016	Valve Housing



Quick, efficient way to provide a water cup drinker for pigs using gravity flow tank or barrel. Aluminum cup with cradle base for added stability. Includes interior 209 gravity valve.

Gravity Flow Water

Top Mount

Drill a 7/8" hole in the side of barrel or tank to install the adaptor. Includes nipple.

#17515	Gravity Flow Water Cup
#13235	Model 75 finish nipple
#13307	Model 97 Spiglet nipple

<u>⚠</u> WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Steel-jacketed, heated fountain with 150-hog capacity. Measures 13" wide x 23-3/4" long. See more features online under the Farmstead Equipment section.

#BRMC32E Outdoor Hog Waterer

🗘 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



(1) #2000310100	Top mount water bracket
(2) #5000920100	Top spacer connector
	1/4" V-bolts

🚹 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Water and Feed Systems **Hanging Bracket**

🔥 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel Water Bracket

#3531 SS 450 water bracket

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pipe

· Male thread both ends

#8151720500	. 1/2"	x 36"	SS	Pipe
#8151660500	1/2"	x 48"	SS	Pipe
#565101/	2" x	42" G	alv.	Pipe

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov







Straight & 90° Tee

1/2" Galvanized Tee
1/2" Stainless Steel Tee
1/2" Galvanized 90°
1/2" Stainless Steel 90°

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Nipple Bar

Nipple Bar provides an additional water source during the first few weeks for pigs placed in wean-to-finish barns. Constructed of stainless steel with HSNA-38 nursery nipples. Hook package attaches unit to the gating and allows for easy removal after the pigs are started.

(12) Nipple Bar
(8) Nipple Bar
(4) Nipple Bar

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov







C) #75B1/2.....Female Coupler x 1/2" MPT





Nipple Bar Hook Package

- (1) Square tube u-bracket
- (2) Hook brackets
- (1) PTO pin
- (2) 1/4" zinc nylocks
- (2) 1/4" X 1-3/4" zinc bolt

#8155631100.....





......Nipple Bar Hook Pkg

⚠ WARNING:



Adjustable Waterer

- · 2 nipples per pen (not included)
- · Pinch bracket adjustment

#56605	36" Stainless Steel, Single
#8150070200	36" Galvanized, Single
#56508821	24" Galvanized, Double
#8150010200	36" Galvanized, Double
#56607I	36" Stainless Steel, Double

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel **Swinging Water Bracket**

• End water bracket problems forever with this stainless steel hanging water bracket.

#3525-36SS...... 36" Water Bracket - Y #3525-10-SS Straight Water Bracket

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Galvanized & Stainless Steel **Quad Pipe Waterers**

.... 36" SS Quad waterer #Q3636" Galv. Quad waterer

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Trough Waterer

- · SCH 80 galvanized pipe
- · Includes heavy duty brass valve

#8150910700	 	. 1/2"
#8150900700	 	1"

↑ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



European **Crate Waterer**

#8150600700.......38"-1/4" Galv. pipe w/nipples #8150640500 38-1/4" SS pipe w/nipples

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Gestation Waterers

- · Add nipple waterers to your gestation stalls
- Nipple not included
- · Attach to stalls with K-clamp (2 required)

#56505......36" Single stainless Steel #HSH0111/2" Galv K-clamps for attachment

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Molded Plastic Water Swing Bracket

- · Non-corrosive
- · Reduces wear and tear on pen panels
- · Threads molded right in for consistency, better sealing and easier maintenance.



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Water Swing Bracket

Stainless steel construction with nipples spaced approximately 12-1/2" apart and with the shielding of the PlayGuard discouraging hog infighting. For consistent water delivery, choose the Model 2000 Wrench Curve Nipple. (nipples not included)

#17338...... Water Swing Bracket

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Ceiling bracket

#HW08Galvanized #HW08SSStainless Steel

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Offset Double Stall Waterer

- · Stainless Steel
- 24" height
- · Upright pipe is right of center facing nipples
- Upright bent for angle top stall



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stall Waterer





This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Water Pipe Clamp Kit

Clamps to 1/2" rod (1) Galv Clamp (2) 5/16" U-bolt SS (4) 5/16" Locknuts SS

#2090261200



......1/2" Clamp Kit

⚠ WARNING:





INSTALLATION AND PLACEMENT GUIDELINES



Our studies show that placement is critical to the efficient use of cup waterers. Follow these guidelines for the best results:

- Cups should rest 6" from the floor to the bottom lip of the bowl.
- Place the feeder no closer than 19" to the edge of the bowl to reduce excessive feed in the bowl or feeding pigs blocking access.
- · Install no farther than 36" from the feeders reduces the likelihood of pigs dunging the cup.

Order both for complete installation #8150781501 AquaChief cup with pipe and nipple only

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Featuring the Exclusive **AQUAFLO** Trigger Nipple to eliminate spraying and reduce wastage

AquaBowl is formed as a one-piece, stainless steel bowl with no welds to leak, no corners to gather debris or sharp edges to injure pigs. The wide mounting flange with pre-punched holes installs to any type of floor. Farrowing equipment lasts longer when using an AquaBowl because pens stay drier.

#HS610AquaBowl only #HS610-1SS pipe w/ AquaFlo nipple

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Welded Water Cups





Heavy 304 stainless steel welded construction with a 16-gauge cup body and 11-gauge back mounting plate. Includes S.S. top mounting bracket. Does not include gate mounting hardware or nipples.



Offset back plate forms gap to prevent manure buildup against gate.



Includes threaded pipe end.



Includes top mounting bracket

#8160191500.....Single Water Cup Package #8160171500 Double Water Cup package #8160201500 Single Nursery Water cup package

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Back up Plate Kit

· AquaChief cup and bolt package includes all products listed below. No separate ordering needed!

Mounts 1 cup.




#8152501200Galv kit INCLUDES: #606194) 1/4-20 x 1-1/2" SS bolt #60603......4) 1/4" S.S. lock nuts #81525002004) 8" Galv. back up plate

#60579 4) 1/4" flat washer **⚠WARNING:**

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Water Cup Pipe Clamp Kit





(1) 8152670200 Galv. clamp bracket

(1) 60647 Zinc V-bolt

(2) 60680 Zinc Locknuts (2) 60579 SS Flat Washer

#8152671200 Single water panel clamp



WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Hog Slat's exclusive line of nipple drinkers feature stainless steel construction, chemical-resistant Viton O-rings, adjustable flow rate and screen cap to keep out debris.



Nursery Nipple

Size: 3/8" x 1/2" MPT Flow: 3.2 qts/min. @ 40 PSI Usage: Birth to 50 lbs.

#HSNA-38...... Nursery Nipple #HSNA-38-5 pack of 5



Finish Nipple

Size: 1/2" MPT

Flow: 4.2 qts/min. @ 40 PSI Usage: 50 lbs. to Finish

	#HSNA-50	Finish Nipple
:	#HSNA-50-5	pack of 5



Trigger Nipple w/Silicone Insert

Size: 1/2" MPT

Flow: 3.2 qts/min. @ 40 PSI Usage: Cup Waterers

#HSNA-50TS	Trigger Nipple
# 1101111 OO 10	TIIGGOI IIIPPIO



Wet/Dry Nipple w/Silicone Insert

Size: 1/2" MPT

Flow: 4.0 qts/min. @ 40 PSI Usage: Wet/Dry Feeders

#HSNA-50WD Wet/Dry Nipple





The RIO nipple utilizes the patented HydroDam insert to reduce spraying and deliver a gentle water flow. Pigs drink naturally with less waste.





The AquaFlo forward spring design releases water flow without compressing the spring for reduced material fatigue and longer service life. When animals activate the spring, water flows out of the body through the forward part of the housing dispensing an even, steady flow of water without spraying. AquaFlo nipples include a gravity flow orifice setting. AquaFlo nipples include a gravity flow orifice setting.



Finish Nipple

Size: 1/2" MPT

Flow: 4.2 qts/min. @ 40 PSI Usage: 50 lbs. to Finish

#HSNR-50finish nipple #HSNR-50-5pack of 5

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Flow rate per orifice setting - Quarts/min. @ 40 psi.			
Item#	Small	Middle	Large
HSNA-38	1.0	1.6	3.2
HSNA-50	1.0	1.8	4.2
HSNR-50	1.0	1.8	4.2
HSNA-50TS	1.5	2.7	3.2
HSNA-50WD	2.5	3.5	4.0
HSNAF-90*	1.8	3.3	4.6
HSNAF-90TS*	1.8	3.3	4.6

^{*}Also includes gravity flow orifice setting.



Trigger Nipple

Size: 1/2" MPT

Flow: 4.6 qts/min. @ 40 PSI Usage: Cup Waterer

#HSNAF-90TS......Trigger Nipple



Size: 1/2" MPT Flow: 4.6 ats/min. @ 40 PSI

Usage: Breeding Herd

#HSNAF-90 Bite Nipple

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Replacement Parts

replacement laits		
Item#	Description	Nipple Model
HSNA-38-003	Spring	HSNA-38
HSNA-38-007	0-Ring	HSNA-38
HSNA-50-003	Spring	HSNA-50, HSNR-50,
HSNA-50-006	Screen	HSNA-38, HSNA-50, HSNA-50,
		HSNA-50TS
HSNA-50-007	O-Ring	HSNA-50, HSNA-50
HSNA-50TS-3	Silicone Insert	HSNA50TS
HSNAF-90T-7	Spring	HSNAF-90, HSNAF-90TS

Swine Nipples



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Edstrom Wet Feeder Nipple

• 2 qt./ min @ 40 psi

#565754Wet Feeder Nipple



Edstrom Sow Nipple

• 2.5 qt/min @ 40 psi

#565751Sow Nipple



Edstrom Hog Nipple

• 2.5 qt/min @ 40 psi

#565753.....Hog Nipple



Edstrom Piglet Trainer Nipple

- 1 qt./min @ 40 psi
- · Adjustable drip setting

#565155Piglet Trainer Nipple



Edstrom Piglet Nipple

• 1.5 qt/min @ 40 psi

#565752.....Piglet Nipple



AquaChief Nipple

• Replacement nipple for AquaChief

#HSNA-50TS...Aqua Series Trigger w/ Silicone Insert #56571SI.....Replacement Silicone Insert #56571.....AquaChief Nipple w/ Spring #565780....Replacement spring



Bekalo L90

- High flow rate 1.2 gal/min
- Stainless steel/ brass construction
- Replaceable valve seat

#NSL-90 Bekalo L90



TROJAN Model 75 Cone Throat Nipple

- · Stronger, thicker hex-head body
- · Simplified design eliminates Delrin washer
- Cone throat reduces water waste and spray

#14775A New Model 75



TROJAN Spiglet 97 Nipple

- 100% Stainless Steel
- · 3 position adjustable orifice
- · For farrowing and nursery pigs

#56574Trojan Spiglet 97 Nipple



Monoflo® Nipples

#56577	1/2" Finish
#565771	1/2" x 3/8" Nurserv



Monoflo Wet/Dry Feeder Nipple

• 1/2" female thread

#5657121/2" female



Monoflo Wet/Dry Feeder Nipple

- Center Flow
- · Adjustable Flow Rate

#3509-00-00Center Flow Dial Nipple



AquaGlobe® Bite Ball Valve

#HSAP-2509	Sov
#HSAP-2508	Finish
#HSAP-2505	Nursery



Egebjerg Nipple

- Wet/dry nipple
- Works with 18 to 80 psi
- Replacement nipple for tube feeders
- No spring

#E93417 Tube-O-Mat



Limit Nipple


- · Center flow nipple
- · Adjustable water flow
- · Operates at 1 to 100 psi

#L70	Pig	Nipple
#L80	. Finish	Nipple



Includes 3/4" hose, (2) SS hose clamps and PVC tee. Just push hose over 1/2" water pipe and clamp.

#565411	4′
#565421	5′
#600211	3/4" x 3/4" x 3/4"



Plumbing Kit Complete Assembly & Parts

- 1/4" x 6' reinforced hose
- · Saddle clamp with shut off
- 1/2" Nylon female swivel connector

#56559	1/4" x 6' plumbing (complete)
#565541	Washer for saddle clamp
A) #56554	Saddle clamp with shut off
B) #56550	1/4" swivel nut and insert
C) #4511-0251	1/4" braided hose (6' required per kit)
D) #1053	1/4" Speedy Jaw clamp
E) #565510 1/2	" swivel nut and insert with washer
F) #WF3230	In-Line Valve 1/4" barb x 1/4" barb

Spigot

• 1/2" & 3/4" brass spigot

#60242......1/2" brass spigot #60243.....

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Spigot

• 3/4" full port

#602431.....



⚠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Spigot

• Ball valve style handle

#262482 Spigot/Hose Bibb 1/2" #262483 Spigot/Hose Bibb 3/4"

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Brass Boiler Drain

#HE292966 Drain Boiler 1/2" MPT Brass BD-12M #HE2627451/2" brass spigot

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Speedy Jaw Clamp

Bibb Hose

• 3/4" plastic

Stainless Steel

#HSHC-06 SAE06 7/16" - 25/32" SS

#HSHC-08......SAE08 1/2" - 29/32" SS #HSHC-12.....SAE12 11/16" - 1-1/4" SS

#HSHC-16......SAE16 13/16" - 1-1/2" SS #HSHC-20.....SAE20 13/16" - 1-3/4" SS #HSHC-24......SAE24 1-1/16" - 2" SS #HSHC-36......SAE36 1-13/16" - 2-3/4" SS

#HSHC-56.....SAE56 3-1/16" - 4" SS

#HSHC-MO4 SAEMiniO4 7/32" - 5/8" SS

#HSHC-M06 SAEMini06 7/16" - 25/32" SS

#HSHC-96...... SAE96 5-5/8" - 6-1/2" SS

⚠WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Hose Clamps

1/4", 3/8"	
#1053	

# 1053	I/4
#1052	3/8
40700070	0/4" to 7/0" Die ele 17: 7011

#60243P3/4" plastic hose bibb





#HE262421...... Drain Boiler Plastic 3/4" MPT

Barb Nylon Fittings

Plastic Boiler Drain

• 1/2" female thread

1) #TAF-1084.1/2" FPT x 1/4" 2) #565510 Nut Swivel, 1/2" x 1/4" Barb w/washer

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#603065 1/2" FPT x 1/4

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel Barb Fitting

#603066



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



1/2" x 1.4". End plastic fitting problems with our stainless steel

#565516 Stainless Steel Swivel & Barb





Drinker Hose

• FHT x FHT

Item#	Length	Diameter	Color
#52754	3′	1/2"	Red
#52753	8′	1/2"	Red
#52755	10'	1/2"	Red
#52756	12′	1/2"	Red
#52745	4′	3/8"	Black
#52747	8′	3/8"	Black
#52746	10'	3/8"	Black
#26053-04	4′	5/8"	Red
#26053-08	8′	5/8"	Red
#26053-10	10'	5/8"	Red
#26053-12	12′	5/8"	Red

⚠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov







#HHSW-B #HE191318

3/4" Hose Washers

#52793	Black vinyl washer
	Red rubber washer
#HHSW-B	Black rubber washer w/ screen



Garden Hose Female Coupler

1) #HW58FB	. Brass	Female,	5/8"	barb
2) #HW34FB	Brass	Female.	3/4"	barb

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

10.







Nylon Hose Fittings

3) #RCT-41	3/4" FGHT x 1/2" barb
4) #HMNG3434	3/4" MGHF x 3/4" barb
5) #HFNG3434VW	3/4" FGHF x 3/4" barb
#52792	3/4" FGHT x 1/4" barb
	3/4" MGHT x 1/2" barb



Specialty Garden Hose Adapter

8)	#60167	Brass	3/4	" MPT	x 3/4"	MHT
9)	#RCT-3413	Nylon,	3/4"	MGHT	x 1/2"	MPT
10)#RCT-3415	Nylon,	3/4"	MGHT	x 3/4"	MPT

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Specialty Garden Hose Adapter

11) #602542..... Brass, 3/4" MHT x 3/4" FIP 12) #122-EDBrass, 3/4" MPT x 1/2" MPT 13) #G20-031 ... Brass 3/4" Swivel FHT x 1/2" FPT

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Rubber & Braided Water Hose

#4511-0251	Braided Hose - 1/4" ID - Clear
#4511-0381	Braided Hose - 3/8" ID - Clear
#565611	Rubber Hose - 3/8" ID - Red
#60254	Rubber Hose - 5/8" ID - Black
#60255	Rubber Hose - 3/4" ID - Black
#60256	Rubber Hose - 1" ID - Black
#52771	1/2" Standard Green Water Hose
	1/2" Heavy duty red water hose
#15935	Garden Hose 5/8" x 50' hose w/ fittings
#AP98108804	Hose Water 3/4" x 50' MxF GHT Heavy Duty (AG200)
#AP98108809	Hose Water 3/4" x 100' MxF GHT Heavy Duty (AG200)

Garden Hose Barb Coupler

FEMALE	B. 198	
#05711361	Heavy	Brass w/ Hose Clamp - 3/4"
#07307069	Heavy	y Brass w/ Hose Clamp - 1/2"
#07313034	Heavy	Brass w/ Hose Clamp - 5/8"
MALE	·	-
#05704564	Heavy	Brass w/ Hose Clamp - 3/4"
#07299415	Heavy	Brass w/ Hose Clamp - 1/2"
#07313646	Неалл	Brace M/ Hose Clamp - 5/8"

♠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Garden Hose Male Barb Coupler

6) #HW58MB	Brass	Male,	5/8"	barb
7) #HW34MB	Brass	Male,	3/4"	barb
#HHW12M-B	.Brass	Male,	1/2"	barb

⚠ WARNING:


This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Barb Nylon Fittings

• High impact nylon hose fittings

	#N3412					
15)	#NC1234	. 1/2"	MNPT	Х	3/4"	barb





1) Timer

#5900101-hour cycle



:	#61005	3/4" W/ bypass
	#60361	Solenoid Valve 1 inch, 115V
	#603620	Solenoid coil 115V
	#60376	. Reducer bushing 1" MPT x 3/4" SLIP (SCH 40)



3 & 4) Pipe Strap & Screws

#60029		Pipe strap 3/4"
#80517 #9 x	1	1/2" white screw



5) Tee with Fogger

#61025	3/4"
#60304	Yellow fogger tip only



6) PVC Pipe

#60342 20′	x 3/	4" (SCI	H 40
-------------------	------	---------	------




1) #59600 Thermostat 2) #59600DDigital Thermostat



Soaker Systems & Parts

1) #56554	Saddle clamp w/ shut off
2) #NS30384-8	Swivel
3) #NS50595	Nozzle caps w/o hole
4) #56554	Saddle clamp w/ shut off
5) #60171 Bushing re	educing PVC 1/2" MPT x 1/4" FPT
6) #WF1022	Micro spray adapter
7) #WF4070 Adjust-	a-flow 360° sprinkler emitter
8) #610300 Adjust-	a-flow 180° sprinkler emitter
N/S) #AN13115V	ar-Jet™ 90° sprinkler emitter









#52789 Valve Drain 1/2" FPT Brass #DV-500.....Valve Drain Brass 1/2" MPT

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Automated Pre-soaker

- Automate your pre-soak system to save time and water
- 24 hour time clock allows you to pre-soak building to your wash schedule
- · Prewired panel for easy installation
- · Just plug it in

#590041Pre-soaker system



Sprinkler

Standard Flow

• Each sprinkler will cover a 20-ft x 20-ft. area (shown with optional tee, tee not included)

Full Flow Sprinkler

full flow spinner suspended

reliable performance. Rugged

"C" frame design with a flow

between two bearings for

rate of 70 GPH at 25 PSI.

• 1/2" sprinkler features a



#61030.....Standard Flow Sprinkler, 1/2" #603753/4" S x 3/4" S x 1/2" FPT Tee

#61030A...... Full Flow Sprinkler, 1/2" #603753/4" S x 3/4" S x 1/2" FPT Tee



Visions Econo-Cool (Formerly Meter-Man)

Designed to control the flow of water based on the time and temperature setting you choose. The Econo-Cool controller will automatically activate the solenoid valve and allow water to flow to the emitters when the air temperature is warmer than the temperature setting of the thermostat.

#ECS500Controller, 1" solenoid #UCS152-24V24 V, 1" solenoid 3/4" SLIP & COMP fittings

#EC 102-NACord w/12 V condor transformer



C-110S Edstrom Control

The C-110S Controller is used to regulate the showering and interval cycles in a livestock cooling system. It has output to control one 24VAC electric valve. This easy-to-program controller can be set to operate either in Two-Stage Mode or Smart Mode.

Two-Stage Mode provides traditional two-level cooling - a lower intensity cooling cycle operates when the temperature is above the low threshold. A higher intensity cooling cycle operates when the temperature is above the high threshold.

Smart Mode provides innovative, infinite-stage cooling. Interval time is automatically adjusted as the temperature changes. The interval time is the period of time when no showering occurs and the water is allowed to evaporate from the animals. As temperature increases, the interval time will decrease, thus giving animals more frequent shower cycles, to reduce heat stress. This provides exactly the right amount of cooling at any temperature while minimizing water usage.

Spray-Cool Electric Valve Filter Kit

- 24 vac
- GHT fittings
- · Filter · 1.7 lbs.

#60299





Cooling System Control

Cooling System Control provides an economical solution for controlling spraying or dripper systems. Assembled from common plumbing fittings and timer/thermostats on a PVC panel, field repairs can be accomplished without ordering special parts.





Comes pre-wired in NEMA enclosures:

- Check Valve
- Pressure Regulator
- 110V Solenoid Valve
- Filter
- Single-Stage Thermostat
- · Adjustable Timer with independent on/ off knobs, 30 minutes with 1/2 minute increments
- · Power Cord
- · Also available with 24 hour time clock



1) #60281	Hose Drain
2) #23204491110B	1 gph drip nozzles, bag of 20
		Mist Emitter, 5 GPH at 15 psi
4) #1610-0841	1/2" Tee
6	,) #60266	Barb Adapter Drip System, 1/2" x 1/2"
		Hole Punch
8	,) #60268	Loop Clamp, 30 per package
		5/32" Barbed Connector, 20 per package
	•	







Fogger Bushing

#527971/2" x 1/8" Fogger Bushing



Fogger Tee


#603771 1/2" x 1/8" Fogger Tee

Booster Pumps

Rugged booster pumps features cast suction and discharge casting with a 304 heavy wall stainless steel pump shell. Powered by a single phase 115/230 volt motor with thermal overload.

#52704	1/3 Hp
#52705	1/2 Hp
#52707	3/4 Hp
#52706	1 Hp
	- r

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#52783

.3 GPH w/adapter

Fogger Nozzle with Adapter

#52781 1 GPH w/adapter



#603184 with screen 1/8" 2 GPH Plastic

Plastic Fogger Nozzle

#527801with screen 1/8" 1 GPH Plastic

Tefen White Fogger Nozzle (only)

#PWP5N0780FWH 1.00 GPH @ 100PS no screen

Tefen Cream Fogger Nozzle (only)

#PWP5N21105C 1.97 GPH @ 100PS no screen

Tefen Blue Fogger Nozzle (only)



#PWP5N2180BL....... 1.7 GPH @ 100PS no screen



#PWP5NSF-L... Stainless Steel 200 mesh w/Plastic Insert

Polypropylene Fogger Nozzle Filter

#PWP5NPF-L.....polypropylene 160 mesh



Flexible management tool used to counter heat stress and improve the performance of tunnel ventilation systems.



GrowerSELECT

Sprinkler Control Unit

Programmable unit automatically increases run time and frequency of the system operation.

#HSWS-01 Sprinkler Control Unit



Sprinkler Assembly

Low pressure (50 psi), rotating sprinkler assemblies cover approximately 450 square feet each and are available in different drop lengths to match varying building configurations.

#HSWS0540..... 22" drop w/spinner, valve & tee #HSWS0545..... 30" drop w/spinner, valve & tee



Manifold Station with AC controller and Valves

#HSWS0193	. 2 lines
#HSWS0202	4 Lines

GrowerSELECT

Sprinkler System Package (22" Drops)

Includes a controller, complete manifold, 2 sensors, and all drops. Does not include pvc supply line, fittings, or sensor wire. Must also include one data plug per farm.

Item#	Description	House Size
HSWS2ST-42	2 Station Manifold W/ 42 Drops	Up to 50'wide x 400' long
HSWS2ST-52	2 Station Manifold W/ 52 Drops	Up to 50'wide x 500' long
HSWS2ST-56	2 Station Manifold W/ 56 Drops	Up to 50'wide x 550' long
HSWS4ST-92	4 Station Manifold W/ 92 Drops	55' wide or more x 660' long

Maintain water in troughs and tanks without floats, sensors, or electricity.

- WORKING WATER PRESSURE: Minimum 7 psi and Maximum 50 psi
- WATER TEMPERATURES: Minimum 34°f and Maximum 104°f

#EV1EuroValve without pipe #8153920500 1/2" x 48" SS pipe, no threads #8153930500 1/2" x 60" SS pipe, no threads



Nipples and Barbs

= =	
1A) #P3M12	1/2" x 1/2" MPT nipple
B) #P3M3412	1/2"x 3/4" MPT reducing nipple (not shown)
2) #SD3	Nylon barb, 1/4"
3) #SD3P-B*	Brass barb, nylon base, 1/4"
4) #SD3P-B1/2*	Brass barb 1/2", nylon base
5) #60306	
	1/2" MPT x 1/2" barb
= -	

<u>⚠</u> WARNING:

*This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



ASCO Solenoid Valves

#238210-058-D...... Coil for 20114 Solenoid #20166......3/4", 110V, 5-125 PSI, Normally Open

⚠ WARNING:

*This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Brass and Stainless Steel Solenoids

Valves are designed to allow maximum flow rate under standard operating pressures. High-quality rubber diaphragm creates a tight seal with direct action valve. Operation Mode: Normally closed (N/C), valve opens when coil is energized. Voltage: 24V or 110V. Material: Solid Brass. Thread: 3/4" female NPT (inlet and outlet). Ambient Temperature: 15 to 125 degree Fahrenheit. Port: 3/4" NPT. Pressure Rating: up to 145 PSI. NSF: Certified.




#PWPSB34110NC......3/4 FNPT Brass Solenoid Valve 110V (Normally Closed) #PWPSB3424NC....... 3/4 FNPT Brass Solenoid Valve 24V (Normally Closed) #PWPSS34110NC... 3/4 FNPT Stainless Steel Solenoid Valve 110V (Normally Closed) #PWPSB34220NC ... 3/4 FNPT Brass Solenoid Valve 220V (Normally Closed)

WARNING:

*This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Insul-Seal Insulated PVC



.. Pipe insulated Sch 40 2" x 10' #IN-002......2" insulated elbow, Sch 40 90°

Pressure Gauge

- 1/4" NPT
- 2" dial

- Z ulai	
#61042	0-15 psi
#61038	
#52759	0-100 psi
#52854	0-200 psi
#527593	0-300 psi




Water Meter Coupling

· Adapts water meter to standard 3/4" pipe threads

#H1021-6035.... Water Meter Fitting Bronze 3/4" (sold each) #DI73WM059 Bronze Couplers 1" - Pair (2)









Accurately delivers preset volume then

automatically closes. Simple to install, no electricity. 3/4" MPT.

- Flow rate: Min-.35 to 6.61 Gpm
- · Working pressure: 7.25 to 145 PSI
- Max temperature: 140° F

C) #DI73WM207	250 gal
D) #DI73WM206	
E) #DI73WM205	· ·




This cold water meter is rated for 1/4 to 20 GPM flow rates. Includes 3/4" Male NPT coupling. Frost resistant bronze body with epoxy coating to avoid pinholes. Large pointer dial registers low flow rate by 1/10 of gallon. Pulse model equipped with 1 gallon pulse output fully compatible with most house ventilation controls. Tempered glass lens with plastic lid. Horizontal mount only.

#HSWMNP5/8" x 3/4" Water Meter #HSWMPLS.....5/8" x 3/4" Water Meter w/ Pulse #WM-ACC-RSReed Switch with lead wire

⚠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



The Sonata accurately measures extremely low volume and flow with no moving parts to ensure long lasting precision.

- Registers low volume at 0.05 GPM
- Supplies dual 1 & 10 pulse output
- · Allows independent dual output connection
- · Reliable, long lasting precision.
- · Addresses extremely low volume and flow
- Leak detection can be enabled when paired with a Rotem controller

#DI73WMS01 Plastic housing w/ 3/4" coupler



This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



3/4" Totalizer Water Meter

Polypropylene water meter that reads water flow and transmits an electric pulse to house controllers or metering equipment. Complete with gaskets and couplers.

Max Temp: 105° F
Max Pressure: 150 psi
Max Flow: 20 GPM
Min Flow: .25 GPM
Nominal Pipe Size: 3/4"

⚠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Poly Top Brass Pressure Valve

Automatically controls excessive water pressure to protect water systems components. Thermoplastic cage provides maximum corrosion resistance. Bottom clean out port allows access to seat disc and strainer.

Max Supply Pressure: 400 psi
Max Set Pressure: 125 psi
3/4" Threaded Connections

#36C10401 Apollo Poly Top, 25-75 psi **#36C10402** Apollo Poly Top, 10-35 psi

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Brass Water Pressure Reducer

Designed to reduce high inlet pressures to a workable lower outlet pressure. Balanced internal piston smooths out rapid pressure fluctuations.

- · Cast bronze body w/ SS internal parts
- Max Water Temp.: 180°
- Max Water Pressure: 300 psi
- 3/4" Threaded Connections

#2102440......Adjustable 25-75 psi **#634461**......Adjustable 0-50 psi (preset at 30)

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECTPressure Regulator

The GrowerSELECT® regulator provides constant water flows even at low pressure settings to reduce water wastage. Rugged corrosion-proof housing is impervious to rust, corrosion and medications.

- Adjustable pressure setting.
- · Includes sight gauge
- 3/4" MPT fittings
- Max 50 psi input pressure

HS762	10-25 psi
HS772	3-10 psi



Maxiflo Pressure Regulator

Provides constant even flow of water with adjustable output. Also incorporates a check valve to prevent back flow.

- Max Water Temp.: 100° • Max Water Pressure: 300 psi
- Inlet 1/2" BSP Outlet 3/4" MPT
- High impact plastic housing

#52787......Maxiflo pressure regulator 6001 (1/4 to 3 psi) **#61037**.....Maxiflo pressure regulator 6003 (1-1/2 to 13 psi)



BadgerMeter

- · Lead Free Cast bronze housing
- Operating range 1/2 to 25gpm
- Sealed thermoplastic measuring chamber w/disc meter
- Couplings shown are not included
- · Horizontal mount only

#BADGERMETER.....Badger Meter



Universal Pressure Regulator

Corrosion resistant poly and fiberglass body with synthetic valve components.

- 5-60 PSI adjustable pressure range
- 1" NPT inlet and outlet
- 4.5 to 60 psi adjustment knob
- · Horizontal or vertical installation
- Optional pressure gauge

#DI2205950A	no	gauge
#DI2205950K	w/	gauge



4-Way

(slip x slip x slip x slip)	
#60366	
#60367	3/4"
#60368	1"
#60369	1-1/4"
#60370	1-1/2"

#60371

Coupling	
,	
#60015	1/2
#60025	3/-
#60035	
#60045	1-1/-
#60055	1-1/2
#60065	

Tee

	į	į,			
slip)					ė
	•••		•••	••	

slip x slip x slip)	
60010	1/2"
60020	3/4″
60030	1"
60040	1-1/4"
60050	1-1/2"
60060	2"
60070	3″

Tee

(slip x slip x fpt)	
#60011	1/2"
#60021	3/4"
	1′
#60041	1-1/4′
#60051	1-1/2′
#60061	2"
#600701	3″

90° Elbow	
(slip x slip)	
	1/2"
#60022	3/4"
#60032	1"
#60042	1-1/4"
#60052	1-1/2"
#60062	2"
#60072	3"

#60075

45 FIDOM	N. 100
(slip x slip)	
	1/2"
#60023	3/4"
	1"
#60043	1-1/4"
#60053	1-1/2"
#60063	2"
#60073	3**

E


and Cap	
60018	1/2"
60028	3/4"
60038	
60048	
60058	1-1/2"
60068	
60078	3*

Ball Valve

(slip x slip)	
#60215	1/ 2
#602160	3/4
#602170	1
#602180	1-1/4
#602190	1-1/2
#602201	2

#60258.....

Male Adapter



Female

Adapter	
(slip x fpt)	
#60016	1/2′
#60026	3/4'
	1′
#60046	1-1/4'
#60056	1-1/2'
#60066	2′
#60076	3'

#602166 3/4" valve, SxS

#60403......2" #527458..... 1-1/2" for Cool Cell

In-line Check Valve

Reducing Tee

(slip x slip x slip)	
(Slip x Slip x Slip)	
#600301	1" x 1" x 3/4
#6005111-1	1/2" x 1-1/2" x 3/4



Barb Tee


(slip x slip x barb)

#6002113/4" x 3/4" x 3/4"



#60341	1/2
#60342	3/4
	1
#603461	1-1/2
#60348	2
#60351	3

Pipe Strap



PVC Pipe Cutter



• Cuts up to 1-1/4" pipe

#PW8-PCT158MH	metal handle
#PW8-PCT158RH	rubber handle

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Primer & Glue Multi Pack

#16810145Primer/Glue Multi Pack, 4 oz

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Oatey Rain R Shine



#30890	4 oz.
#30891	8 oz.
#16813594	16 oz.
#30894	

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

PVC Cement



· Heavy bodied for PVC

#602445



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Pipe Cleaner

- Clear
- · CP VC. PVC or ABS

#602446 ... PVC Cleaner, Rectorseal Clear 8 oz SAM CL-3L Low VOC

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Polar Weld


- · All temperature PVC cement · Remains liquid even at low
- temperatures



#602455Polar Weld, 1 quart

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov








#602451 Rectorseal Hot Blue Pint #602462 Rectorseal Hot Blue Quart


▲WARNING:



SPIN-DOWNTM **Sediment Filters**

- · Clear Cover is easily removed for total cleaning (No tools required*)
- Flow capacity for entire system
- Sediment is visible through the clear cover indicating when the filter needs cleaning
- · Sediment is quickly and easily removed by opening the ball valve at the bottom of the filter cover
- Reusable polyester and stainless steel element screens in many mesh sizes
- · No down time
- *Using tools voids warranty









Rusco Spin-Down® Filters, L-Style

Includes polyester screen. Ball valve (602151) sold separately.

Item#	Port Size (slip)	Mesh	Flow/gpm
61008-24L	1-1/2"	24	10-50
Replacement	1-1/2" cartridges, poly	ester screen	
#60110L			60 mesh
#610086L			100 mesh
#610083L			140 mesh
#601100L			250 mesh
	nousing & O-ring		
#60112L			1-1/2" O-ring
#610088L			1-1/2" clear housing



Rusco Spin-Down® Filters, T-Style

Incoming water swirls around the filter housing, flows through the screen center, and out the discharge port. Heavier sediment drops to the bottom and is easily flushed out by opening the ball valve. Includes Filter with cartridge screen and ball valve.

Item#	Port Size (slip)	Mesh	Flow/gpm
61007	1"	60	1-25
61008	1-1/2"	60	10-50
610085	1-1/2"	12	10-50
61009	2"	100	18-100



Rusco Spin-Down® Replacement Cartridges, Filter Housings & O-Rings

The Housings & O-Kings	
1" Cartridge	
#60107	60 Mesh, Polyester Screen
#601071	100 Mesh, Polyester Screen
#610082	140 Mesh, Polyester Screen
#601072	250 Mesh, Polyester Screen
#601074	500 Mesh, Polyester Screen
1-1/2" Cartridge	
#60110	60 Mesh, Polyester Screen
#610086	100 Mesh, Polyester Screen
#610083	140 Mesh, Polyester Screen
#601100	250 Mesh, Polyester Screen
2" Cartridge	
#60123	60 Mesh, Polyester Screen
#601231	
#610232	
#610092	250 Mesh, Polyester Screen
Filter Housing	
#60104	
#60109	1-1/2"
#60121	2"
Housing O-ring	
#60108	
#60112	•
#60125	2"



Rusco Sun-Shield

Black sun-shield for Rusco $^{\text{\tiny TM}}$ 1-1/2" Spin-Down filter housings. Slips over filter housing to prevent sun damage and the formation of algae. Black neoprene construction.





1/2" Threaded Ball Valve

Replacement ball valve for flushing Spin-Down filters.

#602151 1/2" Threaded Ball Valve

MESH SIZE TO MICRON CHART

Mesh	Microns	Typical Material Removed
60	250	Fine Sand
100	150	Sediment
200	74	Rust Flakes
325	44	Clay particles
400	37	Silt

Boshart® Water Filter Housing

Constructed of FDA grade polypropylene cap with clear acrylic styrene housing..

• Dimensions: 11.8"H x 4.72"W

• 3/4" Inlet/Outlet • Max Temp: 125°F • Max Pressure: 125 psi

#603598 Housing only. No filter included





The Big-Bubba filter housings are made of rugged glass-reinforced polypropylene so they will not chip, rust, or dent. Big-Bubba filters have two outlets (2" slip) on opposite sides to allow more flexibility with piping configurations. Overall height is 40" with a 12" width. Maximum flow rate is 150 gpm with maximum working pressure of 125 psi.





Filter Housings

Polypropylene housing with black cap and pressure release valve. Leak-proof seal with top-seated Buna O-ring. Max pressure 125 psi.

Item#	Port Size (NPT)	Housing Size	Body Color
PWP3-25SHC1034H	3/4"	2.5" x 10"	Clear
PWP3-45JHB1010H	1-1/2"	4.5" x 10"	Blue

Ozark Filter Housing

Head is constructed of fill polypropylene with a clear acrylic housing.

- Dimensions: 13-5/8" high x 5-1/2" wide
- 3/4" NPT inlet/outlet ports
- · Max Temp.: 125°
- Max Pressure: 125 psi
- Uses 2.5" Dia. by 9-3/4" to 10" long cartridges with flow rates from 1 to 10 gpm

#3MBPI-1COzark Filter Housing (no filter)



Pleated Cartridges

Item#	Size	Material	Micron
PWP2-251020-PP	2-3/8" x 10"	Polyester	20
603601	2.5" x 9-7/8"	Polyester	20
PWP2-451050-PP	4.5" x 10"	Polyester	50

String Wound Cartridges



Item#	Size	Material	Micron
PWP2-251020-SW	2-3/8" x 10"	Polypropylene	20
EP20X9-78P	2-3/8" x 9.78"	Polypropylene	20
603602	2.5" x 10"	Polypropylene	5
601014	2.5" x 10"	Polypropylene	10
HS60360	2.5" x 9.75"	Polypropylene	20
60360	2.5" x 10"	Polypropylene	20
601015	2.5" x 10"	Polypropylene	30
TSWR 1952	4" x 10"	Polypropylene	20
603603	4.5" x 10"	Polypropylene	20
PWP2-451020-SW	4.5" x 10"	Polypropylene	20
EP50X9-78P	4.5" x 9.78"	Polypropylene	50

Spun Filter

Item#	Size	Material	Micron
603600	2.5" x 10"	Polypropylene	50



Filter Wrench

#3MWRENCH For (Ozark & standard 2-1/2" housing
#TS106415	For 4" Blue housing
#Z783	Ziggity blue housing



Banjo Y Strainer Filter

Fiberglass reinforced poly housing with female NPT ports. Stainless steel screen with clean out plug. Max 150 PSI.

#LS075-20	3/4" w/ 20 mesh
#LS150-50	1-1/2" w/ 50 mesh
#LS150-12	1-1/2", 12 mesh
#LS200-30	2" w/ 30 mesh
#LS141-G	0-ring for end of screen
#LS150-G	3-1/2" 0-ring
#LS220	20 mesh screen
#LS230	30 mesh screen

Rotomax Nozzle

Rotating head delivers a powerful blast to make short work out of your toughest cleaning jobs. The best rotating nozzle on the market.



- · Lighter weight Less fatique
- · Ceramic nozzle protected by plastic outer shield
- · Repair kit is half cost; Less expensive to rebuild

• 9.6 oz.





Item#	Color	Pressure Range	Flow Range	Size
#799114	RED	1300-2000 PSI	2.1-2.6 GPM	4.5
#799115	BLUE	1450-3500 PSI	2.9-4.06 GPM	5.5
#799116	BLACK	1450-3500 PSI	4.2-5.5 GPM	6.5
#725917	Repair Kit, replacement washers, seals and tips			

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Spray Gun Lances



• 1/4 MINPI	3.
	1/4" x 36", 4000 PSI , Zinc plated w/ grip & side handle
2a) #SA07000470.	1/4" x 36", 6000 PSI, Zinc plated w/ grip
2b) #LG36SS	
3) #LG18FLEX	1/2" x 18", 2000 PSI, Zinc plated, Flexible grip
4) #LG90HNDL	Adjustable grip for lance

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



NOZZLES

Dirt Killer Nozzles

The Industrial Dirt Killer (IDK) features a slower spinning turbine that creates a larger water droplet with greater impact making it an outstanding choice for cleaning concrete and steel. Rebuilding the IDK nozzles is easy with the rebuild kit which includes all the internal parts necessary to make it like new. Rated use at 4700 PSI and 180° water temperature



with 1/4" male threads. The Dirt Killer (DK, part# DK97410713) has high speed rotating turbine which delivers the punch of a 0° nozzle with the coverage of a 25° fan. This effectively gives it 10 times the cleaning power of a standard flat tip nozzle. Rated at 3200 PSI and 180° water temperature with 1/4" female threads.

#DK97410711	Nozzle Dirt Killer 8.0 IDK Red
#DK97410712	Nozzle Dirt Killer 5.5 IDK Black
#DK97410713	Nozzle Dirt Killer 4.5 DK Yellow
#DK97410714	Nozzle Dirt Killer 5.5 DK Black
#DK97410715	Nozzle Dirt Killer 7.0 IDK Blue
#DK97410717	Nozzle Dirt Killer 10.0 IDK Brown
#DK97410718	Nozzle Dirt Killer 4.5 IDK Yellow Or Green
REPAIR KITS	
#DK9741097	Nozzle Dirt Killer Replacement Kit 4.5 DK
#DK97410971	Nozzle Dirt Killer Replacement Kit 5.5 IDK Black
#DK97410972	
#DK97410973	Nozzle Dirt Killer Replacement Kit 8.0 IDK Red
#DK97410975	Nozzle Dirt Killer Replacement Kit 10.0 IDK Brown
#DK97410976	Nozzle Dirt Killer Replacement Kit 4.5 IDK Yellow
#DK97410978	Nozzle Dirt Killer Replacement Kit 5.5 DK Black

🗘 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Premium High-**Pressure Hose**

3/8" double braid hose with NPT fittings and bend restrictors. 6000 PSI and 250 degree maximum temperature. Fittings included.



#HFH6000-10	3/8" x 10'
#HFH6000-40QC 3/8" x 40"	5800 Msc, Quick Connects
#HFH6000-50	3/8" x 50'
#HFH6000-75	3/8" x 75'
#HFH6000-100	3/8" x 100'

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



5-Pack High Pressure Spray Tips

Kit includes five different tips. O for cutting, 15 for chiseling, 25 for flushing, 40 for washing and a chemical nozzle.

#97331.....5-Pack High Pressure Spray Tips

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- · Harden Stainless Steel construction
- 1/4" NPT
- 15° flat spray pattern
- gpm @ 3000 psi

#5330090	1512 tip, #12 orifice, 6.93 gpm
#5330088	1508 tip, #08 orifice, 10.93 gpm
#5330092	1530 tip, #30 orifice, 25.98 gpm
#5330093	1560 tip, #60 orifice, 51.96 gpm

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Pressure Washer Gun

- 3/8 FMPT inlet x 1.4" FMPT outlet
- 5000 PSI maximum
- 10 GPM
- 300° maximum temperature
- · Stainless steel valve components

#LG5000......Giant Gun Jet

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- 3/8" FMPT inlet x 1" FMPT outlet
- 5000 PSI maximum
- 12 gallon minimum
- 300° maximum temperature
- · Stainless steel valve components

#SA202305600 Easy Pull Trigger Spray



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





High-Pressure Nozzle Filter

- · Recommended for use with rotating nozzles
- · Male plug not included

#799602 1/4" MPT x 1/4" FPT

⚠WARNING:



Coupling

#60095	1/2" - SCH 80
#609660	3/4" - SCH 80

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Steel Union

#60097 1/2" - SCH 80

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



45° Elbow

#60093.....1/2" - SCH 80

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



90° Elbow

#60092. 1/2" - SCH 80 #609772......3/4" - SCH 80

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#6009073/4" x 21' - SCH 80 ♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



.....1/2" x 6" - SCH 80 #60098. #6009053/4" x 6" - SCH 80

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Reducing Tee

#609722..3/4" x 3/4" x 1/2" -SCH 80 #6095331" x 1" x 1/2" - SCH 80

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Steel Tee

#60090..1/2" - SCH 80

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



• 3000 psi - 2 lbs.

• 2000 psi - 13.6 oz.

.. 1/2" - 3000 PSI #60241 1/2" - 2000 PSI

↑ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Reducer

#1059...... 1/2" - 3/8" - SCH80

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Conduit Hanger

• Nipple x Female pipe

• 4000 psi - 200° F

#728827..... #728833.....

#10394 1/2" - Galvanized 270

⚠WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#728831 3/8" - Steel **#728837**......1/2" - Steel #728821 1/4" - Brass

High Pressure Female Nipple

#728825.....

High Pressure Brass Couplers





⚠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





4-Way Cross

#60096......1/2" SCH 80

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#728826......1/4" - Stainless **#728832**......3/8" - Stainless **⚠WARNING**:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Plug Male

1/4" - Steel

- · Nipple x Male thread
- 4000 psi 200° F

#728823	1/4" - Steel
#728835	1/2" - Steel
#728822	1/4" - Brass
	3/8" - Brass
#728824	1/4" - Stainless
#728830	3/8" - Stainless

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Rectorseal **Thread Sealant** #5 Yellow



#60248.....#5 Multi-purpose 16 oz

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Rectorseal **Thread Sealant** T Plus 2



......3/8" - Brass

......1/2" - Brass

#602481 w/PTFE Teflon 16 oz White

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Rectorseal Thread Sealant Millrose Blue Monster



.....w/PTFE Teflon 16oz Pint #602491.....

⚠WARNING:

Stennicator Pump

Compact electrical unit accepts a pulse from a dry contact water meter and injects directly into the water line. Unaffected by water quality, scale or solids. Stock solution does not contact any moving parts. Includes 10' cord.

- Flow range: 2.7 Ounces per Minute
- Flow ratio: Fixed 1:128
- Pressure: Up to 80 psi
- Size: 5.4" x 4.4" x 5.9"

#E20MH81S Stennicator Pump, 1:128 Ratio



Digital Pump This unit is an adjustable version of the popular Stennicator pump and is activated by a dry contact water meter with an output relay to monitor water consumption. It can be used with an existing water meter used with house controllers. Eliminates dilution of liquid chemicals such as

Includes 10' power cord. • Flow range - .5 to 30 gpd

Econ Integrator

- Available as 4.5, 16 and 30 gallons per day units
- · Adjustable in 1% increments
- Size: 5.4" x 4.4" x 5.9"

#E20RHF81S	4.5 gp
	16 gp
#E20RHH81S	30 m



STENNER PUMPS

Classic Single Head Adjustable Pump

Electromechanical, versatile, self-priming pump.

45MHP10 Model

- Output: 0.5 to 10.0 GPD
- Output Adjustment: 20:1, 1% increments
- · Pressure: To 100 psi
- Size: 10.6" x 5.3" x 6.0"

#45MJH2A1S45MHP10 model-Single head adjustable



- Adjustable from 5% to 100% in 2.5" increments
- · Max output 17 gallons per days

#85MJH2A1S Stenner Chlorine Pump





Classic Tube Kit (2/pack) High Pressure

· Includes Duckbill

#UCCP1FD	Tube Kit #1, 3 gpd
#UCCP2FD	Tube Kit #2, 10 gpd
#UCCP7FD	Tube Kit #7, 40 gpd
	_

Stennicator and **Integrator Tube Kit**

#EC30F-2 Integrator Pump F tube / 4.5 gpd #EC30G-2Integrator Pump G tube / 16 gpd #EC30H-2 Stennicator Pump and Integrator Pump H tube / 30 gpd



Suction/Discharge Tubing

20' rolls

#AK4002B	1/4", UV blacl
#MALTO2B	
#SPMAITOO2	



Check Valve Duckbill (2/pack)

#UCCVDBO...... Check Valve Duckbill



Roller Assembly

#SEC350 Integrator white (F tube/ 4/5 gpd) #EC351 Stennicator and Integrator, black (G tube/ 16 gpd & H tube/ 30 gpd)



Classic Series Feed Rate Control Service Kit

· For classic single head adjustable pump

#SFSK1 FRC kit



1/4" Injection Check Valve



1/4" Flow Indicator with Bracket

Visual reference to confirm solution is pumping; bracket (not shown) secures vertical installation.

#AK600 1/4" Flow Indicator with Bracket





A true 11 GPM electric medicator not affected by water quality.

Pump receives electric pulse from a water meter to automatically adjust injection rates to changing water flows.

- Fixed 1:128 ration
- PVDF solenoid head for enhanced chemical resistance
- Self-priming pump head with manual air bleed for fast priming doesn't lose its prime during operation
- Alarm to detect and notify of suction or discharge interruption when bucket is empty
- Single piece, chemical resistant Teflon® (PTFE) diaphragm design
- · PVDF solenoid head for enhanced chemical resistance
- · IP65 acid resistant housing
- 120V, 60 Hz power

1)

#E128..... Etatron metering pump



Pump Head

#SCP8006871 Pump head



2)




#SFT0832021 Foot filter
#KRA0007021-1 Injection and foot filter valve kit



Replacement Tubing/per foot

4) #A100004202-1	PVC 6x8 IIIII suction tube
5) #DUT0000006-1	4x6 mm priming tube
6) #ATU0000603-1	PE 6x8 mm discharge tube





Replacement Tubing Kit

- · Injection valve and foot filter
- 6 x 8 mm PVC and polyethylene tubing

#SC00031021.....Replacement tubing kit

4) # #TTTOOO4202 1



Medicator Medicator



DPLH128 Medicator

Connection Size: 3/4" NPT Unit Weight: 3 lbs **Dimensions:** 11.25" x 6.5"

Operating Flow: 1/3 Pint/Min to 11 GPM

Pressure: 4.3 to 85 PSI


Ratio: 1:128

Dilution Rate: 1 oz/gal Maximum Temperature: 104°F

Accessories: Clear suction tube, mounting bracket, weighted strainer,

quick start guide

#DPLH128 Medicator



DPLH128 Replacement Parts

#DPL001	Lid, Black
#DPL002	Wishbone for DPLH128 Medicator
#DPL003	O-Ring Top for DPLH128 Medicator
#DPL004	Assembly Piston Assy And Plunger
#DPL005	Body, Black
#DPL006	Spring (2) DPLH128 Medicator
#DPL007	Kit With Sleeve Valve Spring And Pin
#DPL008	Assembly Suction Hose
#DPL009	Kit With Top And Bottom Seals
#DPL010	Kit With Black Stem Barb And Hose Nut
#DPL011	Plunger for DPLH128 Medicator



Assembly Suction Hose #DPL008



Scan for YouTube

DIY maintenance video

Kit with Sleeve, Valve Spring and Pin #DPL007

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Kit with Top and Bottom Seals #DPL009



Kit with Black Stem Barb and Hose Nut #DPL010





D128R Medicator

The original flat top medicator; the producers choice for over 35 years. Features adjustable ratios of 1:200, 1:128 or 1:100 that can be changed by simply moving a pin.

• Flow range: .09 GPM to 7 GPM • Preset at one oz. per gallon, 1:128

• 7 to 70 PSI • Size: 13" x 6-1/4"

#52900......D128R Medicator




D128R Rebuild Kit

#MKD128RRebuild kit

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



D128R Replacement Parts

-	
1) #529291	Cap
	Cap O-ring
3) #52925	Wishbone Spring Assembly
4) #52927	Piston Shell
5) #52918	Body
	Actuator Spring
7) #52923	Plunger
8) #52910	Slide Valve Spring
9) #52913	Slide Valve Pin
11) #52911	Top Seal
13) #52912	Bottom Seal
14) #52907	Stem Cap
15) #52909	Suction Hose Nut
16) #MP004	
17) #PDIO43	Strainer for 1/4" hose, D128R, D25F, D25RE2





D14MZ2 Medicator

Versatile unit capable of delivering 14 GPM for larger houses. Features exterior adjustable sleeve to allow you to quickly change ratios from 1:500 to 1:50.

• Flow range: .05 GPM - 14 GPM • Adjustable ratio: 1:500 to 1:50 • Percentage: .2 to 2%

• Pressure: 4.3 to 85 PSI • Size: 19-1/8" x 6-5/16" • 3/4" NPT inlet/outlet

#D14MZ2VF11.....D14MZ2 Medicator





D45RE15 Medicator

A high volume unit with 20 GPM. Designed for use with multiple house sites. Adjustable exterior sleeve for regulating ratios from 1:500 to 1:66.

• Flow range: .4 GPM - 20 GPM · Adjustable ratio: 1:500 to 1:66 Percentage: .2 to 1.5% • Pressure: 7 to 70 PSI • Size: 24" x 7.5"

• 1" NPT inlet/outlet

#D45RE15 D45RE15 Medicator





D25RE5 Medicator


High dilution range (1% to 5%) enables a single unit to handle medication, vaccination and line cleaning duties. Exterior adjustment sleeve allows quick adjustment of ratios.

• Flow Range: .05 to 11 GPM • Adjustable ratio: 1:100 to 1:20 • Percentage: 1% to 5% • Pressure: 4.3 to 85 PSI

• Size: 14" x 6-1/4" • 3/4" NPT inlet/outlet

#D25RE5 D25RE5 Medicator

Dosatron Repair Kits









D40MZ2/D8RE2 Mini Maintenance Kit

#PJDI120VMINI-H.....mini kit



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



D45RE15 Mini Maintenance Kit



#PJO96MINI-Hmini kit

D14MZ2 Mini Maintenance Kit

Replacement Seal Kit

#PJDI116VF

D14MZ2



seal kit

⚠WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov








piston kit








D8RE2 Medicator

The D8RE2 is no longer available and has been replaced by the D40MZ2.

Repair and replacement parts for the D8RE2 are available.



See Page 139 for Repair Kits

D8RE2 Replacement Parts

1) #8MP039	Bell housing assy. w/air bleed 0-ring
2) #PDI700	Air bleed cap
3) #MPDI184	Air bleed
4) #8P155	
5) #8J041	Bell housing O-ring
6) #8PJ066NPT Equipped pur	np body sub assy. w/diffuser US version
7) #8PJ068VF	Sub-assy vacuum breaker
	Nut
9) #8PC002	Rack guide
	Sub assy. piston fastening adapter
	Plunger piston sub-assy. + seal VF
12) #PDI754	Plunger
13) #JDI121VF	Plunger seal VF
14) #8PC002	Motor sub-assy. without plunger rod
15) #8P022	Rack guide
16) #8P021	Rod with rack
17, 20, 28) #8M005	Screw for piston
18, 29) #8M007	Washer
19) #8MP033	Motor piston SHELL sub Assy
21) #8J007	Piston O-ring
22) #8PJ009	Upper valve assy. for piston + seal EP
23) #8M015	Toggle spring
24) #8M006	Draw Bolt
25) #J006VF	0-ring seal VF
26) #8MP031	Barrel sub assy.

27) #0MD010	Volvo booring ann oggy
-	
	0-ring seal
32) #8PJ031	Lower valve assy. for piston + seal EP
33) #8CD033VF	Complete injection assy. VF
34) #JDI122VF	Injection stem O-ring Seal VF
35) #PDI753	Injection stem
	Sleeve O-ring VF
37) #8P159	Graduated injection sleeve
38) #PDI702	Injection stem nut
39) #PPDI037	Adjusting ring w/eyelet
40) #PDI751	Anti-rotation ring
41) #PDI746	Blocking ring
42) #PJDI118VF	
43) #PDI747	Suction valve nut
44) #PDI748	
45) #MPDI189	Suction hose assy. 16mm
	Suction hose 16mm (sold by the foot)
47) #MPDI209IND	Strainer/foot valve 16mm
NS) #MPDI196	
NS) #8P044	Wall bracket
NS) #8EM003	Motor seals set
NS) #20J002	0-ring seal
NS) #8J041	Bell housing 0-ring
NS) #PJDI120VVF	.Injection seals Kit V VF + suction valve + barbed fitting



D40MZ2 Medicator

The D40MZ2 replaces the D8RE2 high capacity medicator with an improved piston and 63% fewer replacement parts. Its 40 GPM flow rate handles the needs of large multi-house sites. The exterior sleeve regulates the injection rate from 1:50 to 1:500.

• Flow range: 2.2 - 40 GPM • Adjustable ratio: 1:500 to 1:50

• Percentage Range: 0.2 to 2% • Pressure: 4.3 to 116 PSI • Size: 25-1/4" x 8-1/2"


• 1-1/2" NPT inlet/outlet



DOSATRON

D40MZ2 Replacement Parts

Bell Housing Assembly
Air Bleed Protective Cap
Air Bleed
Bell Housing
Bell Housing O-Ring
Bypass
Body Assembly
Vacuum Breaker Valve
Nut
Wall Bracket
Piston Assembly
Plunger Assembly
Plunger
Plunger Seal
Piston Assembly
Pushrod Plastic Seal
Upper Piston Valve O-Ring
Omega Spring
Connecting Rod
Piston Maintenance Kit
Omega Spring
Connecting Rod
Upper Flange
Lower Flange
Upper Flange
Piston Shell
Lower Flange
Injection Stem Assembly
Injection Stem O-Ring
Injection Stem
0-Ring
Injection Sleeve
Adjusting Sleeve
Anti Rotating Ring
Locking Nut
Check Valve Assembly
Check Valve Nut
Hose Nut
Pushrod Plastic Seal
Upper Piston Valve O-Ring
Upper Piston Valve O-Ring
Bell Housing O-Ring
Seal Kit - D40MZ2/D14MZ5/D8RE2
Plunger Seal
Injection Stem 0-Ring
0-Ring
Check Valve Assembly
Hose Assembly
Strainer Assembly





D25F Medicator

Features a higher flow rate designed to handle bigger animals and larger buildings. Fixed 1:128 ratio eliminates possible mistakes in medicating your animals or birds.

- Flow of .05 to 11 GPM
- Fixed ratio at 1:128
- Pressure: 4.3 to 85 PSI
- Connection Size 3/4" NPT



D25F





D25RE2 Medicator


An enhanced version of the 11-GPM unit that features an exterior adjustment sleeve allowing you to quickly change ratios from 1:50 through 1:500.

- Flow of .05 to 11 GPM
- Adjustable Ratio: 1:500 1:50
- Pressure: 4.3 to 85 PSI
- Connection Size: 3/4" NPT




11 GPM

DOSATRON



	•	
1)	#DP420	Lid
2)	#52917	Lid 0-ring
3)	#PC061VF	Piston
4)	#MP178	Wishbone spring assembly
		Actuator spring
6)	#P019	Plunger
7)	#J009VF	Plunger seal
8)	#P159U1	Body
		Cone
10) #J024VF	Stem 0-ring
11	#P439	Injection Stem
		Check valve assembly
13) #J051VF	Check valve seal
14) #P169	Hose barb
15) #52909	Hose Nut



D25RE2 Replacement Parts

1) #PDI568	Cone
2) #J024VF	Stem 0-ring
3) #P165	Sleeve
4) #PJ121VF	Stem assembly
5) #JDI098VF	0-ring
6) #P450	Stem
7) #P167	Sleeve
8) #P189	Plastic nut
9) #P168	Locking nut
10) #MPDI122	Check valve assembly
11) #J051VF	Check valve seal
12) #P169	Hose barb
13) #52909	Suction hose nut







The DM11F uses a completely redesigned hydraulic motor that is piston-free, which allows the medicator to work properly even in environments with sand, algae, or high mineral content in the water supply. The DM11F also features a highly chemical resistant housing to allow for use of a wide range of chemicals, including pH water treatment chemicals and other substances commonly used to combat bio-film.

Maximum Flow: 11 GPM
Minimum Flow: 0.02 GPM
Injection Percents: 0.8%

Injection Ratios: 1:128 Fixed
Pressure Range: 1.5 to 85 PSI
Connections: 3/4" NPT

#DM11F.......DM11F Diaphragm






Slider Repair Kit
#PPDI048.....Slider Repair Kit



Mini Maintenance Kit

#PJDI900MINI-LS.......Mini Maintenance Kit



DM11F Replacement Parts

i	1) a	#MPDI199	
į	2)	#MDI367	Screw
į			Nut
1	4)	#PJDI127HT	Diaphragm
i			Plastic seal for diaphragm
ė			Body
į	7)	#PPDI048	
į	8)	#MDI387	
į	9)	#JDI128HT	Actuator gasket
i	10)	#PJDI125H7	Γ Actuator subassy and gasket
İ	11)	#JDI129HT.	Actuator gasket
i			O-ring seal for actuator (2 req)
į	13)	#PDI777	Upper transfer body
į			Transfer body
į	15)	#MDI355	Screw
į			Transfer body gasket
Ė	17)	#MDI356	Nut
į	18)	#8J040HT.	O-ring for isolation body
i	19)	#PDI846	Isolation body
į	20	#PDI848	Plunger
į	21)	#JDI105VT.	Plunger o-ring top
į	22) #J009VF	Plunger seal bottom
į	23	#JDI100HT	O-ring for stem body
į	24) #PPDIO45	Injection stem assembly
į	25) #PD1702	Top stem nut
i	26) #PJDI115H7	FAFCheck valve assembly
Ţ	27) #PDI739	
į			Check valve spring
į	29) #PDI729	
į	30) #JDI105VT	0-ring for check valve cone
i	31)	#JDI130HT	0-ring for hose barb
į	32) #PDI740	Hose barb
į	33) #PDI734	
1	34) #PDI735	Lower stem nut
i			
1	36) #52908	Strainer for 5/16" hose, DM11F
1	37) #PDI806	
- 6			



Chemilizer

HN55 Medicator, Fixed

WATER MOTOR

- · Has no sliding piston to wear out.
- Is not affected by chemicals since they are injected directly into the water line for mixing.

CHEMICAL PUMP

- · Twists in and out of water motor.
- · Easy maintenance.

SPECIFICATIONS

- Maximum Flow: 11 GPMMinimum Flow: 0.02 GPMPressure Range: 3-85 psi
- Connections: 3/4" NPT

#CH9000-209...... HN-55 Medicator, Fixed, 1:128




HN55 Medicator, Adjustable

SPECIFICATIONS

- Flow Range: .02 to 11 GPM • Adjustable ratio: 1:50 to 1:164
- Percentage: .6 to 2%
- Operating pressure: 3 85 PSI

 $\textbf{\#HN55ADJ}....\,\text{HN-55 Medicator, Adjustable, } 1:50\text{--}1:168$



1) #52978	Twist air vent
2) #52944	Тор сар
3) #52959	Actuator arm
4) #52952	I/O valve
5) #52962	0-ring 109 (Discontinued)
6) #52996	Assembly for Inlet Tee
7) #6068014	10-32 nut
8) #52946	Bottom cap
9) #5289022	10-32 stainless steel screw
11) #FG8015	Main body assembly
12) #529486	Motor piston clip
13) #52997	Assembly for Outlet Tee
14) #52950	Diaphragm assembly
15) #FG8014	Body assembly top
16) #52955	0-ring 159
17) #52956	0-ring 009
18) #52958	Pivot arm
19) #52953	Tension ring

20) #FG5027 Medication hose assembly



Replacement Kit for I/O Assembly

#52952.....Replacement Kit for I/O Assembly



Sleeves

A) #10095071	Ceramic Sleeve
B) #10097374	Kynar Sleeve



Fixed 1:128 Pump

Kynar sleeve with Viton seal assembly.

#FG9209-V Fixed 1:128



Adjustable 5% Pump

Fits new style Chemilzers only Ratio 1:20 - 1:64 Percentage 5% -1.6%

#10095982......Adjustable 5%





Fixed Pump Rebuilt Kit- Ceramic

For fixed ration pumps with ceramic sleeve Kit includes: (1) blue replacement stem (w/ o-ring and gasket installed), (2) replacement pump body o-rings and (1) Viton check valve.

#0R9409-V	1:128
#0R9410-V	1:100



Adjustable Pump Rebuild Kits

Kits include:

- (1) Pump Stem
- (1) Upper Stem O-Ring

Adjustable 2% Pump

Fits all Chemilizer models

Percentage 2% -.06%

Ratio 1:50 - 1:164

- (1) Stem O-Ring
- (1) Check Valve Kit
- #10096920.....1:20 -1:64 #10096938.....1:50 -1:164



Adjustable Pump Stem

Includes upper and lower stem o-rings.

#10096903...... Adjustable stem



Fixed Ratio Pump Stem


Includes o-ring and gasket

#OR9009......1:128 Fixed



Fixed Pump Rebuilt Kit- Kynar


For fixed ration pumps with Kynar sleeve Kit includes: (1) white replacement stem (w/ o-ring and gasket installed), (2) replacement pump body o-rings and (1) Viton check valve.



Fixed Ratio Repair Kit- Kynar

For fixed ration pumps with Kynar sleeve Kit includes: (3) replacement o-rings, (3) replacement gaskets and (1) 1% Viton check disk

#FG9910Fixed



Fixed Ratio Repair Kit- Ceramic

For fixed ration pumps with Ceramic sleeve Kit includes: (6) replacement o-rings and (1) 1% Viton check disk

#0R9910.....Fixed




Clear Suction Hose

Approximately 4 feet long.



Weighted Filter

#52949...... Black PVC





#IS8030Service kit





#IS1032-A1Connecting rod assembly

Quick Clip Pump Piston #IS8039Quick clip pump piston

Gator Replacement Parts				
1) #IS1021	Motor cap top			
2) #IS2001	Motor cap 0-ring seal			
3) #IS2020	Tension bands(set of 2)			
	Intake/exhaust valve sub assembly			
5) #IS2016	Union adapter O-ring seal			
6) #IS1092-A1	Hose adapter assembly (set of 2)			
7) #IS1011-A2	Main body assembly			
9) #IS1071-A1	Motor piston/cylinder assembly			
10) #IS1032-A1	Motor/pump connecting rod assy w/IS2011 O-rings			
	Motor bottom cap			
	Retainer washer (pack of 10)			
-	Intake/exhaust valve seals (set of 4)			
	Retainer washer (pack of 10)			
	Washer (pack of 10)			
-	Pivot shaft			
	Stop (set of 2)			
	Pressure plate ring			
	Pump body with sleeve assembly			
•	Pump cap			
	Suction hose - 5'			
	Chemical filter assembly w/screen			
-	Pressure tube			
26) #IS3010	Pressure fitting			

Chemical Pump Assembly Replacement Parts

Key	Item#	Description
40-1	IS1061S-3A	Pump Body w/sleeve assy.
40-2-128	IS8031XTP	Replacement Cartridge (1/128)
40-3	IS3063-A1	Filter Assembly with 3063-1
40-4	IS3020-1	Pressure Tube
40-5	IS3010	Pressure Fitting
40-6	IS8039	Quick Clip Pump Piston (Pack of 1)
40-7-128	IS1111	Pump Cylinder (1/128)
40-7-100	IS1112	Pump Cylinder (1/100)
40-8	IS1121	Pump Cylinder Seal
40-9	IS8038	Pump Check Valve (Pack of 2)
40-10	IS1102-A1	Hose Barb w/ Seal
40-12	IS3030	Suction Hose 5'
40-13	IS3063-1	Filter Screen
40-14	IS2010	Pump Body Seal O-ring (Set of 2)
40-15	IS2017	Pump Body Sleeve Seal O-ring
40-16	IS1151	Pump Body Sleeve
40-17	IS1052	Pump Cap

O DOSATRON

Proportioner Venturi Valve

Venturi proportioners provide an economical method of accurately dispensing chemicals. Interchangeable, color coded tips vary injection rates. 1/4 turn changes from ON to rinse.

- Self cleaning polypropylene
- Cleaning flow rate: up to 2 GPM at 58 psi
- · Washing flow rate: up to 13 GPM at 58 psi
- Temperature: up to 160° F
- Built-in check valve
- · Suction valve and strainer

#DSA-VENTURI......Proportioner Venturi Valve

Owik-Blend **Injector Pump**

Preset unit injects Proxy-Clean® directly from the jug without premixing a stock solution. Reliable 3% venturi injects without

moving parts to break. Steel cabinet with extra 3% tips, ships with connection hoses preclamped for installation.

#WC001 Proxy Clean Quick Blend 3%





Dilution Ratio: 1:128 Fixed (.08%) Water Flow Rate: .03 to 11 GPM Operating Pressure Range: 2.9 to 129 PSI Connection Size 3/4" BSPT

#DI7125010......2501 Fixed Rate Pump



Dilution Ratio: 1:500 to 1:50 (.03 to 2.0%) Water Flow Rate: .03 to 11 GPM

Operating Pressure Range: 2.9 to 120 PSI Connection Size 3/4" BSPT

#DI7125360000024 Suction Tube Kit



Agitator Pumps

- 1/200 hp, 115 V
- 6-1/4" H x 4-1/4" W x 6-1/4" L
- No more clumping at the bottom of the stock tank.
- · Keeps hard-to-mix chemicals in suspension!

#5002036' cord



Mix and Measure Bucket

Graduated 5-gallon mixing bucket. Ideal for medicator stock tank. Lid not included

#3250230 Mixing Bucket



• for Model 2502

#DI7125200Seal Kit



Mechanism **Springs**

· Plastic, (2)

Suction Tube Kit

• 10mm for Model 2502

#DI7125360000191Mechanism Springs



#DI7125360000119..... .Check Valve Kit






• for Model 2501

#DI7125360000206Seal Kit

SuperDos

SuperDos is designed with a patented internal mixing chamber that promotes homogeneous mixing, while segregating harsh chemicals from critical internal components. It comes in various models that easily satisfy the demands of your most challenging applications.

- · Proprietary composite body for chemical compatibility and for mixing aggressive chemicals
- Built-in on/off switch (30 and 45 models only), which allows user to stop the injection - but not the system
- · Separate internal mixing chamber to prevent chemical contact with motor piston — for longer life and uniform mixing
- · Interchangeable lower ends with the ability to adjust ratios while in operation
- · Highly aggressive, chemical-resistant models available





Wear Parts Kit E

#HS011831PV Kit Parts E for 30 2.5%



#HS011833PV..... Kit Parts E for 20 2.5%



Wear Parts Kit G

#HS011843PV......Kit Parts G for 20 2.5%



Parts Kit A

#HS011850V.. Washer & Dosage Gasket for 20/30 2.5%



Gasket Injector Mixing Chamber

#HS194605 ... Gasket Injector Mixing Chamber for 20/30



♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Dosage Piston

#HS010044P......Piston Dosage for 20/30 2.5%



Wear Parts Kit D

#HS011461VKit Parts D for 30 2.5%



Wear Parts Kit G

#HS011841PVKit Parts G for 30 2.5%



Wear Parts Kit H

#HS011863 Motor Piston Adv 20/30 ON/OFF



Wear Parts Kit F

#HS011961V Kit Parts F for 20/30 2.5%





Washer Injector

#HS197090......Washer Injector SuperDos 20



Top Housing

#HS194610 Top Housing For SuperDos 45



O Ring


#HS212025V O Ring Outer Cylinder Lower End for 20/30




#HS194615 Plug Non Bypass Injector for 20

WWW.HOGSLAT.COM

ROTEM Replacement parts for Platinum Plus and Plus Jr



1A) #DI78CPPKBDLED	New Style Key Pad
2) #DI784CLCD	Cable - LCD
2A) #DI78SPPPLCDLED	New Style Cable - LED
3) #DI784CKEY	Cable - Keypad
4) #DI784PPMB	Main Board - CPU
4A) #DI784CPPARM	New Style Main Board - CPU
5) #DI784JUCP	Jumper - CPU
6) #DI784CBUS	Cable - Bus to Bus
7) #DI784CMAI	Cable - Platinum Main
8) #DI784PPPS	Power Supply
9) #DI784RDIC	Digital Card
10) #DI784ANOU	Analog Input
11) #DI784IBUS	Input bus for Platinum Plus





Communication Card

10.

#DI784COMM.....Communication Card



Relay Block for Winch Card

#DI784REWC..... Relay Block for Winch Card



Variable Output Card

#DI784ANACVariable Output Card





Static Pressure Sensor

#DI784STAT Static Pressure Sensor



ROTEM°

Rotem Pro


Poultry House Control Computer

- Large range of hardware combinations enables extremely flexible system design
- Less wiring to ventilation fans required (when used in conjunction with the HUBs).
 Expansion boxes support input/output devices, removing the need for additional controllers.
- · Improved software capabilities support an unlimited number of devices, including scales, meters, digital thermostats, and more.
- Extended longevity of hardware components.
- Minimal internal heat improves durability in hot climates.
- Reduced electrical noise levels inside the controller improve signal quality.
- Simplified troubleshooting enables detecting faulty cards easily and quickly.

#DI784RPRO40	.Rotem Pro	/40 Relay	/S
#DI784RPR050	.Rotem Pro/	50 Relay	/S







Rotem Platinum Pro Spare Parts

1) #DI784SPPROXLLCDLED	LCD Display
2) #DI784CPPARMPRO	Main Board
3) #DI784KEYP	Key Pad (Discontinued)
4) #DI784CBOARDONE	P4 RS485 Card
5) #DI784SWONPRO	Switch Card
6) #DI784SBUSPRO	Switch Bus
7) #DI784STAT	Static Pressure Sensor
8) #DI78CBOARDPRO	Connection Board
9) #DI784RDICPRO	Digital Input/ Water, Feed, Alarm
10) #DI784ANOUPRO	Analog Input Card/ Sensor
11) #DI784IBUSPRO	Input/ Output Bus
12) #DI784ALARPRO	Alarm Card
13) #DI784CPPPS100DVPRO	Power Supply
14a) #DI784REONPRO	Relay Card
14b) #DI784RELAPRO	Relay Block 10 Relay w/ 10 Switches

15) OPTIONAL PARTS	Analan Ontont Card Discourse
#DI784ANACPRO	0 1
#DI784CPPISO485PRO	
16) #DI784CABLPRO	Cable-Switch/ Relay
17) #DI784CKEY	Key Pad Cable
18) #DICABLE-PLATINUM LCD	
19) #DI784CMAIPRO	Main Cable
20) #DI784RELC	Plastic Relay Lock
OPTIONAL PARTS (NOT SHOWN)	
#DI784PPROWC	Winch Card Set
#DI78PPPCSS30APRO	Current Sense Set
#DI784PPROSOWC	Winch Switch Card Only
#DI784CPPROWCBRC	

ROTEM°

Rotem One

Poultry House Control Computer

Touch screen brings together mission critical data in one easy to read screen. Defining functions is done directly from a large screen designed for its ease of use.

- \bullet Large range of hardware combinations enables extremely flexible system design
- \bullet Less wiring to ventilation fans required (when used in conjunction with the HUBs).
- Expansion boxes support input/output devices, removing the need for additional controllers
- Improved software capabilities support an unlimited number of devices, including scales, meters, digital thermostats, and more
- Extended longevity of hardware components
- · Minimal internal heat improves durability in hot climates
- Reduced electrical noise levels inside the controller improve signal quality
- · Simplified troubleshooting enables detecting faulty cards easily and quickly

#DI784R0540	One	Touch	40R/50
#DI784R0550	One	Touch	50R/50



Extension Box for Rotem Controllers

Rotem Relay Expansion Boxes provide additional relays for Rotem controllers.





Rotem Relay Expansion 50 Box: Up to an additional 50 relays

#DI784RX520	Relay 20 Stage Expansion in 50 Box
	Relay 30 Stage Expansion in 50 Box
	Relay 40 Stage Expansion in 50 Box
	Relay 50 Stage Expansion in 50 Box
	, , ,

Rotem Relay Expansion 30 Box: Up to an additional 30 relays

#DI784X310	Relay	10 Stage Expansion in 30 box
	Relay 2	0 1
	Relay 3	0 1



Rotem Enhanced Backup


#DI78PRBU27SECD4V1 RBU-27 SE Enhanced Backup



Communicator 2.0

The Rotem Communicator 2.0 delivers next level control with an extensive alarm package and remote access to your farm's controllers via the web. From its feature-rich, yet easy-to-use alarm configuration and management software, the alarm package delivers vital, real-time data giving you the unprecedented ability to quickly manage any problems that arise.





Backup Circuit Board

#DI78CRBU5ST.....Backup Circuit Board



Relay for Backup Box

#5X848...... Relay, DPDT, 8 Pins, 240VAC



Airstream GTC5-2N6FA Controller

#GTC5-2N6FA	8 stage combo-2 var,2 heat, 2 on/off, 2 curtain
#GE330-0536	Top replacement board only
#GE330-0537	Bottom replacement board only

Airstream GTC5-2V2SA Controller

#GTC5-2V2SA	4 stage control-2 var, 1 heat, 1 on/off
#GE330-0243	Top replacement board only
#GE330-0244	Bottom replacement board only

Airstream GTC5-2V4SA Controller

#GTC5-2V4SA	6 stage control-2 var, 1 heat, 3 on/off
#GE330-0241	Top replacement board only
#GE330-0242	Bottom replacement board only

Airstream GTC5-1V6SA Controller

#GTC5-1V6SA	7 stage control-1 var, 2 heat, 4 on/off
#GE330-0245	Top replacement board only
#GE330-0246	Bottom replacement board only

Airstream GTC5-2V8SA Controller

#GTC5-2V8SA	10 stage control-2 var, 1 heat, 7 on/off
#GE330-0349	Top replacement board only
#GE330-0354	Bottom replacement board only
#GE330-0319	Slave box only

Airstream GTC5-1V10SA Controller

#GTC5-1V10SA	11 stage control-1 var, 1 heat, 9 on/off
#GE330-0255	Top replacement board only
#GE330-0256	Bottom replacement board only
#GE330-0257	Slave box only
	,

Airstream GTC5-1N8FA Controller

#GTC5-1N8FA	8 stage combo control-2 var, 3 heat, 3 on/off, 1 curtain
#GE330-0253	Top replacement board only
#GE330-0254	Bottom replacement board only
#GE330-0249	Slave box only

Airstream GTC5-1N5F1A Controller

#GTC5-1N5F1AB 6 stage combo	control-1 var, 2 heat, 2 on/off, 1 curtain
#GE330-0379	Top replacement board only
#GE330-0252	Bottom replacement board only

Airstream GTC5-1N4F1A Controller

#GTC5-1N4F1A	5 stage control-1 var, 1 heat, 1 on/off
#GE330-0259	Top replacement board only
#GE330-0250	Bottom replacement board only

TC5 Series

Improved Features!

- Larger enclosure more wiring space
- Humidity control available
- Alarm output standard





GPF-6

#GPF-6	Potentiometer feed back inlet control
#GE330-0377	Bottom replacement board



Potentiometer

#G52-0197	Potentiometer w/ 2" gear
#G52-0196	Potentiometer w/ 1" gear



i uses	
#EL1031	
	4 amp slow blow TC5
	10 amp
#EL1051	1 amp
	5 amp curtain machine output
	,



Temperature Sensors

#HSPROBE-S	. 18"	Cord
#HSPROBE-M	. 12'	Cord
#HSPROBE	.30′	Cord



Hired Hand Evolution 3001

Hired-Hand offers poultry producers the most versatile line of controls on the market. Configured with up to 64 programmable stages, temperature ramping, on-board history, and other advanced features. The Evolution line also allows you to customize with addon modules. Choose from software packages, wireless networks, expansion, variable output and back-up modules. The result is a user-friendly design that handles all of your natural and/or power ventilation needs.

#H3701-6065...... Version 21 chip for EV-3001 controller (free with return of old chip to hired hand)

Hired Hand Evolution 4000 Control System

Though it has inherited many characteristics from its 3000/3001 predecessors, the Evolution 4000 does boast many new features that set it apart from controllers released by Hired-Hand in the past. An SD card slot for upgrading software versions, copying and pasting saved programs and enhanced historical data collection and recall has been added to the controller. In addition. new features include one touch language translation between English and Spanish and a bright white LCD display for a much clearer and easier to read screen.

The new controller also features
heavy duty industrial pluggable stage terminals, pluggable IDP input
torminals and LED status indicators for more officient installation and

terminals and LED status indicators for more efficient installation and maintenance. Additionally, the unit comes complete in a NEMA rated ABS enclosure with stainless steel hinges and latches. NEMA Rated ABS Enclosure (24"x15.5"x9") with stainless steel hinges and latches. All in one box design makes for faster installation and requires less wall space. Shipping Dimensions: 28"x21"x15".

#H6607-8220 Evolution 4000 - 40 Stage Controller



Fail Safe Relay Circuit Board

#H6407-1511PCB161 EV fail safe rly w QA



Curtain Relay Circuit Board

#H6407-1516PCB167 EV curtain rly w QA



Main Relay Circuit Board

#H6407-1513 PCB161 EV relay w QA



16-Stage Switch Board

#H6407-1518 PCB168 EV 16 Stg SWX w QA



3001 Interface Board

#H6407-1523.....PCB170 EV 3001 Interface w QA



Variable Speed Card

#H6407-1536.....PCB172 EV Variable w QA



3000 Interface Board

#H6407-1522.... PCB170 EV 3000 Interface w QA



3000 Display Module

#H6407-6062 Display blue/white



Master Control Board

#H6407-1520...... PCB169 EV Master I/O w QA



16-Stage Power Supply

#H6407-1528.....PCB 171 EV 16 Stg PS w QA



3001 Display Module

#H6407-6059 EV 3001 Display Assy



Dimmer Card

#H6407-1538.....PCB174 Dimmer M/A w QA



A

The MAXIMUS Solution

MAXIMUS Connect. Manage. Maximize



MAXIMUS Controller

Customizable control of your farm's environment and management systems





Egg Flow Management

Synchronized collection flow for better egg quality.





Stay Connected

Monitor and input data from your computer, phone or other mobile device.





Feed Management

Measures feed levels and sends alerts to prevent feed outages.







Variable Board

#MKITPCB100......Variable Board



Input Board

#MKITPCB103.....Input Board



#MKITPCB102 Relay Module



External Contractor Module

#MKITPCB122..... External Contractor Module



Switch Board w/ Potentiometer

#MKITPCB105-1 Switch Board w/ Potentiometer



Switch Board w/ 2 Switches

#MKITPCB105-2..... Switch Board w/ 2 Switches



Temperature Sensors



Relay Vase Board

- DG

#MKITPCB101Relay Vase Board




Variable Board w/ Heat Sink

#M7000-0004...... Variable Board w/ Heat Sink



EDGE® is a single platform that is versatile and intuitive allowing it to handle all control applications. The unique design makes EDGE® the only controller on the market that can be configured to match your operation's specific requirements. It is also flexible enough to be adapted to new construction or existing system upgrades.



- Multi-Location Control
- · Remote Connectivity
- Simple Configuration
- · Ventilation Based on CFM per Head
- Self-Diagnostics
- Full Redundancy
- Fail Safe Mode
- Data Analysis
- Modular Architecture
- Plug-In Modules
- Multiple Types of Inputs
- · Variable Lighting
- Secure Wire Configuration
- LED Temperature Probes



Multifan IC

Models

#MVFIC-610/S	.Intelligent Control, 6 inputs and 10 outputs
#MVFIC-410ND/S	Intelligent control, 4 inputs and 8 outputs

Modules for IC Controls

#MVFCM10-2/S Fan control mo	dule per module 10 amp each (up to 1.5 HP each relay @ 230V)
#MVFCIM-1/S	Curtain inlet module
#MVFCIP-1/6/S Curtain/ inlet p	ositioner module, 1 per drive, 6 amp Open close for 3 wire motor
#MVFVSM-2/S	Variable speed fan module - 2 stages per module

Replacement Boards for IC Controls

_		
Model #	Bottom Boards	Top Boards
MVFIC-610/S	MVFBB-IC-610	MVFTB-IC-610
MVFIC-410ND/S	MVFBB-IC-410	MVFTBF-IC-410ND
MVFCM10-2/S	-	MVFTBF-CM10-2
MVFCIP-1/6/S	MVFBB-CIP-1/6	MVFTB-CIP-1
MVFVPM-2/S	MVFBBVPM-2	NA
MVFCIM-1/S	MCIM-11	MVFTB-CIM-1



Multifan ECS

Models

#MVFECS-3M/S ... ECS control, 3 stages, 2 variable, 1 on-off vent/ heat stage (10 amp max) **#MVFECS-5M/S** ... ECS control, 2 stages, 2 variable, 1 on/off, vent/heat stage (10 amp max) 2 on/off vent

Replacement Boards for ECS

Model #	Bottom Boards	Top Boards
MVFECS-1	MVFBB-ECS-1M	MVFTB-ECS-1M
MVFECS-2	MVFBB-ECS-2M	MVFTB-ECS-2M
MVFECS-3	MVFBB-ECS-3M	MVFTB-ECS-3M
MVFECS-4	MVFBB-ECS-4M	MVFTB-ECS-4M
MVFECS-5	MVFBB-ECS-5M	MVFTB-ECS-5M



#MVFDIGSEN	Digital temp probe (1 ft.)
#MVFDIGSEN-20	Digital temp probe (20 ft.)



Aerotech Controls

Aerotech AeroBoss 1.6

#A555124	6 stage control, 1 var., 2 neat, 3 on/on
#ATW1254	Front cover only
	······
Aerotech AeroSpeed 1.6	

norotoon norospood no

#AST5124	7 stage control, 1 var., 2 heat, 4 on/off
#ATW1276	Front cover only
#ATW1277	Back board only

Aerotech AeroStep 8

#AST5026	8 stage control, 2 heat, 6 on/off
#ATW1268	Front cover only



Stage Manager

The HS730 SERIES Stage Manager Controller provides intermediate control between an environmental control system and accessories such as fans, pumps, heaters etc... With each accessory connected to individual stages within the Stage Manager, the operator is able to manually operate the accessories ON or OFF independent of the environmental controller. The HS730 Stage Manager relay cards provide isolation between the control signal and the load or accessory, allowing a 120VAC control signal to operate a 240VAC motor as example. Stage switch controls are located on the front panel with control signal indicator and write on labels to fully customize controller layout and stage identification.



ITEM# DESCRIPTION

HS730-88 Control 8 Relays



ITEM# DESCRIPTION

HS730-2S4R

Control 2 Switches & 4 Relays



DESCRIPTION ITEM#

HS730-66 Control 6 Relays



ITEM# DESCRIPTION

HS730-1212 Control 12 Relays


Electrical Rating

Relay PCB Control Control Signal: 120VAC @ 60Hz, single phase. Output: Relay DPST Contact maximum rating 15 Amp, 2HP @ 240VAC Switch Control DPDT Toggle switch Max. Ratings: 15A @ 250 / 277VAC 1 1/2 HP @ 125 VAC 2 HP @ 250 VAC



Natural Ventilation Chimney

- 25-1/4" O.D. x 66" Tall
- · Composed of fiberglass with aluminum support
- Actuated baffle
- · Damper hardware and roof flashing kit included
- Easy Installation



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Vent Actuators

#HS667-24	
#HS667-24-240	24" Linear Actuator, 240 V, Blue
#HS667B-24	24" Linear Actuator, 120V Slow Speed, Black
#IDAW2	115 V, 12" Travel
#RC433	
	Canarm 120V 500 lb canacity 24" Actuator

🔔 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Time Clocks

Designed for industrial, commercial and residential applications. Highest HP ratings in the industry for loads up to 40 amps, providing direct 24-hr. control of most loads. Provides 1 to 2 "ON/OFF"



operations each day with minimum ON/OFF time of 1 hours. All models equipped with one "ON" and one "OFF" tripper.

#INT101P...... 24 hr. w/ plastic case #INT101PCD82.....24 hr. w/ plastic case, window **#59036**......24 hr



2-hour mechanical timer mounted in spray-proof plastic electrical box.

Resistive Ratings: 20 Amp, 125 VAC, 50/60 Hz 10 Amp, 250 VAC, 50/60 Hz 10 Amp, 277 VAC, 50/60 Hz

#HS649Spring wound timer



Precisely modulates the speed of ventilation fans. Temperature set point is adjustable from 35 to 95 degrees F. Features fully insulated moisture proof enclosure. Fan motors must be permanent split capacitor or shaded pole with built-in thermal fuse. Universal 125/240V control.





Quantum Fan Control

24-hr with Skip-a-day

A skipper option to not operate on selected days. Cutout screws are inserted in the dial for days which operation is to be skipped. Provides up to 10 ON/OFF operations each day with min. ON/OFF operations of 1 hour and max. ON time of 20-hours. Includes one CUTOUT tripper (also



serves as an "ON" tripper), one "OFF" tripper and three skipping screws.

#INT173 2	4-hr w/ skip-a-day, 120V
#INET174	7-day skipper, 240V
#INER8806P101C	14 day skipper, 240V



Our timer is easier for you to manage, and it's more straight forward than those confusing percentage

cycle timers. Simply select the minutes you want the electronic device you are controlling (ie. Fan Motor) to turn on and the minutes you want it off - up to a 30 minute cycle with a 30 second minimum setting. It works on both 120 and 240 Volt applications and comes in a NEMA4 enclosure. Each knob has a maximum on or off time of 15 minutes.

#HS834 Adjustable cycle timer







Tork Timers

#T8001	Timer 120 V 24 hr. clock
#T8004	Timer 240 V 24 hr. clock, 10 amp
#HE610410	Motor for T8001 timer
#T201M	Motor for T8004 timer
#HE610404	Timer Metal Indoor, NEMA1,
	120 V, 40A (Tork #1101)

#HE610406... Timer Noryl Indoor/Outdoor, NEMA 3R, 120 V, 40A (Tork #1101-N)

#HE610410......Motor Replacement for Timer 120 V 40A (Tork# 101)



24-Hour Timer with Plastic Case

Designed for industrial, commercial and residential applications. Highest HP ratings in the industry for loads up to 40 amps, providing direct 24-hr. control of most loads. Provides 1 to 12 "ON/OFF" operations each day with minimum ON/OFF times of 1 hour.

#59070.....24-Hr. Timer w/ Plastic Case




- 1 to 30 ON-OFF operations per hour. 60 tabs permit 1 minute switching changes
- Indoor/ Outdoor Plastic Enclosure
- 20 Amp rating
- 120 V
- SPDT

#590010 1-hr. cycle timer.plastic case

Adjustable Percentage Timer

Sealed enclosure designed for confinement conditions. New externally mounted push button allows programming without removing the cover. Eight selectable time durations: 30 seconds, 1, 3, 5, 10, 30 minutes, 1, 4 hours. Cycling pattern from 3% to 97% to total cycle duration. Manual override to allow users to bypass programmed cycling.



· Switch: SPST · Resistive: 20 amp

• Motor Load: 2 HP/240; 1 HP/120

#INCT2000 Adjustable Percentage Timer





#IN156T1950A

Replacement Tripper Pins

1. for Intermatic T101, T103, T104 Time Clocks 2. for Intermatic T1905, T1906, T1975R Time Clocks

1) #156T3492A.....Replacement tripper pins 2) #IN156T1950A......12-pack



Spring Wound Timer

#INFD1H	1-hr. spring wound timer
#INFD2H	2-hr. spring wound timer
#INFD4H	4-hr. spring wound timer
#FD6H	6-hr. spring wound timer
	12-hr. spring wound timer



Hi/Lo Thermometer

Records the high and low temperature in Fahrenheit. Push button resets the display. Great for use in egg coolers

#59630..... Hi Lo Thermometer

Single Stage **Thermostat**

Single stage thermostat designed for ventilation and heating applications in high moisture environments or outdoor use; NEC 547 compliant. NEMA 4X compliant enclosure with special O-ring cover seal for an improved barrier seal.

· Switch action: SPDT • Range: 30 to 110° F • Differential: 3.5° F

• Demensions: (LxWxH) 9" x 4" x 3"

#HS596001 Single Stage Thermostat





‡59600	Single Stag
	2 Stag
FEOCOOCE	Cinalo Ctoro res/C D I or

#59600GP..... Single Stage w/G.P. Logo



• 15 amp max

#59598.....Pre-wired Thermostat #U02-260120' cord only, 14 ga., 3-wire SJ

NEMA Digital **Thermostat**

Accurate singlestage electronic temperature control with Single Pole, Double Throw output

relay. Rugged thermoplastic NEMA 4X housing with easy-to-read LCD temperature display and lockable front-panel touchpad for set up and adjustment.

#59600D NEMA 4 120-240 VAC



Thermostat

environments.

designed for heating and


- for controlling ventilation or heating.
- · Metal housing with liquid-filled sensing element.
- 30° to 110° temperature range.
- 7/8" Diameter hole for 1/2" conduit.

#59001 Single Stage



VT15-WD **Thermostat**

The T15 is a single-stage mechanical thermostat for primary or backup operation of fans and heating equipment. Featuring a weatherproof housing with isolated electrical connection



to be re-calibrated. Fixed 1.8 degree bandwidth. 120 or 240V. 50/60hz. 10 amp maximum load. SPDT.

#VT15-WDMultifan Single Stage



Temperature Sensors

- · Replacement sensor probes for use with NEMA digital thermostats.
- · Stainless steel bulb
- · Lead can be extended up to 800 feet.
- · Splash proof

#A99BB-25C	9-3/4" long
#A99BB-200C	6-1/2 feet long
#A99BB-600C	19-1/2 feet long



- for heat or cool
- 120/240 VAC
- · Adjustable set point
- NEMA 4X enclosure
- 1 to 35 Degree differential
- 1 temperature sensor input

#79081Honeywell 4-stage Thermostat



Ranco Digital Thermostat Controller 24V Input

- Temperature Setpoint Range: -30° to 220°F
- · Differential range: 1° to 30°F
- Pilot duty: 125VA at 120/208/240VAC
- Sensor: Thermistor, 2" long x 1/4"dia 8' cable (included)
- Control Ambient Temperatures Operating: -20° to 140° Storage: -40° to 176°
- · Ambient humidity: 0 to 95% RH, non-condensing
- Enclosure: NEMA 1

#3ZP79 24 V input w/ 8' sensor #3ZP77 120-240 V w/ 8' sensor



TemproSTAT

The TemproSTAT is ideal for controlling heating devices to avoid frozen pipes and waterers.

- Turns of at 35° F and off at 48° F
- Compact 3-1/4" x 1-3/4" x 1"
- · 15 AMP rating, 1800 watts @ 120V combined load for both receptacles
- · 1 male grounded plug to install into 120V outlet
- · Pilot light illuminates when receptacles are energized
- UL and CSA compliant

#KTP526Freeze protection thermostat



Digital Thermostat

#TSW-250 Two Stage Weatherproof 90 to 255 V #TSW-260 Two Stage Weatherproof 12 to 24 V



Replacement Sensor

Temperature sensor with 2-3/4" x 3" NEMA 4X PVC housing. Can be suspended or surface mounted. 304 stainless Steel probe measures 3-1/2". Operating 250° F. Direct replacement sensor for Chore-Time or

temperature range is -40° to Hired Hand controls.

#EL1087 Replacement Sensor

Agri-Alert 800EZL/800EZK

(Replaces GAA-800 & GAA-800T)

- SD Card (MMC) compatible for EZe initial setup & backup.
- EZe removable terminal board.
- EZe removable phone card.
- EZe removable outdoor card.
- · Programming wizard for EZe set up.
- Voice tagging, personalize your own voice message per zone.
- New larger screen with graphics for EZe view.
- · See all conditions at a glance, no more scrolling of the screen.
- Tri-color LEDs for indicating zone status
- · Cellular Base compatible.
- 2 programmable relays can be assigned to multiple zones or controlled by the phone
- 500-event memory buffer.
- Self contained NI-MH rechargeable battery, one box on the wall.
- · Auto resetting overload protections, no more fuses.
- · Manual and "How to setup" CD included with every alarm.

#GAA-800EZL	Agri-Alert 8-stage w/o temp card and P/S
#GAA-800EZK	Agri-Alert 8-stage w/ temp card and P/S
	Top Board for 800EZK alarm
#GE330-0501	Back Board w/ enclosure for 800EZK alarm
#GAA-EZBAT	Battery Pack to Agri-Alert 800
•••••	,



Farm Hand Alert Alarm

- · 230 VAC 50/60 Hz operation
- · Monitors power outage
- Contains 12 VDC battery to operate siren during power outage
- Monitors 2 auxiliary inputs for fault conditions
- · Contains low battery indicator

#H6607-1586.....Farm Hand Alert Alarm



Farmsitter

- Sensaphone advances monitoring and alarm technology!
- Barn-proof enclosure
- · Web capable status and data logger
- · 12-hour rechargeable battery
- · Surge/lightning protection built in
- Extended 3-year warranty!

#FGD-1800-CD Farmsitte





Agri Alert 128 Color Touch Alarm

- 7" color touch screen allows all zones to be seen at once
- Internet connectivity provides remote access, eliminating your need to go to the barn every time it notifies you
- · Email and SMS notifications
- 128 zones lets you monitor a large site with a single system
- Phone dialer provides guaranteed delivery of alarm notification even if you don't have internet
- · Built in security makes sure only authorized users can adjust the system

#GAA-128K Agri Alert 128 Color Touch Screen Alarm

Hired Hand Alert Alarm III

- 230 VAC 50/60 Hz operation
- · Monitors power outage
- Contains 12 VDC battery to operate siren during power outage
- Monitors 2 auxiliary inputs for fault conditions
- · Contains low battery indicator

#H6607-0115......Alert Alarm III w/ Siren US Cord Set



Agri-Alert 128 Add-On Components

#GAA-BATTERY	Agri Alert Rechargeable Battery, 7A/H
#GAA-KP400	Agri Alert Home Keypad, 4 Zones
#GAA-KPB400	Agri Alert Farm Keypad, 4 Zones
	Agri Alert Microphone Extension Kit
#EL1143	Agri Alert Siren, 12V DC
#GAA-T40	Agri Alert Transformer 40-VA
#GAA-TP800	Agri Alert 8 Zone Extension Box (up to 6 per AA-9600)
#GAA-VRB1	Agri Alert Power Failure Relay Kit, 1PH
#GAA-VRB1-220	Agri Alert Power Failure Relay Kit, 1PH, 220V
#GAA-VRB3	Agri Alert Power Failure Relay Kit, 3PH
#GAA-PC	Agri Alert Phone Card
#GAA-OTC	Agri Alert Outdoor Temp Card

Rechargeable Battery

- 12 vac battery
- Used with alarm systems

,	
#52027	12 V. 5 AMP Hours
#GAA-BATTERY	Agri Alert Alarm 7amp 12V
	6V, 4 Amp, 4.5V Output
	12 V / 8 AMP Hours



Sensaphone[®] **Monitor**

The Sensaphone® alarm monitor is an inexpensive way to monitor any type of facility. Once the Sensaphone® detects a problem it automatically starts dialing your pre-programmed phone numbers and advises you of the problem. It continues to dial until someone responds to

- · Each unit monitors power and temperature
- · Line seizure feature gives unit the ability to "seize" line when it needs to dial unit
- · Custom voice messaging
- · Can dial your beeper, pager or cell phone
- "Listen-In" feature allows you to hear on-site sounds
- · Output for a siren
- Uses 6 1.5 volt "D" cell batteries as backup (not included)
- Operating range: 320 to 1500 F; remote temperature sensing range of -200 to 1500 F
- · 6' power cord
- Uses the 2.8K temperature sensor

#FGD-400 Model 400, 4 configurable inputs, Dials up to 4 phone numbers #FGD-800 Model 800, 8 configurable inputs, Dials up to 8 phone numbers



Sensaphone® Model 1400 & 1800

The Sensaphone 1400 is a powerful monitoring, alarm, and event logging system ideal for watching over unattended or remote locations.

- · Rugged, weatherproof NEMA-4X enclosure offers protection in harsh environments
- · Receive voice alerts and alarm notifications over standard telephone lines
- · Auto dialer: Notifies up to eight people by voice phone call in the event of an alarm
- · Up to eight external sensors monitor temperature, humidity, water and more
- · Included relay output can switch local devices on/off based on alarm activity
- Temperature-sensing range of -109° to -168°F | -85° to -76°C
- · Record custom voice alerts and receive alarm messages in your own voice

#FGD-1400-CD Model 1400, 4 configurable inputs, Dials up to 8 phone numbers #FGD-1800-CD Model 1800, 8 configurable inputs, Dials up to 8 phone numbers





Sensor Magnetic Reed For Sensaphone

#FGD-0006......Magnetic Sensor



Water Pressure Alarm Switches

Activates alarm when water pressure drops below adjustable range of 0-30 PSI.

#520150Low Pressure Water Switch #SM-2C-010F...... Nason Water Pressure Alarm Switch, 10psi preset



Farm Alarm IV **Monitoring System**

#FAWYRLSM4-0	Alarm Master WYR-LS 4.0 Temp, Power, Water, Battery Backup
#FAWYRLSSL4-0	Alarm Slave Temp, Water, Power, Battery Backup
#FAWYR-LSRGENKT	



Temperature Sensors

p	
#FGD-0101	Probe, 2.8K Series
	Weatherproof with 12' wire
#FGD-0102	Probe, 10K Series
	Weatherproof with 12' wire
#DSAL-RTS-MR	Sensor, Indoor 2.8K Series



Wireless barn alarm for swine and poultry producers

* Ships direct from vendor



BarnTalk 4G Gateway The Gateway is the brains of

The BarnTalk 4G Gateway includes:

the BarnTalk platform. • (1) Cellular Gateway Unit

• (2) LTE/LoRA Antennas



#BTGW0100 Standard 110V

Wireless Water Meters

Monitor water use from main water supply or individual rooms.

#BTWM2000	3/4", 20 GPM
#BTWM2500	1", 30 GPM
#BTWM3200	1-1/4", 50 GPM
#BTWM4000	1-1/2", 80 GPM





Outdoor

temperature sensor.

Remote Dry Contact contains (2)

or (N/C). Alarms and notifications

terminals for Dry Contact (N/O)

are completely customizable in

Wireless Dry **Contact Sensor** Sensor can remotely monitor relays and power outlets. Each

the BarnTalk app.

#BTTS0200.....Outdoor temp sensor

Wireless Temp Sensor -Indoor

Add-on/replacement outdoor temperature sensor.

#BTTS0100 Indoor temp sensor



Wireless Humidity Sensor - Indoor

Add-on/replacement relative humidity sensor

#BTTS0300.....Indoor humidity sensor



#BTTS1000Dry Contact Sensor

LTE/LORA Antenna

Add-on or replacement LTE/LoRA antenna



Adjustable Sensor Hanger

Adjustable sensor hanger with carabiner for use with remote sensors.



#BTHW0700 Hanger




Replacement Battery for Sensors

#BTHW0400..... Sensor Battery



Replacement Battery for Gateway

#BTHW0500......Gateway Battery



Pre-drilled right angle bracket for mounting the BarnTalk wireless antennas.

#BTHW0800......Antenna Bracket





51" & 54" X-Brace Ventilation Fan

For AirStorm fans manufactured with encapsulated bearing assemblies, see Page 186 for Pillow Block Conversion Kits



- · Rugged Fiberglass Housing
- · Stainless Steel Fan Blade
- PVC Interior Shutters
- · Heavy-Duty Poly Cone
- · High Service Factor Motors

AS-54XEBDLP **Parts List**



Housing, 54" Fiberglass Prop 54" 3-Blade SS 1) AS-54101 2) HSFP-5431S 3) AS-54206 Cone. Polv

4) HS902-3 Wire Guard 5) HS901-6B Shutter PVC 57" x 59"

6) PAK 1041 Pulley AK104-1 7) HS903-3 Tensioner Rotary Assembly with Splash Guards

8) PAK3458 Motor Pulley AK34-5/8

9) HS9014C Motor 1.5 HP, 1725 RPM, 115/230, 1 PH HS9314-VFD Motor 1.5 HP, 1725 RPM, 230/460, 3 PH

N/S) HS903-7A Belt, Power Twist Gray

N/S) UCP20516G5 Bearing 1" Pillow Block Standard 2 Set Screws N/S) SHAFT 1-1800T Shaft 1" x 18" (1/4 x 1/8 x 18 Thru Keyed)

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


AirStorm X-Brace 54" Fan

Model	Description	Shutter	Rough Opening	RPM	Drive	Speed	HP
AS-54XEBDLP	54", w/o cone	PVC	58" x 60.5"	1725	Belt	Single	1-1/2
AS-54XEBDLP-V	54" w/VFD, w/o cone	PVC	58" x 60.5"	1725	Belt	Variable	1-1/2 (3 Ph)
TO DAVEDDED III	TT: 1. TICC	TZ:4					

AS-54XEBDLP-HE High Efficiency Conversion Kit AS-54206

54" Poly Cone

.15" SP **CFM** CFM/WATT 25,600 15.7





- · Rugged Fiberglass Housing
- · Stainless Steel Fan Blade · PVC Interior Shutters

- · Heavy-Duty Poly Cone
- · High Service Factor Motors

AS-51XEBDLP **Parts List**

Item # Description

Housing, 51" Fiberglass Prop, 51", 3-blade SS 51" Poly Cone 1) AS-51101 2) HS900-51FA 3) AS-51206 4) AS902-51 Wire Guard

Shutter PVC, 53-7/8" x 53-7/8" 5) 101209-1-8 6) PAK 1041 Pullev AK104-1 Rotary Tensioner Assy 7) **HS903-3**

8) PAK3458 Motor Pulley AK34-5/8 Motor 1.5 HP, 1725 RPM, 115/230, 1 PH 9) **HS9014C** Motor 1.5 HP, 1725 RPM, 230/460, 3 PH HS9314-VFD

N/S) **HS903-7A** Belt, Power Twist Gray

Bearing 1" Pillow Block Standard 2 Set Screws N/S) UCP20516G5 N/S) SHAFT1-1800T Shaft 1" x 18" (1/4 x 1/8 x 18 Thru Keyed)

AirStorm X-Brace 51" Fan

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov DDM

♠ WARNING:

Model	Description	Shutter	Rough Opening	RPM	Drive	Speed	HP
AS-51XEBDLP AS-51XEBDLP-V AS-51206	51" w/o cone 51 w/o cone w/VFD 51" Poly Cone	PVC PVC	55" X 55" 55" X 55"	115/230 230/460	Belt Belt	Single Variable	1-1/2 1-1/2

	BESS	0.0	0" SP	0.	05" SP	.1	0" SP		15" SP
Model	Test	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT
AS-51XEBDLP	18216	27,400	17.6	26,100	16.5	24,600	15.1	22,900	13.7



57" X-Brace Ventilation Fan



Efficient Drive System

Powerful High Service Factor 1.5 HP motor. Self-adjusting tensioner automatically keeps the 1/2" link belt at the proper tightness for maximum efficiency.



Optional Mounting Kit (#AS-57FMH)

Stainless steel kit adapts fan to a through-wall installation.







Poly Butterfly Shutter

Corrosion resistant poly dampers seal tight with magnetic closures and dual springs. An aluminum damper ring maintains maximum stability in any temperature extreme.

9) PAK3058

17) HS902-57E

N/S) HS903-7






Rigid X-Brace Supports

Innovative X-Brace design moves the anchor points of the support arms to the housing corners for maximum stability. The support arms are manufactured from aluminum tube for increased corrosion protection and incorporate a triangular edge profile to reduce wind turbulence. Rubber corner mounts cushion the fiberglass housing from fan vibrations.



Improved Bearing Life

New solid base bearing housing increases mounting stabillity, reducing vibration significantly. The new bearing also includes a double-lip FloBack seal to improve lubrication and add additional protection against contamination to reduce maintenance. Fan features Stainless Steel motor and bearing mounting plates.



AS-57ERDRP Parts List

MO-01100DI I	arts hist
Item #	Description
1) HSFP-5731S	Prop 57", 3-Blade, SS
HSFP-5731G	Prop 57", 3-Blade, Galv.
2) AS-54X115A	Assembly, Upright, Fan 54" Aluminum X Frame Unpainted

Description Item

3) AS-54X110 Mount, Motor, Stainless, 54" X Frame 4) AS-54X118B Plate, Support Shaft ASM

5) UCP20516G5 Bearing 1" Pillow Block Standard 2 Set Screws

Block, Isolation, Interior Air Storm X Frame 6) AS-54X312

7) HS9019C Motor 1.5HP 1725 RPM 1 PH 208-230V HS9378-VFD Motor 2 HP 1725 RPM 230/460 3 PH

8) HS903-3 Tensioner Rotary Assembly with Splash Guards

> Pulley AK30-5/8 Composite 991

10) AFD99100

Shaft 1" x 18" (1/4 x 1/8 x 18 Thru Keyed) 11) SHAFT1-1800T

12) AS-57309B Venturi, Fiberglass Panel 57"

13) AS-57319 Support Plate, Corner 57" FBG Fan

14) WS901-57U Assembly, Butterfly 57" Fan

Bracket, Cone Support 57" Fan 15) AS-57320 16) AS-57305P

Panel Cone 57" Poly Black

57" Fan Prop Exit Guard

Belt, Power Twist Gray

Rough

AirStorm X-Brace 57" Fan

Model	Description	Shutter	Opening	RPM	Drive	Speed	HP
AS-57EBDBP	SS Blade & Hdwr. w/cone	PVC	57" x 57"	1725	Belt	Single	1-1/2
AS-57EBDBP-V	SS w/VFD drive & cone	PVC	57" x 57"	1725	Belt	Variable	2 (3 Ph)
AS-57EBDBPGA	Galv. Blade & Hdwr. w/cone	PVC	57" x 57"	1725	Belt	Single	1-1/2
AS-57EBDBPG-V	Galv w/VFD drive & cone	PVC	57" x 57"	1725	Belt	Variable	2 (3 Ph)
AS-57EBDBP-HE	High Efficiency Conversion Kit						



WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

	BESS	0.0	0" SP	0.	05" SP	.10	" SP	.15	" SP
MODEL	TEST	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT	CFM C	FM/WATT
AS-57EBDBP	20379	33,400	26.6	31,500	23.6	29,400	20.9	26,500	17.9
AS-57EBDBP-HE	20378	30,600	31.1	28,800	27.5	25,900	23.2	22,900	19.5
AS-57EBDBPGA	20376	33,200	25.7	31,300	22.8	29,200	20.2	26,600	17.7
AS-57EBDBPG-HE	20377	30,600	30.5	28,600	26.9	26,200	23.3	23,000	19.5
AS-57EBDBP-V	HS-00709*	32,613	23.3	29,300	20.7	26,534	18.1	23,796	12.5

test chamber



Fiberglass Ventilation Fans



WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Parts List Item

1) AS902-14EC

AS-14

2) HS9007 HS9308-VFD

3) HS903-1

4) HS900-14A 5) 10110A

6) AS-14206

Description

Guard Fan 14"

Motor 1/4 HP 1725 RPM 115/230V 50/60 Hz Motor 1/3 HP 1725 RPM 230/460V 3 PH

Nut Transtorque 1/2" w/ 7/8" Hex Nut Keyless Bushing

Prop 14" Fiberglass

Shutter PVC, 19" X 19"

Cone 14" Poly

AirStorm 14" Fan

Model	Description	Shutter	Rough Opening	RPM	Drive	Speed	HP
AS-14EDDLP	14" w/o cone	Plastic	20" x 20"	1725	Direct	Variable	1/4
AS-14EDDLP-V	14" w/VFD drive w/o cone	PVC	20" x 20"	1725	Direct	Variable	1/3 (3 Ph)
AS-14EDDLP-L	14" w/o VFD drive & cone	PVC	20" x 20"	1725	Direct	Variable	1/3 (3 Ph)
AS-14206	14" Poly cone						


Model	BESS Test	O. CFM	00" SP CFM/WATT	O CFM	.05" SP CFM/WATT	CFM	10" SP CFM/WATT	СГМ	.15" SP CFM/WATT
AS-14EDDLP	18231	2340	11.3	2200	10.3	2070	9.7	1890	8.8
	18230*	2100	9.5	1990	8.9	1860	8.4	1690	7.6

*Performance shown with no cone



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Item #

1) AS-18101 2) AS902-18EC

3) **HS9008** HS9308-VFD

4) HS903-1

5) HS900-18A

6) 10115-5

7) AS-18206

Housing, 18" Fiberglass

Guard Fan, 18"

Motor 1/3 HP, 1725 RPM, Var Sp, 115/230 Motor 1/3 HP, 1725 RPM, 230/460V, 3 PH

Transtorque 1/2" w/ 7/8" Hex Nut Keyless Bushing

Prop 18" Fiberglass

Shutter PVC, 24-1/2" X 24-1/2" Single Door

Cone, 18" Poly

AirStorm 18" Fan

Model	Description	Shutter	Rough Opening	RPM	Drive	Speed	HP
AS-18EDDLP AS-18EDDLP-V AS-18EDDLP-L AS-18206	18" w/o Cone 18" w/VFD drive w/o cone 18" w/o VFD drive & cone 18" Poly Cone	PVC PVC PVC	25.5" x 26" 25.5" x 26" 25.5" x 26"	1725 1725 1725	Direct Direct Direct	Variable Variable Variable	1/3 1/3 (3 Ph) 1/3 (3 Ph)

	BESS	0.0	00" SP	0.	05" SP	.1	10" SP		.15" SP
Model	Test	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT
AS-18EDDLP	15684	4,980	11.7	4,780	11.0	4,580	10.3	4,350	9.7
	15685*	4,490	10.0	4,310	9.5	4,120	9.0	3,920	8.5
AS-18EDDLP-V	18232	4710	11.1	4490	10.5	4290	9.9	3920	8.5



Fiberglass Ventilation Fans



WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Item # Description

Housing, 24" fiberglass 1) AS-24101 2) AS902-24EC Guard Fan 24" White Hog Slat

3) HS9006A Motor 1/3 HP, 1075 RPM, 115/230, 1 PH HS9306A-VFD Motor 1/3 HP, 110 RPM, 230/460, 3 PH

Transtorque 1/2" w/ 7/8" Hex Nut Keyless Bushing

Prop 24" Fiberglass

Shutter PVC, 32-1/2" x 32-1/2" Double Door

Cone, 24" poly

AirStorm 24" Fan

Model	Description	Shutter	Rough Opening	RPM	Drive	Speed	HP
AS-24EDDLP	24" w/o cone	PVC	34.5" x 34.5"	1075	Direct	Variable	1/3
AS-24EDDLP-V	24",w/VFD drive w/o cone	PVC	34.5" x 34.5"	1100	Direct	Variable	1/3 (3 Ph)
AS-24EDDLP-L	24",w/o VFD drive & cone	PVC	34.5" x 34.5"	1100	Direct	Variable	1/3 (3 Ph)
AS-24206	24" Poly Cone						

AS-24 **Parts List**

4) HS903-1

6) 101194-5

7) AS-24206


5) HS900-24A

Model	BESS	0.0	0" SP	O.O	05" SP	.10	0" SP		15" SP
	Test	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT
AS-24EDDLP	17295	7,330	16.7	6,930	15.2	6,570	14.1	6220	12.9
	17298*	6,430	13.6	6,140	12.7	5,750	11.7	5,350	10.7

*Performance shown with no cone



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Parts List

AS-36

Item	#	Description

1) AS-36101A

2) AS902-36EC

3) HS9009A

4) HS903-1

5) HS900-36E

6) 101204

7) AS-36206

Housing, 36" Fiberglass

Wire Guard, 36"

Motor, 1/2 HP, 850 RPM, 115/230, 1 PH Transtorque 1/2" w/ 7/8" Hex Nut Keyless Bushing

Prop 36" Fiberglass

Shutter PVC, 42" x 42"

Cone, 36" poly

AirStorm 36" Fan

Model	Description	Shutter	Rough Opening	RPM	Drive	Speed	HP
AS-36EDDLPA	36" w/o cone	Plastic	43.5" x 43.5"	850	Direct	Variable	1/2
AS-36206	36" Polv Cone						

Model	BESS Test	O.O CFM	00" SP CFM/WATT	O. CFM	05" SP CFM/WATT	 CFM	10" SP CFM/WATT	CFM	.15" SP CFM/WATT
AS-36EDDLP	15556	11,550	20.6	10,780	18.4	9,940	16.4	8,900	14.2
	15557*	10,510	17.7	9,790	16.0	8,980	14.4	8,150	12.8



The PolyStorm fan series combines premium components with our roto-molded High-Density Polyethylene housing. Corrosion resistance features include fiberglass props, PVC shutters, and stainless steel mountings. At the core of every PolyStorm fan are rugged dual voltage motors with an industry-leading, 2-year warranty. PolyStorm fans are an excellent choice for new ventilation systems or lower-cost replacements fans.





- Roto-molded High-Density Polyethylene plastic housing resists cracking or breaking.
- Stainless steel mountings
- Corrosion resistance, composite fiberglass props
- Low maintenance, airfoil style PVC shutters with full-length spring steel rods
- Poly-coated wire guard
- Heavy-duty, dual voltage, 60/50 Hz motors with a 2-year warranty

Model	Description	Rough Opening	RPM	Voltage	Speed	Motor Hp
PS-14EDDLP	14"	18-1/4" X 18-1/4"	1725	115/208-230	Var	1/4
PS-18EDDLP	18"	22-1/4" X 22-1/4"	1725	115/208-230	Var	1/3
PS-24EDDLP	24"	28-1/4" X 28-1/4"	1140	115/208-230	Var	1/3

	0.00" SP		0.05	0.05" SP		' SP	0.1	0.15" SP	
	CFM	C/Watts	CFM	C/Watts	CFM	C/Watts	CFM	C/Watts	
PS-14EDDLP	1741	8.8	1619	7.8	1338	6.6	1019	5.4	
PS-18EDDLP	3520	8.1	3311	7.6	3094	7.1	2863	6.6	
PS-24EDDLP	5597	9.0	5661	8.6	5358	8.0	5050	7.3	

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



36" Galvanized Slant Wall Fan

6 WS-36SBDL	3 10 9	B 2 1 5 Detail A
กกต-วดขอกก	a raits list	11 11
Item #	Description	· II
1) HS9010C	Motor 1 HP 1725 RPM 115/208-230	OV 50/60 Hz

1) HS9010C HS9315A-VFD	Motor 1 HP 1725 RPM 115/208-230V 50/60 Hz Motor 1/2 HP 1725 RPM 230/460V 3P VFD Compatible
2) PAK2858A	Pulley AK28-5/8
3) PAK641	Pulley 6.25" X 1"
4) HS900-36H	Prop 36" Galvanized 4 Blade 1" Shaft
5) HS903-8	Tensioner Rotary Assembly 1.7" Light Gray
6) HS902-36E	Wire Guard
7) WS-36105	Cone Section (4 req.)
8) HS901-36L	36" Alum Shutter
9) UCP20516G5	Bearing 1" Pillow Block - 2 Set Screws
10) SHAFT1-1000T	Shaft, 1" x 10" Keyed.
N/S) HS903-7A	Belt Power Twist Grav

Model	Description Shutter Rou		Rough Opening	Voltage	Drive	Speed	HP
WS-36SBDLA WS-36SBDLA-V WS-36SBDLA-L	36" 36" VFD w/ Drive 36" VFD w/o Drive	Aluminum Aluminum Aluminum	40-3/4" (W) x 42-3/4" (H) 40-3/4" (W) x 42-3/4" (H) 40-3/4" (W) x 42-3/4" (H)	115/230 230 230/460	Belt Belt Belt	Single Variable Variable	1/2 1/2 (3-Ph) 1/2 (3-Ph)
Model	BESS Test CFM	0.00" SP	0.05" SP		SP	Airflow	Ratio

Airflow Ratio WS-36SBDLA 18225 11,080 18.2 10,470 16.0 9970 14.8 .82

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



54" Galvanized Slant Wall Fan


Item # Description	₩
WS-54SBDLA Parts List	Detail A
8 10 6	9 3 5

	aft Housing (see	200 106 HCCCI	72001				
Tongion	Jack Shaft Housing (see page 186 HSSCK200)						
rension	Tensioner Rotary Assembly w/ Splash Guards						
Pulley A	K28-5/8						
Pulley A	K104-1						
1-1/2 H	p motor, 1725 R	PM, 230 Volt					
2 Hp mc	2 Hp motor, 1725 RPM, 230/460 VFD compatible						
Prop 54	" 4-Blade Galva	nized WS Fan	_				
Belt Pov	er Twist Gray						
Wire Gu	ard, 68"						
Shutter	54" WS SW Fan	58" x 59" x 2.5"					
Cone Pa	nel (4 req.)						
Voltage	Drive	Speed	HP				
	Tensione Pulley A Pulley A 1-1/2 Hj 2 Hp mc Prop 54' Belt Pow Wire Gu Shutter	Tensioner Rotary Assem Pulley AK28-5/8 Pulley AK104-1 1-1/2 Hp motor, 1725 RP 2 Hp motor, 1725 RPM, 2 Prop 54" 4-Blade Galvan Belt Power Twist Gray Wire Guard, 68" Shutter 54" WS SW Fan Cone Panel (4 req.)	Tensioner Rotary Assembly w/ Splash Gu Pulley AK28-5/8 Pulley AK104-1 1-1/2 Hp motor, 1725 RPM, 230 Volt 2 Hp motor, 1725 RPM, 230/460 VFD cor Prop 54" 4-Blade Galvanized WS Fan Belt Power Twist Gray Wire Guard, 68" Shutter 54" WS SW Fan 58" x 59" x 2.5" Cone Panel (4 req.)				

Model	Descripti	ion	Shutter	Rough Opening		Voltage	Drive	Speed	HP
WS-54SBDLA WS-54SBDLA-V	54" 54" VFD	w/ Drive	Aluminum Aluminum	•	7) x 60-1/2" (H) 7) x 60-1/2" (H)	230 230/460	Belt Belt	Single Variable	1-1/2 2 (3-Ph)
Model	BESS Test	O.C CFM	00" SP CFM/WATT	O. CFM	05" SP CFM/WATT	.1 CFM	O" SP CFM/WATT	Airflow	Ratio
WS-54SBDLA	14344	28,400	23.6	27,100	21.5	25,400	19.2	.75	

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Replacement Parts

Item #	Description
1) HS902-13	Wire Guard
2) HS901-52	Butterfly Shutter Galv., Less Spring
3) HS900-52G	52" Prop
4) HS902-52	Interior Guard
5) PAK4158	Pulley, AK41-5/8
6) HS9019C	Motor, 1.5 Hp, 230V, 50/60 Hz
HS9378-VFD	Motor, 2 Hp, 208-230/460V 50Hz
7) PAK941	Pulley, AK94-1
8) HS903-3	Tensioner Rotary Assembly w/ Splash Guards
9) UCP20516G5	Pillow Block Bearing
10) SHAFT1-1000T	Shaft, 1" x 10" Keyed.
11) WS-52105	Cone section (4 req.)
N/S) HS903-14	Butterfly spring

V-Belt, 1/2" x 59" Cogged

52" Galvanized Butterfly Fan (Includes cone)

Model	Description	Shutter	Rough Opening	Voltage	Drive	Speed	HP
WS-F52B2A	52"	Butterfly	56-1/2" x 56-1/2"	230	Belt	Single	1-1/2
WS-F52B2A-V	52" VFD w/ Drive	Butterfly	56-1/2" x 56-1/2"	230	Belt	Variable	2 (3-Ph)
WS-F52B-HE2A	High Efficiency Conversion Ki	t					

N/S) HSAX57

Model	BESS Test		O" SP CFM/WATT	O. CFM	05" SP CFM/WATT	.1 CFM	0" SP CFM/WATT	CFM	15" SP CFM/WATT
High Volume	17278	30,000	21.3	28,700	19.4	27,000	17.2	25,300	15.3
High Efficiency	17279	27,300	23.6	25,700	20.8	22,300	16.3	20,200	14.1

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Replacement Parts

Item #	Description
1) WS-54205	Panel Cone 68" OD 36" Depth
2) WS-54304	Panel, Bottom Outside Mount 54" Fan
3) WS-54314	Bracket, Cone Support Panel Fan
4) WS-54315	Brace, Cone Support Panel Fan
5) PAK3458	Pulley AK34-5/8
6) PAK 1041	Pulley AK104-1
7) HS903-7A	Belt Power Twist Gray (BOM Only)
8) HS9019C	Motor 1.5 HP 1725 RPM 50/60 Hz 1 PH 208-230V 1.2 SF
HS9314-VFD	Motor, 1.5 Hp 208-230/460V 50/60 Hz
9) HS903-2	Jack Shaft Housing (see page 186 HSSCK200)
10) HS902-1	54" Fan Prop Guard 68" Cone Md
11) HSFP-5431G	Prop 54" 3-Blade Galvanized
12) HS902-4	Guard Box, Collapsable 60" X 60" X 16"

54" Galvanized Panel Fan (Includes cone)

Model	Description Shutter		Rough Opening	Voltage	Drive	Speed	HP
WS-54PBDBG WS-54PBDBG-V WS-54PBDBG-HE	54" 54" VFD w/ Drive High Efficiency Conve	Butterfly Butterfly rsion Kit	MIN 53" X 53" MAX 57-1/2" X 57-1/2"	230 230	Belt Belt	Single Variable	1-1/2 1-1/2 (3-Ph)

	BESS	0.00	0" SP	0.	05" SP		10" SP		15" SP
Model	Test	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT
High Volume	18222	31,800	21.9	30,400	20.1	28,400	17.6	26,100	15.8
High Efficiency	18221	30,500	22.8	29,100	21.3	27,000	18.7	22,300	14.2

Replacement parts for Windstorm 52" Butterfly Fans

⚠WARNING:

*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Models purchased before April 2014

WS-F52B High Volume - 52"

Item #	Description	Item #	Description
PAK4658	Cast motor pulley 4.6" x 5/8" bore	PAK3958	Cast motor pulley 3.75" x 5/8" bore
PAFD112100	Composite pulley 11.25" x 1" bore	PAFD 104100	Composite pulley 10.25" x 1" bore
HSAX64	Cogged v-belt, 1/2" x 66"	HSAX63	Cogged v-belt, 1/2" x 65"
FS0604ZF	Idler Assy, 5.5" arm x 3" pulley	FS0604ZF	Idler Assy, 5.5" arm x 3" pulley
SHAFT1-1150	Shaft 1" x 11.5"	SHAFT1-1150	Shaft 1" x 11.5"
HS9019C*	1.5 Hp motor, 115/208-230, 56H, 1725 rpm	HS9019C*	1.5 Hp motor, 115/208-230, 56H, 1725 rpm

Models purchased April 24 to November 2016

WS-F52B2 High Volume - 52"

Item #	Description				
PAK4158	Cast motor pulley 3.95" x 5/8" bore				
PAK941	Composite pulley 9.25" x 1" bore				
HSAX61	Cogged v-belt, 1/2" x 63"				
FS0604ZF	Idler Assy, 5.5" arm x 3" pulley				
SHAFT1-1150	Shaft 1" x 11.5"				
HS9019C*	1.5 Hp motor, 115/208-230, 56H, 1725 rpm				

WS-52B2-HE2 High Efficiency - 52"

WS-52B-HE High Efficiency - 52"

Item #	Description
PAK4458	Cast motor pulley 4.25" x 5/8" bore
PAFD112100	Composite pulley 11.25" x 1" bore
HSAX64	Cogged v-belt, 1/2" x 66"
FS0604ZF	Idler Assy, 5.5" arm x 3" pulley
SHAFT1-1150	Shaft 1" x 11.5"
HS9019C*	1.5 Hp motor, 115/208-230, 56H, 1725 rpm

Models purchased Nov 2016 to Present

WS-F52B2A High Volume - 52"

Item #	Description
PAK4158	Cast motor pulley 3.95" x 5/8" bore
PAK941	Composite pulley 9.25" x 1" bore
HSAX57	Cogged v-belt, 1/2" x 59"
HS903-3	Idler Assy, 6.5" arm x 2.75" pulley
SHAFT1-1000T HS9019C*	Keyed shaft, 1" x 10" long 1.5 Hp motor, 115/208-230, 56H, 1725 rpm

WS-F52B2-HE2A High Efficiency - 52"

Item #	Description
PAK4458	Cast motor pulley 4.25" x 5/8" bore
PAFD112100	Composite pulley 11.25" x 1" bore
HSAX59	Cogged v-belt, 1/2" x 61"
HS903-3	Idler Assy, 6.5" arm x 2.75" pulley
SHAFT1-1000T	Keyed shaft, 1" x 10" long
HS9019C*	1.5 Hp motor, 115/208-230, 56H, 1725 rpm

VFD Improves Performance of Variable Speed Fans

VFD Control

Controller converts low voltage from house controller and sends a related signal to a fan motor in hertz. Allows for more accurate control of variable speed and cfm output.

- 240 Volt
- Waterproof NEMA 4X enclosure
- Manual override

#HSFI-1004	1/2 Hp
#HSFI-1001	1 Hp
#HSFI-1002	2 Hp

RFI Filters

RFI Filters, or radio-frequency interference filters mitigate the high frequency electromagnetic disturbance present on the power and signal lines.

#HSFI-RFI.... Radio-Frequency Interference filters



		CFM @ .05" Static Pressure				
		60Hz	52Hz	44Hz	36Hz	
AS-18EDDLP-V	18" VFD	4490	3910	3230	2380	
AS -24EDDLP-V	24" VFD	6820	5980	5010	3810	
AS-36EDDLP-V	36" VFD	11730	9870	7710	5360	
AS-51XEBDLP-V	51" VFD	25800	22300	17500	11900	
AS-54XEBDLP-V	54" VFD	28900	24900	18900	12700	
AS-57EBDBP-V	57" VFD	29300	25800	22400	17400	

Shutter fans ship fully assembled, ready to install right out of the box.

Features include:

- Pre-wired with a 10' cordset for 115 volts
- Variable or single speed (Control not included.)
- 3-bladed aluminum prop
- Aluminum shutter with tie bar to connect vanes, reducing flapping in high winds
- Interior fan guard





⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Item#	Size	HP	Amps	cfm/.05	Rough Opening
#VES12C	12"	1/10	1	880	12-1/ 2" x 12-1/ 2"
#VES161C	16"	1/10	1	1300	16-1/2" x 16-1/2"
#VES20C	20"	1/3	3.5	2920	20-1/2" x 20-1/2"
#VES24C	24"	1/2	4.8	4310	24-1/2" x 24-1/2"



Variable Speed Control

Infinite speed control rated at 6 amps at 120 volts. Mounts in standard 2" gang box, not included.

#NE105F.....Variable Speed Control

Single Stage Thermostat

Single stage thermostat designed for ventilation and heating applications in high moisture environments or outdoor use; NEC 547 compliant. NEMA 4X compliant enclosure with special 0-ring cover seal for an improved barrier seal.

- Switch action: SPDT
- Range: 30 to 110° F
- Differential: 3.5° F
- Demensions: (LxWxH) 9" x 4" x 3"

#HS596001 Single Stage Thermostat






Single Sidewall Inlet

- 5-1/2" x 22-1/2"
- 430 cfm
- · Self-adjusting inlet

#HSI200Single Sidwall Inlet



Competitor Series 54" Fans

- · A durable and aerodynamic fiberglass housing and discharge cone backed by a limited life-time warranty
- A high performance stainless steel propeller
- A PVC shutter included with fan. (Part #PS-59C)
- A high efficiency 1-3/4 HP motor in single or three phase
- An automatic belt tensioning system
- · Heavy gauge, corrosion resistant aluminum drive train support
- · Stainless steel hardware
- An optional winter closure panel (Part #20-0697)

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Model#	HP	Phase	RPM	CFM/.05sp	CFM/per watt @05	Framed Opening
#GCS54C1-P	1.75	1	587	30,044	20.2	58.0" W X 60.5" T
#GCS54C3-P	1.75	3	587	30,044	20.2	58.0" W X 60.5" T



AP Performer Fans

- · Fiberglass housing
- Rugged motors with hidden internal capacitor
- 5/16" aluminum motor mounts
- Low maintenance PVC shutters
- Balanced propellers constructed of composite fiberglass



♠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Item#	Description	Fan	CFM/.05	CFM/.10	R.O. W x H
#GAPP-12F	1/4 HP - 12" fan with PVC shutter	12"	1,447	1,334	16-1/2" x 17-3/8"
#GAPP-14F	1/4 HP - 14" fan with PVC shutter	14"	2,385	2,270	19-3/8" x 19-5/8"
#GAPP-14FC	1/4 HP - 14" fan with PVC shutter and cone	14" w/cone	2,710	2,610	
#GAPP-18F	1/3 HP - 18" fan with PVC shutter	18"	4,205	3,964	25-1/2" x 25-1/2"
#GAPP-18FC	1/3 HP - 18" fan with PVC shutter and cone	18" w/cone	4,890		4,720
#GAPP-24F	1/3 HP - 24" fan with PVC shutter 24"	6,002	5,463		35" x 35"
#GAPP-24FC	1/3 HP - 24" fan with PVC shutter and cone 24" w/cone	7,120	6,710		
#GAPP-36F	1/2 HP - 36" fan PVC shutter 36"	10,297	9,392		43-3/4" x 43-3/4"
#GAPP-36FC	1/2 HP - 36" fan PVC shutter and cone	36" w/cone	11,310		10,360
#GAPPB-50	1 HP - 50" fan with PVC shutter	50"	20,151	17,792	55-1/2" x 55-1/2"
#GAPPB-50C	1 HP - 50" fan with PVC shutter and cone	50" w/cone	23,200		20,577



Replacement Motors for AP Performer Fans

Item#	Description	Fan
#HS9028KIT	115/230 V, 1 ph. 3300 RPM	GMB-10
#HS9007	1/4 HP, 115/230 V, 1 ph, 1725 RPM	GAPP-12
#HS9007	1/4 HP, 115/230 V, 1 ph, 1725 RPM	GAPP-14
#HS9008	1/3 HP, 115/230 V, 1 ph, 1725 RPM	GAPP-18
#HS9006A	1/3 HP, 115/230 V, 1 ph, 1100 RPM	GAPP-24
#HS9009A	1/2 HP, 115/230 V, 1 ph, 900 RPM	GAPP-36
#HS9019C	1-1/2 HP, 115/208-230 V, 1 ph., 1725 RPM, 1 spd	GAPP-50
#HS9019C	1-1/2 HP, 115/208-230 V, 1 ph., 1725 RPM, 1 spd	GFS52CL16SA

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Replacement Props for AP Performer Fans

Item#	Description	Fan
#G13-0017	Prop, Composite, 9-3/8" dia, 5/16" shaft	GMB-10
#G13-0130	Prop, Composite, 12" dia, 1/2" shaft	GAPP-12
#G13-0106	Prop, Composite, 14-3/4" dia, 1/2" shaft	GAPP-14
#G13-0107	Prop, Composite, 19" dia, 1/2" shaft	GAPP-18
#G13-0209	Prop, Composite, 25-1/4" dia, 1/2" shaft	GAPP-24
#G13-0129	Prop, Composite, 36" dia, APP and MA	GAPP-36
#G13-0044	Prop, Composite, Performer Fan 50	GAPP-50
#G13-0132SS	Prop, Boss Fan 52, Stainless Steel	GFS52CL16SA

Aerotech VX Series Fans


- Fiberglass housing with roto-molded poly discharge cone
 Cast aluminum airfoil prop
- Powder coated motor support and outlet guard
- Stainless steel hardware
- PVC shutters

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


Aerotech VX Series Fans 9" - 26"

Item#	Description	Нр	Drive	CFM/.05	CFM/.10	R.O.WxH
#AVX14F1CP	14" fan w/ shutter and cone	1/8	Direct/VR	1,910	1,790	17-1/2" x 17-1/2"
#AVX16F1CP	16" fan w/ shutter and cone	1/4	Direct/VR	3,100	2,900	22-1/2" x 22-1/2"
#AVX18F1CP	18" fan w/ shutter and cone	1/3	Direct/VR	4,300	4,120	22-1/2" x 22-1/2"
#AVX24F1CP	24" fan w/ shutter and cone	1/3	Direct/VR	6,090	5,740	28-1/2" x 28-1/2"
#AVX26F1CP	26" fan w/ shutter and cone	1/3	Direct/VR	7.800	6.740	30-1/4" x 30-1/4"




Aerotech AT24Z - 24" ADVANTAGE FAN

Key	Description	OEM#	G.S. Part #
1	Housing 24" Advantage Fan	#AFH3424	N/A
2	Clip Shutter For Right Side SS	#AFH2119	N/A
3	Blade 24" w/ 1/2" Bore	#AFP1033SS	N/A
4	Mount for Motor 24"	#AFH1010	N/A
5	Motor Fan 1/3 Hp 1075 RPM for 24" Fan	#AFM1008	#HS9001
6	Clip Shutter for Left Side Ss	#AFH2117	N/A
N/S	Shutter Plastic 27–5/8"	#APZ24	10118-6
N/S	Cone Discharge 24" w/ Guard	#A24RC	N/A
N/S	Round Plastic Coated Guard	#AFH1237	N/A



Key	Description	OEM#	G.S. Part #
1	Housing Fiberglass 36" Fan	#AFH2136A	N/A
2 & 3	Strut H Conversion 36" DD Advtg	#AFH1952	N/A
4	Blade 36" 5/8" Bore with Set Screw	#AFP1013SS	N/A
5	Motor 1/2 Hp 850 RPM (variable speed)	#AFM1011	#HS9016
5	Motor 1/2 Hp 850 RPM (single speed)	#AFM1048	N/A
6	Cone 36" Fiberglass 4 sections (+guard and hdw.)	#A365FC	N/A
7	Guard Round PVC Coated 36" For Cone	#AFH1336	N/A
N/S	Shutter Plastic 41-7/8"	#APZ36	#101203-1-8



Key	Description	OEM#	G.S. Part #
1	Housing Fiberglass 48"	#AFH2148A	N/A
2,3,4	Conversion Kit 48" H Strut	#AFH1945	N/A
5	Belt V 1/2" x 49" Kevlar	#AFH1410	#HSA47K
5	Belt V 1/2" x 49" Standard	N/A	#HSA47
6	Belt Link Red Fenner Drives	#AFH2053	N/A
7	Sheave For Prop 1" Ak104	#AFH2O34	#PAK1041
8	Bearing 1" Pillow Block With Zirk	#AFH2013	16G
9	Shaft for Propeller 1"	#AFH2036	N/A
10	Blade 48" Bd 3 Bld Al 1" bore with Set Screw	#AFP1016SS	N/A
N/S	Motor 1 HP 1725 RPM 3 Phase	#AFM1029	#HS9301
11	Motor 1 HP 1725 RPM 56 FR 120/240 V 5/8" Shaft	#AFM1024	#HS9000
12	Pulley AK34-5/8	#AFH2032	#PAK3458
13	Pulley Idler V-Belt 3" (Pulley Only)	#AFH2406	#VX3012
14	Cone 48" Fiberglass 4 Sections w/ Guard & Hardware	#A481FC	N/A
15	Guard Round PVC Coated For 48" Fan Cone w/ Hardware	#AFH2648	N/A
N/S	Shutter Plastic 53-7/8"	#APZ48	#101209-1-8



Multifan

Q Panel Fans

The Multifan panel fans adapt to a wide range of uses including side-wall fans, pit fans, and stir fans. Motors and impellers are perfectly matched for each fan model diameter and size.


- Total enclosed motors with die-cast aluminum housing.
- Lightweight polypropylene impeller stays in balance and reduces power needs.
- · Corrosion resistant cast aluminum panel housing.

240 V.

Item#	Impeller Diameter	Model	Voltage	0" S.P.	.05" S.P.	10" S.P.	AMP
#V4E25K1M70100	10"	4E25	240	882	820	760	0.40
#MV4E40K1M71100	16"	4E40Q	240	2960	2870	2780	1.20
#V4E50K1M60100	20"	4E50Q	240	4850	4690	4540	2.00
#V8E92K1M60100	36"	8E92Q	240	11200	10500	9800	3.90

Multifan Q Line Replacement Parts







Large Q on Motor Tag 3/8" between Fins

Model	Size	Motor	Impellers	Arms (3 per fan)
2E30Q	8″	M2E30K6M60100	MW312C6G2B10N01	MGBVP3011G2
4E30Q	12"	M4E30K0M70100	MW312C6G3B10N01	MGBVP3011G2
4E35Q	14"	M4E35K0M70100	MW362C6P3B10NB	-
4E40Q	16"	M4E40K0M70100	MW412C6P3B10NB	GBVP4011ZW
4E45Q	18"	M4E45KOM70100	MW460C6P3B10NB	MGBVP4511ZW
4E50Q	20"	M4E50K0M70100	MW512C6P3B10N84	MGBVP5011G2
6E63Q	24"	M6E63K0M70100	MW646G5G5B17N03	MGBVP6310ZW
8E92Q	36"	M8E92K3M70100	MW915G3G8L17A04	MGBVP0064K



- Fans Available in: 120V or 240V; 60 Hz or 50 Hz; Single or Three Phase
- Fans built using "Q" motors, arms, and impeller



(Fit in Existing Poly Fan Housing and Wall openings.)

Item#	Impeller Diameter	Voltage	Nominal RPM	AMP	Speed Cont.*
120V					
#MV4E3004P70	12"	120	1645	1.10	T+E
#MV4E4006P70	16"	120	1600	2.30	T+E
#MV4E4507P70	18"	120	1600	3.00	T+E
#MV4E5008P70	20"	120	1565	4.00	T+E
#MV6E6302P70	24"	120	1020	5.60	T+E
240V					
#MV2E3006P60	12"	240	3200	1.40	T+E
#MV4E3002P60	12"	240	1600	0.60	T+E
#MV4E4003P60	16"	240	1600	1.20	T+E
#MV4E4505P60	18"	240	1600	1.60	T+E
#MV4E5006P60	20"	240	1600	2.00	T+E
#MV6E6301P60	24"	240	1000	3.10	T+E

Frames & Clips Only


Item#	Impeller Diameter	Description
#MVV16PF/CLIPS	16"	16" plastic frame w/ arm clips
#MVV18PF	18"	18" plastic frame w/ arm clips
#MVV20PF	20"	20" plastic frame w/ arm clips
#MVV24PF	24"	24" plastic frame only
#MVFCLIPYT	CLIP	Clip for plastic frame 3/set

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


Pruden Polystainless Fans

- Full turn down weather hood for built in wind protection
- Stainless Steel Venturi offers tight blade tip clearance for efficient air delivery
- Stainless Steel motor mount hardware for easy inside removal.
- Replaceable plastic blades with aluminum hub.



Item#	Description	Нр	cfm/.04	cfm/.10	RO WxH
#PFPS-12C	12" w/ PVC shutter	1/6	1,395	1,325	18-3/4" x 18-3/4"
#PFPS16D	16" w/ PVC shutter	1/4	2,540	2,315	21-3/4" x 21-3/4"
#PFPS20E	20 w/ PVC shutter	1/4	3,320	3,060	25-3/4" x 25-3/4"
#PFPS20G	20 w/ PVC shutter	1/3	4,095	3,735	25-3/4" x 25-3/4"
#PFPS-20G	20 w/ PVC shutter	1/2	4,765	4,345	25-3/4" x 25-3/4"
#PFPS24H	24" w/ PVC shutter	1/3	5,210	4,680	29" x 29"





Replacement Motors

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Item#	Нр	Voltage	RPM	AMPS	Pruden #	Fan model
#HS9035	1/4	115/230	1625	3.2/1.6	PFM14	PFPS16D, PFPS20E
#HS9037	1/3	115/230	1625	4.2/2.1	PFM13B	PFPS2OG
#R9002	1/2	115/230	1700	5.0/2.5	N/A	PFPS2OGG
#HS9038	1/3	115/230	1100	3.8/1.9	PFM13	PFPS24, PFP24H
			_			




Replacement Shutters

Item#	Size	Fan Model
#101081	17-1/2" x 17-1/2"	PFPS12C
#10111	20" x 20"	PFPS16D
#10115-5	22-1/2" x 22-1/2"	PFPS20E, 20G, 20GG
#10118-5	27-1/2" x 27-1/2"	PFPS24H. 24C



Replacement Fan Blades


Item#	Bore	Pitch	RPM	Wings	Fan model
#PC12	1/2"	45°	1625	3	PFPS12C
#PFPB16D	5/8"	40°	1625	3	PFPS16D
#PG20	1/2"	40°	1725	3	PFPS20G
#PFPB20GG	1/2"	45°	1725	3	PFPS20GG
#HS17001	1/2"	45°	1100	4	PFPS24H, PFPS24C





Coolair NBRB52 Fan Parts List


Key	Description	CANBRB52	Key	Description	CANBRB52
1	Fan Panel	CA14-169-181-1	12	Motor Bracket	CA14-161-15-6
2	Blade Assembly	CA14-235-164-4	13	Belt	CA1247.3-65
3	Blades	CA14-113-86-1	14	Disc Assembly	CA14-229-11-5
4	Disc	CA14-132-31-1	15	Uprights	CA14-193-86-1
6	Bearings	CA12-31-3-2	16	Bearing Protector	CA12-174-62-2
7	Spacer	CA14-183-4-5	17	Shim	CA14-160-103-1
8	Shaft	CA14-180-20-1	18	Tensioner Bracket	CA14-158-68-1
9	Locknut	CA1202.7-5/8E	19	Rotary Belt Tensioner	CARBT3
10	Shaft Assembly	CA14-208-5-1	20	Bearing Protector	CA14-126-79-1
11	X-Braces	CA14-115-6-5		-	



Coolair NCF36-48 Fan Parts List

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Key	Description	CANCF36	CANCFA36	CANCFA48	CANCFB48
1	Fan Panel Assembly	CANCF36/LBA	CANCFA36/LBA	CANCFA48/LBA	CANCFB48/LBA
2	Blade Assembly	CA14-235-63-1	CA14-235-62-1	CA14-235-90-1	CA14-235-72-1
3	Blades	CA14-113-33-1	CA14-113-33-1	CA14-113-60-1	CA14-113-44-1
4	Bearing Protector	CA12-174-62-2	CA12-174-62-2	CA12-174-62-3	CA12-174-62-3
5	Disc	CA14-132-17-1	CA14-132-17-1	CA14-132-15-1	CA14-132-15-1
6	Bearings	STD6203	STD6203	STD6205	STD6205
7	Spacer	CA14-183-4-5	CA14-183-4-5	CA14-183-4-3	CA14-183-4-3
8	Shaft	CA14-180-20-1	CA14-180-20-1	CA14-180-6-3	CA14-180-6-3
9	Locknut	CA1202.7-5/8E	CA1202.7-5/8E	CA1202.7-7/8E	CA1202.7-7/8E
10	Bearing Cap	CA14-119-4-1	CA14-119-4-1	CA14-119-5-1	CA14-119-5-1
11	Shaft Assembly	CA14-208-5-1	CA14-208-5-1	CA14-208-5-5	CA14-208-5-5
12	X-Braces	CA14-115-6-4	CA14-115-6-4	CA14-115-6-5	CA14-115-6-5
13	Motor Bracket	CA14-161-15-5	CA14-161-15-5	CA14-161-15-6	CA14-161-15-6
14	Belt	HSA58	HSA58	HSA71	HSA71
15	Disc Assembly	CA14-229-10-4	CA14-229-10-4	CA14-229-10-7	CA14-229-10-7




& Coolair

Coolair NBF Fan Parts List

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Key	Description	CANBF24	CANBF30	CANBF36	CANBF42	CANBF48	CANBFA54
1	Fan Panel Assembly	CALL	CALL	CANBF36/LBA	CALL	CANBF48/LBA	CALL
2	Blade Assembly	CA14-235-68-1	CA14-235-69-1	CA14-235-62-1	CA14-235-71-1	CA14-235-72-1	CA14-235-97-1
3	Blades	CA14-113-38-1	CA14-113-40-1	CA14-113-77-1	CA14-113-42-1	CA14-113-44-1	CA14-113-61-1
4	Struts	-	-	=	-	-	CA14-186-23-1
5	Disc	CA14-132-13-1	CA14-132-13-1	CA14-132-17-1	CA1408.13-1	CA14-232-15-1	CA14-232-15-1
6	Bearings	CA12-31-3-2	CA12-31-3-2	CA12-31-3-2	CA12-31-3-2	CA12-31-5-2	CA12-31-5-2
7	Spacer	CA14-183-4-1	CA14-183-4-1	CA14-183-4-5	CA14-183-4-5	CA14-183-4-3	CA14-183-4-3
8	Shaft	CA14-180-6-4	CA14-180-6-4	CA14-180-20-1	CA14-180-20-1	CA14-180-6-3	CA14-180-6-3
9	Locknut	CA1202.7-5/8E	CA1202.7-5/8E	CA1202.7-5/8E	CA1202.7-5/8E	CA1202.7-7/8E	CA1202.7-7/8E
10	Bearing Cap	CA14-119-4-1	CA14-119-4-1	CA14-119-4-1	CA14-119-4-1	CA14-119-5-1	CA14-119-5-1
11	Bearing Protector	CA12-174-62-2	CA12-174-62-2	CA12-174-62-2	CA12-174-62-2	CA12-174-62-3	CA12-174-62-3
12	Shaft Assembly	CA14-208-5-3	CA14-208-5-3	CA14-208-5-1	CA14-208-5-1	CA14-208-5-5	CA14-208-5-5
13	X-Braces	CA14-115-6-1	CA14-115-6-1	CA14-115-6-2	CA14-115-6-2	CA14-115-6-2	CA14-115-6-2
14	Motor Bracket	CA14-161-15-1	CA14-161-15-1	CA14-161-15-3	CA14-161-15-3	CA14-161-15-3	CA14-161-168-1
15	Belt	CALL	CA1247.1-48	CA1247.1-58	CA1247.1-61	CA1247.1-71	CA1247.1-75
16	Disc Assembly	CA14-229-10-2	CA14-229-10-2	CA14-229-10-4	CA14-229-10-6	CA14-229-10-7	CA14-229-10-7
17	Shim	-	-	-	-	-	CA14-160-103-




& Coolair

Coolair NEF36/NEFC48/NEFB52/NEF54 Fan Parts List

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


Key	Description	CANEF36	CANEFC48	CANEFB52	CANEF54
1	Fan Panel	CA14-169-148-1	CA14-169-180-1	CA14-169-181-1	CA14-169-211-1
2	Blade Assembly	CA14-235-125-1	CA14-235-126-3	CA14-235-165-2	CA14-235-195-1
3	Blades	CA14-113-68-1	CA14-113-69-2	CA14-113-86-1	CA14-113-86-2
4	Disc	CA14-132-23-1	CA14-132-31-1	CA14-132-31-1	CA14-132-31-1
5	Bearings	CA12-31-3-2	CA12-31-3-2	CA12-31-3-2	CA12-31-3-2
6	Spacer	CA14-183-4-5	CA14-183-4-5	CA14-183-4-5	CA14-183-4-5
7	Shaft	CA14-180-20-1	CA14-180-20-1	CA14-180-20-1	CA14-180-20-1
8	Locknut	CA1202.7-5/8E	CA1202.7-5/8E	CA1202.7-5/8E	CA1202.7-5/8E
9	Shaft Assembly	CA14-208-5-1	CA14-208-5-1	CA14-208-5-1	CA14-208-5-1
10	X-Braces	CA14-115-6-4	CA14-115-6-7	CA14-115-6-5	CA14-115-6-5
11	Motor Bracket	CA14-161-15-5	CA14-161-15-5	CA14-161-15-6	CA14-161-15-6
12	Belt	CA1247.1-44	CA1247.3-65		CA1247.3-65 -
13	Disc Assembly	CA14-229-10-9	CA14-229-11-5	CA14-229-11-5	CA14-229-11-5
14	Bearing Protector	CA12-174-62-2	CA12-174-62-2	CA12-174-62-2	CA12-174-62-2
15	Uprights	CA14-193-86-2	CA14-193-86-1	CA14-193-86-1	CA14-193-86-4
16	Shim	-	-	CA14-160-103-1	CA14-160-103-1





Aerotech Dragonfly

Key	Item#	Description	Qty.	Key	Item#	Description	Qty.
1	FH1951	Orifice panel, galv.	1		FH2419	Tensioner arm only, aluminum	1
2	FH3961	Top housing panel, galv.	1	22	FH2138*	Motor Sheave AK35x5/8" bore with keyseat, C	Ί 1
3	FH3962	Left/Right side housing panel, galv.	1	23	FH2130	Cone support bracket, GC type, galv.	4
4	FH3960	Bottom housing panel, galv.	1	24	FH4349	Discharge cone (Top/Bottom section), galv.	2
5	FH3962	Left/Right side panel of housing, galv.	1		FH4450	Discharge cone (Left/Right section), galv.	2
6	FP2549	Prop assembly, 3-blade, galvanized	1	25	FH2654	Guard, Flat side cone, 1/2 circle, pvc coated	2
7	FH2429	Support Bracket for motor mounting plate, galv.	. 1	26	FH1750	Inlet guard, 56" S.Q., 2" x 2", galv.	1
8	FH2846	Mounting Plate for NEMA 56 motor	1	27	DG1050	Assembly, Dragonfly, 50" fan	1
9	FH2428	Center support brace for Strut, galv.	1	28	KX1459	Spring, Constant force, 1" W, 1.15LB	2
10	FM1024*	Motor, 1HP, 1725 RPM, 56Fr., 1ph, 120/240	1	29	AC2072	Spring reel spool, 2.75" O.D., 1.25"W.	2
11	FH1302	Reinforced Brackets for Strut, galv.	2	30	FA2712	Tube, Hinge, 26.2"L	4
12	KN1860	Hex nut, M25x10mm, zinc plated	1	31	FA2722	50" Dragonfly door. flat	2
13	KX1208	Cover plastic	1		FA2724	50" Dragonfly door, offset	2
14	FH1930	Strut, galvanized	1	32	FA 1732	Short wing support bracket	2
15	FH1932	Spacer plate, plastic	2	33	KX1043	5/16" Push-in fastener, nylon	4
16	FH1505*	V-belt, 87" A-section (A85), aramid fiber	1	34	FA 1733	Dragonfly door wing	2
17	KX1130	Bushing, aluminum	1	35	FA 1730	Tall wing support bracket	2
18	FH2137*	Propeller sheave, aluminum	1	36	FH1965	Universal shutter clip, galvanized	2
19	FP2060	Hub with bearing and shaft	1	37	KX 1015	Draw latches	2
20	FH2504	Mounting bracket for belt tensioner	1	38	FH1278	Guard support clips	2
21	FH2402	Belt tensioner assembly with 3" idler pulley	1	39	KX1470	Retainer Spring 239 KX1470 Retainer Spring	2
	FH2406	3" idler pulley only, with bolt	1				



Grower	Fans with Galvanized Cones	cancer and	d birth defects or other reproductive harm.	For more information, go to www.P65V	/arnings.ca.gov
Key	Description	GB36VxCP	GB365VxCP	GB481VxCP	QTY
1	Orifice Panel, galvanized	AFH3136	AFH1248	AFH1252	1
2	Top Housing Panel, galvanized	AFH2201	AFH2201	AFH2221	1
3	Right Housing Panel, galvanized	AFH2201	AFH2201	AFH2221	1
4	Bottom Housing Panel, galvanized	AFH2204	AFH22O4	AFH2224	1
5	Left Housing Panel, galvanized	AFH2201	AFH2201	AFH2221	1
6	Propeller, galvanized	AFP 1041	AFP 1041	AFP1042	1
7	Strut, galvanized	AFH2094	AFH2436	AFH2448	2
8	Link Belt	-	AFH2083	AFH2053	1
	Aramid Fiber Belt	-	AFH1503	AFH1518	1
9	Motor Sheave	-	AFH2003	AFH2029	1
10	Motor, 1 Hp, 1725 RPM, 56Fr.,				
	1 ph, 208-230/115 V	HS9005*	HS9015	HS9000	1
11	Motor Support	-	AFH2815	AFH2818	1
12	Belt Tensioner Assembly				
	with 3" idler pulley	-	AFH2402	AFH2402	1
	3" idler pulley only, w/ bolt	-	AFH2406	AFH2406	1
	Tensioner Arm only, aluminum	-	AFH2419	AFH2419	1
	Mounting Bracket for Belt Tensioner	-	AFH2504	AFH2504	1
14	Bearing, 1" bore x 1.44"CL, CI Holder	-	16G	16G	2
15	Bracket, bearing mount, galvanized	-	AFH2815	AFH2815	1
16	Shaft, 1" dia., steel	-	AFH2086	AFH2101	1
17	Propeller Sheave	-	AFH2091	PAK 1041	1
18	Shutter clip, left, galvanized	AFH2110	AFH2110	AFH2110	VARIES
19	Shutter clip, right, galvanized	AFH2111	AFH2111	AFH2111	VARIES
20	Shutter, all plastic	101203-1-8	101203-1-8	101209-1-8	1
21	Cone Support Bracket,				
	GC type, galvanized	AFH2130	AFH2130	AFH2130	4
22	Discharge cone, galvanized, (1) Section	AFH4236	AFH4236	AFH4248	4
23	Guard Kit, 48FC/48GC cone,				
	PVC CTD, w/Hardware	AFH1336	AFH1336	AFH2648	1

Cumberland Butterfly Fans

36" Fan

50" Fan

• 1/2-HP motor • 9,984 CFM


• 1-HP motor • 22,400 CFM

#G50SCL16GA	Galv. slant wall w/cone
#101210	54" black shutter
#GCGSB36 36	6" 1/2 slant wall belt drive w/o shutter
#101202	39" black shutter

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Cumberland Butterfly Fan Performance

Model	RPM	HP	VOLTAGE	.05-SP	CFM/WATT	.10-SP	GFM/WATT
G50CBF16GAHF	638	1.5	115/230	25,427	21.5	23,603	18.9
G54CBF16GAHF	594	1.5	115/230	30,500	20.5	29,500	19.8




Cumberland Butterfly Fan Replacement Parts

• Parts shown for 1-phase, 60Hz application. Call for others.

(1) #PAK3958	Pulley (motor) fo	or 50" fan
(1) #PAK3458	.Pulley (motor) for 36" 8	k 54" fans
(2) #HSA38	Faı	n Belt 36"
(2) #HSA58	. Fan Belt 60" (for 50" &	54" fans)
(NS) #HS9015A	Motor for 36"	Belt drive
(NS) #HS9010A	Motor for 50"	Belt drive
(3) #G16-0014	Pulley (prop) for	or 36" fan

(6) #HS900-54CA Prop Blade for 54" fan	(3) #PAL 1041Pulley (4) #G16-0045	Shaft 36" Shaft 50" Shaft 36" Shaft 30" Shaft 30" Shaft 30" Shaft 30" Shaft 50" Shaft



Replacement Parts for Hired Hand Mega Flow Fans

1) #H6403-5010	1) #H6403-9202	Steel, 36"
1) #HS900-54CA Steel, 3 Blade, 54" 2) #SHAFT1-1563 1" x 16" shaft 3) #16G Pillow blocking bearing 4) #H1011-5002 prop pulley - 36" 4) #PAFD104100 prop pulley - 48" & 52" 5) #HSAX44 V-belt - 36" 5) #HSAX49 V-belt - 48" & 52" 6) #PAK3458 Motor pulley - 36" 6) #PAK3958 Motor pulley - 52" 7) #FS0605ZF 3.5" Idler arm assembly 7A) #VX4004 Pulley only 8) #HS9015A Motor 1/2 Hp 1725 rpm 115/230 - 36"	1) #H6403-5010	Steel, 3 Blade, 48"
2) #SHAFT1-1563	1) #G13-0239	Steel, 3 Blade, 52"
3) #16G	1) #HS900-54CA	Steel, 3 Blade, 54"
4) #H1011-5002 prop pulley - 36" 4) #PAFD104100 prop pulley - 48" & 52" 5) #HSAX44 V-belt - 36" 5) #HSAX49 V-belt - 48" & 52" 6) #PAK3458 Motor pulley - 36" 6) #PAK3958 Motor pulley - 52" 7) #FS0605ZF 3.5" Idler arm assembly 7A) #VX4004 Pulley only 8) #HS9015A Motor 1/2 Hp 1725 rpm 115/230 - 36"	2) #SHAFT1-1563	1" x 16" shaft
4) #PAFD104100 prop pulley - 48" & 52" 5) #HSAX44 V-belt - 36" 5) #HSAX49 V-belt - 48" & 52" 6) #PAK3458 Motor pulley - 36" 6) #PAK3958 Motor pulley - 52" 7) #FS0605ZF 3.5" Idler arm assembly 7A) #VX4004 Pulley only 8) #HS9015A Motor 1/2 Hp 1725 rpm 115/230 - 36"	3) #16G	Pillow blocking bearing
5) #HSAX44	4) #H1011-5002	prop pulley - 36"
5) #HSAX44	4) #PAFD 104100	prop pulley - 48" & 52"
5) #HSAX49	5) #HSAX44	V-belt - 36"
6) #PAK3458		
6) #PAK3958	6) #PAK3458	Motor pulley - 36"
7) #FS0605ZF 3.5" Idler arm assembly 7A) #VX4004 Pulley only 8) #HS9015A Motor 1/2 Hp 1725 rpm 115/230 - 36"	6) #PAK3458	Motor pulley - 48"
7A) #VX4004 Pulley only 8) #HS9015A Motor 1/2 Hp 1725 rpm 115/230 - 36"	6) #PAK3958	Motor pulley - 52"
7A) #VX4004 Pulley only 8) #HS9015A Motor 1/2 Hp 1725 rpm 115/230 - 36"	7) #FS0605ZF	3.5" Idler arm assembly
8) #HS9015A		
0) #IICOOO		
8) #HS9000	8) #HS9000	Motor 1 Hp 1725 rpm 240V for 48" & 52" Fans




Hired Hand Replacement Props for Hired Hand Funnel Flow Fans

Item#	Description	Fan
#HSFP-003	Prop, Aluminum, 4 Blade	FF-18
#H6403-0121	Prop, Stainless Steel, 4 Blade	FF-24
#H6403-6112	Prop, Composite, 3 Blade	FF-36 DD
#H6403-6118	Prop, Composite, 3 Blade	FF-36 BD
#H6403-6111	Prop, Composite, 3 Blade	FF-48 HF
#H6403-6111	Prop, Composite, 3 Blade	FF-48 STANDARD
#HSFP-009	Prop, Stainless Steel, 3 Blade	FF-48 HE
#H6403-6113	Prop. Composite, 3 Blade	FF-52




Replacement Motors

#H3017-5024 1/4 Hp, 240v, 1 ph, 1725 rpm FF-14 #H3017-5024 1/4 Hp, 240v, 1 ph, 1725 rpm FF-18 #H3017-5018 1/3 Hp, 240v, 1 ph, 1100 rpm FF-24 #H3017-0136 1/2 Hp, 240v, 1 ph, 1725 rpm FF-36 BD	Item#	Description	Fan
#H3017-3099 1 Hp, 240v, 1 ph, 1725 rpm FF-48 HF	#H3017-5024	1/4 Hp, 240v, 1 ph, 1725 rpm	FF-18
	#H3017-5018	1/3 Hp, 240v, 1 ph, 1100 rpm	FF-24
	#H3017-0136	1/2 Hp, 240v, 1 ph, 1725 rpm	FF-36 BD
	#H3017-5036	1/2 Hp, 240v, 1 ph, 850 rpm	FF-36 DD



Cumberland Mega Flow 36-Inch - #G6603-10003

Key	Item#	Description
1	SHAFT1-763T	Shaft 1" x 7-5/8"
2	UCP20516G5	Pillow Block Bearing - 1"
3	AFD84100	Pulley - 8.25"
4	BAX47	Belt, AX47, Cogged
5	FS0604ZF	Idler Assy 3.00" V-Belt AL
6	PAK3458	Pulley AK34-5/8
7	HS9015A	Motor, 1725 RPM, 1/2 hp, 115/208-230
8	G6403-0135	Guard, Galv FF 36" – 2.00" Cone
9	G13-0234	Prop, Galv, 36" 4 Blade
NS	47813	Key Shear 1/4" x 1/4" X 1.00"
10	H6611-9022	Shutter 45.5" x 45.5", Galv Frame & Alum Louvers
NS	G1040-0105	Latch, Draw Tension Zinc Latch
NS	Cone	
	G0404-10291	36/48 Cone Brkt (4 Reg)
	G0404-10048	36" Cone Sections (4 Reg)
NS	Galvanized Housing	• •
	G0404-10246	36" Cone Sup Brkt
	G0404-6973	36" Panel Bottom
	G0404-6974	36" Panel Top
	G0404-6975	36" Panel Left
	G0404-6976	36" Panel Right
	G0404-10047-B0	36" Orifice
	G0404-10057	36" Vert Support



Cumberland Mega Flow 48-Inch - #G6603-10002

Key	Item#	Description	
1	SHAFT1-763T	Shaft-1" x 7-5/8"	
2	UCP20516G5	Pillow Block Bearing - 1"	
3	PAFD 104100	Pulley - 10.4"	
4	BAX60	Belt, AK60, Cogged	
5	FSO604ZF	Idler Assy 3.00" V-Belt AL	
6	PAK3258	Pulley AK32-5/8	
7	HS9000	Motor, 1725 RPM, 1 hp, 120/240	
8	G6403-0143	Guard-48 2" Cone	
9	G13-0235	Prop, Galv.48-B, 3 Blade, Lg Orf	
NS	47813	Key Shear 1/4" x 1/4" x 1.00"	
10	H6611-9023	Shutter, 54.25 x 54.25, w/	
		Galv Frame & Alum Louvers	
NS	G1040-0105	Latch, Draw Tension Zinc Latch	
NS Cone			
	G0404-10291	36/48 Cone Brkt (4 Req)	
	G0404-10332	48" Cone Section (4 Req)	
NS	Galvanized Housing	·	
	G0404-11495	48" Cone Sup Brkt	
	G0404-6977	48" Panel Bottom	
	G0404-6978	48" Panel Top	
	G0404-6979	48" Panel Left	
	G0404-6980	48" Panel Right	
	G0404-10318-B0	48" Orifice	
	G0404-10335	48" Vert Support	

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Cumberland Mega Flow 54-Inch - #G6603-10000

Key	Item#	Description	
1	SHAFT1-763T	Shaft, 1" x 7-5/8"	
2	UCP20516G5	Pillow Block Bearing - 1"	
3	G12-0493	Nylon Pulley Afd - 9.93"	
4	BAX52	Belt, AX52, Cogged	
5	FS0604ZF	Idler Assy 3.00" V-Belt	
6	PAK3458	Pulley, AK34-5/8	
7	HS9014C	Motor, (Rev Rot), 1750 RPM 1.5 Hp 115-208/230	
8	G11-0409	Guard, Grill, 70-5/8"	
9	G13-0233	Prop, 54" Galv (Low Sp)	
NS	47813	Key Shear 1/4" X 1/4" x 1.00"	
10	H6611-9028	Shutter 59.5 x 59.75, w/	
		Galv Frame & Alum Louvers	
NS	G1040-0105	Latch, Draw Tension Zinc Latch	
NS	Cone		
	G0404-10652	54" Cone Brkt	
	G0404-11450	54" Tab Cone Side	
	G0404-11451	54" Tab Cone Top/Bottom	
NS	Galvanized Housin	g	
	G0404-10362	54" Cone Sup Brkt	
	G0404-10640	54" Panel BOttOm	
	G0404-10641	54" Panel Top	
	G0404-10642	54" Sw Panel Right	
	G0404-10643	54" Sw Panel Left	
	G12-0769	54" Orifice	
	G12-0772	54" Vert Support	



GrowerSELECT


Replacement ACME **BDR48 Fan Housings**

Constructed of 20 ga. Galvanized G90 steel, these replacement housings work for multiple ACME BDR48 Shallow Housing applications.

#HSBDR48-RK.....Shallow Housing Kit

↑ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Acme Fan Replacement Parts

1) #EE941365	Roll Pin
	36" Fan Blade Propeller
	48" Fan Blade Propeller
4) #EE121321B	Orifice Frame for 48" Fan
4) #EE125244	Orifice Frame for 36" Fan
6) #605082	Bolt 5/16" x 3/4" length
	Bearing Base for 36" Fan
7) #EE121317	Bearing Base for 48" Fan
•	Bearing & Shaft Assy. 36" fan
	Bearing & Shaft Assy. 48" fan
9) #EE121185Sh	aft For 36" Acme Fan Old Style
	naft For 48" Acme Fan Old Style
•	Motor Pullev 36" Fan

11) #EE121481	Motor Base 36" Fan
11) #EE121484A	Motor Base 48" Fan
12) #HSAX38Fan Be	elt 36" Fan Motor on Top
12) #HSAX28Fan Belt 3	6" Fan Motor on Bottom
12) #HSA58Fan Be	elt 48" Fan Motor on Top
12) #HSA46 Fan Belt 4	8" Fan Motor on Bottom
13) #EE129057	Fan Pulley for 36" Fan
13) #PAL11425MM	Fan Pulley for 48" Fan
14) #HS9015A 1/2 Hp M	otor Standard Duty for 36"
14) #HS9010A. 1 Hp Moto	or Standard Duty for 48"
14) #HS9000 1 Hp M	lotor Heavy Duty for 48"

10) #PAK3058..... Motor Pulley 48" Fan

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Bearing

• For Coolair and Acme products

#STD6203.....fits 21/36" shaft #STD6205.......fits 1" shaft



Hub Bushing for Pulley #HS931450......Bushing



Fan Props

#EE139177 54" Prop



Idler Pulley for Belt Tightener

#HS993485Idler





Fan Pulleys

#PAL11425MM 48" Pulley w/ Keyway **#PAK104H** 48" Pulley req. hub bushing #HS931450




Shaft and Bearing Assembly

#HS129058	. 48″
#HS125396	. 54"

Pillow Block Conversion Kits

Converts Acme, AirStorm or Windstorm drive system from encapsulated bearings to pillow block bearings for easier long term maintenance and lower replacement costs.

#HSSCK100 AirStorm AS-54EBDLP - Stainless #HSSCK200......Windstorm WS-54SBDLA & WS-54PBDBPG - Galv. $\mbox{\#HSSCK200A}..... \mbox{Acme} \mbox{\$ 54" BDR - Galv}.$ #HSSCK200B Acme® 48" BDR - Galv.



From this...

To this





DYNOFA

DYNOFAN is ideal for use in horse barns, garages, workshops, loading docks, patios, outdoor entertainment areas and more!

- · Heavy-duty steel fan basket and mounting arm
- Corrosion resistant black powder coated finish
- Suitable for use in high-moisture environments
- Balanced aluminum 3 prop blade
- Adjustable up to 140°

- · Permanently sealed ball bearings
- Overload protection
- OSHA approved grille design
- 9' long SJTW cord
- UL 507 tested and rated



SPECS	
Motor size	1/8 Hp
Voltage	120
Speed	3
Āmps	
Rpm	1550/1440/1250
Frequency (Hz)	
Speed controller included	Manual pull chain
Cord included	Yes, 120V, prewired
Cord Length	
Mount style	Ceiling/wall
Mounted included	Pre-installed
Guard spacing (in)	1/2
Product Weight (lb)	

<u>⚠</u> WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



DYN18SOO 18" Outdoor Stir Fan, 3-Speed

• AIR DELIVERY	Airflow*	6300/5300/4900
• SPECS		
		1/5 Hp
Voltage		
Speed		3
Amps		1.45/1.36/ 1.27
Rpm		1570/1400/1000
		60
		Manual pull chain
Cord included		Yes, 120V, prewired
Cord Length		9′
Mount style		Ceiling/wall
Mounted included		Pre-installed
Guard spacing (in)	1/2

Product Weight (lb)23

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




DYN30POO 30" Oscillating Pedestal Fan

• AIR DELIVERY	Airflow*	9540/9090/7950

•	SPI	EC	S
---	-----	----	---

DYN14SOO

D1 1100	
Motor size	
Voltage	120
Speed	
Amps	
Rpm:	1080
Frequency (Hz)	60
Speed controller included	Manual pull chain
Cord included	Yes, 120V, prewired
Cord Length	9′
Mount style	Pedestal
Mounted included	Yes
Guard spacing (in)	1/2
Product Weight (lb)	75



* INTERNATIONAL **STANDARDS**

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





• AIR DELIVERY	Alfilow	 18360/14890
annaa		

· SPECS	
Motor size	1/2 Hp
Voltage	120
Speed	2
Amps	3.8
Rpm	1110
Frequency (Hz)	60
Speed controller included	Selection knob
Cord included	
Cord Length	9′

Mounted includedPre-installed

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

10000/14000



Wind**s**mili

⚠ WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Windstorm Circulation Fans

- Wide spacing reduces the performance-robbing buildup of debris & feathers on the fan guard.
- · Complete with pre-wired 10' cord for 115 volt.
- Totally enclosed motor with built-in three (18") or two (20" & 24") speed control



WS-18C3 18" Circulation Fan 3-Speed



Airflow 1730/1410/1120 **BESS Test Number** c19595

SPECS

AIR DELIVERY

Motor size 1/5 120 Voltage Speed 3

Amps .92/.73/.60 Rpm 1537/1244/955

Frequency (Hz) 60

Speed Controller Included: Manual 3-sp

Cord Included: Yes, 120 V, pre-wired

Cord Length:

Mount Style: Ceiling/wall Mount Included: Pre-installed

Guard Spacing (in): 2" Product Weight (lb): 16

WS-20C2 20" Circulation Fan 2-Speed



WS-24C2 24" Circulation Fan



AIR DELIVERY AIR DELIVERY

Airflow 2070/1740 **BESS Test Number** c21037

• SPECS

Motor size 1/11 120 Voltage Speed 2 Amps 1.07/.89 1068/880 Rom Frequency (Hz) 60 Speed Controller Included: Manual 2-sp

Cord Included: Yes, 120 V, pre-wired

Cord Length:

Mount Style: Ceiling/wall Mount Included: Pre-installed

Guard Spacing (in): 2" Product Weight (lb): 18

2-Speed



Airflow 2720/2470 **BESS Test Number** c21038

SPECS

1/7 Motor size 120 Voltage Speed 2 Amps 1.25/1.15 1072/961 Rpm Frequency (Hz) 60 Speed Controller Included: Manual 2-sp

Inverter Compatible: Nο

Cord Included: Yes, 120 V, pre-wired

Cord Length: 10

Mount Style: Ceiling/wall Mount Included: Pre-installed

Guard Spacing (in):

Product Weight (lb): 24





Windstorm Stir Fans



WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

- · Heavy galvanized ceiling mount bracket tilts to adjust airflow direction.
- · Totally enclosed variable speed motor pairs with most speed controls (sold separately) to vary air delivery.
- 115/230 Volt motor. Pre-wired cord not included.

WS-20CV 20" Stir Fan Variable Speed



AIR DELIVERY

3370 Airflow (thrust cfm) Efficiency (thrust cfm/W) 11.7 5xD Centerline Velocity (fpm) 1050 **BESS Test Number** c20186

• SPECS

Motor size 1/3 Hp Voltage 115/230 Speed Single/variable 3.8/1.9 Amps Rom 1700 Speed Controller Included: No Cord Included: No Cord Length: N/A Mount Style: Ceiling Mount Included: Yes Guard Spacing (in): 1/2 Product Weight (lb): 36

WS-24CV 24" Stir Fan Variable Speed

AIR DELIVERY

5200 Airflow (thrust cfm) Efficiency (thrust cfm/W) 12.1 5xD Centerline Velocity (fpm) 1190 BESS Test Number c20187

SPECS

1/2 Hp Motor size Voltage 115/230 Single/variable Speed Amps 4.8/2.4Rom 1725 60/50 Frequency (Hz) Speed Controller Included: No Cord Included: No Cord Length: N/A Mount Style: Ceiling Mount Included: Yes Guard Spacing (in): 1/2 Product Weight (lb): 47

WS-36CV 36" Stir Fan Variable Speed



AIR DELIVERY

9800 Airflow (thrust cfm) Efficiency (thrust cfm/W) 19 5xD Centerline Velocity (fpm) 1040 **BESS Test Number** c20248

SPECS

Motor size 1/2 HpVoltage 115/230 Single/variable Speed 6.0/3.0 Amps Rpm 825 60/50 Frequency (Hz) Speed Controller Included: No Cord Included: No Cord Length: N/A Mount Style: Ceiling Mount Included: Yes 1/2 Guard Spacing (in): Product Weight (lb): 65



 $\label{eq:windstorm} \textbf{Windstorm}^{\text{\tiny{TM}}} \ \textbf{box fans provide outstanding performance at an affordable price. They}$ feature heavy galvanized steel housings with a secure wire guard which is easily removed for service.

Item#	Нр	RPM	Thrust (cfm)	cfm/W
WS-36BDD	1/2	850	9,950	21.7
WS-48BDD	1	850	16,900	19.0

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Shutter Mounting Kit for Box Fans

Kit converts box fan for use as a wall mount exhaust fan. Kit includes:

- 3) Galvanized mounting brackets
- 17) Zinc screws
- 1) PVC Shutter

#WS-36411	Includes 3	38″ x	38"	PVC shutter
#WS-48411	Includes 5	52" x	52"	PVC shutter



#HS9005A	Motor, 1/2 Hp 850 RPM 115/230V 60Hz
#HS900-36D	Prop 36" Galvanized 3 Blade 0.625" Shaft OD
#HSCS-002	Cord SJ 14/3 9' 220 V

48" Box Fan Replacement Parts

#HS9084	Motor, 1 Hp 850 RPM 230V 60Hz
	Prop 48" Galvanized 3 Blade 0.625" Shaft OD
#HSCS-002	Cord SJ 14/3 9' 220 V
	Wire Mesh Guard, 48"

*For OSHA compliant guards, contact your local Hog Slat representative.



60" Updraft Paddle Fan

 43,500 CFM 	 10" Stem
- 71 XIMDa	• 120 Val+

#NE190A-7R	Updraft paddle fan, 60"
	Control 5 Fan Infinite Speed 120 Volt
#NE150F	Control 8 Fan Infinite Speed 120 Volt
#NE200F	Control 12 Fan Infinite Speed 120 Volt



Replacement Blades

36" Box Fan

• Replacements for Schaffer, J&D and Windstorm stir fans

Item#	Size	Bore Size
HSFP-011	20"	1/2"
HSFP-012	24"	5/8"
HSFP-013	36"	5/8"

Stir Fan Motors

- TEAO (totally enclosed air over)
- 115/230 volts
- 48Y Frame
- 60 Hz

			Carlo Division
Item#	HP	Fan Size	RPM
HS9076	1/3	20"	1725
5330016	1/2	24"	1725
HS9082A	1/2	36"	825



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Munter's **Circulation Fan**


- Corrosion-resistant housing
- Var speed 1/3 hp motor
- Flexible 4-point mounting
- · Bird-guard kit available

#ACX24P1.....24" plastic circ. fan

PVC Fan Shutters

- Low maintenance
- PVC vanes with true airfoil design
- Heavy PVC frame with reinforced corners
- 1" flange
- · Many sizes available
- · Spring steel galvanized rods extended entire length of the shutter with unique lock down ends





We build custom sizes!

Item#	Color	Size (A x B)
10105	White	14" x 14"
10106	White	15" x 15"
10106-1	White	15-/8" x 15-1/8"
10107	White	16" x 16"
10107-5	White	16-1/2" x 16-1/2"
10108	White	17" x 17"
101081	White	17-1/2" x 17-1/2"
10109	White	18" x 18"
10109-1	White	18-1/8" x 18-1/8"
10109-3	White	18-3/8" x 18-3/8"
10110A	White	19" x 19"
10111	White	20" x 20"
10112	White	21" x 21"
10112-3	White	21-3/8" x 21-3/8"
10112-5	White	21-1/2" x 21-1/2"
10112-6	White	21-5/8" x 21-5/8"
10113	White	22" x 22"
10113-5	White	22-1/2" x 22-1/2"
10115	White	24" x 24"
10115-3	White	24-3/8" x 24-3/8"
10115-5	White	24-1/2" x 24-1/2"
10116	White	25" x 25"
10116-8	White	25-7/8" x 25-7/8"
10117	White	26" x 26"
10118	White	27" x 27"
10118-3	White	27-3/8" x 27-3/8"
10118-5	White	27-1/2" x 27-1/2"
10118-6	White	27-5/8" x 27-5/8"
10118-75	White	27-3/4" x 27-3/4"
10119	White	28" x 28"
101192	White	30" x 30"
101195	White	33" x 33"
101195-5	White	33-1/2" x 33-1/2"
101196	White	34" x 34"
101196-5	White	34-1/2" x 34-1/2"
101198	White	36" x 36"
101198-3	White	36-3/8" x 36-3/8"
1		, -

Item#	Color	Size (A x B)
101199	White	37" x 37"
101202	White	39" x 39"
101202-5	White	39-1/2" x 39-1/2"
101203-1	White	41" x 41"
101203-1-6	White	41-5/8" x 41-5/8"
101203-1-8	White	41-7/8" x 41-7/8"
101204	White	42" x 42"
101204-5	White	42-1/2" x 42-1/2"
101205	White	44" x 44"
101207	White	48" x 48"
101208-1-0	White	51" x 51"
101208-1-1	White	51-1/8" x 51-1/8"
101209-1-8	White	53-7/8" x 53-7/8"
101210-4	White	54" x 54"
101210-1	White	54-1/8" x 54-1/8"
101210	Black	54-1/8" x 54-1/8"
10211-1	White	55" x 56-1/2"
10211-2	White	55-1/8" x 56-3/4"
101212	White	58" x 58"
	=	



Clip Retainer Shutter



24" Transition Hood with FasLock

The FasLock slide kit mounts to the poly transition and securely attaches the fan to the face of the hood.

- Constructed of UV resistant polypropylene.
- Bottom opening 31" x 33"
- Face opening 39" x 39"







Stainless Steel Slide Bar holds top flange securely in place.



Remove the slide bar and tip fan forward for maintenance or cleaning.

#628062PA.24" Poly Transition #HSFLT-24A FasLock Mounting Kit



WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Hog Fan Guards

Item#	Fan Size	Guard (Part)	Painted Guard	Galvanized Guard
AS-24EDDLP	Airstorm 24"	N/A	8100410100	8100410200
AS-36EDDLP	Airstorm 36"	Panel (48"x16")	8100430100	8100110200
AS-54EBDLP	Airstorm 54"	Panel (63"x16")	8100440100	8100280200
		(2) Wall Brackets	2020760100	2020760200
		(2) Gate Rods	2020100100	2020100200

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Stainless Steel Pit Transition

Pit transition for 24" fan mounts on pit sidewall over suggested concrete opening of 43" x 19". Reduces trash buildup in fan housing and allows use of discharge cone to increase fan delivery. Ships assembled.



#7990240500......Stainless Steel Pit Transition

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- Phenolic plastic impregnated 3/4" Finland birch plywood
- · Superior product
- · Non-warping

#84400..... 5' x 6' pit cover



Fiberglass Transition

#628062 30" x 38' x 39"

Wind Diverter

Wind diverter mounts on fan discharge to prevent strong winds from reducing CFM output. Fiberglass construction with stainless steel mounting arms. Fits most fans.



	W.
#HSWD-14	14"
#HSWD-18	18″
#HSWD-24	24"
#HSWD-36	36"

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Fan Cover

Constructed of durable, 6 oz. poly curtain material. The Fan Cover seals ventilation fans to reduce energy loss. White exterior with black exterior to limit light transmission. Secures around fan cone with adjustable shock cord and azium nut. Available in sizes 23" through 72"

#FANCVR62BWX	62" Round
#FANCVR64BWX	64" Round
#FANCVR66BWX	66" Round
#FANCVR68BWX	68" Round



Fan Cap

Manufactured from a durable, lightweight ripstop material. The Fan Cap seals ventilation fans to limit energy losses. An elastic strap holds the cap securely in place. When the fan powers up, the cap blows off to prevent damage. Stores easily in a small container when not in use.

#ISFC48	36" - 52"
#ISFC54	54" and larger



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

24" Pit Transition Fan Complete

The Airstorm 24" pit transition fan incorporates a 24" panel fan, poly transition hood, and shutter into a single compact unit. Poly shutter slides in stainless steel channels for easy removal without tools. Rough opening is 22" x 30".



#AS24PTC24	' Pit	transition	fan	com	olete
------------	-------	------------	-----	-----	-------

Replacement Parts

#HS9088C	1/3 Hp motor, 1140 rpm,
	115/208-230v
#HS900-24A	24" fiberglass prop
	(req. transtorque)
	24" fan guard
#HS903-1Transtor	que, 1/2" w/ 7/8" bushing
#101194-5 PVC	Shutter 32-1/2" x 32-1/2"

*24" panel fan performance data

	0.0	00" SP	0.	05" SP	.10)" SP	.15	5" SP
Model	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT	CFM	CFM/WATT
AS-24PTC	6500	14.7	6200	13.5	6000	12.6	5700	11.6

GrowerSELECT

Replacement Fan Motors for GrowerSELECT AirStorm and Airstream Performer Fans

- · Removable plastic motor cap protects internal capacitor and provides access to wiring terminals.
- · Water slinger protects moisture from being forced past the double bearings while fan is operating.
 • Full 56 Frame motors with 5/8" interior shaft and double sealed
- ball bearings.
- You don't have to sacrifice performance to save money!





⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Нр	RPM	Voltage	Amps	*AP OEM Part #	Fan Size
1/6	3300	115/230	1	15-0145	8" & 10"
1/4	1725	115/230	3.4/1.7	15-0109	14"
1/3	1725	115/230	3.8/1.9	15-0110	18"
1/3	1075	115/230	3.4 /1.7	15-0105	24"
1/2	850	115/230	6.2/3.3	15-0116	36"
	1/6 1/4 1/3 1/3	1/6 3300 1/4 1725 1/3 1725 1/3 1075	1/6 3300 115/230 1/4 1725 115/230 1/3 1725 115/230 1/3 1075 115/230	1/6 3300 115/230 1 1/4 1725 115/230 3.4/1.7 1/3 1725 115/230 3.8/1.9 1/3 1075 115/230 3.4/1.7	1/6 3300 115/230 1 15-0145 1/4 1725 115/230 3.4/1.7 15-0109 1/3 1725 115/230 3.8/1.9 15-0110 1/3 1075 115/230 3.4/1.7 15-0105







♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Item#	Нр	RPM	Voltage	Amps	*AP OEM Part #	Fan Size
#HS9031†	1/6	3250	120/240	1	FM1038	9"
#HS9003	1/8	1625	120/240	1.5/.75	FM1010	14"
#HS9002	1/3	1625	120/240	4.0/2.0	FM1009	18"
#HS9001A	1/3	1100	120/240	4.3/2.1	FM1008	24"
		†Single Speed • *Use of	Original Equipment Manufa	acturer part numbers is fo	r reference only.	

GrowerSELECT

GrowerSELECT

Replacement Motors for

Munters / Aerotech Fans

Single Speed Fan Motors

- TEAO motors
- · Permanently lubricated ball bearing
- Dual start/run capacitors
- 5/8" Shaft
- · Auto Overload





♠ WARNING:

Item#	RPM	Нр	Frame	Voltage	Amps	Use
#HS9005A	850	1/2	48	115/230	6.6/3.3	Direct Drive, 36"
#HS9015A	1725	1/2	56	115/208-230	5.3/2.6-2.6	Belt Drive, 36"
#HS9010C	1725	1	56	115/208-230	11.2/6.0-5.6	Belt Drive, 48"-50"
#HS9000A	1725	1	56	115/208-230	8.6/4.9/4.3	Belt Drive, 48"-50" (High S.F. 1.4 Motor**)
#HS9019C	1725	1-1/2	56	115/208-230	13.4/6.7-6.7	Belt Drive, 52"-54"
#HS9014C	1725	1-1/2	56	115/208-230	10.8/5.4	Belt Drive, 52"-54" (High S.F. 1.5 Motor**)

^{**}SF = Service Factor.



Fan Pulleys



Tensioner Idler Pulley - Chore-Time

#HB2100..... Tensioner idler pulley assembly 3" w/zerk



Tensioner Idler Pulley - Chore-Time

#FT1875 Tensioner idler assembly 5.5" Arm 3" Diameter, no zerk (Fenner Drive)



Idler Pulley - Chore-Time

#VX3014.....Idler pulley kit 3" w/dust cap



Idler Pulley - Chore-Time

#FS0604ZF......Idler pulley assembly 5.5" w/arm 3" Diameter w/zerk (Fenner Drives)



Idler Pulley - Munters/Aerotech

#AFH2406 ... Metal pulley 3" A section 3/8" B C.I. for idler pulley



Idler Pulley - Cumberland

#G91-0058Idler Pulley 3" w/dust cap



Idler Pulley - Cumberland

#FS0581ZF Idler pulley assembly 3" w/zerk (Fenner Drives)



Idler Pulley - Cumberland

#VX3004 Idler pulley 3"



Idler Pulley - Hired-Hand

#B1146......Idler Pulley 4"



Idler Pulley - Hired-Hand

#FS0605ZF..... Idler pulley assembly 4" assembly w/arm w/zerk(Fenner Drives)



Idler Pulley - Hired-Hand

#VX4004 Idler Pulley 4"



Idler Pulley

#VX3012......Idler pulley 3" SB002 Bushing 3/8" ID 1/2" Shoulder



Tensioner Assy -Windstorm and AirStorm

#HS903-3With splash guard for belt drives except Windstorm 36"




Tensioner Assy - Windstorm 36"

#HS903-81.7"



- Built of WEAR RESISTANT high modulus compression rubber.
- Embedded with LOW STRETCH polyester fiber cable cords.
- Neoprene outer ply to PREVENT SLIPPAGE.







Type A Belt				
#HSA20	1/2"	Х	22"	Standard
#HSA21				
#HSA23	1/2"	Х	25"	Standard
#HSA24	1/2"	Х	26"	Standard
#HSA26	1/2"	Х	26"	Standard
#HSA28	1/2"	Х	30"	Standard
#HSA29	. 1/2"	Х	31"	Standard
#HSA30	1/2"	Х	32"	Standard
#HSA31	1/2"	Х	33"	Standard
#HSA32	1/2"	Х	34"	Standard
#HSA33	1/2"	Х	35"	Standard
#HSA34	1/2"	Х	36"	Standard
#HSA35	.1/2"	Х	37"	Standard
#HSA36	1/2"	Х	38"	Standard
#HSA37	1/2"	X	39"	Standard
#HSA38	1/2"	Х	40"	Standard
#HSA39	. 1/2"	Х	41"	Standard
#HSA41	1/2"	X	43"	Standard
#HSA42	1/2"	X	44"	Standard

Type A Belt	
#HSA43	
#HSA44	1/2" x 46" Standard
#HSA45	1/2" x 47" Standard
#HSA46	1/2" x 48" Standard
#HSA47K	1/2" x 49" Kevlar
	1/2" x 50" Standard
#HSA49	1/2" x 51" Standard
	1/2" x 53" Standard
	1/2" x 55" Standard
	1/2" x 56" Kevlar
	1/2" x 57" Standard
	1/2" x 58" Standard
	1/2" x 60" Standard
#HSA59	1/2" x 61" Standard
#HSA61	
	1/2" x 67" Standard
	1/2" x 73" Standard
#HSA73	1/2" x 75" Standard

Type A Belt	
Type AX cogged	Belt
#HSAX31	1/2" x 33" Cogged
#HSAX38	1/2" x 40" Cogged
	1/2" x 41" Cogged
	1/2" x 45" Cogged
#HSAX46	1/2" x 48" Cogged
	1/2" x 58" Cogged
	1/2" x 61" Cogged
	1/2" x 62" Cogged
#HSAX64	1/2" x 66" Cogged
Type B Belt	
#HSB35	5/8" x 38" Standard
#HSB38	5/8" x 41" Standard



POWERTWIST® Drive V-Belts

You'll always have the right size replacement belt on hand with the POWERTWIST V-Belts. Simply remove a link and adjust the size to fit. Constructed of polyurethane elastomers reinforced with polyester fabric. POWERTWIST belts will out perform conventional rubber belts in harsh conditions.

#AFH2053	1/2" belt, ft.
#AFH2054	
#AFH2053-5	5' length
#AFH2053-25	9



Accu-Link® Adjustable Link V-Belts

Accu_Link* snap-twist-assembly, requiring no tools, means quick replacement of any existing fan belt. Accu-Link belts are constructed from strong polyester fabric with a durable urethane coating.

#52682	1/2" belt, ft.
#52682-5	
#52682-25	25' length




Timken (Fafnir) Bearing

- \bullet Model #VAK1 features a epoxy-coated, two bolt cast iron housing.
- Non-expansion bearing with a one-inch bore. 2.689" high by 5.5" wide.

A simple guide for measuring V-belts

Ordering the correct replacement belt is as easy as taking a few simple measurements.


Much of the equipment in use around today's confinement systems use some type of rubber drive belts or V-belts. For example, replacing the V-belts on fans every year is just a smart investment as worn belts can reduce performance by as much as 20%.



First, to determine what type of belt is on your fan, measure the width of the belt. Most fan belts are A-type belts with a measurement of 1/2". If the fan belt measures 5/8", it is classified as a B-type belt. You may see a belt described as type AX. The X means it has a cogged design or notches in the belt. The cogged profile increases the power transfer and is typically used only for industrial applications because of its higher cost.

Next, you need to measure the length of the belt. Use a cloth measuring tape (not a steel one) and wrap it around the outside of the belt. You also use a thin string to take this measurement and place it on a steel tape to get the correct length.

Next, for "A" Belts (1/2" width), subtract



two inches from the outside measurement to select the correct V-belt. For example, if the outer measurement is 48-inches and you subtract two inches, then HSA46 would be the right belt for your fan.

For "B" Belts (5/8" width), subtract 3" from the outside measurement to select the correct V-Belt. For example, if the outer measurement is 48-inches and you subtract three inches, HSB45 would be the right belt for your fan.

Hog Slat's line of GroBelts offers producers top-quality V-belts at a great price. GroBelts feature wear-resistant, high modulus compression rubber embedded with polyester cords to reduce stretch.



The Laser Kit is easy to use, just place the laser pointer in one of the pulley grooves and adjust the target pulley on the shaft until it lines up.



Laser Fan Pulley Alignment Kit

Two-piece kit packaged in plastic storage case. Target piece also contains a pulley groove gauge to quickly check pulley wear

#HS783.....Laser Fan Pulley Alignment Kit



Watch the demo video

Go to YouTube Search: Hog Slat – Pulley Laser

GrowerSELECT Insulated Actuated Bifold Inlets

Provides accurate control of incoming air to direct it across ceiling to reduce drafts at floor level.



#HSIN3000C-I **Airflow Performance Data (CFM)**

Opening Width	Static Pressure (In, H ₂ 0)			
(In)	0.05	0.1	0.125	0.15
1	300	450	500	550
2	650	950	1050	1150
3	950	1350	1550	1700
5	1400	1950	2200	2400
6	1750	2450	2750	3050
8	1950	2750	3100	3400
Fully Open	2250	3250	3600	3950

* Computer generated data

Rough opening: 25" x 27-1/2"



HSIN4900C-I **Airflow Performance Data (CFM)**

111111111111111111111111111111111111111				
Opening Width	Static Pressure (In, H ₂ 0)			
(In)	0.05	0.1	0.15	0.2
1	600	850	1050	1250
2	1150	1650	2050	2400
5	2350	3350	4000	4300
6	2850	4050	5000	5750
8	3200	4500	5500	6350
Fully Open	3750	5350	6550	7600

* Computer generated data

Rough opening: 24-1/2" x 46-1/2"



Side Entry Cleat

Allows for fast and easy adjustment of the rope. Cleat retains the rope securely when adjustment is not necessary.



Latch Mount and Cable Guide



Side mounted latch does not get blocked while opening by ceiling obstructions. Latch shuts the inlet tightly and securely. Combination piece also serves as a guide for the rope that helps open/ close the inlet.



Exterior Seal

Matching tongue and groove on door and frame eliminates gaps when inlets closes.



GrowerSELECT Insulated Curved Door Sidewall Inlet



HSIN3050SW 3050 13" x 44"

- · Curved inlet door directs air to the ceiling for effective mixing.
- · Foam insulated inlet door reduces condensation.
- Seals tightly to minimize heat loss and air infiltration
- Corrosion resistance plastic construction

Airflow Performance Data (CFM)

Opening Width	Static	Pressure (I	n, H ₂ 0)
(In)	0.05	0.1	0.15
1.5	200	400	550
3	550	850	1100
6	1200	1700	2000
11*	2150	3050	3700

* Computer generated data



Single Sidewall Inlet

- 5-1/2" x 22-1/2"
- 430 cfm
- · Self-adjusting inlet

......Single Sidwall Inlet





- · Ideal for use with pre-heated hallways
- Rough opening 13-1/2" x 46-1/2"

#62990..... Gravity Wall Inlet

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Replacement Parts

8" x 44"

.....Replacement weightReplacement bracket

♠ WARNING:







13. 7/8" Nylon Pulley · with zinc swivel housing



• 96 per pound #80543.....

14. J-Nail







#HSH0671200 LBS. HB-12M **#HSH074**......4" x 4" x 5" long, painted

Adjust-A-Baffle

- 1" polystyrene with fiberglass coating
- · Flexible PVC hinge
- Available in 8". 12". 16". 18". 20" and 24" widths
- 8' sections



How to order your Adjust-A-Baffle:

now to order your Adjust-A-Baine.	
1. Order Baffle and Hinge separately (must order in 65' lengths):	
#GAP-18961" x x	8" x 96"
#GAP-11296	2" x 96"
#GAP-11696	6" x 96"
2. Order Baffle and Hinge separately (must order in 65' lengths)	
#GAP-WS65 Baffle weather-str	rip - 65'
#GAP-HS65 Hinge for baffle syste	em - 65'
3. Order S.S. Rod & Clamp package (must order in 100' lengths)	
#GRCP-SW-B	package
(INCLUDES: 105'-1/8" SS rod; 33-Azium Nuts; 60-3/16" x 1" lag eyebolts; 33-30" polyester lift	
33-Nylon fender washers; 40-1/8" Cable Clamps)	
4. Order S.S. Cable to connect rod to winch & closure spring	
#61739	el cable
#617321	
5. Order Winch & Hardware	o oranip
#DL61737	keener
#61740L-bracket fo	-
#60516	
#60682	
#60670	
6. Order Corner Pulleys (one for Winch, one for Spring Return End)	oquirouj
#HSH001	a nullev
#61744	
#60649	
#60681	
7. Order Baffle Return Spring (takes place of counter weight)	iock iiut
#HS17110Baffle return	n anrina
#nsimio	n spring

Actuated **Plastic** Ceiling Inlet



Pre-mounted actuation pulleys for simple and consistent installation. Single rod actuation. Durable corrugated plastic insulation stop. End panels designed to prevent air discharge from the ends of the inlet. A unique aerodynamic discharge orifice provides improved efficiency and air speed while routing condensation away from the air stream to prevent freeze up. Improved performance at a horizontal airflow to prevent drafting of pigs.

Item#	Air @ .10 SP	Framed Opening
#GACI-4000P2	4000 CFM	19" W x 46.5" L
#GACI-2500P2	2500 CFM	19" W x 27" L



Jet Ventilation Ag Roof Vent

Revolutionary, patented design, maximized Jet technology. Four directional louvers direct air along the ceiling and hold air up longer while mixing with room air and distributing it evenly. Features patented inlet design. Creates less draft and chilling and is engineered to allow more CFM through inlet than a C2000. TopJet inlets operate at higher static pressure for better air mixing. The snap-together design allows for minimal worksite waste. Rated at 1,812 cfm at .125 sp. Patent No. 6,475,078

Call for special pricing for large quantities and installation quotes! #DL90640.....Jet Ventilation Ag Roof Vent



Ceiling Air Inlet

- · Laminated baffle to prevent damage during cleaning
- · Plastic housing with stainless steel insert
- · Adjustable locking lever allows the unit to be shut off or restricted

#GCAI-1000CW...... 1125 CFM w/ 17" x 17" R.O. #GCAI-2700CW3128 CFM w/ 25" x 25" R.O.



Munters Attic Inlet

- Aerodynamic frame and door design for precise control
- · Unique constant force springs provide easy adjustment of static pressure
- Doors close tightly to prevent attic condensation
- · Stainless steel door hinges for high durability
- Integrated door latches are standard Easy installation
- · Models for mechanical or static pressure control of
- · Fully recyclable materials · Lower fuel cost
- · Drier room environment · Improved air quality

#ABI28SP-01	Static pressure activated
#ABI28SPM-01	Mechanically actuated



Double L 360° Insulated Attic Inlets

360° Airflow Attic Inlets direct tempered air evenly along the ceiling in all directions, resulting in uniform temperatures throughout room. Removable bottom lid for easy cleaning and installation.

#GC1140 Gravity Flow: 2,048 cfm @ 0.15 static pressure. New Rough Opening - 23.75" x 23.75". Patent Pending. #AC3010 Actuated: 2,518 cfm @ 0.15 static pressure.

New Rough Opening - 23.75" x 23.75". Patent Pending. #GC1140 ... Gravity Flow 4 Way Insulated Attic Inlet #AC3010 Actuated 4 Way Insulated Attic Inlet





inlet is made of UV stabilized polystyrene. The quad inlet is assembled from four single directional inlets, PVC mounting frame, 18-inch attic sleeve, and one-inch polystyrene insulation board. Single directional inlets are manually adjusted to direct air along the ceiling, towards the floor or closed. During minimum ventilation the quad inlet will deliver 500 crm at 0.05 in of water. Overall Size: 31" x 31" 9" Packaging: Unassembled. Rough Opening: 27 7/8" x 27 7/8"


#HSI2000	4-way Inlet
#HSI200	Single Sidewall Inlet
#HSI204	Housing
#HSI202	Insulation Stop
#HSI203	Insulation Board
#HSI205	Blade Top
#HSI206	Blade Bottom
#HSI207	Pin Pivot for Top Blade
#HSI208	Pin Pivot for Bottom Blade
#6088611	Screw 1" Self Tapping





Hinge System

Innovative offset hinge seals tight but allows door to move away from the wall as it opens to prevent dust and debris accumulation in the bottom of the panel.






Exclusively from Hog Slat!


1" or 1-1/2" Panel

Available in 1" (R-7) or 1-1/2" (R-9) panel with aluminum skin and structural supports.



C-Lock Panel


Integrated C-Lock panel connection eliminates the need for additional tools or fasteners.




Doors



WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov









Choice of Attachments

Choose from tension loaded brackets or low profile plastic nut connectors.

NUMEROUS SIZES AVAILABLE!



See It In Action!

Scan for YouTube: **Tego Tunnel Door**

Replacement Parts for Tunnel Doors



Eagan Rail



Tego Hinge

#TD4969 Door jinge



Reeves Hinge

#TDHINGE.....New style



Tego Flat Seal

#TD850.....per ft.



Tego P-Seal

#TD1125......350/ box



Reeves Flat Seal

TDSEALper ft.



Eagan Bracket

#EVTHDBRKT.....Double



Eagan Bracket

#EVTHBRKTSingle



Tego Bracket - Old Style

#8010440700.....Lift bracket



Reeves Split Bolt

#TDBOLT Each



Tego Carriage Bolt -Old Style

#6080825-16"x1-1/2"




Tego Split Bolt

#TD800	Each
#TD800-10PK	Pkg of 10

1" Cattle Float

The unique patented design of the Hudson Cattle float uses fluid pressure, as opposed to a lever arm and ball, as the force to close the valve. This compact, self-contained design greatly enhances the valve's reliability. The valve body is made of durable glass-filled nylon.

When properly installed, the valve will meet anti-siphon requirements. 300 gph at 30 psi. Bracket sold separately.







Tranz Former Valve

Converts float valves to a high flow Diaphragm style valve. Increased flow rate fills tanks faster during periods of peak demand. Fits most clamp-on floats and installs quickly without drilling. Contains an internal filter and

comes with a manufacture 2 year warranty. Boost flow

rates over 4 times that of using the Trough O Matic alone





See It In Action! YouTube: Tranzformer by **Jobe Valves**

Cool Cell

Clean-Out Brush

the entire length of the system.

#J-TFV fits #610802, Trough-O-Matic

Repair Kit for Cattle Float

Kit complete with Cone Screen, Retainer Ring, Diaphragm and Float.







Brush attachment for cleaning water distribution pipes. Manufactured with a female slip

coupling that glues directly to 3/4" PVC pipe creating a long handle capable of reaching

PVC Union

#603841 1-1/2" PVC Union



In-line Check Valve

#527458......1-1/2" for Cool Cell



Strainers & Screens

#11271-VI	1-1/2" In-Line Strainer
#10866-VI	20 Mesh Screen for In-Line Strainer

Topaz Float Valve by Jobe

• for Megacool and other cool cell systems





#JOMFV1D	MegaFlow High Flow 1" Inlet 80 GPM @ 65 PSI
#JOMFV20DLT	MegaFlow High Flow 3/4" inlet 65 GPM @ 65 PSI
#JORJV20HF	Rojo Low Flow 3/4" Inlet 6.8 GPM @ 75 PSI
#JOTPV1D	Topaz High Flow 1" Inlet 80 GPM @ 75 PSI
#JOTPV20DLT	Topaz High Flow 3/4" Inlet 55 GPM @ 75 PSI
••••••	









#KPF06

#KPF444-RK

#KPT75SS	Valve only 3/4" inlet/Outlet
#KPF06	
#HSES-RA11	SS eye bolt assy
#KPF444-BK	

Trough-O-Matic **Float Valve**

Flow rate: 245 gallons/hour Dimensions: 3" W x 7.5" L x 3.5" High Operating pressure: 20-50 PSI



Kerick **Float Valve Tank Mount**

• PT75LS 3/4" In/Out



#HS826 Valve Float Tank Mount



• 1/2 Hp • 220 Volt



...... 110V Effluent Pump

Repair Parts



Manufactured of quality cellulose paper, oven-cured with acrylic polymer glue and fungicides.

Cool Cell Cleaners See Page 324

#H2-64E	H2Pad 6" x 12" x 48" Pro Tec Edge 15/45 Flute
#H2-65E	
#H2-66E	




Production of H2PAD

begins by selecting heavyweight Saturation Grade Kraft Paper designed for high water absorption rates. This specialty Kraft is also formulated for consistent resin pick-up; a crucial step to ensure proper resin impregnation during manufacturing.



A proprietary resin

contains critical formulation of acrylic polymer glues, melamine additive for fire resistance, and fungicide additive. A special viscosity additive ensures even application on each sheet.



Triple Curing Process

The first oven bakes the resin coating on the paper. The second oven cures each sheet individually after corrugating and before pressing to ensure consistent glue contact points. A third oven cures each media block for three hours before cutting and sanding.



Constant Monitoring

Throughout the manufacturing process, technicians constantly monitor the moisture content of the paper. Consistent moisture content is critical to proper adhesion of glues and the curing process.






3/4" ProTec Edging

increases pad life by protecting against UV light and mechanical damage when cleaning. Helps to prevent the buildup of algae and minerals on the air entry side of the H2PAD. Special wetting additive promotes even water distribution by reducing the amount water collecting on the pad surface.

PAD RETAINER CLIP

Stainless steel wire retainers used to hold cool cell pads in place. Pad retainers add additional rigidity to the center of pads to help maintain straightness over time. Retainer Clips should be used to stabilize pads that are more than five feet high and and when pads are stacked.

#HS756.....Cool Cell Retainer Clip









Splice Coupler

#HSES-03.....for Trough HSI Evap Systems

8" Rubber Cap

#HSES-RA14......8" Cap Rubber Round Style Trough



10" PVC Cap

#5274670 10" Cap PVC Round Cool Cell System




Rubber Cap with Clamp

#5274611 8.16" Cap Rubber For Reeves Cool Cell



Rubber Cap

#AEC1094..... 8" Rubber Cap for Munters Cool Cell



Trough, Square



Trough, Round

#HSES - RA9......8" x 10'6' includes bell end



Trough Cement

#HSES-34.....Trough Cement, 10.3 oz tube



Trough Support Bracket

#HSES-27 for HSI Evap Systems



Trough Support Bracket Cover

#HSES-52......16ga 304 Stainless Steel



Round Trough Support Bracket

#HSES-RA5Round Style 8"

Little GIANT

Submersible Pumps

Little GIANT offers a full line of submersible pumps for all evaporative cooling systems. These pumps are engineered to provide the highest efficiency and dependability for extended and continuous use.

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



• 4/10 Hp shaded pole motor

• 70 GPM @ 5' head · Cord Length: 20'

• 115 V; Amps: 13; Watts: 1000

• (H) 9.3 x (W) 9" x (L) 11.7"

• Switch: Automatic

#9EN-CIA-RF230 V (9EH-CIA-RFS)



• Model#: 10-CIA

• 1/2 Hp split phase motor

• 83 GPM @ 5' head · Cord Length: 10'

• 115 V; Amps: 11; Watts: 1100

• (H) 10.3" x (W) 9.4" x (L) 9.3"

• Switch: Automatic

#61088...... 115 V automatic (10-CIA)



• Model#: 6-CIA

• 1/3 Hp split phase motor

• 46 GPM @ 5' head

· Cord Length: 8'

• 115 V; Amps: 9; Watts: 720

• (H) 6" x (W) 8.5" x (L) 9.5"

· Switch: Automatic

#506158115 V automatic (6-CIA)



• 115 V; Amps: 9; Watts: 720

• (H) 7.25" x (W) 7.25" x (L) 9.5"

· Switch: Manual

#506271115 V manual (6-CIM-R)



• Model#: 6EC-CIA-SFS

• 1/3 hp motor

• 53 GPM @ 5' head

· Cord Length: 10'

• 115 V; Amps: 14.5; Watts: 600

• (H) 11.28" x (W) 8.48" x (L) 10.66"

· Switch: Automatic Snap Action Float Switch

#506807 115 V automatic (8-CIA)



• Model#: 8-CIM

• 4/10 Hp shaded pole motor • 54 GPM @ 5' head

· Cord Length: 25'

• 115 V: Amps: 10: Watts: 830

• (H) 6" x (W) 8.5" x (L) 9.5"

• Switch: Manual

#508058 115 V manual (8-CIM)




• 115V; Amps: 7.5; Watts: 800

• (H) 11.0" x (W) 8.9" x (L) 8.4"

· Switch: Manual

• 1-1/2" Discharge port #509805115 V manual (9EC-CIM)





#610891for 506158 pump



- steel body • 1.5" NPT
- 110 GPM
- 1/2 Hp
- #1DW51C0EA.....115V #1DW51C1EA.....230V #9L122..... Capacitor for 1DW51C0EA #9L113 Capacitor for 1DW51C1EA



#I.SP0311	1/3 Hp, 115V
#LSP0712F	3/4 Hp, 230V
	Capacitor for LSP0711F





Liberty Submersible Pump

- Model #257
- 1/3 Hp motor
- 45 GPM @ 5' head
- · Cord length: 10'
- 120 V, 5.2 amps running, 8 amp start
- · Auto vertical float switch · Cast body w/ Epoxy powder coat finish

#61257......120V, Auto





Sump or Jet Pump

Your choice of Jet Pump or Submersible Pump with Sump Tank.



Improved Drainage

Increased open area of trough cover quickly drains water away from pad bottoms to extend pad life.









Less Pad Streaking

Increased water flow directed to pad front. Open top design for quick visual inspection. Aluminum pad retainers held with user-friendly Tri-Knob fasteners.



Heavy H2Pad

Coated with ProTec to protect against UV and mechanical damage.





Greater Trough Capacity

Square trough increases water reservoir by over 24% over the round trough.



Extension Kit for Round Pipe Cool Cell Systems

10' Add-on Kit for Round Style 8" Trough Evaporative Cooling System

Includes trough, cover cover, sprayer, deflector, pad retainer and 8" trough. Does not include pad or end panel.

#HSES-RA10.....Extension Kit

Stronger Brackets

4" Wide Brackets prevent damage

to trough and double leg supports

eliminate twisting and sagging.

Submersible **Cool Cell Pump**

Pumps typically used for cool cell systems are adapted from other industries; waste water, sump pumps, etc. They are designed with a higher head pressure and low volume to lift water as high as 35'.

We went to one of America's leading pump manufacturers with a request to build a pump specifically designed for cool cell systems. This pump features a re-designed VORTEX IMPELLER resulting in a unit with a LOWER HEAD PRESSURE with HIGHER VOLUME. This combination allows our pump to service a longer cool



Get 3/4 Hp Performance from a 1/2 Hp Pump!

The special impeller allows the use of a 1/2 Hp motor instead of a 3/4 Hp motor. Electrical usage is decreased by up to 25%.

Rugged Features for a Long Lasting Pump:

- · Oil-filled motor
- · Epoxy coated, cast iron housing
- 2" discharge with 1-1/2" bushing to 115 / 230 Volt- 5.5/2/7 amps adapt to most systems
- 2" bottom suction inlet
- 9' waterproof power cord
- Silicon carbide seal
- 15.87" high x 9.5" wide

#H2P-230S......1/2 Hp submersible pump, 230 V

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Jet Pump Motor

US Motors® 3/4 HP replacement motor for Hog Slat and Hired Hand Mega Cool nonsubmersible jet pumps. Motor is encased in drip-proof enclosure. 48Y frame. 1 year warranty.

Part#	Voltage	Amps	Hired-Hands
#HS9029	208-230	4.1-3.7	1062-5032
#HS9079	115/110	7.2/10.3	



Leaf Trap

6" diameter leaf trap for Jet Pump.

- 1-1/2" inlet
- 2" outlet

#H2P-002.....Leaf Trap



Jet Pump

The Compact Jet Pump delivers outstanding performance. Efficient design minimizes friction and turbulence reducing power consumption.

Self-priming pump design protects internal components from wear.

Strainer basket features a Transparent Lid for easy inspection. Larger capacity extends time between clean out. Easy access drain plug for service and winterizing.

Features Include:

- · Available as 115 or 230 volt models
- Includes 9 foot power cord
- 1-1/2" discharge pipe
- · Open drip proof motor

#H2P-120JA	3/4 Hp Jet Pump, 120 V
#H2P-240J	3/4 Hp Jet Pump, 240 V

🚹 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Wet End Pump

Hi Flo 3/4 HP wet end pump for evaporative jet pump

#H2P-001 Wet End for Jet Pump



PVC Union

PVC pump union fitting with o-ring and gasket. Slip.

#H2P-003	1-1/2" - Jet Pump
#H2P-004	2" - Submersible Pump






HERCULITE®

Herculite sets the standard for high performance livestock curtains. Manufactured from flexible PVC composite fabric with polyester scrims for high tear strength. Herculite curtains are shrink and mildew resistant with excellent UV.

Item#	Net Size	Weight (oz.)	Color	Hems
61673BVA	66"	13	Frosty Clear	1
CVT136	68"	13	Frosty Clear	1
CVT137	80"	13	Frosty Clear	1
61673AVA	66"	9.5	Frosty Clear	1
61674	68"	9.5	White	1
61884-4	80"	13	Frosty Clear	1-1 pocket




Polylite®

Choose from Polylite* Super with 10x10 weave or the costing saving Poly Econo with a 9x9 weave. Also available in light blocking Black/White Premium option.




Item#	Net Size	Weight (oz.)	Color	Hems
Polylite® Super	_			
61686-14	18"	4.2	Clear	1
61686-33	21"	4.2	Clear	1
61685	57"	4.2	Clear	1
61686	69"	4.2	Clear	1
61687	81"	4.2	Clear	1
61692	66"	4.2	Clear	2
61693	78"	4.2	Clear	2
61686-37	73"	4.2	Clear	1-2 pockets
• Polylite® Econco				_
61686EC	69"	4.3	Clear	1
61687EC	81"	4.3	Clear	1
Black/ White Premium				
BWP201	18"	6	B/W	1
616853	57"	6	B/W	1
616865	69"	6	B/W	1
BWP701	81"	6	B/W	1
Specialty Curtains				
616763	84"	9.5	White - Vinyl	1 - 7 pockets
61673B3	94"	13	Clear Frosty Vinyl	1-2 pockets
1 1				-



FabTex®

The Super Clear coating allows the most light transmission of any high weight curtain in the market. Durable PVC material remains flexible even during cold temperatures.


Item#	Net Size	Weight (oz.)	Color	Hems
FABTEX160X60	57"	17	Super Clear	1
FABTEX160-6	60"	17	Super Clear	1
FABTEX160X72	69"	17	Super Clear	1
FABTEX160-7	60"	17	Super Clear	1-2 pockets
FABTEX160-9	91"	17	Super Clear	1-2 pockets



Agri-Barrier[™] Vinyl Curtain

PVC laminated curtain manufactured with mildew and UV blocking additives. Crystal Clear color for maximum light admission.

Item#	Net Size	Weight (oz.)	Color	Hems
CEL1668SHTS	69"	16	Crystal Clear	1
CEL1684W3P	84"	16	Crystal Clear	1-2 pockets



Agri-Tex™ Ag Curtains

- Maximum UV stabilization
- Fabricated with Lock-Stitch sewn hems
- Superior tensile straight
- Weldable composition
- · Easily collapsible

Item#	Net Size	Weight (oz.)	Color	Hems
616468	68"	14 oz.	Ultra Clear	1
6160968	68"	9	Milky Clear	1
61614T	84"	14 oz.	Ultra Clear	1-3 pockets



Insulated Curtain

6-ply insulated curtain with a compressed R-4 rating. Sewn every 4" to prevent insulation sag and to allow the curtain to fold more evenly when opening.



Item#	Net Size	Weight (oz.)	Color	Hems
CI7L2	24"	NA	Gray/ White	1
CI7L3	36″	NA	Gray/White	1
CI7L5	60"	NA	Gray/White	1
R62X66	66"	NA	Gray/White	1
CI7L6	72"	NA	Gray/White	1
CI7L7	84"	NA	Gray/White	1



Brooder Curtains

Curtain & TriPly

Vinyl Glue

weather extremes

vinyl coated and vinyl laminated fabrics · Highly resistant to temperature and

· Excellent for Patching and Sealing

Manufactured from 10x10 Super-Poly

Custom sizes available!



#61571	
#61570	White curtain tape - 150' Roll
#61571BW	Polylite black & white 3" x 60' roll
#844192	White tri ply repair tape (ceiling)
#844193	Black tri ply repair tape (ceiling)
#61571B	

• Super-Strong, waterproof, flexible bonds to



Insulated Tunnel Curtain with Center Pocket Hem

- Black/ White
- Single Hem/ Center Pocket
- 3- Layer- 2 layers of curtain / 1 layer 3/16" bubble insulation. R value of 3
- 4-Layer 2 layers of curtain / 2 layers 3/16" bubble insulation. R value of 5

1 24/01 2 14/010 01 041 (4111 / 2 14/010 0/10	Dubbio ilibulationi il falao oi o
#INBWBUB501-V1	56 - 3-layer
#INBWBUB601-V1	72 - 3-layer
#INBWBUB701-V1	84 - 3-layer
#INBWBUBD601-V1	72 - 4-layer
#INBWBUBD701-V1	84 - 4-layer






Gorilla Tape

Long lasting alternative to curtain tape.

#105629	Black 30 yd. roll
	White, 1.88" x 30 yd. roll
	Clear, 1.88" x 27' roll
#106425	Tough & Wide 3" x 25 yd. Roll Black
#6010902	





Professional grade premium quality formulation for temperature resistant permanent bonds.

- · Dries clear without yellowing
- · Sets in 10 minutes, fully cured in 24 hours.
- · Moisture and UV resistant.



Bondseal Spray Adhesive

Multi-purpose glue with adjustable spray pattern.

#844195 Multi Purpose, 16 Oz



3M Scott Weld **Spray Adhesive**

Clear Hi-Strength adhesive with great bonding performance to multiple materials.

- 10-minute cure time
- Clear
- · 180 psi shear strength




#6785091..... #90 High Strength, 24oz



Poultry Wire

- PVC galvanized 20 gauge wire with 1-inch hex opening
- · Stainless Steel option

The state of the s	00
#805689-1PW Wire Poultry PVC Coated 1' X 150' 3/4" Hex 20 Gaug	је
#80569-1PW Wire Poultry PVC Coated 2' X 150' 3/4" Hex 20 Gaug	је
# 80570-1PW Wire Poultry PVC Coated 3' X 150' 3/4" Hex 20 Gaug	је
#80571-1PW Wire Poultry PVC Coated 4' X 150' 3/4" Hex 20 Gaug	је
#80580-1PW Wire Poultry PVC Coated 5' X 150' 3/4" Hex 20 Gaug	је
#80580PW	је
#80581-1PW Wire Poultry PVC Coated 6' X 150' 3/4" Hex 20 Gaug	је
#80581PW	је
#80582Wire Poultry PVC Coated 7-1/2' X 100' 1" He	ex
#80585PW	је
#80580-1SSWire Poultry Stainless Steel 5' X 150' 3/4 Hex 20g	ја
#80581-188Wire Poultry Stainless Steel 6' X 150' 3/4 Hex 200	ја



Counter Weights

A) #NC61752	25 lb. concrete
B) #NC61751A	4-1/4" diameter, 12 lbs, PVC
C) #HS917-4162	" solid metal, 17" long, 15 lbs

Curtain Brackets

- Fits 66" curtain
- · Space every 4'
- Constructed of 1/4" x 1" powder-coated metal

#8010790100	5' 8" curtain bracket painted
#8010690100	7' 3-1/2" curtain bracket end wall
#8010450100	4'6" curtain bracket w/ 5" angle. Painted


WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Plastic Bird Netting

• 330'/roll

,	
#TNX60020409	
#TNX60032409	6.5' x 330' Mesh Size .51" x .59" CintoFlex H
#TNX60033409	
#TNX60045409	
#TNX60050409	
	_



Bracket for Curtain

• Extended

#8050680100Backet for Curtain



· Galvanized double dipped

#805421	1-1/2" long, galv, square 64/ lb
#855ARZ	1" long, galv round head 74/ lb
	1-1/4" long, plastic cap 286/lb
#SWSSCN150	1-1/2" metal cap
#SWSSCN250	2-1/2" metal can

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Fence Staples

#84548G	2" Fence Staple
#80549	3/4" Bird Wire Staples

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Batten Strips

Use to fasten bottom of curtain to building, does not crack or rot like wood.

#84588......8' x 1-3/4" aluminum batten strip



Black Poly Strapping

• 1-3/4" wide x 300' roll


#61572.... Black poly strapping, 1-3/4" x 300' roll



Retainer Strap

• 2" wide X 300' roll

#TS102925 Retainer strap for curtain



- · Low stretch.
- · UV resistant.
- · Abrasion resistant.

#61724	1/8" x 1000'
#61724-500	
#61725	
#61725-500	



Black Poly Rope

618061/4	" black poly rope - 1000"
HB10243/16	" black poly rope - 1000"

Crank Handle · Hand crank, shephard hook, zinc #HS70501 #HS70502......51 #H\$70503......87

Adjustable Hand/ Drill Handle

• Adjustable from 5-8', painted

#G07099550 Adjustable Handle

Drill Crank, Painted

· Drill powered, shepherd hook, zinc

#HS70504	3′
#HS70505	5′
#11970506	0'

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Single Drum Ceiling Winch

- 3000 lb. capacity
- 45:1 gear ratio
- 3-3/4" diameter hub
- · Cast construction, red finish

#AMT24030Single Drum Ceiling Winch



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Winch Mounting Brackets

1) #617403" x 3" x 7" long, painted 2) #HSH074......4" x 4" x 5" long, painted

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


Split Reel Ceiling Winch

- · 2000 lb. capacity
- · Self-braking
- 4.1:1 worm gear ratio
- 1-3/4" diameter reel
- · Cable Capacity: 134' (67' per side) of 1/8"
- · Black epoxy finish

#HSW01Split Reel Ceiling Winch

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- · 2000 lb. capacity
- Self-braking
- 4.1:1 worm gear ratio
- 1-3/4" diameter reel
- · Cable capacity: 140' of 1/8"
- · Black epoxy finish

#HSW02Single Reel Ceiling Winch

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Automatic brake holds handle in position when released to prevent injuries from free spooling handle.

- Drum Diameter: 2.5"
- Gear Ratio: 5.4:1
- · Cable Capacity (1/4"): 60 feet
- · Strap Capacity: 31 feet
- · Zinc plated finish

#DL5351-24Z......1200 lb **#DL5352-24Z**......1500 lb

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Hand Winch

- · 1200 lb. capacity
- Drum Hub Diameter: 1.3" · Gear Ratio: 3.87:1
- · Handle Length: 6.7"
- · Cable capacity: (3/16): 65 feet
- · Black Epoxy Finish

#HSH067 Hand Winch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hand Winch

- · 1400 lb. capacity
- Drum Hub Diameter: 7/8"
- Gear Ratio: 4.4:1
- Handle Length: 9.5"
- Cable Capacity: (1/4"): 40 feet
- Strap Capacity: 31 feet

#DL61737 Hand Winch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- · 3500 lb. capacity
- Drum Hub Diameter: 1-5/16"
- · 2-speed · Gear Ratio: 12:1 (High) 6:1 (Low)
- * Auto brake/Reversible racket
- · Handle Length: 9.5"

Up to 3X faster than manual winches!

- · Cable Capacity (3/8"): 37 feet
- Zinc finish

#DL3500 Auto Brake Hand Winch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Speed Crank

The Speed Crank increases the speed of operating manual winches while eliminating the work and strain. The overall length is eight-inches with a 1/2" shaft. Center opening fits over a one-inch nut handle.

#HS802




WARNING:



Fits 1/2" drill



Fits over base of the winch handle



Rod Winching Systems

Electric Ceiling Winch with control

- 5000 lb. capacity
- Prewired 3/4 hp, 120V motor
- 2 ft/ min lift speed
- 2" diameter spilt reel
- 9' power cord
- 9' controller cord

#24051 Electric Ceiling Winch with control





1) Manual WindLift Winch

- 5000 lb. capacity
- 90:1 ratio
- · 2" diameter spilt reel
- · Cable capacity: 64' of 3/16" cable
- · Pre-drilled and tapped to accept strap kit
- · Black epoxy finish

#HSW03Manual WindLift Winch

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Heavy Duty Drills - 1/2"

#27727	Milwaukee D-Handle
#598691	DeWalt Jumbo, Spade Handle
#6710339	Milwaukee Hole Hawg, Right Angle



2) Strap Kit with Bolt

#HSH055	5000 lb. (pair
#HSH050	Strap Bolt only for HSH055
#HSH056	2000 lb. (pair
#HSH051	Strap Bolt only for HSH056
#AMT251403	3' x 1/4" Sling rope w/thimbles

⚠WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HSH053	Dead-end clevis for 1/8"	rod
#HSH054	Dead-end clevis for 3/16"	rod
#AMT17073	Auto locking clevis for 1/8"	rod
#AMT17072	Auto locking clevis for 3/16"	rod

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#AMT170743/16"

4) Galvanized Cable Clamps



▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



5) Suspension Rod

#HSH17060-0390	1/8" x 390' Roll
#HSH17060-0490	1/8" x 490' Roll
#HSH17060-590	1/8" x 590' Roll
#HSH17061-0390	3/16" x 390' Roll
#HSH17061-0490	3/16" x 490' Roll
#HSH17061-0590	3/16" x 590' Roll

6) Premium **Diamond Braid** Cord w/ Wax

#61724D	1/8" x 1000'
#61724D-500	
#61725D	3/16" X 1000'
#61725D-500	3/16" X 500'





7) Rope Adjuster

HSCA-1	Feed Line Drop Cord Adjuster	
HSCA-3	Heavy Duty Cord Adjuster	•

7/8" Galvanized Swivel Pulley

• Rated Capacity: 132

· Bracket Material: 18 ga G90 Galv.

· Sheave Material: White nylon



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1-7/8" Galvanized **Swivel Pulley**

Rated Capacity: 220

· Bracket Material: 12ga, G90 Galv.

· Sheave Material: Red Nylon

#HSH004 1-7/8" Galv. Swivel Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1-1/2" Galvanized Split Pulley

• Rated Capacity: 2000

• Bracket Material: 12 ga G90 Galv.

· Sheave Material: Galv. Steel

#HSH0081-1/2" Galv, Split Pulley

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

2-1/2" Corner Pulley

• Rated Capacity: 1120

• Bracket Material: 11 ga G90 Galv.

· Sheave Material: Red Fiberglass

#HSH0252-1/2" Corner Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

2-1/2" Thru-Wall Pulley

• Rated Capacity: 880 · Bracket Material:

11 ga G90 Galv.

· Sheave Material: Steel

#61749.....2-1/2" Thru-Wall Pulley

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

3-1/2" Double **Back Pulley**

• Rated Capacity: 4,000

· Bracket Material: 12ga, G90 Galv.

· Sheave Material: Red Cast Iron

#HSH0713-1/2" Double Back Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

7/8" Stainless Steel **Swivel Pulley**

• Rated Capacity: 132

· Bracket Material: 18 ga Stainless Steel

1-3/8" Stainless

Steel Split Pulley

· Sheave Material: Red nylon

#HSH0037/8" S.S. Swivel Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

• Rated Capacity: 660

· Bracket Material: 12 ga G90 Galv.

• Sheave Material: White nylon

#HSH010 1-3/8" SS Split Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1-3/4" Galvanized **Split Pulley**

• Rated Capacity: 660

· Bracket Material: 12 ga G90 Galv.

· Sheave Material: Red reinforced nylon

#HSH005 1-3/4" Galv. Split Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

3-1/2" Corner Pulley

• Rated Capacity: 3,000

· Bracket Material: 11 ga G90 Galv.

· Sheave Material: Cast iron

· Bearings: Sealed bearings

#HSH001.....3-1/2" Corner Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

3-1/2" Thru-Wall Pulley

• Rated Capacity: 3000

· Bracket Material: 8 ga G90 Galv

· Sheave Material: Cast iron

· Bearings: Sealed Bearings

#HSH009 3-1/2" Thru-Wall Pulley

↑ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

3-1/2" Horizontal Pulley

• Rated Capacity: 2,000

· Bracket Material: 11 ga G90 Galv. · Sheave Material: Red Fiberglass

#HSH0423-1/2" Horizontal Pulley

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1-7/8" Galvanized **Swivel Pulley**

• Rated Capacity: 660

· Bracket Material: 12 ga G90 Galv. · Sheave Material: White nylon

#HSH037.....1-7/8" Galv. Swivel Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1-1/2" Stainless Steel Split Pulley

• Rated Capacity: 220

· Bracket Material: Stainless Steel

· Sheave Material: Stainless Steel

#521531..... 1-1/2" SS Split Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1-7/8" Galvanized Split Pulley

• Rated Capacity: 660

• Bracket Material: 12 ga G90 Galv.

· Sheave Material: White nylon

#HSH0381-7/8" Galv. Split Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

3-1/2" Corner Pulley

• Rated Capacity: 2,000

· Bracket Material: 11 ga G90 Galv.

· Sheave Material: Red Nylon

#HSH007.....3-1/2" Corner Pulley

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

7/8" Galvanized **Swivel Pulley**

· Rated Capacity: 2200

· Bracket Material: 11 ga G90 Galv.

· Sheave Material: Cast iron

Bearings: Needle

#HSH0404-1/2" Corner Pulley

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

3-1/2" Enclosed Single Block Pulley

Rated Capacity: 2,000

· Bracket Material: 11 ga G90 Galv.

· Sheave Material: Red Fiberglass

#HSH039 3-1/2" Enclosed Single Block Pulley


▲ WARNING:











Chain & Sprocket Corner Kit

• Rated Capacity: 2200

· Bracket Material: 11 ga G90 Galv. · Sheave Material: Black Steel Spocket

· Bearings: Needle

#HSH006 Chain Sprocket Corner Kit #52155-1*.....Bracket only #HB3003Sprocket pulley only

*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Horizontal Bracket with Chain Sprocket

• Rated Capacity: 2000

· Bracket Material: 11 ga G90 Gal

· Sheave Material: Plated steel · Bearings: Sealed Bearings

#HSH043 Horizontal Chain Sprocket



*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bracket With Dual Pulleys

This bracket has two pulleys. One pulley can be used to guide the main cable or rod and the other pulley can be used to guide the opening and closing of the vent doors. The bracket should be secured to the wall with two wood screws (not provided).

• Rated Capacity: 132

• Bracket Material: 11 ga G90 Galv. · Sheave Material: Red Nylon

#HSH041 Bracket with Dual Pulleys

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Corner Bracket

- 3/16" thick painted steel brackets
- 15" long x 4-1/2" tall legs
- · Shown with HSH001 corner pulley (not included)

#617431	Large Corner Bracket
	U-bolt
#60692	Lock nut

▲WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Cup Hook Driver

Driver holds cuphooks in place allowing for single-handed placement. After insertion, cuphook is released with a simple pivot of the tool. Also excellent for removing existing cuphooks safely. Fits drills with 1/2" chuck.

#HB6008......Cup and Hook Driver



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Cup Hook

#60665.... 1/4" x 3-1/2" #606655 1/4 x 3-1/2" - SS

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Screw Hook

......3/8" x 4" zinc #HSH049..... #HSH048Screw Hook 0.268" X 3-1/2" Zinc

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



J-Nail

#80543...... 1-3/4", galvanized dbl. dipped, 61/lb

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





#61745 3" x 3" Pulley Bracket #60649......5/16" U-bolt #606815/16" Nylock #60580...... 5/16" Washer

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Conduit & **Curtain Pipe**

#61720.....1/2" x 10' galv. w/crimped end #10802 Rebar 3-3/8" x 10' #60340..... Pipe 1/2" x 21' galv. w/end coupling

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Curtain Clamp Hanger

#HSH026SS 1/2" SS Curtain Clamp Hanger

▲WARNING:





Aircraft Cable

Stainless Steel

Item#	Size	Dia.	Breaking Strength
61731	7x7	3/32"	920 lbs.
61739	7x7	1/8"	1,700 lbs.
61739-250	7x7 250′	1/8"	1,700 lbs.
61739-500	7x7 500′	1/8"	1,700 lbs.
61739-1000	7x7 1000′	1/8"	1,700 lbs.
617271	7x19	5/32"	2,400 lbs.
617281	7x19	3/16"	3,700 lbs.
617281-250	7x19 250'	3/16"	3,700 lbs.
617281-500	7x19 500'	3/16"	3,700 lbs.
617281-1000	7x19 1000′	3/16"	3,700 lbs.
617291	7x19	1/4"	6,400 lbs.
617276	7x19	5/16"	9,000 lbs.

Galvanized

Item#	Size	Dia.	Breaking Strength
52260	1x7	1/16"	500 lbs.
52260-500	1x7 500'	1/16"	500 lbs.
52260-1000	1x7 1000'	1/16"	500 lbs.
61726	7x7	1/8"	1,700 lbs.
61726-250	7x7 250'	1/8"	1,700 lbs.
61726-500	7x7 500'	1/8"	1,700 lbs.
61726-1000	7x7 1000'	1/8"	1,700 lbs.
617261	7x19	1/8"	2,000 lbs.
61727	7x19	5/32"	2,800 lbs.
61728	7x19	3/16"	4,200 lbs.
61728-250	7x19 250'	3/16"	4,200 lbs.
61728-500	7x19 500'	3/16"	4,200 lbs.
61728-1000	7x19 1000′	3/16"	4,200 lbs.
61729	7x19	1/4"	7,000 lbs.
61729-100	7x19 100′	1/4"	7,000 lbs.

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HSH059 ______ For cable up to 3/16" #598821Heavy Duty, replaceable blades, for cables up to 1/4" #AMTC9BLADE Replacement blades for #598821, price per blade, need two per tool

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Swagging Tools

#6032619......Crimping/Swagging Tool, 18" Red #AS58471 Crimping/Swagging Tool, 24" Red #59925.....Swagging Tool Heavy Duty

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Sta-Kon Crimpers

#HE823015...... Klein 1005 Red Handle #10906..... Economy Crimper

≜WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




#HSH027......3/16"



♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Cable Clamps

#61732	1/8" Galvanized
#61733	3/16" Galvanized
#61734	1/4" Galvanized
#HSH052	1/16" Shocker wire clamp
#617321	1/8" Stainless Steel
#617331	3/16" Stainless Steel

♠ WARNING:





Air Transfer Gasket

#JPT2436 Gasket



Tether Kit

#JAN3213 1 per 120' Unit

Blower Motor

- 1/40 Hp
- 115V
- .60/ .75 amps
- 2420/2480 rpm
- 148 CFM at free air
- 60 Hz



#HS9070Blower Motor



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Poly Curtain Pockets

Roto moulded from high density polyethylene for excellent impact strength. Formulated with UV inhibitors to prevent discoloration. Average thickness of .200"

#PCP1496	14" x 96" White poly	y, pair
#PCP1866A	18" x 66" White poly	y, pair
#PCP1884A	18" x 84" White poly	y, pair



Stainless Steel Curtain Pockets

- 304 Stainless Steel
- 18 gauge

#8410961500 Curtain pocket left 18" x 96" #8410971500 Curtain pocket right 18" x 96" #8420011500 Curtain pocket left 18" x 66" #8420031500 Curtain pocket right 18" x 66"

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Poly Patch

#JPP4 4" x 48'




Black Flex Hose

#JA69673" x 3'



Polyvent III Bag

#JAPV5	5' Polyvent Bag
#JAPV4	4' Polyvent Bag
#JAPV3	3' Polyvent Bag



Welded Hog Panel

Constructed of .225 dia wire with 8" vertical spacing. Welded before galvanizing.



#8064134" x 16' galv. welded hog panel #80647 ... Horse panel, 2' x 16' 4 Gauge, 2 x 4 Spacing

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



VCS Curtain System

- · Minimizes rodent nesting problems
- Visual appearance improvement
- · Easy Clean-Up
- · Extended life compared to previous method of
- · Design ease for future replacement or repairs
- Easy 4-step installation

#61849	18' sections w/hardware
#61894	Curtain pockets
#617256	Cord With Reads

Pro-Tech, Inc. **Curtain Minder** CM5000D

A knob on the front of the Curtain-Minder controls the delay time for releasing the curtain winches. The delay is adjustable between zero



and ten minutes. Zero or near zero allows the operator to test the systems and the curtain winching system quickly. The adjustment also provides the operator the ability to match the transfer time on an automatic standby generator.

- 230 Volt
- Adjustable 0-10 minute time delay
- · Alarm output
- · Controls up to 4 winch kits
- 12 volt batterv

#52208...... Curtain Minder CM5000D



Pro-Tech Winch Kit

The WK1510 is the original WK1500 but includes a reed switch which can be used as alarm output.

#WK1510 Winch Kit

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





*Shown with optional mounting bracket HS667-01KIT

Linear Vent Actuator

Hog Slat's 24" Linear Actuator is designed to be used with automatic ventilation controls. Bi-directional control with a built-in potentiometer feedback for position sensing of inlets with adjustable limit switches. Clamped extension boots and superior motor seals offer improved protection of interior components from dust and water. Includes terminal connection enclosure. Hog Slat's linear actuator has an IP Code (or International Protection Rating) of 65 versus competitive brand's rating of only 53. 50 inlet capacity with a 1:1 ratio. 800 pound max load at a 1:1 ratio.

Item#	Voltage	Travel/Sec.	Housing Color
#HS667-24	120	1/4"	Blue
#HS667-24-240	240	1/4"	Blue
#HS667B-24	120	5/64"	Black

#HS667-01KITOptional 12 ga. galvanized mounting bracket, 10.22" x 51" w/ hdwr

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

PowerDropTM

for affordable protection

- Alarm contact for the PowerDrop[™] signals an alarm system upon the release of the curtain.
- · Switch features stainless steel actuator and watertight construction
- 304 S.S. Construction
- · Contacts are normally open or normally closed, rated at 3 amps 250 volts
- · Not effected by cold or wet weather
- 5 minute drop delay
- · Battery free operation
- · Now for Poultry with 2-minute delay



1 20 V, 5 min delay
120 V, Poultry, 2 min delay
120 V, 5 min delay w/ alarm contact
120 V, Poultry, 2 min delay w/ alarm contact
208 V, 5 min delay
208 V, Poultry, 2 min delay
208 V, 5 min delay w/ alarm contact
208 V, Poultry, 2 min delay w/ alarm contact
240 V, 5 min delay
240 V, Poultry, 2 min delay
240 V, 5 min delay w/ alarm contact
240 V, Poultry, 2 min delay w/ alarm contact
Alarm kit

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Hired Hand Curt-O-Matic

- · Automatically drops the side curtains of your confinement house if the power should fail.
- · With optional thermostat Automatically drops the side curtains in the event of high temperature extremes, preventing thousands of dollars in potential loss.
- · A huge return for a small investment.



#H6450-1220 Hardware Package for Curt-O-Matic ♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



⚠ WARNING:





Optional chain & sprocket drive eliminates cable breakage. Features a 13 tooth sprocket with a size 50-5/8" roller chain.



Smooth Operation

Aluminum load block rides on acetal plastic bearings and quide blocks imbedded in the cabinet side, for smooth motion and to stabilize the shaft.



Easy Servicing

Features a removable front cover, precision cut outs, and swivel points to allow for easy removal of the ACME screw and block.





Three sealed, ball bearing head pulleys for multiple mounting options. Farm-duty, ACME screw efficiently transfers power to load block.



Suited for Multiple Motor Sizes

Fitted for 120V, 240V, 15, 30 and 60 RPM models.

Simple Limit Switch

Dual limit switch is backed by secondary safety lock-out switch. Includes auxiliary switch for backup fans.



Local Controls

Manual control switch allows for quick adjustments of the screw and limit switch positions directly from the box.

Patented Closure Patent #10.314.283 B2

Water resistant box protects switches and electrical components in one single enclosure.

#HS583E-2415	24" travel, 15 rpm, cable system
#HS583E-2430	24" travel, 30 rpm, cable system
#HS583E-2460	24" travel, 60 rpm, cable system
#HS583E-2430S	24" travel, 30 rpm, sprocket drive
#HS583E-3615	36" travel, 15 rpm, cable system
#HS583E-3630	36" travel, 30 rpm, cable system
#HS583E-3660	36" travel, 60 rpm, cable system
#HS583E-3630S	
#HS583E-4830	48" travel, 30 rpm, cable system
#HS583E-4860	
#HS583E-4830S	
#IB303E-40303	46 traver, 50 tpin, sprocket drive



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECT

Multi-Curtain Machine Isolator

Allows up to 4 curtain machines, linear actuators or other climate management equipment to be controlled in unison by a single input signal. Each output is an isolated dry contact SPDT relay output allowing a variety of connection possibilities. 120V control signal with 5 amp contact rating.

#HS766.....Isolator

Gear Motor

• 115 V. 60 Hz. 1/8 HP

• 30 RPM



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

GrowerSELECT

Raise-Off-Lower Switch

• Prev. #G1775

#EL1001Raise-Off-Lower Switch

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Toggle Switch

• DPDT, 10 Amp, 250 V, 2 Position

#EL 1005



... Toggle Switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Acetal **Load Nut**

#HS583-8-2AAcetal Load Nut

Bearing Flange

• 1" I.D. 3-piece



#HS583-42 Bearing Flange

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Snap Action Roller Switch

• 15 Amp

#EL1135..... Snap Action Roller Switch

Acme Screw

• 36"

#HS583-11A36B Acme Screw

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Curtain Machine Side Cover

Plastic side cover to protect openings on GrowerSELECT curtain machines where cable and chain exit.

#HS583-100.....




Cover

Growerselect

HS583E Curtain/Vent Machine Replacement Parts

Key	Part#	Qty.	Description
1	HS583-34	3	Pulley, Cast 3-1/2", double ball bearings
2	HS583-42	1	Bearing Flange 1" I.D
3	HS583-8-2A	1	Load Nut Replacement Kit
4	HS583-9	2	Slide, load block
5	HS583-8	1	Kit, Complete Load Block Assembly & Load Nut
6	HS583-8-7	1	1-1/4" External snap ring, supplied with HS583-8-2A
7	HS583-41	1	Threaded collar, seal thrust bearing nylon
8	HS583-12	1	Thrust bearing, 1" ID, D9
9	HS583-11A24B	1	ACME screw, 24" machine
	HS583-11A36B	1	ACME screw, 36" machine
	HS583-11A48B	1	ACME screw, 48" machine
10	HS613		Spider Gear-spacer Hytrel (white) L090/L095
11	LOV38146	1	Coupling Jaw L095 5/8" bore & keyway
12	HS9050	1	Motor 1/8 HP, 115V AC, 60 Hz, 1.9A FL, 28RPM
	HS9051	1	Motor 1/8 HP 230V AC, 50/60Hz, 0.75/0.90A FL, 24/29 RPM
	HS9052	1	Motor 1/8 HP, 115V AC, 60 Hz, 1.65A FL, 16RPM
	HS9053	1	Motor 1/8HP 115V 60Hz, 1.9A FL, 60RPM
	HS9054	1	Motor 1/8HP 230V 50/60Hz, 0.75/0.90 FL, 60RPM
13	EL1001	1	Switch, Toggle SPDT, 10A @ 250 Volt, CTR OFF
14	EL1005	1	Switch, Toggle DPDT, 10A @ 250 Volt, CTR OFF
15	HS583E-31	1	Switch assembly with (6) EL1135 micro switches
			for enclosed style only.
16	HS583-46-6	1	Bellows Rubber Limit Rod
17	HSLABEL-008	1	Label, Warning-Shock Hazard
18	HS612	1	Knob, tri-handle, 1/4–20 insert
19	HS583-45	1	Handle, Front door
20	HSLABEL-084	1	Label, "Caution Automatic Equipment"
21	HS583-28	2	Collar, steel 3/8" w/ set screw



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


Key	Part#	Qty.	Description
22	HS583-27-24	1	Limit rod, 24" machine
	HS583-27-36	1	Limit rod, 36" machine
	HS583-27-48	1	Limit rod, 48" machine
23	HSLABEL-083	2	Label, "Warning Moving Parts"
24	HSLABEL-087	1	Label, "Grease Location"
25	HS583-29	2	Spring, limit rod
26	EL1083	2	Rubber cover, toggle switch


GrowerSELECT

HS583 Curtain/Vent Machine (without enclosed switches)

Key	Part#	Qty.	Description
1	HS583-34	3	Pulley, Cast 3-1/2", double ball bearings
2	HS583-42	1	Bearing Flange 1" I.D
3	HS583-8-2A	1	Load Nut, acetal plastic
4	HS583-9	2	Slide, load block
5	HS583-8	1	Load block assy., load nut, cotter pins
6	HS583-8-7	1	1-1/4" External snap ring & HS583-8-2
7	HS583-41	2	Threaded collar, seal thrust bearing nylon
8	HS583-12	1	Thrust bearing, 1" ID, D9
9	HS583-11A24B	1	ACME screw, 24" machine
	HS583-11A36B		ACME screw, 36" machine
	HS583-11A48B	1	ACME screw, 48" machine
10	HS613	1	Spider Gear-spacer Hytrel (white) L090/L095
11	LOV38146	1	Coupling Jaw L095 5/8" bore w/keyway
12	HS9050	1	Motor 1/8 Hp 115V 60 Hz 30RPM AC
13	HS583-31	1	Switch assy. & (6) EL1135 micro switches
14	EL1001	1	Switch, Toggle SPDT, 10A @ 250 Volt, CTR OFF
15	EL1005	1	Switch, Toggle DPDT, 10A @ 250 Volt, CTR OFF
16	HS612	1	Knob, tri-handle, 1/4-20 insert
17	HS583-45	1	Handle, Front door
18	HSLABEL-084	1	Label, "Caution Automatic Equipment"
19	HSLABEL-083	2	Label, "Warning Moving Parts"
20	HSLABEL-087		Label, "Grease Location"
21	HS583-27-24	1	Limit rod, 24" machine
	HS583-27-36	1	Limit rod, 36" machine
	HS583-27-48	1	Limit rod, 48" machine
22	HS583-28	2	Collar, steel 3/8" w/ set screw
23	HS583-29	2	Spring, limit rod
24	EL1083	2	Rubber cover, toggle switch
25	HSLABEL-008	1	Label, "Warning–Shock Hazard"

Enclosed Switch Retrofit Kit Retrofit Kit converts machines with exposed limit switches and controls. #HS583E-46KITRetro kit





GrowerSELECT

HS583E Curtain/Vent Machine, Sprocket Drive

Key	Part#	Qty.	Description
1	HS583-44	2	Sprocket, 13 Tooth #50, w/ Sealed Ball Bearings
2	HS583-42	1	Bearing Flange 1" I.D
3	HS583-8-2	1	Load Nut, nylon
4	HS583-9	2	Slide, load block
5	HS583-8	1	Load block assembly w/ load nut & cotter pins
6	HS583-8-7	1	1-1/4" External snap ring, supplied with HS583-8-2
7	HS583-41	2	Threaded collar, seal thrust bearing nylon
8	HS583-12	1	Thrust bearing, 1" ID, D9
9	HS583-11A24B	1	ACME screw, 24" machine
	HS583-11A36B	1	ACME screw, 36" machine
	HS583-11A48B	1	ACME screw, 48" machine
10	HS613	1	Spider Gear-spacer Hytrel (white) L090/L095
11	LOV38146	1	Coupling Jaw L095 5/8" bore with keyway
12	HS9050	1	Motor 1/8 Hp, 115V AC, 60 Hz, 1.9A FL, 28RPM
	HS9051	1	Motor 1/8 Hp 230V AC, 50/60Hz, 0.75/0.90A FL, 24/29 RPM
	HS9052	1	Motor 1/8 Hp, 115 V AC, 60 Hz, 1.65A FL, 16 RPM
	HS9053	1	Motor 1/8 Hp 115 V 60Hz, 1.9A FL, 60 RPM
	HS9054	1	Motor 1/8 Hp 230V 50/60Hz, 0.75/0.90 FL, 60 RPM
13	HS583E-31	1	Switch assembly with (6) EL1135 micro
			switches for enclosed style only
14	EL1001	1	Switch, Toggle SPDT, 10A @ 250 Volt, CTR OFF
15	EL1005	1	Switch, Toggle DPDT, 10A @ 250 Volt, CTR OFF

Key	Part#	Qty.	Description
16	HS612	1	Knob, tri-handle, 1/4-20 insert
17	HS583-45	1	Handle, Front door
18	HSLABEL-084	1	Label, "Caution Automatic Equipment"
19	HSLABEL-083	2	Label, "Warning Moving Parts"
20	HSLABEL-087	1	Label, "Grease Location"
21	HS583-27-24	1	Limit rod, 24" machine
	HS583-27-36	1	Limit rod, 36" machine
	HS583-27-48	1	Limit rod, 48" machine
22	HS583-28	2	Collar, steel 3/8" w/ set screw
23	HS583-29	2	Spring, limit rod
24	EL1083	2	Rubber cover, toggle switch
25	HSLABEL-008	2	Label, Warning–Shock Hazard
26	HS583-8-5	2	Bolt Adapter #50 Chain Curtain Machine
27	60580	2	Washer Flat SS 5/16"
28	60681	2	Nut Lock 5/16"
29	HS583-46-6	1	Bellows Rubber Limit Rod
30	HS583-55	2	Swivel 3/8" Eye/Jaw Galv
31	HS583-8-6	2	Adapter #50 Chain
32	HS583-70	1	(2) 36" #50 Roller Chain for 24" machine
	HS583-80	1	(2) 48" #50 Roller Chain for 36" machine
	HS583-90	1	(2) 60" #50 Roller Chain for 48" machine
33	EL50RC	4	Master link, #50 chain



#DI710ARE1MOD......Relay Set 110V Modified W/Safety Switches #DI710AWDC Winch Drum for Curtain Machine

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Motor

#DI710AMJR14.....

......1/4 Hp Motor only, 110V

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Relay, 110 V

A) #DI710AELEC B) #DI710AELECLH.....Left Hand

......Right hand



Door Install Kit

#DI6400008..... Seam caps & Screws

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Strap Kit

#DI6400003Tunnel Door

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#DI710AG3250DVMComplete unit right hand, 110V #DI710AG3250......Right hand, gear only 250 w/110 volt relay set #DI710AG3250LH.....Left hand, gear only 250 w/110 volt relay set

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Racket Wrench

#DI6400024

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hinge

#DI6120043.....

🚹 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Spacer

#DI6120042 For hinge



Door Seal





A.T. Newell Style **Curtain Machines**



Whisker **Switches**

#HSAC1568 Assembly #EL1126......Micro switch only



Limit Switch Actuator

#G1126.....Limit switch actuator



GrowerSELECT 1/2 Hp Motor

#HS9013...... 1725 RPM, 115V, 1Ph, 60Hz

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#G17636 position



Relay - Reversing

#GAC1558-1K w/115 vac coils

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bearing

#12G......3/4" pillow block, Prev.# G1292





#EL1059Limit switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

GrowerSELECT Manual-Auto

Switch



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Thermostat

#596012-stage replacement



Motor Only

#HS1742......1 RPM, 60Hz 110V

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Micro Whisker Switch

• Replaces OEM#1568

#EL1126......Switch only



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- Replaces OEM#1412
- 3″ Dia.
- 1/2" bore

#PAK3012.....AK30-1/2







#G1738Timer complete

AP Repair Parts

*Use of Original Manufacturer's part numbers is for reference only



Natural Ventilation Control

- · Adjustable on/off run time
- · Automatic control with manual override
- · Remote sensor

#GTC1-NV......Natural vent controller



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- · Comes with block and hardware
- 30 RPM
- 110V


#G53-0230w/ block and hardware

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Curtain Controllers

The newly-designed curtain controller is a screwdriven automated curtain machine with an 1/8 Hp, 115 vac, 60 Hz motor in either 15, 30 or 60 RPM. Multidirectional, frame-mounted, head pulleys and latch out assembly are standard on all machines. Thermostat controls, electronic controls and extra bracket kits are sold separately. Comes with a 3,000-lb. lift capacity.



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



• 115 V

#HS9056.....OEM# G53-0103BA

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bearing

· 1" pillow lock bearing, locking collar included

#16G.....Bearing, OEM# G16-0076

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Top Coupler

#G52-0330 Top Drive Coupler w/ welded nut

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bottom Coupler

#LOV38146 Lower Drive Coupler w/ lock collar

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Drive Block

1) #HS631Plastic Insert, OEM# 52-0275

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bearing

#GAC52-0174Thrust bearing w/ support

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Switches

3) #EL1041 Limit switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Spider Gear

#HS613 Hytrel spider gear



Drive Screw


#G50-005636" travel drive screw

⚠ WARNING:











Strap Drive Machine

Cost effective strap drive machine for controlling inlet doors and curtains. Reduced maintenance with sealed and lubricated gearbox and nylon strap belt. Easy set external limit switches with instantly reversible 1/2 hp, 115 volt motor.

- Shaft RPM 2.1
- Belt Speed 28 Ft/min
- Power 5,000 lbs
- Pulls 2,500 lbs
- Belt 14 Ft

Application Guidelines:

- Curtains 500 feet long
- Inlet Vents 100 (Cabled 2:1 to slow)
- Tunnel Doors 240 feet long

#PCSW2500Strap Drive Curtain and Inlet machine




Aerotech Curtain Machine BA4000

1) #AC1955 Ba	r, limit switch activation, BA4xx2
#AC1956Ba	r, limit switch activation, BA4xx3
#AC 1957Ba	r, limit switch activation, BA4xx4
#AC1959Ba	r, limit switch activation, BA4xx5
2) #AC1941	Clamp, limit adjustment
	Cotter Pin
4) #KX1455	Spring, Compression
	Retainer, Limit Switch Spring
6) #AC1914	Bracket, Open/Close Switch
7) #KE1154 Co	nnector, moisture resistant 14-22 AWG
	Circuit Board
	Switch, micro
	Capacitor, 12.5 mfd for BA4000 only
	Capacitor, 12.5 mfd for BA4500 only
	Bulkhead, middle
12) #AC 1905	Bearing, thrust, 3-bolt flange, 1" I.D.
	Washer, flat, zinc plated
14) #AC1601	Coupler body, 1" bore, 095
	Spider Insert, for 090/095, rubber
	Coupler body, 1/2" Bore, 095
	Bulkhead, lower
	Gearmotor w/ brake, 30 rpm
	Brakes for AC1606/AC1607, round
	Cotter Hairpin, 1/8" D x 2.5" L
	Flat washer, nylon
	Spacer, nylon
24) #AC1901	Cable puller
25) #KN1951	Locknut for ballnut
	Guide block, on cable puller, plastic
	Chassis Cap, bottom end
	Bulkhead, upper
	Bearing, 2 bolt flange, 1" I.D.
	Ball Screw Assembly, BA4xx2
#AC1487	Ball Screw Assembly, BA4xx3


WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



	*
#AC1488	Ball Screw Assembly, BA4xx4
31) #AC1909	Chassis Cap, top end
32) #AC1922	Chassis, BA4xx2
#AC1923	Chassis, BA4xx3
#AC1924	Chassis, BA4xx4
#AC1926	Chassis, BA4xx6
33) #AC1908	Bracket Pulley Cover
34) #AC1943	Pulley, w/ bearing
35) #AC1961	Spindle for 3.5" Pulley 3
36) #AC1907	Bracket, Pulley Base 1
37) #AC1916	Pull Retainer, BA4xx2 1
#AC 1917	Pull Retainer, BA4xx3 1

#AC1918	Pull Retainer, BA4xx4 1
#AC1920	Pull Retainer, BA4xx6 1
38) #AC1928	. Cover, BA4xx2, w/ hinges/latch 1
#AC1929	.Cover, BA4xx3, w/ hinges/latch 1
#AC1930	.Cover, BA4xx4, w/ hinges/latch 1
#AC1932	.Cover, BA4xx6, w/ hinges/latch 1
•	Hinge, cane bolt, RH 1
40) #KX1041	Latch, Slide bar assy, SS Varies
41) #KX1042	Latch, Lock bushing, ZP 1
42) #AC1933	Hinge, cane bolt, LH, ZF





Aerotech Baffle Actuator

1) #AC1333	Cover
2) #AC1475C	
3) #AC1326	(DISC) Gearhead, 360:1
4) #AFP2053	Prop fastener, 5/16" x 3/4" OD
5) #AC1345	Spider insert, 070 coupler, rubber
6) #AC1328	Complete coupler
7) #AKP1010	Slotted spring pin, 1/16" D. x 1.25" L
8) #AC1070	2-Bolt bearing flange, 1/2" bore
9) #AC1080	Ball screw w/ nut and flange
- i	-


MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

10) #AC1308	Cable guide block
	Ball nut guide
•	Snap action switch with EXT spring, 15A
-	DPDT relay, 20Å, 120 coil

Part number AC1340, Potentiometer Add-On Kit has been discontinued. Use part number APTRLKS, Stand Alone Potentiometer Kit. Please note, APTRLKS is a separate external unit and does not mount internally like the AC1340.

Hired Hand Repair Parts *Use of Original Manufacturer's part numbers is for reference only





GrowerSELECT

Replacement Load Nut Assembly

- · Plastic insert
- Replaces Brass Load Nut OEM #6402-1254

#HS576.....Load Nut Assembly



GrowerSELECT PowerTrak™ Load Nut Assembly

#H6450-5049......Complete

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Aluminum Load Block

#HS574.....OEM part #0401-3560

⚠ WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Growerselect Wiring Harness

#HS6650-5024..... Wiring harness #HS1902-0158......10' Wiring harness

Temperature Sensor

· Replaces sensor for all Hired-Hand controls



GrowerSELECT

Gear Motor

- · For new style machine, door opens on hinge
- 115V, 60 Hz, 1/8 Hp

#HS9050...... 30 RPM OEM part #6650-0063 #HS9052.....16 RPM OEM part #6650-0062

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov


GrowerSELEC Gear Motor

- · Bison old style
- · Door lifts off

#HS9050-060230 RPM, 110V



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- Modular construction for ease of service.
- · 5,000 LB. capacity.
- · Built-in head bracket with needle-bearing pulleys.
- · Channel lock trak-drive system captures load block
- 15% increase in load block support surface for greater life.
- · Easy-adjust springcam limit switch system.
- · Convenient hinged spring lock door is easily removed.
- Greater protection from the elements.

#H6602-023630 RPM, 36" travel #H6602-0244...... 60 RPM, 36" travel

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECT

Plastic Spider Coupling

#HS613 OEM part #1050-1365

GrowerSELECT

5/8" Lovejoy Coupling

#LOV38146 OEM part #1047-1367



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECT

Limit Switch Assembly

#HS837 3 wire, new style




⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov









⚠WARNING:

Automatic Curtain Control

The HS740 Automatic Curtain Controller is used to control up to two curtain machines or linear actuators in order to regulate the temperature inside a room. Built-in timer reads signal from thermostat or other input every five minutes to open or close curtains.

- · Adjustable open and close times
- 120 Volt
- · 8 Amp contact rating



Negative Pressure Vent Control

This controller opens and closes vents as required to maintain the building's static pressure within the defined range set the high and low limit pointers.

- Manual / Auto selection
- 120 V
- 3-wire connections
- · Includes 25' of tubing.



#HS653Negative Pressure Control



Cube Relay for Vent Controller

• 3PDT, 120V, 11 pin - for 8 wire

#EL1013..... replaces HH 0EM# 3015-1548



Plug-in Relay for Vent Controller


• DPDT, 120V, 8 pin - for 3 wire


#EL 1015 replaces HH 0EM# 3015-2884



Photohelic Gauge

#HS650KIT.....Photohelic gauge






Hired Hand PowerTrak Inlet Machine

1) #H0404-5011	Pulley bracket
2) #H6450-2881	Pulley shaft
3) #H0404-5012	Head bracket
4) #H0404-0101	Upper flange brkt
5) #H6450-5049	
6) #HS583-28	
7) #H0404-5040	Top bearing plate
8) #16S	1 01
9) #G50-0089	-
io) #H6402-0107	
11) #HS583-41	
•	

12) #H0404-5016	Load-bearing bracket
13) #H0404-5019	· · · · · · · · · · · · · · · · · · ·
14) #LOV38146	
15) #HS613	, , , , ,
16) #HS9050	1 1 9
17) #H6450-0205	
18) #H1024-0102	,
19) #H0201-3129	1 0
20) #HS583-12	Thrust bearing
21) #H0404-5023	Bottom bearing flange
N/A) #H6450-5500	Sprocket conversion kit

Chore-Time Linear-Lift™ & ProTerra Winch

*Use of Original Manufacturer's part numbers is for reference only





2) #23212... 3) #C41957 4) #AGL44417 Chain Connecting Rod 5) #AGL20017 Connecting Link

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



208-230/220-240 V

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Chore-Time Gear Box

#C3261-15......Chore-Time Gear Box

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Chore-Time Switch Assembly

#C38904 Chore-Time Switch #EL1056 SPDT switch replaces OEM# 46324



GrowerSELECT

SOX Spider Spacer

#LOV 10621 C3633



Chore-Time **Thrust Bearing Bracket**

#C35566 Chore-Time Thrust Bearing Bracket

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Chore-Time Pulley Wheel

#C41540 Chore-Time Pulley Wheel



Machined Flexible Coupling

#C35944 Machined Flexible Coupling

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECT

Pinion

#HSP05 Chore-Time OEM# 3429

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Chore-Time **Drive Screw**

#C35945-4 Chore-Time Drive Screw

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Nut Assembly

#C41957Chore-Time Nut Assembly

▲WARNING:


Proterra AGLA47859 Series (Standard)



Proterra AGLA47859 & AGLA48028 Series Curtain Winch parts

1) #AGL42780	115 V Motor
#AGL36370	230 V Motor
2)	Swivel Top Winch Base
#AGL47836-26	26"
#AGL47836-36	36"
#AGL47836-48	48″
#AGL47836-66	
4) #AGL47762	L.H. Winch Motor Bracket
5) #AGL47763	Winch Thrust Bracket
6) #AGL47771-2	R.H Winch Panel
7) #AGL47771-1	L.H Winch Panel
8) #AGL47772	Winch Swivel Partition
9) #AGL47834	Winch Cover Bracket
10) #AGL36363-2	Flexible Type L Coupling
11) #AGL35944	Flexible (Mach.) Coupling
12) #LOV10621	
14) #AGL2663	125" x .75" Cotter Pin
15) #HS806	
16) #AGL36397	Industrial Thrust Bearing
17) #AGL2525-68	ProTerra Decal
18) #C47759	Machined Winch Nut
19) #AGL2503	Red Pulley Wheel
20) #C41525	Retainer Ring
21) #AGL49813	Compression Spring
22) #AGL47835-1	Lower Winch Cover
23) #AGL41857	Set Collar
24) #AGL2529-634	Grease Decal
25)	Winch Switch Rod
#AGLE1401-36.50	26"
#AGLE1401-46.50	36"

Proterra AGLA48028 Series (Chain Drive)



🚹 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#AGLE 1401-58.50	48″
#AGLE1401-76.50	66"
26)	1-5 Threaded Acme Shaft
#AGL47856-26	26"
#AGL47856-36	36″
#AGL47856-48	48″
#AGL47856-66	66″
27) #AGL47876	Swivel Top Pulley Assembly
28)	Winch Cover Assembly
#AGL47873-26	26″
#AGL47873-36	36″
#AGL47873-48	48″
#AGL47873-66	66"
29) #AGL3-12194	Handle
30) #AGL47658	25' Winch Cable
30)	Drive Chain
#AGL21045-14	26″
#AGL21045-15	36″
31) #AGL42728	8-32 Set Screw
	Cable Tie
	5/16-18 x .625" Carriage Bolt
34) #AGL8490	5/16-18 Hex Flange Nut
•	1/4-20 Hex Flange Nut
36) #AGL2150	5/16 x 18 x 1.25" Bolt
	Winch Decal
38) #AGL1839	5/16 -18 x .50 Bolt
41) #AGL2527-10	Danger Decal
45) #AGL44417	Chain Connecting Rod
•	Connecting Link (#40)
47) #AGL5083-2	1/4-20 x 2-1/4" SH Cap Screw

Complete Units

CABLE:

#AGLA47859-2230..

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

⚠ WARNING:

CHAIN:

#AGLA48028-2230

#AGLA48028-4160.....

Agri Ventilation Systems Vent/Curtain Machine



B - parts for Ball Screw Machine



A - parts for Actuator Machine

#AVDR-AN-1802	
#AVDR-AN-4000	Drive Standard 4' Dr AN 4000
#AVDR-AN-5002	Drive Machine In Line 5' 107 RPM
#AVDR-AN-6000	Drive 6' (68") Travel Dr AN 6000
	Vent Machine 48" w/o motor

MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



(B) Ball Nut Assembly

(for Mini Ball Screw Machine)

#AVBS-BN-1000..... Ball Nut Assembly

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



(A) Dipstick Oil Plug

#AVHW-OP-1000 Dipstick Oil Plug



(A) Switch Assembly

#AVDR-BX-1000.....Complete



(A) Inside Replacement Drives

\$AVDR-00-1801	18"
\$AVDR-00-3100	3′
\$AVDR-00-4100	4′
\$AVDR-00-5100	5′
‡AVDR-00-6100	6'

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



(A) Motor 1/4 Hp

reproductive harm. For more information, go to www.P65Warnings.ca.gov



(A & B) Motor 1/6 Hp

#AVEP-FR-0040......1/6 Hp 40 RPM

↑ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



(A) Collar with Thumb Screw

#AVHW-LC-1000.....w/ Thumb Screw

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



(A) Limit Switch

• Fail-safe limit switch for assembly box

#EL1042	Limit Switch
#EL1043	Limit switch
#AVDR-0-B1110	Spring for switch



(A & B) Love Joy Coupler

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



(A & B) Spider Gear

#AVDR-LJ-000Ufor Love Joy Coupler



(B) Relay

#EL1015.....for Mini Ball Screw Machine



(B) Run Capacitor

(for Mini Ball Screw Machine)

#AVEP-CP-0006......Capacitor



(B) Electromagnetic Brake

#AVBS-BR-0090 for ball screw

⚠ WARNING:



Guardian® 2.0

New spark igniter - no separate flame sense and new igniter position for Hot



Direct Spark Ignition

#LB250DSI-LP-2 250,000 Base Unit - Propane #LB250DSI-NG-2 250,000 Base Unit - Nat. Gas



Thermostats

#LB05568L.B. White Surface Mount #59598.....Remote w/ 20' cord, plug end #LB20176.....L.B. White remote w/ 25' cord, Spade end

Hot Surface Ignition

#LB60HSI-LP-2	60,000 Base Unit - Propane
#LB60HSI-NG-2	60,000 Base Unit - Nat. Gas
#LB100HSI-LP-2	100,000 Base Unit - Propane
#LB100HSI-NG-2	100,000 Base Unit - Nat. Gas
#LB250HSI-LP-2	250,000 Base Unit - Propane
#LB250HSI-NG-2	250,000 Base Unit - Nat. Gas

Pilot Light Models

#LB346-3PLLP...... Classic 60,000 Base Unit - Propane #LB348-3PLNG...... Classic 60,000 Base Unit - Nat. Gas #LB377-3PLLPClassic 115,000 Base Unit - Propane **#LB379-3PLNG**......Classic 115,000 Base Unit - Nat. Gas #LB250PL-LP-2 Guardian 250,000 Base Unit - Propane #LB250PL-NG-2....... Guardian 250.000 Base Unit - Nat. Gas



Gas Hose

#LB20543 ... 1/4" x 10', 1/4" NPT rigid x 1/4" swivel-60M pilot **#LB21993**3/8" x 10', 1/2" NPT rigid x 5/8" swivel-60M&100M **#LB20714** 1/2" x 10', 1/2" NPT rigid x 1/2" swivel-all 250M **#LB20713** 1/2" x 6', 1/2" NPT rigid x 1/2" swivel-all 250M



1) #LB20111Snap-in, 2 pc. 60 HSI 2) #LB20048Snap-in, 2 pc. all 250 3) #LB07742.....Snap-in, 1 pc for 60 classic

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



1) #LB24414......Natural gas for 250,000 2) #LB06665 LP for all heaters 3) #LB07087 Pilot & HSI, natural gas for 60k-170k 4) #LB06553 Vent over outlet, LP

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Manual Shut-Off Valve

#LB571173......Manual shut-off valve

♠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Sediment Trap

#LB00815 Sediment trap for all heaters

↑ WARNING:

Guardian® 2.0 Forced Air Heaters

Replacement parts • Motor and blower wheels are interchangeable with original Guardian models • Gas valves for pilot 250M interchange with original Guardian



Gas Valve

#LB573774	Honeywell, LP
#LB573773	Honeywell, NG



Flame Sensor Rod - 2.75"

#LB574284		



High Limit Switch

#LB573099	100 & 250M
#LB572501	60M



Transformer

#LB574289 All DSI & HSI models



Ignition Control

:		
:	#LB574287	DSI
:	#I DE7/1200	псі



Igniter And Sensor Assembly

#LB574196 DS	I -	all	models
---------------------	-----	-----	--------



Power Cord 10'



Air Pressure Switch

odels



Igniter

#LB573659	All	HSI	model
-----------	-----	-----	-------





Burner Orifice

#LB574293	LP, 60M
#LB574294	
#LB574213	LP, 100M
#LB574295	NG, 100M
#LB574296	LP, Pilot & HSI 250M
#LB574303	NG, DSI 250M
#LB574304	NG Pilot 250M



Pilot Orifice - 250 Pilot

#LB507829	LP
#LB506968	NG

LB White 250 Direct Spark

Accessories: Page 232

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov






Gas Valve.

Key	Item#	Description
5A	#LB522076	Honeywell, LP
5B	#LB522078	Honeywell, NG

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Burner Orifice

Key	Item#	Description
6A	#LB570053	LP
6B	#LB570054	NG
	A	

♠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Igniter

Key	Item#	Description
7	#LB570021	Spark Igniter Assy



Key Ite	m# Description
Key Ite	n# Description

#LB505566 High Limit Switch

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Sail Switch

Key	item#	Description
10	#LB24157	Sail Switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Blower Wheel

Key	Item#	Description
11	#LB570481	10-3/4" dia x 6" wide

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bracket

9

Key	Item#	Description
12	#I.R570251	Motor Mount Bracket

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Key Item# Description

13 **#LB520169** 1/3 HP Motor **#LB571406** Capacitor for 1/3 HP motor

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Key Item# Description 14 #LB509615 120/24 V Transformer



Ignition Control

Key	Item#	Description
14	#LB524900	Spark Ignition Control



Blower Assembly Complete

Key Item# Description

#LB570280 1/3 HP motor, blower & bracket

⚠WARNING:

LB White 250 Hot Surface

Accessories: Page 232

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Key	Item#	Description
1A	#LB06665	Secondary regulator, LP
1B	#LB24414	Secondary regulator, NG
2	#LB571173	Manual shut valve
3	#LB20714	1/2" x 10' gas hose, NG & LP
4	#LB00815	Sediment trap



Gas Valves

Key	Item#	Description
5A	#LB522076	Honeywell, LP
5B	#LB522078	Honeywell, NG

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Burner	Orifice

Key	Item#	Description
6A	#LB570053	LP
6B	#LB570054	NG

⚠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Igniter

Key	Item#	Description
7A)	#LB573642	Conversion kit to silicone nitride
7B)	#LB573659	New style silicon nitride



Flame Rod Sensor

Key	Item#	Description
0	#I DE20120	Flama Bod Congor & E" Load



High Limit Switch

Key	Item#	Description
9	#LB505566	High Limit Switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Sail Switch

Key	Item#	Description
10	#I.B24157	Sail switch

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Blower Wheel

Key	Item#	Description
11	#I.B570481	10-3/4" dia x 6" wide

<u>^</u>WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bracket

Key	Item#	Description
12	#LB570251	Motor Mount Brkt.

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Key	Item#	Description
13	#LB520169	1/3 HP Motor
	#LB571406	Capacitor for 1/3 HP motor

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Transformer

Key	Item#	Description
14	#LB509615	120/24 V transformer



Ignition Control

Key	Item#	Description
15	#LB509298	Ignition control

LB White 250 Pilot

Accessories: Page 232

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Key	Item#	Description
1A	#LB06665	Secondary regulator, LP
1B	#LB24414	Secondary regulator, NG
2	#LB571173	Manual shut valve
3	#LB20714	1/2" x 10' gas hose, NG & LP
4	#LB00815	Sediment trap
		•



Gas Valves

Key	Item#	Description
5A	#LB521615	Honeywell, LP
5B	#LB521616	Honeywell, NG

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Key	Item#	Description
6A	#LB570053	LP
6B	#LB570054	NG

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pilot Gasket

Key	Item#	Description
7	#LB570461	Pilot Gasket



Thermocouple

Key	Item#	Description
8	#LB503497	22" Snap-in



Pilot Tube

Key	Item#	Description
9	#LB570661	Pilot Tube



Pilot Orifice

Key	Item#	Description
10A	#LB507829	LP
10B	#LB506968	NG

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Terminal Strip

Key	Item#	Description
11	#LB570491	Terminal Strip

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Key Item# Description
12 #LB505566 High Limit Switch 13 #LB24157 Sail switch

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bracket

Key	Item#	Description
14	#LB570251	Motor Mount Brkt.

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Motor

Key	Item#	Description
15	#LB520169	1/3 HP Motor
	#LB571406	Capacitor for 1/3 HP motor

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Blower Wheel

Key	Item#	Description
16	#LB570481	10-3/4" dia x 6" wide

⚠WARNING:

L.B. White 60,000 Pilot Accessories: Page 232

Key	Item#	Description
1	#LB06665	Secondary regulator
2A	#LB20714	1/2" x 10' gas hose, NG
2B	#LB20543	1/4" x 10' gas hose, LP
3	#LB571173	Manual shut valve
10	#LB05568	Surface mount thermostat
17	#LB00815	Sediment trap

Gas Valves

Key	Item#	Description
4A	#LB502309	Basotrol, LP & NG
4B	#LB521615	Honeywell, LP
4C	#LB521616	Honeywell, NG



🗘 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Burner Orifice

Key	Item#	Description	Thinks.
5A	#LB570077	LP	
5B	#LB570078	NG	
	^		



WARNING:
This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Pilot Orifice

Key	Item#	Description
6A	#LB502689	LP
6B	#LB570065	NG



♠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pilot Shield

Key	Item#	Description
7	#I.B573700	Pilot Shield



(5A)(5B)

Thermocouple

Key	Item#	Description
8	#LB503497	22" Snap-in



Motor

Key	Item#	Description
11	#LB520290	1/12 Hp motor

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Motor Mount Plate

Key	Item#	Description
12	#I.R570382	Motor Mount Plate

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



(6A)-(6B)

Pilot Tube

Item#

#LB521380

TO SEDIMENT TRAP

12	#1 DE70220	6 1/2" dia = 2 1/0" resida
Key	Item#	Description

⚠ WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

(12)

(1A)–(1B)

Description

Pilot tube

(11)

(3)

(10)

6-1/2" dia x 3-1/8" wide

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Fan Housing

Key	Item#	Description
14	#LB05579	w/ motor mount

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Item# Description 15 #LB503933 High Limit Switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Description

#LB502680

Air Proving Switch

⚠WARNING:

LB White 60,000 Hot Surface Accessories: Page 232

Key	Item#	Description
1A	#LB06665	Secondary regulator,LP
1B	#LB07087	Secondary regulator, NG
2	#LB571173	Manual shut valve
3A	#LB20714	1/2" x 10' gas hose, NG
3B	#LB20543	1/4" x 10' gas hose, LP
4	#LB00815	Sediment trap

Gas Valves

Key	Item#	Description
5A 5B	#LB522076 #LB522078	Honeywell, LP Honeywell, NG
SD	#LD3ZZU10	noneywen, NG




🔔 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Burner Orifice

Key	Item#	Description
6A	#LB570225	LP
6B	#I.B570226	NG




♠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Key Item# 7A) #LB573642 Conversion kit to silicone nitride 7B) #LB573659 New style silicon nitride



Key	Item#	Description
8	#LB572412	Flame probe 45° bend

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Description #LB503933 High Limit Switch

(5A)(5B)

⚠WARNING:



TO SEDIMENT TRAP

⚠WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

(16)

(14)

(12)

(1A)–(1B)

(11)

์ 3 ์

(10)

Sail Switch

(6A)–(6B)

Key	Item#	Description
10	#LB570027	Sail switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Blower Wheel

Key	Item#	Description
11	#LB570230	6-1/2" dia x 3-1/8" wide

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Motor Mount Plate

Key	Item#	Description
12	#LB570382	Motor mount plate

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Description #LB520290 1/12 Hp motor

13

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Transformer

Key	Item#	Description
14	#LB509615	120/24 V transformer



Ignition Control

Key	Item#	Description
15	#LB509298	Ignition control



Wiring Kit

Key	Item#	Description
16	#LB23709	Wiring Kit w/harness

L.B. White 100 Hot Surface Accessories: Page 232

Key	Item#	Description
1A	#LB06665	Secondary regulator, LP
1B	#LB24414	Secondary regulator, NG
2	#LB571173	Manual shut valve
3	#LB20714	1/2" x 10' gas hose, NG & LP
4	#LB00815	Sediment trap



Gas Valves

Key	Item#	Description
5A	#LB522076	Honeywell, LP
5B	#LB522078	Honeywell, NG

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Burner Orifice

Key	Item#	Description
6A	#LB570281	LP
6B	#LB570282	NG

MARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Igniter

7B

Key	Item#	Description
7A)	#LB573642	Conversion kit to silicone nitride
7B)	#LB573659	New style silicon nitride



Flame Rod Sensor

Key	Item#	Description
8	#LB520139	6.5" Lead



Sail Switch

Key	Item#	Description
10	#LB570493	Sail Switch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Blower Wheel

Key	Item#	Description
11	#LB570304	8" dia x 4-7/8" wide

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bracket

Item#

#LB503933

Key	Item#	Description
12	#LB570383	Motor Mount Brkt.

⚠WARNING:

⚠ WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Motor

Key	Item#	Description
13	#LB520292	1/8 Hp motor

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Transformer

Key	Item#	Description
14	#LB509615	120/24 V



Ignition Control

Key	Item#	Description
15	#I.B509298	Ignition control

Description

High Limit Switch


Hired-Hand Heaters

- 250,000 BTU model available
- Optional direct spark ignition
- · Easy-access electrical control unit
- · Quick-disconnect wiring harness for easy service; gold-plated contacts prevent corrosion
- Electronic hot surface instant-on ignition
- · Safety shut-off after failure detection
- · Manual reset high temp limit switch
- · Backup safety switch

#H6601-0104	75K, LP w/ hanging kit
#H6601-7024	225K, LP, w/ hanging kit
#H6601-7026	
#H6450-0220	

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



= fleater

GrowerSELECT Motors

GrowerSELEC

Flame Probes



Item#	Description	OEM#
#HS9045	1/10 HP for 75K	3017-1302
#HS9040A	1/3 HP for 225	3017-1300
#2MDV4	Capacitor for 1/3 Hp	N/A
#HS6401-2315	Motor/ Plate Assy for 75K	6401-2315
#HS6401-2317	Blower/Motor Assy for 75K	6401-2317
#HSBMA1	Blower/Motor Assy for 225K	6401-1347

🚹 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

GrowerSELECT Blower Wheels




#HSBW3......6-3/8" x 4" CCW for 75K, OEM# 6401-1726 #HSBW1 10-3/4" x 4-7/8" CCW for 225K, OEM# 6401-1318

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Growerselect



#HS501 for 75K, 0EM# 3005-0108 #H\$500for 225K, OEM# 3005-0107

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Low Pressure Gas Switch

#H3001-0111Low Pressure Gas Switch

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov






Air Diverters

#H6401-2876	Wye Duct, 225K
	Wye Duct 75K
	Ť Duct, 225K
#H6401-2888	T Duct, 75K

Stainless Steel







Ceramic Igniter

(conversion kit changes flat ceramic to 2" S.S.)

#HS638Conversion kit, OEM# 6450-0212





#HS7008LP

Gas Valves

#H3004-1301Honeywell w/ nipple to covert White Rogers **#HS7008LP**......Honeywell, LP OEM# 3004-0100 #HS7008NG...... Honeywell, NG OEM# 3004-0101

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Control Module

#HS7001......Hot Surface Ignition models, OEM #3591-1851 #H\$7002 Direct Spark Ignition models, OEM #3591-1200



#EL1215.....Switch Micro, Sail Lever

NARNING:



AP Heaters

*Use of Original Equipment Manufacturer part numbers is for reference only



#HS5420-0-913......Mounting/Motor Assembly 80K, 0EM# 5420-0-913

#G20-5099D1/3 Motor for 225K



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECT

Air Proving Switch

#EL1078 For 80 & 225K, OEM# 5430-1-904



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



GrowerSELECT

Igniter

#HS6342", 24 VAC, OEM# 20-5074M



1-1/4" L.P. Regulator

#609592 for PuraFire



Flame Safeguard Relay

#G20-5001B..... for PuraFire



#HSBW6...... 6-3/4" x 3" CW for 80K, 0EM# 20-5008 #HSBW4......9-7/8' x 6" CW for 225K, OEM# 20-5110

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HS501..... Manual reset, OEM# 20-5046

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Secondary Gas Regulator

• 11-14" water column

#H1045-0100for PuraFire



GrowerSELECT

Flame Rod

#HS596 For 80 & 225K, OEM# 20-5045



- · Used in many applications
- · Compatible with most heater brands.

#HSXF120-24 Universal 120/240, OEM# 20-5036



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

VariFlame Repair Parts





#GVF1-3002.....Flame Probe



#GVF1- 3004 Ignitor Assy (HSI)



#GVF1-1020 ON/OFF Control



#GVF2-1016.....Sail Switch Mounting Bracket

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#GVF3-1022 Gas Valve, LP




Venturi Tube & **Burner Assembly**



Cover Plate

2) #LB572736... Cover plate for thermocouple w/nuts





4B) #LB572731LP

Retaining Screw for Injector Tube 5) #LB09572.....Retaining screw

Primary Burner Orifice (low heat)



6A) #LB570568.....#44 LP 6B) #LB570569.....#52 NG

♠ WARNING: This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Injector Tube

7) #LB09597 Injector tube

WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Thermocouple Fuse clip

11) #LB570227 Thermocouple Fuse clip



Pilot Tube

13) #LB522008..... Pilot tube



(15)

Pressure Valve

8) #LB09861 Pressure valve



Safety Control Valve

10) #LB23955Retaining screw

9A) #LB570454..... Safety control valve 9B) #LB572732 Safety Control Valve "D" Model

⚠ WARNING:

⚠WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



14A) #LB570397.....#42 LP 14B) #LB570398.....#54 NG

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hardware 16) #LB2363610-32, 1 1/2" screw 17) #LB09578..... 10-32 brass nut 18) #LB09568 Spacer

⚠WARNING:




Filter Kit	HEBBI
19) #LB20427	Filter Kit



I-40

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





I-40 Replacement Parts

Key	Item#	Description
1	LB570130	Kit, combustion cones w/gasket
1A	LB570273	Gasket
1B	LB570308	Inner cone
1C	LB500-24543	Outer cone
2	LB500-26141	Hardware for burner plate (nuts, screws, spacers, x3)
3	LB570079	Burner plate with hardware
4	LB500-24050	Ignitor with screws
5	LB572121	Quick link
6	LB573656	Adapter
7	LB573657	Solenoid valve with adapters
8	LB573643 (LP)	Air housing assembly, with orifice & air register plate
	LB573644 (NG)	Air housing assembly, with orifice & air register plate
9	LB573740 (LP)	Orifice, burner

Key	Item#	Description
	LB573674 (NG)	Orifice, burner
10	LB500-27522	*Filter kit
10A	LB572429	Filter
10B	LB573135	Filter sleeve
11	LB572804	Control box w/cover, & bracket
12	LB570660	Wire, black, on/off switch to circuit board
13	LB570456	On/Off switch w/boot
14	LB571939	Boot, on/off switch
15	LB570680	Ignition control
16	LB572100	Connector, liquid tight
17	LB570067	Ignition cable
18	LB570524	Power cord
19	LB500-26541	Adapter, hose





L-40 Low Pressure **Radiant Heat Brooder**


Low profile, energy efficient, heat is what is provided with the L.B. White L-40 radiant brooder. Complete with dual fuel gas valve and 31.5" polished aluminum canopy. The L-40 integrates seamlessly with major poultry house control systems.

#LBL-40.......40,000 Btu, spark Ignition

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Replacement Parts

Key	Item#	Description
1	LB573477	Ignition control
2	LB570456	On/Off Switch
3	LB573481	Gas control valve
4	LB573482	Manifold
5	LB573486	Burner orifice (LP)
	LB573487	Burner orifice (NG)
6	LB573479	Ignition cable
7	LB573478	Ignitor with bracket
8	LB573484	Emitter
9	LB573591	Retention Clip





- · Rugged stainless steel construction
- · Standard with stainless steel filters or optional heavy duty polyester filter
- · Available in LP or Natural Gas models
- Price does not include hoses or couplers

#GAS801125	M2 LP Infrared heater 3,400 BTU w/standard filter
#GAS801200	
#GAS801260	M5 LP Infrared heater 10,000 BTU w/ standard filter
#GAS801260/hdf	
#GAS801351/hdf	

MARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Thermocouple

#GAS806460.....Short M2/M3 #GAS806470.....Long M5/M8



Interior Coil

#GAS806560.....Interior coil



Thermo Unit

• Individual modulating thermostat

#GAS803515	M2/M3 LP
#GAS803517	M5 LP
#GAS803518	M8 LP



Jets

#GAS806326......Jet M2 LP .30mm #GAS806350......Jet M3 LP .39mm #GAS806360.....Jet M5 LP .52mm #GAS806377 Jet M8 LP .72mm

WARNING:
This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hose Adapter

Replaces barb fitting on Gasolec brooder, use with GAS807196 hose kit.

#GAS807209......1/4" MPT x 1/8" FPT

HLB 20-300 High/Low Gas Controller · Controls groups of heaters totaling (up to)

#GAS804130 High Low w/ByPass Right Regulator

#GAS806020......M2

#GAS806040......M8

#GAS806600......SS Rivets

440,000 BTUs LPG

Round Burner (includes SS rivets)

#GAS806030.....



This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Safety Device

#GAS806480..... Safety device w/interior coil

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Dust Filters

#GAS806530	Heavy duty polyester
#GAS806520	Standard, SS





#GAS807196.....LP, ends, fixed 3/8" MPT





G12 Pilot Zone Infrared Radiant Heater


- 42,000 BTU with a large, 42' dia. heat pattern
- · Stainless steel construction
- · Standard heavy duty dust filter
- Available as Pilot Zone, Pilot Individual and Hot Surface Ignition



⚠ WARNING:







Description	Item#	Key	Description	Item#	Key
Hose Socket	#GAS806890		Pilot Jet LP .30	#GAS806835	19)
Screw M5x10	#GAS806905	28)	Pilot Jet NG .40	#GAS806840	
Thermostat	#GAS806910	29)	Washer M 6	#GAS806845	20)
Elbow 3/8m x 3/8f brass	#GAS806915	30)	Suspension Chain	#GAS806850	21)
Bushing 3/8 x 1/4	#GAS806920	31)	Nylock Nut M 6	#GAS806855	22)
Hose Socket 3/8m 90 degree	#GAS806925	32)	Slide bracket - Gasket Plate	#GAS806860	23)
Sensor Bracket	#GAS806930	33)	Screw M6 Gasket Plate	#GAS806865	24)
Sensor Clamp	#GAS806935	34)	Wing Nut M6 Gasket Plate	#GAS806870	25)
Burner Pipe Support	#GAS806940	35)	Burner Pipe Support	#GAS806875	
Pilot Gas Pipe	#GAS806945	36)	Nut M6	#GAS806880	26)
Igniter 26 V/AC	#GAS806975	37)	Lock ring M 6	#GAS806885	27)

Shenandoah Shen Beam

- 42,000 BTU
- · Canopy not included



Shenandoah Shen Glow

- 42.000 BTU
- · Canopy not included



#AGL52102001Pilot / Individual - RS1105

#AGL52104000 Direct spark/Zone

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Shenandoah Brooder Parts



Cone Insulation - Shen Beam & Glow

#AGL11000030no flange



Hybrid Burner Assy - Shen Beam & Glow

#AGL31031061LP



Spark Ignitor - Shen Beam

#HS851.....50" cord



Orifice - Shen Beam & Glow

#AGL11010215#48 (LP) #AGL11010210#37 (NG)



Aluminum Tube - Shen Beam & Glow

#HS657......3/8" x .0345 x 32" **#HS639** 1/4 x .032 /per ft



Ignition Control Board - Shen Beam

#AGL16-550683......DSI



White Rodgers Valve -Shen Beam #AGL11001238.......DSI



Universal Transformer - Buck Boost

#250SV43BSquare D .25KVA 12/24 #FPESB12N-250F.....Federal Pacific .25KVA #G0863545 ... ACME 120/240V-In 12/24V-Out .25KVA #KT1H275 ACME 120/240V to 24V .50KVA (500VA)

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pilot Shield - Shen Glow

#AGL 16-10397......Vertical Pilot Shield #AGL28024042 Pilot Shield

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pilot Orifice - Shen Glow

#AGL11002205 Large Body #78 (LP) #AGL11002203.....Large Body #73 (NG)

⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pilot Orifice

#AGL11000205.....#78 (LP) #AGL11000203 #73 (NG)

⚠ WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Burner Orifice

*For Sibley pancake convection #\$1101-0223.....#52 (LP) #AGL11010218#43 (NG)

⚠WARNING:

Shenandoah Brooder Parts

Select your choice of canopy to complete the brooders!



#AGL11011008	34" galvanized
#AGL21000033	
#AGL16-10398	46" galvanized
#AGL11014053	46" aluminum

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Brooder Covers

· Constructed of 8x8 clear poly

• Attaches with included tie rope to protect brooders from dust and dirt between use.

#BROODCVR20	20"	cover
#BROODCVR34	34"	cover
#BROODCVR46	46"	cover




⚠WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Backup Zone Control

#AGL45104115Backup Zone Control



Ceramic Radiant

* for Sibley pancake convection

#AGL18005057.....Ceramic

Gauging Bits

Universal Thermo


#HS658-48	Bit Drill Gauging #48
#HS658-52	Bit Drill Gauging #52
#HS658-73	Bit Drill Gauging #73
#HS658-75	Bit Drill Gauging #75
#HS658-77	Bit Drill Gauging #77
#HS658-78	Bit Drill Gauging #78
#HS658-79	Bit Drill Gauging #79
#HS658-80	Bit Drill Gauging #80

NARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Pilot Orifice Cleaning



#PPV12-414.....

watch video

#PPV-12......Pen vise with 12 needlesReplacement needles (12 pk)

Shenandoah/Chore-Time Quad Heater



Igniter

#AGL16550135w/ burner mount and wire



• 5 PSI

#AGL16000058 no terminals



Replacement Channel Board Kit

*Includes module and Harness

#AGL16550153 120V





Gas Hose • 1/4" ID X 3/8"

#AGL160500558' Long



Orifice

#AGL16550326 #61 (NG)



Solenoid Valve

#AGL16550137 with terminal clips



⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Now improved with Stainless Steel burner, water resistant ignition control and dual fuel gas valve. 40,000 BTU brooders available in pilot, direct spark and zone models.

#GRO40-CR-L5N5	Direct Spark Ignition (LP & NG)
#GRO40-CR-L5N5-1	Direct Spark Ignition (120V version)
#GRO40-CR-L2	Pilot Zone, LP
#GRO40-CR-L3	Pilot Modulating Control, LP
#GRO40-CR-L9	Pilot Individual Control, LP
#GRO40-CR-N2	Pilot Zone Control NG Rad Alum Canopy CR
#GRO40-CR-N9	Pilot Ind T Stat Control NG Rad Alum CR
#GRO40-CR-B9	Pilot Ind T Stat Control P & B Mix



MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Tru40™

High Pressure Radiant Gas Brooder

- 40.000 Btu
- · Direct Spark Ignition no standing pilot
- Stainless steel burner and emitter

#GRO40I-L5HPAL35	High Pressure, Insulated, LP
#GRO40I-N5HPAL35	High Pressure, Insulated, NG



WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

LoPro[™] Low Profile Brooder

- Low 13" profile ideal for low ceiling houses
- Stainless steel burner
- · Direct spark ignition

#GFPLPBH40-L5	40,000 Btu, high pressure, LP
#GFPLPBH40-N5	5 2
#GFPLPBL42-L5N5	42,000 Btu, LP & NG






Zone Control Panel


A power supply control which utilizes a 375VA transformer to provide the required 24VAC for single or multiple groups brooders. Controls up to (25) 40,000 Btu brooders. Galvanized housing.

#GRO1119 24V Zone Control Panel

⚠ WARNING:



Key	Item#	Description	GR040-L2	GR040-L3	GR040-L9	Key	Item#	Description	GR040-L2	GR040-L3	GR040-L9
1)	#GRO1035	#8-32 x 1/2" Pan Head Screw	-	2	2	29)	#GRO1073	1/2" MPT x 3/8" Tube Fitting (USA Style)	1	-	-
1a)	#GRO1040	#8-32 Hex Locknut	2	4	4	30)	#GRO1064	3/8" Compression Sleeve (USA Style)	1	1	1
2)	#GRO1037	#12-24 Hex Nut	1	1	1	31)	#GRO1066	3/8" Compression Nut (USA Style)	1	1	1
3)	#GRO1051	#12-24 x 1/2" Hex Head Screw	1	1	1	32)	#GRO1085	Main Burner Tubing, 3/8"	1	1	1
4)	#GRO1039	1/4–20 Hex Locknut – Keps	7	7	7	33)	#GRO1086	Pilot Burner Tubing, 1/4"	1	-	-
5)	#GRO1044	1/4-20 x 5/8" Hex Head Screw	2	2	2	34)	#GRO1087	Pilot Burner Tubing, 1/4"	-	1	1
6)	#GRO1050	1/4-20 x 2" Eyebolt (includes nut)	1	1	1	35)	#GF30641060	Gas Valve, RobertShaw NG	1	-	-
8	#GRO1041	#10-24 x 3/8 Pan Head Screw	2	2	2	36)	#GF43648330	Valve Kit, LP	1	-	-
9)	#GRO1036	#10-32 x 1/4" Pan Head Screw	1	1	1	37)	#GRO1076	Gas Valve, SIT #0630501, NG & LPG (w/plug) –	-	1
10)	#GRO1049	#M8 Flat Washer	8	8	8	37a)	#GRO1052	Gas Valve, SIT #0630501, LPG (w/min. rate screw) –	1	-
11)	#GRO1045	#M5 x 35mm Hex Head Screw	3	3	3	37b)	#GRO1053	Gas Valve, SIT #0630501, NG (w/min. rate screw	7) –	1	-
12)	#GRO1046	#M5 Hex Nut	3	7	7	38)	#GRO1054	3/8" MPT x 3/8" Tube Fitting Elbow	<i>J</i> –	1	1
13)	#GRO1047	#M5 Flat Washer	3	7	7	39)	#GRO1103	Pilot Assembly Complete, LPG	1	1	1
14)	#GRO1048	#M5 Spring Lockwasher	4	4	4	40)	#GRO1104	Pilot Assembly Complete, NG	1	1	1
15)	#GRO1062	Cable Clamp 5/16" ID	-	2	2	41)	#GRO1105	Pilot Housing Sub-Assembly	1	1	1
16)	#GRO1089	Emitter Assembly	1	1	1	42)	#GRO1102	Pilot Housing - Outer	1	1	1
17)	#GRO1088	Burner Cap	1	1	1	43)	#GRO1106	Pilot Windshield - Perforated	1	1	1
18)	#GFP44464050	Burner Base Assy (w/swivel clamp)	1	1	1	44)	#GRO1067	Pilot Orifice Holder, 1/8 NPT x 1/4 Tube	e 1	1	1
19)	#GRO1081	Reflector Canopy - Aluminum	1	1	1	45)	#GRO1059	Pilot Orifice (#79), LPG	1	1	1
21)	#GRO1096	Low Profile Hanging Bracket	1	1	1	46)	#GRO1058	Pilot Orifice (#76), NG	1	1	1
22)	#GRO1083	Burner Pan (center mounted)	1	1	1	47)	#GRO1063	1/4" Compression Sleeve (USA style	e) 1	1	1
24)	#GF43982030	V-Clamp (manifold support)	1	1	1	48)	#GRO1065	1/4" Compression Nut (USA style)	1	1	1
25)	#GRO1057	Main Burner Orifice (1.9mm) - LP Gas	1	1	1	49)	#GRO1061	1/4" Break-Away Fitting (gas valve end	l) 1	1	1
26)	#GRO1055	Main Burner Orifice (#31) - Natural Gas	s 1	1	1	50)	#GRO1080	Thermocouple, 36" Snap-In	1	1	1
27)	#GRO1056	Main Burner Orifice (#50) - LP/Butane Gas	s 1	1	1	51)	#GRO1092	Installation Manual (not shown)	1	1	1
28)	#GRO1084	Main Burner Orifice Fitting Sub-Assy	v 1	1	1	52)	#GRO1090	Kit, Complete Fastener (not shown)	1	1	1



GRO40-CR-N5 & GRO40-CR-L5 Parts List

Verr	Tt a ma #	Description	TDD4OCD E Otto	Vorr	Tt a m #	Description	DD4OCD E Otto
Key	Item#	Description S	SRB40CR-5 Qty	Key	Item#	Description SF	RB40CR-5 Qty
1)	#GFP02345010	Pan Head Screw #4-20X5/8" Plastite	2	28)	#G3601020	Nut Compression 3/8" Usa Style	2
2)	#GFP02337010	Pan Head screw #6-19 X 1/4" Plastite	2	29)	#GRO1085	Tubing Main Burner 3/8" For GRO40	1
3)	#GFP02174150	Pan Head Screw #6-32 X 1/2"	2	30)	#GFP4451100	Junction Box Complete Plastic	1
4)	#GFP02168160	Pan Head Screw #10-24 X 7/8"	3	31)	#GFP44452100	O-Ring Gasket Junction Box	1
4a)	#GFP02336010	O-Ring Retainer	2	32)	#43536190	Bracket, Box Support for CR Version	1
5)	#GRO1108	PHMS #10-24 x 3/8" SS	5	32a)	#GFP43536210	Brace, Box Support	1
6)	#GFP02259000	Hex Head Screw 1/4-20 X 5/8" SS	3	33)	#GF44468050	Bracket Electrode for the CR Version	1
7)	#GFP02167019	Hex Nut - 1/*4-20 Keps SS	9	34)	#HS648	Igniter Spark For Direct Spark Brooder	1
8)	#GFP02167029	Nut for GRO40 CR Emitter (6 Per Brood	der) 8	35)	#GRO1077	Module Ignition Direct Spark Brooder	1
9)	#GFP02129100	Washer Flat 1/4" SS	8	36)	#GRO1078	Cable Ignition 35" Spade/Spark Plug GRO40 DSI Bro	
10)	#GFP02309010	Eyebot 1/4-20 X 2 Includes One Nut	1	37)	#G30279000	Transformer For Space Ray Tube Heate	r 1
11)	#GFP40219520	Spacer Bolt Stainless	3	38)	#GF30753000	Valve White Rogers for CR version (15N	(118) 1
12)	#GF43525250	Emitter Assembly Less Burner Cap	1	39)	#GFP43444010	Wire Harness From Ignition Module	2
13)	#GFP44465060	Burner Cap .Srb40 Stainless CR Version (43309	9000) 1	40)	#GFP30739020	Terminal Block 3 Pole	1
14)	#GFP44464050	Burner Assy Stainless CR Version	1	41)	#GRO1079	Connector Cord 1/2"	1
15)	#GRO1081	Canopy Reflector Aluminum	1	42)	#GFP30381010	Switch, Rocker - SPST Power on/off	1
17)	#GF43826030	Low Profile Hanging Bracket (w/ eyebolt) CR Ve	ersion 1	43)	#GRO1069	Tie Wire GRO40	3
18)	#GF43304040	Burner Pan-Center Mount - SS	1	44)	#GFP43539260	Installation Manual	1
19)	#GFP43983030	Manifold Support Assy Radiant Shield	. 1	45)	#GF43534100	Fastener Kit SRB40CR	1
20)	#GFP43982030	V-Clamp Manifold Support	1	46)	#GFP43269000	Label 24 Volt Supply	1
21)	#GRO1057	Orifice Main Burner 1.9MM LP Gas	1	47)	#GFP43311100	Label Lighting Instructions	1
22)	#GF03259330	Orfice Burner 7/16-27 #33 NG L5 to N	15 1	48)	#GFP43623190	Label Wire Connections	1
23)	#GRO1056	Orifice Main Burner 50 LP Butane Gas	1	49)	#GFP43269120	Label Torque Setting Flip/Flop Regulator Sc	rew 1
24)	#GF43305980	Main Burner Orifice Fitting (CR Version	n) 1	50)	#GFP43311210	Label Nameplate Rating Plate	1
25)	#GFP43311930	Label Holder Plate for the CR Version	1	51)	#GF43311180	Label Hazard/Caution for the CR Versio	n 1
26)	#GFP3602070	Fitting Male Coupler 68EEE	1		#GFP43523408	Control Arm Complete /w/ Gas Valve	-
27)	#GRO1064	Sleeve 3/8" Compression USA Style	2		#GFP44170060	Control Box Package DSI	-



The GroTube is an energy efficient, push through radiant tube system with these unique features:

- Choose from either Calorized aluminized steel emitter tube for greater corrosion resistance or standard cold-rolled steel
- · Available in either natural or propane gas models
- Diagnostic lights indicate when the heater is operating and provide a unique "troubleshooting" feature
- \bullet Available in BTU ratings from 75,000 to 150,000 and many lengths to choose from
- · Heavy cast iron burners for longer life
- Can be used in either vented or unvented styles of installation
- TISS (Tube Integrity Safety Shut-Off System) is a patent-pending safety feature that automatically shuts off the heater in the event of a tube failure.


Available in Single or 2-Stage Models!

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Radiant Tube Brooder






Infared photography shows the Big Foot™ Radiant Tube Brooder's large, even heat pattern at litter level



Big Foot's unique design produces a large rectangular heat pattern. Big Foot's wide heat pattern keeps water and food areas warm for easy bird access



The 19° angle of the reflectors is designed to direct energy down directly to floor level where it's needed.

Single Stage

#GFPBF60-15-N5	60,000 SS NG 7.5' Overall 15' Tube
#GFPBF60-20-L5	60,000 SS LP 10' Overall 20' Tube
#GGFP44461030	60,000 SS NG 10' Overall 20' Tube
#GFPBF70-15-L5	70,000 SS LP 7.5' Overall 15' Tube
#GFPBF70-15-N5	70,000 SS NG 7.5' Overall 15' Tube
#GFPBF70-20-L5	70,000 SS LP 10' Overall 20' Tube
#GFPBF70-20-N5	70,000 SS NG 10' Overall 20' Tube
#GFPBF80-20-L5	80,000 SS LP 10' Overall 20' Tube
#GFPBF80-20-N5	80,000 SS NG 10' Overall 20' Tube
#GFPBF90-20-L5	90,000 SS LP 10' Overall 20' Tube
#GFPBF90-20-N5	90,000 SS NG 10' Overall 20' Tube


Two Stage

60,000 2S LP 7.5' Overall 15' Tube
60,000 2S NG 7.5' Overall 15' Tube
60,000 2S LP 10' Overall 20' Tube
60,000 2S NG 10' Overall 20' Tube
70,000 2S NG 7.5' Overall 15' Tube
70,000 2S LP 10' Overall 20' Tube
80,000 2S LP 10' Overall 20' Tube
80,000 2S NG 10' Overall 20' Tube
90,000 2S LP 10' Overall 20' Tube
90,000 2S NG 10' Overall 20' Tube

GROTUBE Heater

Key	Item#	Description	QTY
1)	#GFP02295040	PHTCS #6-32 x 3/8"	3
1a)	#GFP02266010	Speed Clip (for air inlet plate)	2
2)	#GFP02261030	HHTCS #8-32 x 3/8" (green coated)	1
3)	#GFP02242050	PHTCS #8-32 x 3/8"	5
4)	#GFP02150200	HHMS #8-32 x 3/4"	2
5)	#GFP02167010	Locknut 1/4-20 Keps	5
5a)	#GFP02309000	Eyebolt 1/4-20 x 2	1
6)	#GFP02167040	Locknut #8-32 Keps	9
7)	#GFP02212020	HWHSMS #8 x 1/2" B Point (typical all access panels)	45
8)	#GFP02132020	Rivet 1/8"	14
9)	#GFP44139990	Housing Assembly (welded)	1
9a)	#GFP44140111	Valve Holder Plate	1
10)	#GFP44140000	Access Panel (top)	1
11)	#GFP44140040	Access Panel (hinged)	2
11a)	#GFP02201070	Hinge 1-1/16" x 6"	2
12)	#GFP44140058	Access Panel (LH burner end) with sight glass	1
13)	#GFP44140090	Access Panel (RH burner end)	1
14)	#GFP441400	6x Combustion Air Plate	1
15)	#GFP42700500	Burner, Investment Casting - Machined	1
16)	#GFP44146030	Manifold Support Bracket	1
17)	#GFP44146040	Manifold Support Clamp	1
17a)	#GFP44146050	Manifold Extension Bracket	1
18)	#GFP30703000	Blower Assembly	1
19)	#GFP30632500	Spark Module - Fenwal-24V #35-615935-197	1
20)	#GFP30702010	Flame Sensor #PSE-GF24	1
21)	#GFP30702020	Electrode #PSE-GF25	1
22)	#GFP30281000	Terminal Block #EK-204	1
,	#GFP30717000	Terminal Block #EF-10001 (24V thermostat connection)	1
,	#GFP30713000	Fuse Holder	1
22c)	#GFP30202000	Fuse 1/4" x 1-1/4" (2 amp)	1
23)	#GFP30279000	Transformer 120v-24V 20VA	1
24)	#GFP02175020	Strain Relief #SR-6P3-4 (ignition cable)	1
25)	#GFP02175060	Strain Relief #SR-2M-1 (flame sensor wire)	1
26)	#GFP30514020	Grommet .250ID #739 (air sensing tube)	1
26a)		Split Bushing #2871 (misc. wiring, ignition cable, sensor wire)	2
27)	#GFP30700040	Grommet, Pipe Sealing 1/2" #63595K34	1
28)	#GFP42447000	Sight Glass (1-5/8" square plexiglass)	1
29)	#GFP42744079	Air Sensing Tube Asm. (straight) 1/4"od	1
30)	#GFP42744069	Air Sensing Tube Asm. (90 deg bend) 1/4"	1
31)	#GFP30635030	Cord Connector 1/2 #LPCG50	1
32)	#GFP03988100	Plastic Vacuum Air Tube 10" (P2- to static pressure point)	1
33)	#GFP03988100	Plastic Vacuum Air Tube 10" (P1+ to total pressure point)	1

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov




Key	Item#	Description	QTY
35)	#GFP42709000	Shield, Terminal Block	1
36)	#GFP42395010	Gasket, Blower	1
37)	#GFP03946010	Sealing Strip 1/8" x 3/8" wide (access panels) -not shown	Ft.
38)	#GFP42752250	Air Inlet Screen	1
38a)	#GFP30504040	Starting Collar (combustion air inlet)	1
39)	#GFP30701240	Ignition Cable - Female (2) 1/4" QC x 24"lg #PSE-GF23 - not shown	1
40)	#GFP44145060	Manifold Pipe 6-1/4 lg	1
40a)	#GFP03333140	Pipe Nipple 4 lg	1
41)	#GF44010270	Valve Kit, Single Stage, NG	1
41a)	#GF44010400	Valve Kit, Single Stage, LP	1
42)	#GF44010390	Valve Kit, Two Stage, NG	1
42a)	#GF44010400	Valve Kit, Two Stage, LP	1
43)	#GFP03259	Main Burner Orifice #7/16-27"	1
44)	#GFP42741150	Air Restrictor Plate 2-3/4"	1
46)	#GFP42398030	Monitoring Light Amber (gas valve operation)	1
47)	#GFP42398150	Monitoring Light Red (air switch operation)	1
48)	#GFP30186260	Air Switch (set point @ .65WC) GROTUBE PC75 & 100	1
48a)	#GFP30186270	Air Switch (set point @ .34WC) GROTUBE PC125 & 150	1

GROTUBE Body Components

34)

Key	Item#	Description
1)	#GFP02266010	Reflector Speed Clip
2)	#GFP43980010	Wire Hanger
3)	#GFP42873000	U Bolt Clamp, 4 OD Tube
4)	#GFP02127110	5/16-18 Hex Nut (2 per U Bolt)
5)	#GFP43318000	Tube Support/Hanger Bracket, 13"
6)	#GFP43319100	Reflector, 9' - 11-1/2 " long
		(10' section only; 1 per 10 ft. body section)
7)	#GFP43320000	End Reflector
8)	#GFP42921000	Tube Flange Gasket
9)	#GFP44028170	10' Tube Assembly Kit, 4 OD, ATC steel with
		one 6-hole flange (start tube)
10)	#GFP44028100	10' Tube Assembly Kit, 4 OD, HRS steel
		w/o flanges (extension tube)
11)	#GFP44028060	10' Tube Assembly Kit, 4 OD, ALC steel
		w/o flanges (extension tube)
12)	#GFP02189020	#10 x 1/2 Self-Drilling Screw
13)	#GFP30462980	4 OD Tube Compression Coupling w/bolts
14)	#GFP43208020	4 OD U-Bend (optional
15)	#GFP43488000	U-Bend Reflector (optional)
16)	#GFP30504500	Flue Adapter Collar
17)	#GFP44152240	Turbulator

#GFP43563040 Supply Cord -Flat (SPT-1 18/3 x 72" long)





Sentinel® v.2


- 40 foot and 50 foot tube lengths
 Heat output ratings from 125,000 to 150,000 Btu/h
 Natural gas or liquid propane gas models
- Choose from single stage or two stage models
- Dependable spark ignition
- Other Sizes Available

#LB125CSND220140	125,000 Btu, 40', Sg Stage, NG
#LB125CSND220141	125,000 Btu, 50', Sg Stage, NG
#LB125CSPD210140	125,000 Btu 40', Two Stage, LP
#LB125CSPD220140	125,000 Btu, 40', Sg Stage, LP
#LB125CSPD220141	125,000 Btu , 50', Sg Stage, LP




WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#LB150BSPD210141	150.000 Btu. 50'. Two Stage, LP
#LB150CSND220142	
#LB150CSND220198	
#LB150CSPD220142	, , , , , , , , , , , , , , , , , , , ,
#LB150CSPD220198	



Replacement Parts

Key	Item#	Description
1	LB572892	Air turbulation strip (2 for Oval 80 and 3 for Sentinel)
2	LB573970	Vent Cap, AT
	LB573971	Vent Cap, AR
3	LB573011	Tube, calorized, 4 in. x 10 ft., with clamp, (All other Sentinel)
	LB572894	Tube, calorized, 3 in. x 10 ft., with clamp, Oval 80
4	LB573011	Tube, calorized, 4 in. x 10 ft. round w/ clamp, Sentinel
	LB572893	Tube, oval with clamp, Oval 80
5	LB573009	Clamp, 4 in., round, Sentinel
	LB572842	Clamp, 3 in. round, Oval 80
6	LB573004	Hanger, 4 in. round tube
	LB572852	Hanger, 3 in. round tube
7	LB572870	Hanger, oval tube
8	LB572868	U-clips (4)
9	LB572869	End cap with 4 u-clips
10	LB572895	Reflector, with end cap and u-clips



Replacement Parts

Key	Item#	Description
12	LB573775	Latches and strike
13	LB573769	Red LED
14	LB573770	Green LED
15	LB573681	Wire harness
16	LB500-24972	Ignitor with bracket
17	LB572847	Ignition cable
18	LB573682	Air differential pressure switch
19	LB572883	Tube, air differential pressure switch
20	LB573946	Ignition Control
21	LB573697	Transformer
22	LB573006	Gasket, burner
24	LB573774	Gas control valve, LPG
	LB573773	Gas control valve, NG
25	LB572860	Motor
26	LB572864	Fan Wheel
27	LB572865	Power cord with connector
28a	LB550-20713	Hose, 6 ft., 1/2 ID. w/adapter, rigid x swivel, Sentinel
28b	LB550-21994	Hose, 6ft., 3/8 ID. w/adapter, rigid x swivel, Oval 80
29a	LB500-25873	Adapter, 1/2 NPT x 1/2 NPS, Sentinel
29b	LB573804	Adapter, 1/2 NPT x 5/8-18 UNF-2A, Oval 80
30	LB550-06553	Regulator, second stage, propane gas
	LB500-24414	Regulator, second stage, natural gas
31	LB574233	Fan housing
N/S	LB572896	Complete gasket kit for burner box



Alpha Series Heaters produce short wave length infrared that convert 85% of consumed energy to instant, controllable, directional heat.

Solaira Alpha Series electric infrared heaters offer a practical solution to heating enclosed areas without dangerous gas emissions. Perfect for stables, kennels, garages, and wash bays. Alpha Series Heaters are engineered to meet IP55 standard for water spray so they can be installed in both wet (outdoor) and dry conditions (indoor or outdoor).

- · Powder coated aluminum body and mounting brackets, stainless accessories
- · Indoor or outdoor rated for wet or dry conditions
- Rain, snow and spray resistant
- No co2 or nox emissions
- Up to 8,000 hour emitter life





Solaira™ Smart Heater Controls


Solaira Smart controllers allow users to variably control Alpha electric heater output to maximize comfort levels.

DUAL VOLTAGE 34 and 16 AMP Variable control

- 34 AMP unit will control up to 6.4kW @208/240V and 3.2kW @120V
- 16 AMP unit will control up to 3.2kW @208/240V and 1.6kW @ 120V

SMART34-DV	mp
SMART 16-DV	mp

					Minimum Height	
Item#	Description	Total Watts	Voltage	Amps	from Floor	Color
SALPHA 15120S	H1 - Single Emitter	1500	120	12.5	79"	Silver/Grey
SALPHA15240S	H1 - Single Emitter	1500/1125	208-240	6.3/5.4	79"	Silver/Grey
SALPHA20240S	H1 - Single Emitter	2000/1500	208-240	8.3/7.2	79"	Silver/Grey
SALPHAH2-30240S	H2 - Double Emitter	3000/2250	208-240	12.5/10.8	98-1/4"	Silver/Grey
SALPHAH2-40240S	H2 - Double Emitter	4000/3000	208-240	16.7/14.4	98-1/4"	Silver/Grey
SALPHAH3-60240S	H3- Triple Emitter	6000/4500	208-240	25/21.6	120"	Silver/Grey



Poly Lamp

Durable polypropylene lamps will not corrode or dent and flexible sides cushion bulbs from breakage. Polypropylene formulation contains UV stabilizers for longevity. Poly Lamp carries an UL listing. 120-volts with 250-watt maximum rating. Extended three-year warranty.



MARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Nine-foot, ungrounded cord set includes poly hanger clip and the shade includes a wire hanger for additional hanging options. Also available with 12' cord set.



Two-piece fixture screws together on the shade top, instead of bolting, to reduce breakage. Rigid nylon fixture eliminates cord twist when replacing bulbs and the porcelain socket resists heat damage better than plastic.

#HS664	Poly Lamp, 18 AWG, 9' cord
#HS664E	Poly Lamp, 18 AWG, 12' cord
#HS664-CN	Poly Lamp, 230 Volt
#HS664HW9	Poly Lamp, 16 AWG, 9' hardwired
#HS664HWA	Poly Lamp, 16 AWG, 12' hardwired
#HS664-1	Plastic Shade
#HS664-4	Metal hanger
#HS664-5	Plastic hanger
#HS664-9	Cord Set Assy, 18 AWG, 9' cord
#HS664-12	Cord Set Assy, 18 AWG, 12' cord
#HS664-12HWA	Cord Set Assy, 16 AWG, 12' hardwired
#HS664-9HW	Cord Set Assy, 16 AWG, 9' hardwired
#HS664-9HW18GA	Cord Set Assy, 18 AWG, 9' hardwired
	•



Hog Slat® Poly Heat Lamp Shade



Hog Slat® Poly Heat Lamp Cord Set Assembly





Hog Slat® Poly Heat Lamp Plastic Hanger



Monoflo® Heavy Duty Heat Lamps

- · Aluminum spun shade, 20% thicker
- 22 gauge with satin finish
- Separate hanger clip
- Heavy gauge aluminum basePorcelain socket and 10' cord
- · Flexible rubber cord and mounting hook
- Sturdy bulb guard protects animal from bulb while base distributes heat evenly

Heat Lamp Kit (replacement)

- Fully enclosed socket housing with retaining ring
- Spring loaded center contact post
- Brass connecting stud screws & nuts

• 3 prongs with ground optional



Adjusta Heat

- Extra heavy-duty high-impact polypropylene housing

 • Adjustable bulb height built
- into housing
- · Hanger attaches to housing
- UL Approved
- 2-Year warranty

#ADJHEAT	complete w/ 8' cord
#ADJHEAT-12	complete w/ 12' cord



Cord with Socket and Handle Complete

#ADJHANDLECORD88'




Cord with Socket only

#ADJELCORD8	8′
#ADJELCORD12	12′



Plastic Handle Housing

#ADJHANDLE Includes hardware



Hanger

#ADJHEATHANG...... Wire hanger



Shroud

#ADJSHROUD.....Plastic



Heat Bulbs

Infrared clear bulb, 120-volt with brass medium screw

#HS54413	125 Watt Bulb
#HS54412	250 Watt Bulb



Dimpled Heat Bulbs

Heavier glass construction with dimpled face.

#HSHBD-125	125	Watt E	Bulb
#HSHBD-175	175	Watt F	Rulh



- Dimpled face
- Heavier glass construction
- Energy saving 100 & 175 wattage
- **#54415**......175 Watt Bulb



PHILIPS Heat Bulbs

- Uses 30% less energy
- Hard-dimpled glass
- · Rugged construction with medium brass base built to resist water & shock
- 5,000-hour rating
 Long-life usage at 120 V
- Dimmable output
- Adjust it to your application's needs

#544132 Philips Heat Bulb, 175 W



Stanfield® Heat Pads

Delivering safe, efficient heating to animals since 1973

- · Tough, wear resistant fiberglass reinforced composite pad
- 10' power cord
- 120 Volt
- · Order Cord Shield OFH-OOF152 with heat pads as extra protection for power cords.



1-Litter Farrowing Heat Pads

#OFH-RS1B30-1.	1 x 3 ft., 80 W
#0FH-RS1R40-1	1 x 4 ft 100 W



2-Litter Farrowing Heat Pads

#OFH-RS2B30-1	2 x 3 ft., 160 W
#OFH-RS2B40-1	2 x 4 ft., 200 W



24-inch Cord Protector

#OFH-00F152	24" Cord Protector

Mat Controls

For use in controlling heat mats in dog kennels and whelping pens. Not for use in highly corrosive areas.



KMHR 300

- Dial-A-Temp
- · Manual variable control of heat pads
- #KHMR-300 300 W 110 V

Kane Heat Mats

- Easy-to-clean, durable Polyethylene construction
- 120 Volt
- · Includes power cord

Single Heat Mats


#PHMS36	13.5" W x 36" L, 65 watts
#PHMS60	13.5" W x 60" L, 84 watts
#PHMS45	18" W x 45" L, 115 watts
#PHMS57	18" W x 57" L, 127 watts

Double Heat Mats

#PHMD60.......27" W x 60" L, 216 watts



TD-30 Thermostat



- · Touch button control
- · Energy-saving fixed 2° differential
- Temperature alarm wit internal buzzer

#KTD-30 Kane heat mat control

MicroZone

Lamp & Mat Control

MicroZone controls allow you to reduce energy consumption and provide more consistent heating levels for piglets.

- · Self-adjusting, 0-100% variable power output
- Programmable temperature ramp
- · Control is protected against transient voltage spikes, thermal overload and short circuits in heating devices
- · Compact, corrosion and water-resistant housing
- · Can lower electricity costs by 30% or more





Power Supply - 110V

Power supply provides the low voltage power to the MicroZone controller.

.....Power Supply



Power Modulator

Power modulator regulates the power going to the heat lamps or mats in response to commands from the MicroZone controller

#MPM100.....



Temperature Sensor

Replacement sensor

#TS3.....Temp Sensor



Slat Mats

 A high density plastic mat that is placed under the feeder to protect new slats or stop concrete erosion on older slats.

#HS10064	46-3/4" x 3'
#HS10065	46-3/4" x 4'
#HS10066	46-3/4" x 5'
#HS100655	46-3/4" x 6'



Gro-Loc Fasteners

- \bullet Complete assembly includes 3/8" x 4" stainless steel bolt & washer
- · Remains firmly locked and can be retightened
- Packaged in boxes of 100

#GRO-LOC Gro-Loc fasteners

* Excessive torque on this product may cause slat damage

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





PolvMAT

Lightweight 4' x 6' weaning mat weighs only 17 lbs. Non-porous polyethylene construction features diamond-shaped pattern for superior traction. Also formed with a 1" feed saver lip to prevent loss of expensive starter feed.

#PM-1PolyMAT wean/finish mat 3' 9-1/2" x 6'



Rubber Wean to Finish Mats

- · Reduce mortality
- Keep pigs dry
- Provide great traction
- Easy to clean
- 48" wide x 72" long with a 1/2" tall feed saver lip
- 4 reinforced hand holds are bordered by a 1/4" tall lip to prevent loss of expensive starter feeds
- Can be hung by hand holds to simplify storage
- Provides a comfort area for up to 35 pigs

#544187F......48" x 72", 1/2" lip



Mat Hanger

Neatly stores mats up out of the way between groups. Galvanized steel construction with braces to rafters. Hanger brackets are 17" apart.

#2040770100Mat Hanger



Rubber Wean Mats

- Perfect for starting young piglets on feed
- 39" x 39" with 1/2 inch lip & handles

#544186F......Wean to finish mat



Rubber Creep Mats w/o Lip

100% rubber creep mats with extended creep panel tabs and no lip around the edge. Raised ribs provide additional traction for young pigs.

#544189F	48"	Х	42"
#54418F			



Rubber Creep Mats w/ Lip

- Raised tabs to keep them from moving
- Rugged mat can also be used in nursery
 Premium rubber mats with interwoven fibers
- **#54417F**.......28-1/4" x 40" w/feed saver lip





Use as a top coating on new or repaired slats instead of plastic mats around feeders and waterers. The

deeders and waterers. The Armor-Rock Kit will get you started: 1.5 lbs of two part epoxy, 25 lbs. of Admix sand and 25 lbs. of broadcast topping sand.





Before. After. #AC133-AR Armor-Rock Kit



Flex Barn End Door System

Choose from either the V-Flex top opening or S-Flex side opening doors:

- · Welded steel frame
- "Quad Wrap" dead air space insulation
- · Weighs approximately 200 lbs.
- Rubber seal assures tight fit, tightness increases as fans come on.
- · Includes hinges and 6" spring latch closure





S-Flex door allows Hand Operation without winches



Both models open without obstructions and are available in variety of exterior materials.

...... 12' x 9' open to the side Metal door



Door Panels

Door cover panels reduce drafts and improve static pressure. Features two heavy-duty, rust-proof nylon zippers on the sides. Center flap rolls up for storage during warm weather. Standard sizes 10' High x 12' and 14' wide. Can be ordered in custom sizes

#5224111	10'	Х	14′
#DHBW1213-R2Z	10'	Х	12'



STURDY <u>SEAL</u>

Eagan Bi-Fold End Door

- · Significant energy cost savings.
- · Excellent sealing capability.
- Polyurethane foam injected door panels with an R-7 insulation value.
- Door comes complete with all necessary hardware.
- Skin on the back side of the door is black to aid in room darkening.
- Quality product that will last for many years to come.
- Very easy to operate.







*Available in 10', 12' and 14' widths



Hired-Hand Automated RollSeal Door System RS-300

Features Include:

- · Standard sizes up to 13' wide and 14' tall
- · Aluminum tracks and covers
- RollSeal patented seal system, 3 ply fabric, double seal with dead air space for good thermal insulation
- Excellent seal for pressurization applications
- · Additional switches and opening devices
- Remote transmitter/receiver option
- Three operators to choose from:
- Manual chain hoist operator
- Tube motor operator
- Manaras opera continuous duty operator
- Fabric and window options


#H6621-6107	Roll Seal Door Complete 12' W x 10' H
#H6421-6024	Roll Seal 300 Track Right Assy 10'
#H6421-6025	Roll Seal 300 Track Left Assy 10'
#H6450-3502	Velcro Complete Kit For RS-300 Roll Seal 10'
#H6421-9304	Roll Seal Panel RS-300 400 F Velcro 10' Right
#H6421-9305	Roll Seal Panel RS-300 400 F Velcro 10' Left




A Hog Slat exclusive, the Barngard Door™ series has proven to deliver value beyond what is available in the marketplace.

The advanced technology and flexible platform of the Barngard DoorTM series continues to deliver value. Featuring adjustable weatherstrips, header sweep and still sweep. The precision folded jambs, baked bright white finish, $4^{\prime\prime}$ x $4-1/2^{\prime\prime}$ hinges and the industry's best warranty are sure to make this door an industry standard for years to come.









#BG882668	
#BG882668W	Door Complete Barngard R88 2'6" x 6'8" Steel W/22" x 22"
	Door Complete Barngard R88 3'0" x 6'8" W/22" x 22" Lite
#BG884068	
	Door Complete Barngard R88 Double Door 6'0" x 6'8"

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Barn Door

Specialty door designed to handle the extreme conditions of the confinement buildings. Insulated foam core is framed with dimensional lumber and both sides covered with a aluminum skin laminated to 3/8" plywood. The edges are capped with a rugged PVC U-channel. Doors are pre-hung with (3) 8" strap hinges on to the 2' x 4' frame and fully weather-stripped. Door slab comes pre-drilled for installation of the Dura Latch.

Now with stainless steel strap hinges.

#2668LSS	30" Left barn door
#2668RSS	30" Right barn door
#3668LSS	36" Left barn door
#3668RSS	36" Right barn door
#MMS3668KI	Barn door trim kit
#1043	8" tee hinge w/ removable pin



Tri-Ply **#844190**52" x 600' roll




Tri-Ply Strapping

#12181661200 1/2" x .018" x 12000', green #844191......1/2" x .026" x 6600', white



#844192	. 4"	Х	165'	white
#844193	4'	′ x	165'	black





#712100 Round Rail Barn Door Track 12 #712101 ... Wheel Kit for Round Rail Track (sold per pair)

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Barn Door Latch

Rugged, simple latching D-style door latch. Adjusts from 1/2" to 2" door slab. Galvanized steel construction with hardware. Great latch for any door or gate. Can be padlocked through handle. Weight: 1.2 lbs.

#806221......Whitcomb 1/2" to 2" door slab #20700027 Latch 3/4" to 2-1/4" door slab

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel Door Latch

The only completely stainless steel barn latch complete with SS hardware. Spring loaded plunger style latch that installs easily to any style door or gate. Fits up to a 2" door slab. Weight: 2.5 lbs.

#8000601501.....Stainless Steel Door Latch

↑ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



This massive built latch is the most dependable barn door latch on the market. Designed specifically for use in confinement buildings and recommended for use with our Barn Door. Electroplate finish that features 6x6 mounting plate and 3/8" thick striker arm. Includes mounting hardware and will fit up to 2" thick door slab. Weight: 6.5 lbs.

#001760Tuff Latch

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Entry Door Locksets

#80621Schlage keyed entry lock set #HE115956 Steel Harbor Economy Grade Satin Nickel #HE803622 ... Kwikset Lockset Keyed Entry Satin Chrome #5805619.....Lock set, SS, 1/4" striker #HH80609.....Lock set, SS ANSI, grade 3

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#HE873013 Universal Door/Gate Latch \$5.28

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Safety Gate Latch Hook

Heavy-duty, self-locking latch prevents livestock from opening doors and gates. 6" long. plated galvanized finish.

#V2120 Safety Gate Latch Hook

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Cam & Jam Latch

Dual purpose latch used to secure sliding doors. Durable galvanized finish with over-center cam style locking

#P188000Cam & Jam Latch

▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Replacement **Knee Braces**

#80611102008" Support Bar, Galv.




Lock formed 26 ga steel in either white or galvanized finish. Bird screened with 1/2" galvanized hardware cloth. Stack height is 13-1/2" above ridge line. 9" throat allows 3 sq. ft. of free opening for the 4' and 7.5' for the 10' models.

#K50300GALV	4' high profile ridge vent, galv.
	4' high profile ridge vent, white
#RV-900	10' high profile ridge vent, galv.
#RV-900W	10' high profile ridge vent, white

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



High Profile Ridge Vents with Damper

Same basic construction as the high profile model with the addition of air flow regulating damper in the 9" throat. Use as exhaust vents on naturally ventilated buildings. Free opening is 3 sq ft. for the 4' model and 6 sq. ft. for the 8' model.

#K50310-WH204'	Ridge vent w/	damper
#RV800D8'	Ridge vent w/	damper

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth detects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Low Profile Ridge Vents 10'

Fully hemmed and formed 26 ga. steel in either painted or galvanized finish. Only extends 3" above the ridge line. Features 3-3/4" nailing flange for an overall width of 16".

#RV35 10' low profile ridge vent, galv #K50020-WH20 ...10' low profile ridge vent, painted

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Galvanized Ridge Vent

Pre-assembled 24" wide x 48" long ridge vent manufactured from G90, galvanized metal. Complete with 1" x 2" welded wire mesh inside to prevent birds from entering the attic.

#844196...... Galvanized Ridge Vent

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Poly Intake / Exhaust Vent

One-piece construction of rugged polyethylene with UV inhibitors, this ridge vent will not rust when used to exhaust warm, moist air in the confinement buildings. Stands 24" high, 36" wide and 48" long. Rated at 3000 cfm exhaust and includes bird screen.

#SRV-3000 Poly Ridge Vent





Save on LP costs with TempShield!

Insulate your curtains and reduce heat loss! TempShield turns a regular vinyl curtain into an insulated curtain!

Item#	Layer Configuration	Roll Size	Usage Suggestions
#MWDBDF3X125	Foil-Bubble-Bubble-Foil	3'x125'	Curtain/Side wall
#MWDBDF3X200	Foil-Bubble-Bubble-Foil	3'x200'	Curtain/Side wall
#MWDBDF4X125	Foil-Bubble-Bubble-Foil	4'x125'	Curtain/Side wall
#MWDBDF4X200	Foil-Bubble-Bubble-Foil	4'x 200'	Curtain/Side wall
#MWDBDF5X125	Foil-Bubble-Bubble-Foil	5'x125'	Curtain/Side wall
#MWDBDF5X200	Foil-Bubble-Bubble-Foil	5'x200'	Curtain/Side wall
#MWDBDF6X125	Foil-Bubble-Bubble-Foil	6'x125'	Curtain/Side wall
#MWDBDF6X200	Foil-Bubble-Bubble-Foil	6'x200'	Curtain/Side wall
#MWDBDF8X125	Foil-Bubble-Bubble-Foil	8'x125'	Curtain/Side wall
#MWDBWF3x125	Foil-Bubble-Bubble-W poly	3'x125'	Curtain/Side wall
#MWDBWF3x200	Foil-Bubble-Bubble-W poly	3'x200'	Curtain/Side wall
#MWDBWF4x125	Foil-Bubble-Bubble-W poly	4'x125'	Curtain/Side wall
#MWDBWF4x200	Foil-Bubble-Bubble-W poly	4'x200'	Curtain/Side wall
#MWDBWF5x125	Foil-Bubble-Bubble-W poly	5'x125'	Curtain/Side wall
#MWDBWF5x200	Foil-Bubble-Bubble-W poly	5'x200'	Curtain/Side wall
#MWDBWF6X200	Foil-Bubble-Bubble-W poly	6'x200'	Cool Cell/Fan
#MWDBWF8x125	Foil-Bubble-Bubble-W poly	8'x125'	Curtain/Side wall
#MWSBDF6x125	Foil-Bubble-Foil	6'x125'	Curtain/Side wall
#MWSBDF7x125	Foil-Bubble-Foil	7'x125'	Curtain/Side wall
#MWSBDF7x200	Foil-Bubble-Foil	7'x200'	Curtain/Side wall
#MWSBWF6x125	Foil-Bubble-W Poly	6'x125'	Curtain/Side wall
#MWSBWF6x200	Foil-Bubble-W Poly	6'x200'	Curtain/Side wall
			i =

Handi-Foam

PROFESSIONAL POLYURETHANE FOAM SYSTEM SAVES ENERGY!



Handi-Foam Tank with Gun

#P11042 Handi-Foam Tank w. Gun

- · Fills holes and blocks access of insects and rodents
- · Bonds to wood, metal, concrete and is paintable
- Comes with 9' hose, 1/4" brass nozzle and wand
- Tack free in approximately 10 minutes
- · Can be trimmed in 1 hour with a full cure in 24 hours



Dispersing Gun



Gun & Hose Kit



Multi-Purpose Cleaner

#P10083......12 oz. Cleaner



Handi-Foam - Black

#P30295......29 oz. can (no gun)



Handi-Foam with Straw

#P30053.....12 oz. can - black w/ straw









Great Stuff

- · Insulating foam sealant
- 12 oz can
- · Includes straw dispenser
- Seals up to one-inch wide gaps

#77282 12 oz. can

.....



EnerFoam Professional Gun Foam System

- · Replaces up to 40 quart tubes of traditional caulk or adhesive.
- Fast curing. Foam can be trimmed in less than one hour. Initial skin time is less than six minutes! Faster than any other foam
- · Unique mechanical valve. Spring loaded for reuse. Won't glue shut after use.
- · Contains no solvents. Compatible with EPS foamboard.

1) #KENER13	Gun PRO13 for spray foam
2) #KDOW192268	Cleaner for gun (KENER13)
3) #KENER43	Foam spray black, 20 oz. bottle



Touch N Foam Insulation

- Triple expanding polyurethane foam
- Seals & insulates block and concrete
- · For interior/exterior use

#292257 1	2	oz.	can
#09223330	8	oz.	can

trusscore

material + science

TRUSSCORE is the easy to install wall and ceiling paneling that's transforming building practices across North America.

- Ideal replacement for conventional wall systems
- · Cost effective compared to other materials
- Won't support bacterial growth
- · Won't corrode and is resistant to most chemicals
- · Inner truss design for rigidity and strength
- · Lightweight, easy to transport
- · High strength to weight ratio
- · Supports attic insulation loads
- · Bright clean appearance
- · Virtually maintenance free just wipe it clean
- · Highly resistant to moisture and mold
- Class A Fire Rating potential insurance savings
- · Quick and easy to install
- · Hidden fasteners provide smooth finish
- · Pre-punched nailing flange








Item#	Description
HSTC-1610	Panel TRUSSCORE PVC Interlocking Liner 1/2" X 16" X 10'
HSTC-1612	Panel TRUSSCORE PVC Interlocking Liner 1/2" X 16" X 12'
HSTC-1616	Panel TRUSSCORE PVC Interlocking Liner 1/2" X 16" X 16"
HSTC-1620	Panel TRUSSCORE PVC Interlocking Liner 1/2" X 16" X 20'

16"

Available in a width of 16" and 10', 12', 16' and 20'



• Easy to install. Unique overlapping design hides fasteners for smooth finish.



"J"-Trim 1/2"



Corner



Inside Cove Corner Snap-In Kit




Outside Corner Rounded



Base Trim



H Channel Snap-In Kit



45° H Channel



F Trim



PPD Panel

- 4' x 8' x 3/8" thick Fir plywood
- .030 High Density Polyethylene sheet laminated one side
- · Use in non-contact animal areas
- Wt. 38 lbs.

#845744' x 8' plywood w/ .030 HDPE



FRP Panel

- 4' x 8" x 3/8" thick Fir plywood
- .050 textured fiberglass sheet laminated one side
- · Use in animal contact area
- Wt. 41 lbs.

#84571.....4' x 8' plywood w/ .050 FRP



High Density Polyethylene sheets are the perfect choice whenever smooth, slick surfaces are desired. Can be sawed and nailed like wood and are waterproof and chemical resistant. Use the 1/8" thickness over existing plywood surfaces. 1/4" thickness and above can fastened directly to stud walls.

#1038	4' x 8' x 1/8", 21 lbs
	4' x 8' x 1/4", 42 lbs
	4' x 10' x 1/4", 52 lbs
	4' x 8' x 3/8", 62 lbs
	4' x 8' x 1/2". 82 lbs




Nylon Drive Rivet

For fastening interior wall panels. Priced each.

#84576 1/4" x 1-1/2"



PVC AND POLYCARBONATE



"One-Stepper" Screws

Self tapping, hex head with washer screws feature "wings" that drill out a larger hole to allow for expansion. Preferred fastener for installing corrugated PVC sheeting. Priced each.

#805171	#12 x 1-1/4" S.S
#ONESTEPPERS	#12 x 1-3/4" Galv


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Corrugated **PVC Liner**

Durable, strong PVC sheets are excellent choice for lining the interior of confinement structures. These rust proof sheets are able to span 4' centers and still support ceiling insulation. See special one-stepper screws for fastening (Item# 805171).



#HSCL-338146	38" x 146"
#HSCL-338196	38" x 196"
#HSCL-338244	38" x 244"



Predrilled holes for easy installation.

Stainless Steel **Star Drive Screws**

Batten Strips

Flat head for flush finish. Use for fastening interior sheets. Priced each. Sold in 100 piece bags.

The most effective type of covering for sealing and

Animals can't work them loose and damage panels.

preventing damage to the seams between wall panels.

#1030-1	#8 x 1-1/2"
#1031-1	#10 x 2-1/2"
#1032-1	#8 x 1-1/4"
#1033-1	#9 x 2" Phillips Drive

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



• 5/16' x 3-1/2"

· Torx drive

• Grade 5

Ceramic Coated Construction Lags

Grip-Rite® PrimeGuard Coated Deck Screw

- · Star T Drive
- Type 17 point
- Coarse thread
- · Approx. pound/count shown #00E611

#805611	#8 x 2" long, l lb. 126 ct
#805615	#8 x 2" long, 5 lb. 630 ct
	#9 x 2-1/2" long, 1 lb. 87 ct
#805635	#9 x 2-1/2" long, 5 lb. 435 ct
	#9 x 3" long, 1 lb. 73 ct
#805625	#9 x 3" long, 5 lb. 365 ct
#805641	# 10 x 3-1/2" long, 1 lb. 56 ct
#805645	#10 x 3-1/2" long, 5 lb. 280 ct
	#10 x 4" long, 5 lb. 250 ct

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Metal Screws

#80501	Galv. #9 x 1"
#80502	
#80503	Galv. #9 x 2"
#80504	White #9 x 1"
#80517	White #9 x 1-1/2"

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel **Ring Shank Nails**

For fastening interior wall panels. 136 nails per pound. Sold as 1 lb. quantities.

#100404010 ga x 1-3/4" 304 SS





GE Silicone

Contractor grade silicone sealant offers excellent adhesion and durability for general purpose caulking applications. Stays flexible over a wide range of temperature extremes. For exterior and interior use to seal wall panels and exterior metal sheeting. Not recommended to paint. Applies white and dries clear.

#003030	.White,	10.1	OZ.	cartridges
---------	---------	------	-----	------------



NP1

NP1 is a one-component flexible, polyurethane sealant for exterior and interior use. Can be used over a wide temperature range to seal cracks and seams. Can be used in high moisture areas. Available in white and gray.

:	#59500	White, 10.1 oz. cartridges
		Gray, 10.1 oz. cartridges
i	#59500B	Black, 10 oz. cartridges



S-Hooks

#60672	S-Hook Small 1" x .105"
#60677	S-Hook Medium 1-1/2" x .177"
#HSH044 S-	Hook for Brooder 1-7/8" x .192" Uneven
#HSH045	S-Hook Large 2-1/4" x .262"

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Bolts

Stainless	Steel	Hex	Bolts
------------------	-------	-----	--------------

#60686	1/4" x 1" ss
#60619	1/4" x 1-1/2" ss
#606871	1/4" x 2" ss
#60506S	1/4" x 2-1/2" ss
#606191	1/4" x 3" ss
#605071S	1/4" x 3-1/2" ss
#605073S	1/4" x 4-1/2" ss
#605081	
#605082	
#605083	5/16" x 7/8" ss
#606872	5/16" x 1" ss
#605091	
#60510S	5/16" x 1-1/2" ss
#60511S	
#60512S	
#60513S	
#60523S	5/16" x 3-1/2" ss
#60689	
#605141	
#60617	
#605161	
#60610	
#60631	
#60519S	
#60633	
#606331	
#605212S	0/0// 4 1/0//
#60534S	1/2" x 1" ss
	1/2" x 1" ss 1/2" x 1-1/2" ss

#60538S 1/2" x 2-1/2" ss

#60539S 1/2" x 3" ss

#60540S 1/2" x 3-1/2" ss

#60831 1/2" x 4-1/2" ss

#60828...... 1/2" x 5-1/2" ss

Zinc Hex Bolts

#60502

#60502	1/4" x 1"
#60504	1/4" x 1-1/2"
#60505	1/4" x 2"
#60506	1/4" x 2-1/2"
#60507	1/4" x 3"
#60592	1/4" x 3-1/2"
#60594	1/4" x 4-1/2"
#605071	5/16" x 1/2"
#60508	5/16" x 3/4"
#60509	5/16" x 1"
#605092	5/16" x 1-1/4"
#60510	5/16" x 1-1/2"
#60511	5/16" x 2"
#60512	5/16" x 2-1/2"
#60513	5/16" x 3"
#60523	5/16" x 3-1/2"
#60562	5/16" x 4-1/2"
#60514	3/8" x 3/4"
#60515	
#60516	
#60517	
#60518	
#60519	
#60520	3/8" x 3"
#60521	3 /8" x 3-1/2"
#60825	3/8" x 4-1/2"
#60534	1/2" x 1"
#60535	1/2" x 1-1/4"
#60536	1/2" x 1-1/2"
#60537	1/2" x 2"
#60538	1/2" x 2-1/2"
#60539	1/2" x 3"
#60540	
#60542	
#60550	
ncluding nickel, which is known to the State	e of California to cause

↑ WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cau cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Statifiess Steel nex Muts	
#60602	1/4"
#60618	5/16"
#60606	3/8″
#606061	1/2"
	•

Zinc Hey Nuts

1/4" v 1"

Zilic lick wats	
#60570	1/4′
#60571	5/16′
#60572	3/8′
#60574	1/2′
	·····

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

St

Diamicos Dicci noch muis	
#60603	1/4"
#60692	
#60612	3/8"
#60603	1/2"


Zinc Lock Nuts

#60680	1/4"
#60681	5/16"
#60682	
#60683	
#00000	1/ Z

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Stainless Steel



#605813/8" - flat **⚠** WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Stainless Steel Hinge



#10393 3" x 3" Stainless Steel Hinge

⚠WARNING:



Stainless Steel Wedge Anchors

#606552	1/4" x 1-3/4" ss
#606625	1/4" x 2-1/4" ss
#HSWA-3823S	3/8" x 2-3/4" ss
#HSWA-3830S	3/8" x 3" ss
#606556	3/8" x 5" ss
#HSWA-1223S	1/2" x 2-3/4" ss
#606755	1/2" x 3-3/4" ss

Galvanized Steel Wedge Anchors

#60719	3/8" x 2-1/4"
#HSWA-3823	
#60722	
#60721	3/8" x 3-3/4"
#HSWA-3850	3/8″-16 x 5″
#HSCPA-1223	
#90361	1/2" x 4-1/4"

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel Lag Bolts

#607161	1/4" x 2"
#606873	5/16" x 2"
#606876	5/16" x 2-1/2"
#605131	5/16" x 3"
#605231	5/16" x 3-1/2"
	3/8" x 2"
	3/8" x 3"
#606441	

Galvanized Lag Bolts

#606427	5/16" x 2"
#60643	3/8" x 2"
#60645	
#606436	
#60644	

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Stainless Steel J-Bolts

3/8" x 2-3/4"
3/8" x 3-3/8"
3/8" x 3-1/2"
3/8" x 4-3/8"
3/8" x 5-3/4"
3/8" x 6-1/4"
3/8" x 6-3/4"
3/8" x 6-7/8" - square
3/8" x 6-1/4" - square

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Latch Hook and Eve

#N226-381 6" long

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Cable Clamps Stainless Steel



#617321	 1/8"
#617331	 3/16"
#82975	 1/4"
#6173561	 5/16"

Cable Clamps Galvanized

#61732	1/8" - Hot Dipped
#61733	3/16" - Hot Dipped
#61734	1/4" - Hot Dipped
	5/16" - Hot Dipped
#617351	3/8" - Hot Dipped

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Galvanized U-Bolts



· Great for attaching pipes or tubes to gates or g-stalls

#60702	1" 1-3/8" x 5/16"
#60649	1" x 2-1/2" x 5/16"
#606501	2.73" x 3-1/2" x 5/16"
#60650	3" x 3-1/2" x 5/16"

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Spring Snaps

#10385	5/16"	Zinc
#10384	1/4"	Zinc

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Stainless Steel Quick Link

#597082	3/	1	6	3	
---------	----	---	---	---	--

Galvanized Quick Link

#59708	3/16"
#597081	5/16"
#597080	

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Aluminum Turnbuckle

#597125/16" x 6" - Closed Length

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Galvanized & Stainless Steel Cup Hooks

	-
#HSH070	5/16" x 3-1/2'
#606655	1/4" x 3-3/4" SS
	1/4" x 3-1/2"

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#2/0 Straight Link

Use for hanging waterers

#60676.....#2/0 Straight Link

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#1 Stainless Steel Chain

- · For hanging feed systems
- 2' of length for every 4' auger length

#606733#1 Stainless Steel Chain

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#2 Bowtye Weldless Chain



- Zinc
- · Use for extra support for outside feed lines.

#60673 #2 Bowtye Weldless Chain

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#2/0 Bowtye Weldless Chain

- · 100' only
- · Use for hanging feed lines and high-pressure pipes

#60678.....#2/0 Bowtye Weldless Chain

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



K-Clamps

#HSH011	 1/2"
#HSH012	 3/4 "
#HSH013	
#HSH015	 2"
#HSH016	 2-1/2"
#HSH017	

⚠WARNING:



Vanberg Metal Repair & Protection Products

Don't wait until replacement is needed! Save time and money by repairing and protecting now!

AMC-100L Aluminum Moisture Cure Urethane Coating

Easy to use single component coating to prepare and protect metal surfaces.

ROOFS



Before

BINS



Before

ROOFS



Before



After



After



After

AMC 100L Aluminum Urethane Coating

This formula has been formulated to include 'Leafing' technology. T his enables the urethane to bond better and it produces a tougher wearing 'metallic' coating. Coverage: 200-300 square per gallon at 2-5 mm thickness.

#AMC100L	1 at
#AMC100L-1	
#AMC100L-5	•



AMC-100L Repair Kit

Complete kit for exterior small repairs of bins and metal roofs. Typical coverage: 50 sq. ft.

Kit Includes:

- 1-Qt AMC-100L-Q
- 1 Pint RUST CONVERTER
- 4 Pieces SEAM TAPE
- 1 BRUSH



Stops rust in its tracks preventing further corrosion and rusting on metal surfaces. A must before applying coatings. When applied, it chemically converts rust to a stable black compound.



	And the second second
#RC900	
#RC900-1	1 gal. (4/cs)
#RC900-S	





VSC Seam Tape

Contouring, self-adhesive and high strength seam tape great for repairing holes, loose screw heads, splits and seam separations. Stops leaks as well. Excellent structural strength, superior adhesion and accepts VSC solvent based coatings.

#RC800-2	x 50' roll
----------	------------

4 STEPS

TO SUCCESSFUL **METAL COATINGS**

Successful repair and protection is a result of attention to proper preparation techniques and the use of quality products designed to achieve long-lasting performance.



Step 1: **Remove Loose Rust**

Remove loose rust by pressure washing, scraper or brush.



Step 3: Patch

Holes, splits, seams and joints are covered with VSC SEAM TAPE, designed specifically for all weather conditions and are compatible with VSC coatings.



Step 2: Convert Rust

Although abrasive blasting and mechanical rust removal are great methods, they are not always feasible. Experience shows that the treatment of rust is best achieved by VSC RUST CONVERTER.



Step 4: **Corrosion Resistance Coating**

Apply the selected VSC coating to protect metal from corrosive compounds and weather.

Measure Containers

Measuring containers for proportioning mixes.

#TS1QM.....

Pails & Lids

5 gal. pail used to mix and store materials. Spouted or plain lids available

#TS305 1 Pail

#TS305L 1 Plain Lid #TS305PL 1 Spouted Pour Lid



3 pieces assemble to 36" pole. Economy. Thread tip fits all roller frames.

#TSF0007-31'-3' pole set

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



9-inch Roller Cover

#TSR204-9......9", 1/2" nap





Plastic tray resists solvents.

#TSR4049-inch roller tray



Fits threaded tip pole.

#TSF0010-9....

.....9-inch HD frame

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#TSF0010-4......4-inch HD frame **⚠** WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



3" Cut-In Brush

#TSF5117-3.....3" cut-in brush



Elcometer® Concrete Crack Width Ruler

A quick and easy reference tool to measure crack width and length in concrete or other building materials.

#E143..... Elcometer® Concrete Crack Width Ruler

EPO-SET 400

Repair loose anchors in concrete without removing the stud. Simply apply EPO-SET 400 around the loose anchor and in 10 minutes anchor is set with full strength in two hours. Single tube with dual internal

chambers allow EPO-SET 400 to be applied with a standard caulk gun. 9 oz. cartridge comes with one disposable mixing tip; additional tips should be ordered if entire tube content will not be applied in a single use. Application temperature 40° - 90°.

#72400EPO-400 Kit w/ mixing tube **#72400-T**..... EPO-400 mixing tube



Set Bolts

See It In Action! YouTube: EPO-SET 400

Vanberg Concrete Repair & Protection Products



Typical Coverage at 1/4" (55 lb. bag)

- 25 sq. ft. unextended
- 1 cu. ft. mixed 1:1 with gravel (grouting over 1 inch)



Common Uses:

- Slats Troughs
- Feed Platforms Re-set penning
- Floor overlays
- t penning Walls







'FAST' Trough Repair

Use CON-KORITE™ to restore troughs and stall pads — "Even during production"





Feeder Pad Repair











60 #KBC

Con-Korite™ Xtra Mortar

Pure cement formula far outlasts common Portland products! CON-KORITE develops 3,000 psi compressive strength in one hour and nearly 10,000 psi in 28 days. It has exceptional abrasion resistance making it the longest lasting and most cost-effective option for severely worn (any thickness greater than 1/4 inch) slats and floors. It is preferred by producers for repair of broken slat edges and to restore corroded slats... even down to the rebar. Being a concentrate, CON-KORITE can be extended with aggregate up to 1:1 (or use GROUT) to grout deep holes and make repairs in medium duty areas

#KB0060 CON-KORITE™ 55 lb. bag #KB0061 CON-KORITE™ 55 lb. pail #KB0060B 3,000 lb. bulk bag



such as troughs and rough pen floors (2 parts mortar to 1 part sand). Order separately for larger jobs.



Rough Floors Leveled Fast!

Con-Korite[™] SSL

New self-leveling Con-Korite formulation provides easier application on uneven surfaces. Simply pour on repair area and spread, spike roll to finish. Kit includes bag of mortar and 1 gal of KB25. Excellent resistance to wear and corrosion. Approx. coverage 20 sq. at 1/4" thickness.

#KB0040Con-Korite SSL kit



KB25 Acrylic Resin

Can be used for enhanced bond and resistance to absorption. KB25 is ideal for wet environments. General Use: 1 part KB25 to 2 parts water (1 gallon KB25 for 3 – 55lb. bags or pails of mortar).

#KB0026	. 1	gal.	. jug
#KB0027	5	gal.	pail



ARMOR-STONE™ Epoxy Mortar

Many finishing sites have very high levels of corrosive compounds formed from pit gases, water types and feed additives. Over time even $\text{CON-KORITE}^{\text{TM}}$ can be affected. ARMOR-STONE $^{\text{TM}}$ has been shown to be unaffected by these corrosive compounds. A unique blend of ARMORCOAT epoxy and a special blend of aggregates that form a tough wearing and chemical resistant repair.

#AC3800-ASArmor-Stone™ 3800 Kit



Economy + Performance!

ECO-CRETE SLAT PATCH

Eco-Crete Slat Patch

A Hog Slat exclusive from Vanberg Coatings! Eco-Crete is the choice for routine repairs on slats and other concrete surfaces. Ready to use, just add water, place on damaged areas and it's set in just 2-3 hours. Features a high cure strength of 7,600 PSI. For interior and exterior use.

#KB0051.....Eco-Crete 50 lb. pail

Armor-Rock™ 3800 **Epoxy Overlay**

A new formulation that is harder and more chemical resistant to withstand the most rigorous conditions.

Sooner or later slats and pads around feeders and mats are attacked by aggressive chemicals forming from pit gases, animal wastes and feed stuffs. ARMOR-ROCKTM is a well proven system to restore sightly worn concrete or protect "new" surfaces. VSC ARMORCOAT $^{\text{TM}}$ epoxy is combined with VSC aggregates to form an extremely tough-wearing and chemical-resistant non-slip overlay. Since 1989 producers have found the

AC 3800 LIQUIDS KIT IN A BOX/ **AGGREGATES* IN A PAIL** (*Includes AR ADMIX and VSC MEDIUM G-DIAMOND)

ARMOR-ROCK™ SYSTEM to be the most permanent solution. Wastes flow off the slats removing the corrosive compounds that erode the surface.

#AC3800-ARArmor-Rock™ 3800 Kit





It's a simple process too...






Mix 1.5 gal ARMORCOAT

add ADMIX







SAND BROADCAST

Repair cracks permanently!







ARMOR-ROCK poured



Cracks repaired

Download our FREE eBook

The Field Guide to Slat Repair and Replacement

Search in your browser for: Slat Replacement -Hog Slat











Components

#AC3800 ARMORCOAT 3800 - Highest Chemical & Wear Resistance, (1.4 Gal.) #150415......3 gt. Plastic Scoop (for dispensing Armor-Rock on Slats)

Concrete Clean & Etch

Aggressive Formula cleans and etches concrete floors to create a "hold tight" textured surface improving adhesive qualities of sealers and coatings. Removes laitance from new concrete and neutralizes alkali and soap residue. Dissolves scale and lime deposits from pipes and equipment. COVERAGE: 150 sq. ft./gallon. Concentrated for economy. Safer than muriatic acid



Portable Pail Mixer

Portable, fixed angle pail mixer for easy, thorough, consistent blending of mortars and epoxies. Durable, all-steel construction and professional grade, electric motor sustain high performance, continuous operation.





economical prop designed for thorough mixing of epoxies, urethanes and mortars. Use with 1/2", variable speed, electric drill.



Solvent 101

This multi-purpose thinner and clean-up solvent for epoxies. SOLVENT 101 (1 Gal) can be shipped via



#VPC-101-1 1 gal. (4/CS) #DI78PRLD72SV1





ROTEM

RLD-7.2digital / RLD-14digital

The RLD-7.2 is Rotem's two-channel digital light dimmer. This powerful dimmer can be directly controlled by your poultry house controller through either its analog output (0–10 volt) or through its communication line. The RLD-7.2 is designed to be easy, safe and comfortable for installation, maintenance and service. The RLD-7.2 manual control enables setup of maximum light intensity, setup of time for gradual change in light intensity from zero to the preset maximum and also automatic shut down timer. The farmer can turn on the light which will gradually go to its preset maximum intensity, perform his mission and continue to his next challenge. The light will shut down gradually after preset amount of time.

Features:

- Two independent channels
- Heavy duty 40 Ampere TRIAC for each channel
- 7,200 Watts (115 Volt), 14,400 Watts (230 Volt), 50/60 Hz
- Stable operation in low brightness (voltage)
- Manual / Off / Auto mode for each channel
- Settings are saved automatically
- Settings are recovered after power failure
- Rugged terminals for the power cables
- Simple key hole mounting
- · Water tight seals for cable entry

#DI78PRLD72SV1......Rotem Digital Light Dimmer and Card, for 110V
#DI78PRLD72V1.....Rotem Digital Light Dimmer only
#DI78PRLEDV1.....Rotem LED Dimmer





The Performer MR

Digital Poultry House Dimmers

- · Keypad adjusts light level more accurately than rotary dial
- · Independent control of two separate circuits
- Full timer function with manual override
- LED models have four unique programmable settings to adapt to multiple types of LEDs.
- · Digital display
- 120 V, 60 Hz



Precision's 2K Green Reverse Phase/Trailing Edge Dimmer

2000 watt reverse phase light dimmer. This technology offers advantages over Traic or SCR dimmers including soft start, increased noise immunity, and increased bulb life. Tested with many types of bulbs including: CFL, CCF, LED, and Incandescent.

#2KGREEN......Precision 2K Green Reverse Phase/Trailing Edge Dimmer

Propagator 3 Sodium Vapor Light Fixture

Includes: 150 watt bulb 16 ga. aluminum body Non-dimmable



High Pressure Sodium Light

- 1.5 Amp
- 150 Watt
- 5" Reflector

#M4-150W-HPF-5......High Pressure Sodium Light



#52062......150 Watt Sodium Vapor Bulb



#HPSSOCKET-SReplacement socket





#520543 Capacitor - 1.5 150 Watt





ONCE® Swine Lighting

The AgriShift* MLM-S is a durable and efficient swine lighting solutions designed to evenly distribute light for both the herd and humans caring for them. The red spectrum used makes it easy to provide daylight simulation for improved productivity.

Features:

- Highly efficient fixture suitable for modern swine facilities
- Species-specific spectral output featuring Dim-to-Calm[™] technology
- Fully dims* to red, which swine perceive as darkness
- · Can act as a "service light" when fully dimmed
- Durable Built For Your Barn® design
- Luminous Flux 1040 lm
- Equals 75W Incandescent
- 200° Beam Angle



#OIMLM-SSWR-JB.... 10-watt w/ Junction box adaptor #OIMLM-SSWR-JJ.......10-watt w/ Jelly jar adaptor



ONCE® Broiler, Pullet and Turkey Lighting

The AgriShift* MLM-B has an optimized color spectrum with full dimming capability, meeting the birds' developmental needs at every stage of growth. It is designed with Dim-to-Blue* technology to enhance animal welfare, better flock performance and improve feed conversion rates

Features:

- · Enhanced blue/green spectrum
- · Fully dims to provide natural daylight simulation*
- Luminous Flux 1382 lm
- · Equals 60W Incandescent
- 200° Beam Angle



#OIMLM-FSWB-JB.... 10-watt w/ Junction box adaptor #OIMLM-FSWB-EB10-watt w/ edison base #OIMLL-FSWR-HW.......12-watt w/ hard wire adaptor





ONCE® Agrishift Dimmer Control

The AgriShift* Master Controller and Slave Dimmer provide full potential to any ONCE* lighting fixture. They offer smooth dimming solutions that can easily be controlled manually with the front panel controls or remotely with a 0-10VDC control signal.

#0I30-014-00178	Master Controller 120V
#0I30-014-00189	Slave Dimmer 120V
#0I30-014-00180	Master Controller 240V

Issues with Poultry House LED Lamps and Light Dimmers

Summary of Mississippi State University Extension publication, 3510 (POD-08-20)

Poultry growers have seen remarkable energy savings from transitioning from incandescent to LED lamps. However, recently there have been an increasing number of issues with erratic dimming, excessive lumen depreciation, and premature lamp failures. Evidence points to an incompatibility between LED lamps and the light dimmer as the main cause of these issues.

Reports from both the lab and the field tend to indicate that leading-edge dimmer technology and modern LED lamp technology are simply not compatible.



Incandescent (left) and LED lamps center, with globe removed, and right).



LED lamp with globe removed to show LED chips.

Leading-edge dimming technology tends to produce current spikes that are detrimental to LED chips in the lamps. The damage to LED chips caused by these current spikes appears to be cumulative over time and is irreversible. It will eventually lead to accelerated lumen depreciation, strange and erratic dimming problems, and premature lamp failures. Leading-edge dimmers are, by far, the most common light dimmers in poultry houses today. However, trailing-edge dimmers are much more compatible with today's LED technology. We will continue to follow this situation.

However, it may be that poultry growers should consider switching to trailing-edge dimmer technology to alleviate incompatibility issues between LED lamps and leading-edge dimmers.

No grower wants to spend money needlessly, but neither do they want to deal with continuing dimming issues, excessive lumen depreciation, and premature bulb failures if a trailing-edge dimmer will stop the problem.



For the full article, go to

http://extension.msstate.edu/ publications/issues-poultry-house-ledlamps-and-light-dimmers

Overdrive Lighting Systems



6W A19 Overdrive	Equal to =	10W Household OMNI
6W	Lamp Wattage	9.5W
545	Lamp Rated Lumen	800
100%	% Light on floor (est.)	65%
545	Effective Lumen on Floor	520
\$16	Energy Cost over 25,000 hr.	\$26
\$10	Saving in Energy Cost over Life	-

Overdrive LED Bulbs Dimmable & Non Dimmable


- · Lamp Type: LED A19 Bulb-Diffused Cover
- E26 (Medium Base)
- A 19 Shape
- · Lamp Wattage: 6W
- (60W Incandescent Replacement, based on floor lux)
- LED Type: 10 nos. x 0.45W SMD (LM80)
- Reliable Operating Temperature: -40 F to 1130 F
- Color Temperature: 3000K or 5000K
- · Specifically engineered for harsh agricultural environments.
- · Rated for agricultural use not just residential like many other LED bulbs.

Item#	Watt	Kelvin	Lumens	Dimmable
#731	6	3000	480	Yes
#732	6	5000	530	Yes
#793	9.5	5000	900	No
#792	9.5	2700	810	No
#0D733	10	3000	950	Yes
#73 4	10	5000	1050	Yes
#665	20	5000	2700	No
#699	11.5	5000	1100	Yes
#698	15	5000	1600	Yes

731 732 OD733 and

734 feature a

Wet Location Gasket



Overdrive Dimmer Controller with MOSFET control provides the finest dimming requirements for low light levels and strong lamp re-ignition. Dual Output channels can run independent lighting schedules which can illuminate or dim two lighting zones simultaneously. It's not only a dimmer but a controller also. For optimum performance and long life, use this dimmer controller with Overdrive dimmable Lamps.

- · Dual Output zones can run independent lighting schedules;
- 3 Programs Master, Manual, Slave mode for quick and easy programming
- Programmable Master mode for unmanned control
- · Manual Mode with Keypad control
- Slave mode with 0-10V DC analog voltage control
- Supports memory function
- Supports ISP function and Comply with EU-BUS protocol
- Integrated 1.3" OLED Display
- Fully integrated digital control system for Precise and consistent dimming
- 4kV Surge Protection, Over Voltage Protection, Short Circuit Protection
- Replaceable output Fuses
- MOSFET Control reduces dimmer power loss and runs cooler
- Reverse phase trailing edge dimmer.

#ODMR0210......10 amp/ 2 channel 1200W per channel





Overdrive Lighting Cord Sets

- Offering the flexibility of relocating the lights to obtain better production numbers
- Nickel Plated Sockets provide resistance to corrosion
- · 10 Feet Spacing between sockets for effective light distribution
- · Water proof connector provided at both ends.

- Specially designed E26 Sockets to provide water resistance and additional safety
- Standard Lighting Cord of 100 feet with expandable water proof connector
- ullet Heavy duty 14 AWG wire for minimum voltage drop over extended length usage
- 4 inch -Suspended E26 sockets to keep the lamp straight during usage



FELAMP COMPLETE END TO END SHTING SYSTEM LIGHTING SYSTEM



LifeLamp™ LED BULBS

- Designed to withstand confinement house environments with silicon seal between body and lens cover
- · Features Lexan polycarbonate plastic to resist cracking or shattering
- Will dim to 2% with LifeLamp dimmer
- Wide light beam spread

Item#	Watt	Kelvin	Lumens	Dimmable
#DLS16-5WBB27	16.5	2700	1600	Yes
#DLS16-5WBB50	16.5	5000	1900	Yes
#DLS16WBB27	16	2700	1600	Yes
#DLS16WBB50	16	5000	1900	Yes
#DLS9WBB27	9	2700	840	Yes
#DLS9WBB50	9	5000	900	Yes



LifeLamp™ HIGH OUTPUT LED LAMPS

- Use for turkeys, breeders and brooders
- 270° broad beam angle
- Direct replacement for HPS lighting and high watt CFL (Ballast must be bypassed)
- Aluminum die cast body

Item#	Watt	Kelvin	Lumens	Dimmable
#HPS40W27K	40	2700	6000	No
#HSPS40W50K	40	5000	6000	No







#LLLNACAP10

LifeLamp™ LightLines

LifeLamp™ Light Lines to retrofit poultry houses for LED bulbs.



LightLines waterproof, dust-proof connectors ensure long term reliability in the toughest environments.



Sockets built with tin plated copper sockets for superior conductivity and corrosion resistance.

#LLLNA 1050	50' long/ 10' centers/ 5 sockets
#LLLNA2080	80' long/ 20' centers/ 4 sockets
	End cap
	Power connector for 50' line
#LLLNAPC20	Power connector for 80' line



- $LifeLamp^{TM}$ Dimmer
- 3 modes of operation including manual control, slave control from central controller, programmable timing
- Precise, consistent, incremental dimming down to 1%
- Operates seamlessly between 110VAC and 240VAC
- Customizable Housewalk feature for seamless interruption of programming for midflock maintenance

#LDIMLifeLamp™ Dimmer



Compact Fluorescent Bulbs

Item#	Туре	Watt	Kelvin	Lumens
#101245000	CFL	23	5000	1525
#399205	CFL	40	2700	2700
#399403	CFL	55	2700	3700



Hardwired fixture includes (2) wire nuts, (2) lock nuts, driver plate and mounting plate bracket.

- 29 Watt
- Acrylic lens
- 120 Volt
- Polycarbonate
- 5,000 Kelvin flat base







Greenlite Shatterproof LED Bulbs

- Up to 25,000 hour lamp life
- · Shatterproof Globe
- Damp Location Approved
- Specifically engineered for harsh agricultural environments.
- Rated for agricultural use not just residential like many other bulbs.

Item#	Watt	Kelvin	Lumens	Dimmable	
#44415-4PK	6	3000	480	(4 Pack)	Yes
#48684 #48406	6 9	5000 5000	600 800		Yes Yes
#GL60138	9	3000	NA		No
#36259 #48844	12 15	5000 5000	1200 1600		No Yes
#48586	22	5000	2550		Yes



Photocell Dusk-to-Dawn **Outdoor Light**

Replacement photocell for outdoor dusk-to-dawn lights

#DDL7790BSS.....Photocell



Dusk-to-Dawn **LED Security Light**

Constructed with a die-cast aluminum housing and vandal-resistant polycarbonate refractor. Mounts with integral three-hole flange on housing or included 900 extension arm. 120-277 Volt, 50 watt input power with 120V photocell included.






AG 25 LED Fixture

The AG 25 is more than a bulb, it's a lighting fixture. A great choice for retrofits because it eliminates the need for jelly jars and keyless fixtures.

- Brighter with 2165 Lumens more light less fixtures
- More uniformity with 30-foot layout
- 5-Year full replacement warranty · Waterproof I-65 rating
- 25 Watt
- Dimmable









Porcelain & Plastic Keyless Sockets

Nickel-plated brass screw shell keyless sockets are recommended for dimmable fluorescents to decrease failure rates and improve dimming performance.

#HE612405	
#EPC16510	Phenolic Plastic Socket w/ Nickel-Plated Brass Screwshell, no lead
#EPC16500	
#EPC16524	
#EPC16520	



One piece fixture base constructed of glass reinforced polyester resin. Accepts 3/4" conduit. Porcelain socket with brass insert resists heat buildup. Rated for Maximum 150 watt. 12.8 oz. Ideal for use in the harshest environment. Waterproof.

#10120	Scepter
#72231	Replacement porcelain socket





Light Base & Light Mount Base

- · Rated at 150 Watt
- · Ceiling mount base only
- · Threaded
- 8 oz.

#1) #FE1059	Base for light, rated at 150-Watt
	1/2" Ceiling mount - threaded
#10185	3/4" Ceiling mount - threaded
	Light base w/ glass globe
	Light base w/ 7" plastic globe
_	3 ,



Glass Globes

Glass light globe for use with incandescent bulbs up to 100 watt. The outside diameter of the jar mouth is 3.25" and the total height is 6.75".

#88057Glass Globes

Overdrive **LED Jelly Jar Retrofit Fixture**

14 watt 5,000K LED light bulb with a specially designed fixture that replaces standard jar and bulb combinations. Pre-wired, E26 base screws into existing bulb socket and the body screws into most existing jelly jar fixtures. 1,400 Lumens.


#652.....LED Jelly Jar Retrofit Fixture



Plastic Globes

- · More durable
- · Waterproof
- · Protects lamp against breakage
- For use with up to 60-watt incandescent bulb

#HSLC825 8-1/	4	long
#HSLC700	7"	long



- Mounts to 3/4" or 1/2" conduit · Flanged screw mounts for easy
- installation/removal
- · Cast aluminum housing with clear glass globe
- · UL/CUL Listed for wet locations
- 120V 150 watt max
- Dimensions: 9"L x 4.5"W x 4.5"H
- · Color: Gray

#NSIVTB15012.....Vapor tight ceiling fixture







Attach-On Sockets

#612445 Attach-On Standard Socket brass contact #EPC16022...... Attach-On Standard Socket nickel contact





Switch Covers

#FE59143	single gai	ng toggle
#E9G2SSN	double gar	na toaale



Straight Blade Plugs

#5266X.......Plug 2-pole 125 Volt, 15 Amp 5-15P #5466X......Plug 2-pole 250 Volt, 20 Amp 6-20P

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Male Plugs	#88010
#88009	15-Amp, 120-Volt
#88005	15-Amp, 220-Volt
#88010	20-Amp, 250-Volt

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Female Plugs

Female Plug

Twist & Lock

#88040	15-Amp, 120-Volt
#88041	20-Amp, 240-Volt

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov







#880425

& Lock

Male Plug Twist



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#L620-C	20-amp, 250V
	30-amp, 125/250V
	30-amp 250V

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Wall Receptacles

#HSEL100125

#HSEL100106Duplex, 15-Amp, 120-Volt #HSEL100135.. Crowfoot, 50-Amp, 125/250-Volt, black #HSEL100125......Straight blade, 20-Amp, 250-Volt, 6-20R #HSEL100123......Twist Lock, single, 15-Amp, 220-Volt

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov







#S1962 weatherproof vertical/horizontal mount







1 Gang Blank Cover

#8802083 weatherproof w/ 4 SS screws



Switches

#HSEL100022...... Single Pole, 20-Amp, 120-Volt #HSEL100002...... Single Pole, 15-Amp #HSEL100024......Double Pole, 15-Amp #HSEL100029......Double Pole, 20-Amp #HSEL100006.... 3-way, 15-Amp, 120-Volt, ivory

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



1 Gang Vertical **Receptacle Box Cover**

#HSEL100234.....weatherproof, 50-Amp #S1961..... weatherproof, 15-Amp





1 Gang Horizontal **Duplex Box Cover**

#E98DHGN-CAR weatherproof



In Use Weatherproof **Receptacle Clear Cover**

· Accepts single/double gang #WP3100C.....GFI, Toggle switch





Duplex/Toggle Switch Box Cover

- 1 gang
- · Weatherproof

#E9G2DSN-CAR.....vertical mount, gray



#59135-020

Proximity Switch

• for Brock Scale

#59135-020..... Proximity switch (shown)
#57135-000.... Magnetic Switch Actuator
for weigh scales (no wires)



Snap Action Switch

• for Chore-Time

#EL 1056 Chore-Time linear lift switch



Unimax Switch

• AA-421 with roller

#EL0995.....Chore-Time fill system control switch



Micro Switch

• Tall button

#EL0996..... Chore-Time hopper switch for C2912



Micro Switch

• for Chore-Time & Cumberland Control Pans

#EL0997..... Micro Switch



15 Amp Switch

• Harkins Hopper Control Switch

#EL0998......Micro Switch



Push Switch

• Cumberland GFLX-3802 hopper switch

#EL0999.....SPDT manual/automatic



Limit Switch

• 2 per machine needed

#EL1059 AT Newell curtain machine switch



Whisker Switch

• for Spinks & Roxell switch applications

#ISO05150Complete switch



Paddle Switch

• for G07051400 hopper control

#EL1142.....Paddle Switch



Switch

• Feed Control Pan, Hopper & Fill Control Switch

• Replaces switches: C46678, 6X289, GC2200025



Micro Switch

• for AP Drop Tube Switch

#EL 1052AP AP OEM# S-8297



Flex Flow Safety Limit Switch

#GS-7707.....Safety Limit Switch



Micro Switch

#EL1141 2 Terminal Micro Switch



Micro Switch

#EL1067 for Cumberland Plunger Control Pans



Universal 8-Pin Relays

#5X848......DPDT, 8 Pins, 240 VAC #5X847.....DPDT, 8 Pins, 120 VAC



Relay

#3X74211-Pin Octal 3PDT 120 VAC coil 10-Amp



Relay

#EL1008 25-Amp 240 V DPST 6-screw terminals #2XC20...... 25-Amp 120 V DPST 6-screw terminals





Relay

#EL1015.....Plug In DPDT 3-Wire 120 VAC #EL1066.....Plug In DPDT 3-Wire 240 VAC



#EL1014.....DPST 120 V



Relay

#EL1010......Coil 120 V DPST 25-Amp Double Pole Normally Open 6 Spade #EL1054 Coil 240 V DPST 25-Amp Douoble Pole Normally Open 6 Spade



Relay

#EL1013..3PDT Cube 120 VAC



Omron Relays

#EL1084 SPST 240 V w/ Test Button #EL934 Power Relay SPST 120 V 4 Pin #EL935 Power Relay SPST 24 V 4 Pin



Omron Relay

#EL1060.....240 V 14-pin Chore-Time Rooster Winch



Relay

#3X740.....12-Amp 8 Pin 240 V #5X827..... Octal Base 12A, 120 VAC Coil, DPDT 8-pin



Relay Base

#59092.....51x00120 8-pin



Relay



Relay Plug

#EL1009 Relay plug DPST 240 V Coil



Contactor

#DP30C2P-1 2-Pole 30-Amp 120 V Chint Brand #DP30C2P-2 2-Pole 30-Amp 240 V Chint Brand



Contactor

#5330102...... 3-Pole 40-Amp 120 V Chint Brand #5330104...... 3-Pole 40-Amp 240 V Chint Brand



Micro Switch

• for timer GAP-0990

#EL1040......AP OEM# 1740



Micro Switch

• for Chore-Time

#EL1052M......OEM# 46091



Relay

• for AP/Chore-Time

#EL1008Relay for proxy switch



Toggle Switch

• SPST Carling

#EL 1000 10-Amp, 250 V 3/4 Hp



Toggle Switch

• 3 prong SPDT w/Ctr Pos

#EL1001 10 Amp, 250 V 3/4 Hp K1406



Toggle Switch

• 3 prong SPDT

#EL 1002 10-Amp, 250 V 3/4 Hp



Toggle Switch

• 3 prong SPDT Tab w/screw

#EL1003 10 Amp, 250 V 3/4 Hp



Toggle Switch

• 4 prong DPST

#EL1004 10-Amp, 250 V 3/4 Hp



Toggle Switch

• 6 prong DPDT w/Ctr off

#EL100510 Amp, 250 V 3/4 Hp



Toggle Switch

• 6 prong DPDT

#EL1006......10-Amp, 250 V 3/4 Hp



Toggle Switch

• TPDT

#EL1007 10-Amp, 250 V 3/4 Hp



Toggle Switch

• 4-prong DPST

#EL1011 20 Amp, 250 V 1-1/2 Hp



Contactor

•	Sq	uare	D
•	Sq	uare	\mathbf{D}

#5B111	2-Pole 40-Amp 208/240 V
#5B112	2-Pole 40-Amp 120 V Coil
#5B103	2-Pole 50-Amp 24 V Coil



Contactor

• Square D

#5KAK3	3-Pole 30-Amp Resistive Full Load 40 Amp)
#5KAK0	3 Pole 30 Amp 120VAC Open	ι



Contactor

• Square D

#5B130	1_Pole	25-Amn	120 \	ì
#30130	I -POIE	Z3-AIIID	140 \	J



#5B131......2-Pole 20-Amp 24 VAC #5330105......2-Pole 30-Amp 24 V



Contactor

• Square D

#5330106......4-Pole 25-Amp 120 VAC



Fuses

#EL1027	5-Amp Slo Blo fuse, 5-Pk
#EL1030	10-Amp Slo Blo fuse, 5-Pk
#EL1031	15-Amp Slo Blo fuse, 5-Pk
#EL1048	10-Amp Fuse
#EL1051	1-Amp Fuse, 5-Pk



Single Gang Rectangular Non-Metallic Box

#SES077291...3" x 1" dbl. access, 3/4", 1/2" adapters **#10186**.......3" x 1" single access, 3/4", 1/2" adapters



Junction Box

#CARLNE989R	12" x	12"	Х	6",	lid,	gaske
#CARLNE989UUN	12" x	12"	Х	4",	lid,	gaske
#CARLNE989N	8"	x 8"	Х	4",	lid,	gaske
#E989NNI 4" x 4" x 2"	" Non-	-mei	tal	lic	lid	gaske



Reducing Bushing

#101923/4" x 1/2" SCH 40



Male Terminal Adapter

#10196	.3/4"	rigid	non-metal	lic	cond	uit
#E943D	. 1/2"	rigid	non-metal	lic	cond	uit



Female Adapter

#CARLNE942D	1/2" SCH 40 Non-metallic*
#10195	3/4" rigid non-metallic
*Also serves as a 3/4 slip to	1/2 female thread reducing bushing



Conduit Fitting Locknuts

#88024	Steel, 3/4'	,
#88025	Steel, 1/2"	,



T Style Conduit Body

- Non-metallic
- Rigid

#T07	3/4", Type T
#101902	1/2", Type T



LB Style Conduit Body

- Non-metallic
- Rigid

#E986E	3/4",	Type L	ιB
#E986D	1/2",	Type L	ιB



Type C Conduit Body

- Non-metallic
- Rigid

#101901	1/2", Type (
#E987E	3/4", Type 0



Bell End Conduit

- Non-metallic
- Rigid

#HSEL200002	.3/4"	conduit	w/bell	end
#HSEL200001	. 1/2"	conduit	w/bell	end



45° Elbow

- Non-metallic
- Rigid

#UA7AD	1/	2" x	450	SCH	40	standard
#UA7AE	3/	4" x	450	SCH	40	standard



90° Elbow

- Non-metallic
- Rigid

#HSEL200026	1/2" x 900 SCH 40 standard
#HSEL200027	3/4" x 900 SCH 40 standard



Access Pull Elbow

#E990DR	1/2"	non-metallic
#E990ER	3/4"	non-metallic



Rigid Conduit Coupling

#880237	3/4"	rigid	non-metal	lic
#88026	1/2"	rigid	non-metal	lic



End Caps

#10194	3/4″	cap	non-metallic
#CARLNE958D	1/2"	cap	non-metallic



Controller & Alarm Sensor Wire

#HS2427	Yellow 18/2 (per ft)
#55065	Gray 18/2 (per ft)
#57572902	18/3 (per ft)
	18/4 (1000' rolls)



14/3 Cord

• Sold per foot or bulk 250' rolls

#88031	Bulk Cord	14/3 Black
#KT143COR	Bulk Cord	14/3 Yellow



Cable

#88033.....Rubber coated, 4-wire, 16-gauge







Liquid Tight Cord Connector

#LPCG507



Cord Sets

#HSCS-002	9′, 240 V, 14/3
	12′, 120 V, 14/3
	Flush control, 110 Volt, 9', 14/3

#FC	9', 220V, Stai	ndard Plug, 16/3
#143CS6-15P-12.		
#EL1037	21", 240 V, w/s	-hook & terminals



Terminals

• Insulated

#EL1045......250" 16/14 gauge Blue Flag

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Terminals

Insulated

Main

Load

Center

Square D

Breaker

#EL1047#10 16/14-gauge Blue Ring #EL1046250" x .032" 16/14-gauge Blue Piggy Back

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Breaker Circuits • Square D

can be reused if needed.

#Q0215	. 2-Pole 15-Amp QO Type
#Q0220	.2-Pole 20-Amp QO Type
#Q0115	. 1-Pole 15-Amp QO Type
#00120	.1-Pole 20-Amp 00 Type



Breaker Panel

#Q0140M200RBw/main breaker 200-Amp

↑ WARNING:


This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#Q0120M100RB...... 100-Amp, 20-space 240/110 V

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#FC20	
#FC25	3/4′
#FC26	
#FC47	1-1/2′
#FC59	2.

Galvanized 1-Hole Pipe Straps

#HSH0303/4"


⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



PVC Coated 2-Hole Pipe Straps

Corrosion resistant fasteners in a wide array of sizes to hang sensors and electrical wire, PVC and metal pipe, and large tubing.



♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Wire Connectors

· Package of 25

#WNB25	Blue, twist-on size 22-14
#WNR25	Red, twist-on size 18-8
#WNY25	Yellow, twist-on size 18-10
#WN025	Orange, twist-on size 22-14






Electrical Tape

#88048.....3/4" x 60' 7 Mil



#HE461713	4" UV black
#305133640	8" UV black
#HE461763	
#FP99050001	



WAGO® Compact Wire Splicing Connectors

WAGO® compact splicing connectors make quick work of terminating and connection wire leads. Lever operated connectors provide neat, secure splicing results. Easily join different sizes of wire.

Rated Voltage	400 V
Nominal Current	
Max Temperature	185° F (85° C)
Min-Max Wire Size	, ,
(Solid, Stranded, Fine-Stranded)	28-12 AWG

Dimensions	2 Wire	3 Wire
Length	0.81"	0.81"
Width	0.49"	0.67"
Height	0.571"	0.571"
UL Listed	486C	

#WAG0222-412	2 port
#WAG0222-413	

Breaker Spot Temperature Indicators

(Note: Breaker Spot indicators cannot be shipped UPS during summer months because indicators may accidentally activate if they get too hot during shipping.

OMBE-130F

The OMBE-130F activates once the breaker reaches 130° which is the temperature most agree is when a breaker reaches critical levels that cause it to overload or trip. Small enough to fit on almost any breaker. Sold in packs of 30.



#OMBE-130F......5/16" Dia 130° (30/pk)

OMTL-5

The OMTL-5 is designed to be used on main (or larger) breakers to show you when a breaker is gradually getting too hot to give you a larger window to allow you more time to address a potential issue. Indication begins at 105° and goes up in 5° increments to 130° F. Sold in packs of 10.



#OMTL-5 Main Breaker Multi Temp Indicator 105°-130°, (10/pk)

OMTL-C-130

The OMTL-C-130 is another option for main breaker (or larger) applications where higher temperatures may be tolerated. 4 levels of temperature indication starting at 130° increasing every 10° to 160° F. 9/16" in diameter, sold 10 per pack.



#OMTL-C-130High Temp Multi Level Indicator 130°-160° (10/pk)

Thermax

1/2" x 1/2" self-adhesive labels rated at 140° apply directly to breakers. The changes are irreversible, providing a temperature history of the surface being monitored. The labels will not de-laminate when removed for reference. Card of 50.



#HSEL400140 Thermax



#DTK-120/240CM+



#DTK-120SR



#DTK-4LVTEP







#DTK-120/240HD2

#DTK-Z50-HD



Ditek Surge Protectors

#DTK-2MHTPWB

We now stock a complete line of Ditek surge suppression to help protect the expensive and delicate electrical equipment on your farm with AFFORDABLE surge protection options at multiple areas where surges can occur.

#DTK-MRJ31XSCPWP

#DTK-120/240HD2	
#DTK-120HW	Surge Protector DITEK for controllers 120 V only (AVG)
#DTK-120SR	Surge Protector DITEK for controllers 120 V only (best)
#DTK-240HW	Surge Protector DITEK for controllers 240 V only
#DTK-2MHTP	Surge Protector DITEK telephone module replacement for PWB
#DTK-2MHTPWB	Surge Protector DITEK telephone w/hardwired base (best)
#DTK-4LVTEP	Surge Protector DITEK telephone hardwired 4 pair (basic)
#DTK-MRJ31XSCPWP	
#DTK-MRJ45C5E	
#DTK-Z50-HD	Surge Protector DITEK for main panel box (best)
#DTK-120/240CM+	







Load Chutes

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Stationary Loading Chutes

#860000100	20′ load chute, all wood, outside walk board
#860000103	20' load chute, corrugated metal sides. outside walk board
#8608111100	20' load chute, no cover, inside walkway
#8608181100	
#8600010100	28' load chute, all wood,outside walk board
#8600010103	28' load chute, corrugated metal sides, outside walk board
#8600010111	
#8608191100	
	-

Portable Loading Chutes

#8608361100	
#8608371100	
#8608381100	



Lift and Winch Kit

#8601990100	Ground Lift I-Beam Unit (No Winch Package)
#8601980001	Manual Winch Package
#8607000000	Electric Winch Package

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Up to 3X faster than manual winches!





Fits 1/2" drill

Fits over base of the winch handle

.....Speed Crank

Speed Crank

The Speed Crank increases the speed of operating manual winches while eliminating the work and strain. The overall length is eight-inches with a 1/2" shaft. Center opening fits over a one-inch nut handle.



#HS802



Easiest way to safely remove an 800 lb. sow

Faster and variable speed device

Thousands of satisfied customers around the world since 2003



Power switch and battery level Indicator. Twist grip throttle.



180° Pivotal Mast



Flat Proof Tires



Industrial Heavy-Duty Winch



Designed by Pig Breeders for Breeders

#HSVX200S Hercules Arm 200 Var Speed, Non-Articulated w/ Footboard



Battery Charger

#HSSEE0000001X.24-volt



Power Cord

• for external battery charger

#HSSEXC000007X.....Power Cord



Battery

• DCS-50u, 50-amp

#HSSEB0000002A..... #HSSEB0000001P for SR



Winch Button Switch

#HSSES0000019P......UP/ DOWN Button



"UP" Button Switch

#HSSES1000001P... UP green button switch for SR/JR



"DOWN" Button Switch

#HSSES2000001P DOWN yellow button switch for SR/JR



Variable Switch

#HSSES0000002P.... Variable Speed Control Switch



#HSSES0000018P.....KEY switch On-OFF



Motor

#CRHUME200S....... Universal motor and gear kit

12" Gel Filled Wheel



#HSSAW0000013A for SR

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Caster Wheel Frame

HSHSASX0009



#HSHSASX0009..... for Articulating Models #HSHIASX0002 for Non-articulating Models

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



10" Gel Filled Wheel

#HSSAW0000010Afor JR/SR

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Telescoping Rod & Pipe Assembly

#HSHSACX0004.....for JR & SR

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Acme Ratchet

#HSSAX0000001A..... for JR & SR

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Winch SS Cable

#HSSAX0000040S......SS Cable

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Winch Nylon Rope

#HSSAX0000041N.....Nylon Rope



#HSHSASX0038...... Drive axle for HS20VX2 only

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Electrical module

#HSHSIASX0002.....for variable speed only

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Sow Carcass Cart

Large 900 lb. capacity for moving sow and larger animals. 900 lb. winch with 3/16" galvanized cable. 18-1/2" wide x 78" tall with tire height of 13".

#8330211100...... Sow Carcass Cart

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Four-Wheel **Carcass Cart**

Make dead removal safer and easier with this fourwheel carcass cart. Features include two-speed hand winch with 25-feet of galvanized cable, pneumatic twoply tires and casters, solid rod frame, and reclining bed.

Specifications:

Height: 76" Width: 20" Length: 40" Weight: 215 pounds Capacity: 600 pounds

#RWDCCIIFour-Wheel Carcass Cart

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Solid sides aid in winching hogs into place and the deep V-shaped trough keeps them there while moving. Straight pull winch eliminates extra pulleys. 13" tires roll over floor obstructions and maneuver into tight spots. 900 lb. winch with 3/16" galvanized cable. 600 lb. capacity.

#8330221100 ... Carcass Cart w/sheet metal sides #8330231100w/clutch winch

Replacement Parts for Carcass Carts

#HSH0671200 lb winch, black epoxy finish #8331810000 3/16" x 15' galv. cable #833135000013" Wheel #DL5163050800 lb. clutch winch

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Dead Sled

Low profile carcass cart reduces back strain when removing animals from trucks or pens. No winches or cables to maintain! Deep V-trough holds animals in place while allowing you to load and pull from either end. Sled measures 38" long x 33" wide and constructed of 16-ga. metal side with solid rod bumpers. Features eight-4" dia. wheels spaced to provide support for a load capacity of 600 lbs. Ships UPS.

#HSDS-1000 Dead Sled

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#8050221100 Hog Puller, T-style, 1 chain

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

WayPig® 300

- · 300-lb. capacity
- Steel construction
- · Green epoxy finish
- Overall: 55" H x 56" L x 21" W (with wheels: 21" L)
- Inside of Box: 31" H x 49" L x 15" W
- · Shipping Weight: 188 lbs.
- · 10-inch wheels (optional)

` - /	
#79300	
	Wheel and handle kit
#79301	Scale head replacement
#AH300	Stationary market hog scale

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



WayPig® Litter Scale

- · 200-lb. capacity
- · Steel construction
- · Green epoxy finish
- Overall: 51" H x 37" L x 21-1/2" W
- Inside of Box: 21" H x 32" L x 19-1/2" W
- Shipping Weight: 109 lbs.
- · 6-inch wheels

#79302..... WayPig litter scale #79308.....Scale head replacement

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

WayPig® 500 **Market Hog Scale**

• 500-lb. capacity

Bottom View

- · Durable steel construction with green epoxy finish
- Large, stainless steel scale head is accurate and easy to read
- (Outside) 61-1/4"H x 52-1/4"L x 27"W (30"W w/ optional wheel kit installed) (Inside Scale) 41"H x 48"L x 20"W



#79304500-lb market hog scale w/ wheel & handle kit #79305 Optional wheel and handle kit

#AH500-46......Scale head replacement

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



WayPig® 13 **Digital Market Hog Scale**

- 49" Inside length
- · 15" Inside width

#79300DIG Digital market scale #AH1422Optional wheel kit sold separately

📤 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Aluminum Sorting Panels Single (34" high)

bingio (o i mgm)	
#8077040900	2' Panel
#8077120900	
#8077020900	3' Panel
#8077060900	4' Panel
#8077000900	5' Panel
#8077080900	6' Panel
#8077090900	8' Panel
#8077100900	10' Panel

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Double Poly Sorting Panel

Rugged polyethylene with 20" painted hinge. Double 36" expands to 6'0", Double 48" covers 8'0".

#HS800-36D	30"	x Dbl	36"
#HS800-48D	30"	x Dbl	48"



Double (34" high)

#8077050900	2' panel- spans 4'
#8077130900	
#8077030900	3' Panel - spans 6'
#8077070900	4' Panel - spans 8'
#8077010900	5' Panel - spans 10'
#8077110900	6' panel – spans 12'
#10062H	Aluminum replacement hinge

WARNING:
This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Poly Sorting Panel

Lightweight, durable polyethylene panel with multiple molded hand holds. Smooth rounded construction with no sharp edges.

#HS800-18	30" x 18"
#HS800-36	30" x 36"
#HS800-48	30" x 48"



Show Sorting Panel

Special show version of polyethylene sorting panels. Same lightweight construction but now in stylish pink for the arena.

#1006381 30	" tall x 18" long
#1006382 30"	tall x 36" long



Load Out Door Guard

Protect load out doors from damage with this $28^{\prime\prime}$ reversible door guard. 19" solid attachment tube fits between wall bracket clips and fastens with a 1/2" gate rod. Easily cleaned and moved from barn to barn during load out.





.....Load Out Door Guard


Hog Slat Rattle Jug

Convenient to use blue jug with beads inside creates rattling noise to help make moving and loading livestock easier.



- · High-density polyethylene construction
- Cup Demensions 7"W x 6"D x 8" H

#HS801 Hog Slat Rattle Jug



The Hog Slat® pig snare features a j-hook shaped handle, t-bar and 20" cable.

#HS799 Hog Slat Pig Snare

WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



#K07000soft grip, 18" long

♠ WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



RazzCan

Shaking the RazzCan creates a rattling noise to help move pigs when loading and unloading from barns and trailers.


▲WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Hog Flapper

The Hog Flapper is an effective alternative for the humane movement of animals. This one-piece sorting baton uses four flexible flappers to create a loud "CRACK" when struck against solid object. Molded of durable bright orange poly.

#9021Hog Flapper, 19-1/2" long



#TA819......23" long with green handle **#D-212**.....35" long with red handle

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#KRP47CHog Paddle Stick



Rigid Shaft Paddle Stick

- 48" rigid shaft
- · Plastic paddle with noise rattles

#50079RRigid shaft sorter paddle stick



Flex Shaft Paddle Stick

- 48" flex shaft
- · Plastic paddle with noise rattles
- #50079F.....Flex shaft sorter paddle stick

Itz Captive Bolt Stunner

An affordable answer to safe humane dispatching of animals. These German-made instruments feature a nickel-plated exterior and heavy-duty components.

Hog Paddle Stick

· Plastic paddle with noise rattles

• 48" rigid shaft



Powered by 9-mm cartridges, these captive bolt stunners deliver a powerful and effective shot. Gun not sold separately, packaged as a complete kit only.

Length	Diameter	Bolt Diameter	Bolt Penetration

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Blitz

· Durable plastic storage case

- · BLITZ captive bolt stunner
- · Container of (50) 9mm blank cartridges (red or blue)
- · Set of cleaning brushes & cleaning fluid

#BL35-320Blitz Complete Kit

Blitz-LO

13"

Special non-penetrating stunner used to dispatch smaller animals under 40 pounds including small pigs and turkeys. Packaged as a complete kit with one box (50) of low power green blanks.

1.5"



Cleaning Kit

Blitz gun cleaning kit includes handle and two brushes.

#BL35-314 Cleaning Kit



15/32"





2-1/4"

9mm Blank Cartridges

• 50 per container

#BL35-302Low - Green #BL35-305 Medium - Yellow #BL35-301 Strong - Blue #BL35-304Power - Red



Replacement Spring & Buffer Kit

· We suggest replacing these items after using 150 rounds

#BL05-117 Spring & Buffer kit

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Choose a Better Prod!

Durable

Hearing that a truck ran over his SHARPSHOCK and it still worked left us skeptical. We tested it – and it's true!

Flexible

SHARPSHOCK shafts are so flexible they can be bent up to 270°!

Economical

SHARPSHOCK prods use only 4 C batteries instead of 6 making them cheaper to run.

Waterproof

SHARPSHOCK motors and handles are sealed with resin making them completely waterproof.



#SS30-161	Standard Handle (batteries included)
#SS30-140	Replacement C Batteries
#SS30-163	Rechargeable Handle (battery pack and 120V wall charger included)
#BL00-163	Replacement Battery Pack
#SS30-164	
	#SS30-161 #SS30-140 #SS30-163 #BL00-163

Hot-Shot DuraProd

Incorporating the lastest technologies available, the DuraProd $^{\text{TM}}$ delivers consistent, superior performance in a new ergonomic design. Benefits include:

- Durability sealed circuit ensures unit will work in all conditions
- Reliability tested using six proprietary measures to ensure consistent performance
- Safety new patent-pending Circuit Isolation Technology reduces feedback shock during use
- User Comfort new handle design featuring rubber overmolded grip, oversized trigger & hand guard





DuraProd Motor Handle Unit Only #50463



DuraProd Rechargeable Battery Pack #50464



DuraProd Charger w/110V Wall Adaptor #50465



DuraProd Rechargeable Kit #50467

#50461	Battery Handle Unit Only
#50462	Rechargeable Handle Unit Only
#50463	Motor Handle Unit Only

#50464	Recharg	eable Battery Pack
#50465	Base Charger w/	110V Wall Adaptor
#50467 Rechargeable Kit w/Battery	Pack, Charger Base,	12V/110V adapters








Hot-Shot

	Red Sabre™ handle w/ batteries
#MMCHU2HS	Green HS2000 handle w/ batteries
#MMCHU2HSR	Green rechargeable handle
#50420	Power-Mite
#50445	Black flex shaft 13-1/2"
#50446	Black flex shaft 23-1/2"
#50447	Black flex shaft 33-1/2"
	Black flex shaft 43-1/2"
#50440	White rigid fiberglass shaft 15-3/4"

#50447

#50441	White rigid fiberglass shaft 27-3/4"
#50442	White rigid fiberglass shaft 39-3/4"
#50426	12V charger/adapter
#50428	110V charger/adapter
#MMCRBP3	Rechargeable battery pack
#50432	White shaft nut
#50433	HS1 driver replacement motor (green pack)
#50436	SS1 driver replacement motor (red pack)
#50460	Hi alkaline batteries each (size C), 6 pack



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

1 Complete Power Unit

• Shipped Assembled

#452-709M Complete Power Unit

A) Scraper Gear Reducer

- · Right-angle gear reducer with bottom system drive
- Planetary gear system with a 55:1 reduction ratio enclosed in cast iron housing

#L10-00-0473.....Scraper Gear Reducer

B) Motor

- Single phase (PSC) direct drive
- TEAO (totally enclosed air over)
- Resilient base 1 Phase 60 Hz TEFC enclosure
- 5/8" shaft 56 Frame 1725 RPM 115/230 volt

#5330014...... 3/4 Hp base mount

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

C) Sheave Hub

• 1" bore x 8" diameter

#452-718 For scraper gear box

D & E) Scraper Pulley

D) #PAK4458....4-1/2" x 5/8" pulley (gear reducer) **E) #PAK2558**.......2-1/2" x 5/8" pulley (motor)

F) Type A Belt Gro



#HSA24......1/2" x 26" standard type A belt

#452-457..... Manual Scraper Switch

#5903115-Minute Timer



4) Stainless Steel Scraper Blades

#8070280500 Stainless Steel - 6' 5" #8070240500 Stainless Steel - 7' 1"

#8070270500 Stainless Steel - 9' 2"



5) Scraper Stop Rod

#2012580500 1/2" x 58"



6) Corner Wheel Assembly

#452-708......SS Bracket and Wheel

6A) Scraper Wheel Bracket

#8070250500......SS




6B) Axle, Bushing, Wheel

7) Cable



#617276......5/16" - 7 x 19 SS



Use to mount Corner Wheel Assembly to right angle. Bolts not included.

#8070260500......8" x 5" SS, Right Angle



Manhole Grate

#3250110500......SS, 12" x 12"



Flush Control



WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Float & Bracket for **Submersible Pump**

• Float constructed of 6" PVC, 32" wide x 60" long.

Stainless steel bracket 2" x 33"

......Float 6" PVC 32" x 60" Bracket for pump, SS 2" x 33"



WARNING: *This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Wingo Line Cleaner

Line Cleaner is the new alternative in lagoon recycle line maintenance. It is user-safe and environmentally friendly. Line cleaner is a recycle line descaler that breaks down the bonding of salt, lime and calcium build-up in lines and pumps (safe in all types of pumps).



#79016......Wingo Line Cleaner

Muratic Acid

Use for cleaning recycling lines and etching concrete surfaces.

#59738

- 1 gal
- 31.45% active ingredient
- · Highly corrosive

#79010.....

. Muratic Acid



GSI Flush Tank Parts

1) #G20602	56" standpipe
2) #G20605	Piston assy
3) #G20606	Piston connecting rod assy
#G20608	SS Piston connecting rod assy
4) #G20607	8" Gasket for standpipe
#G20621	Piston guide bracket
#8060970500	S.S. Piston guide bracket

Cord Replacement

Replacement cord for Flush control, SJ 14 ga x 9', 110V

#HSCS-001SJ 14/3 9' 110V SJT00W Male End



Time-Delay Relay

#59093..... Time-delay relay



Alternate Relay

#59091 Alternate relay 98A00479



- 1-12 operations per day
- 40A 120V
- · 2NO-1NC swt

#INET1115C 60 second on/off









#61647..... Mercury float switch





Rubber Diaphragm & Flush Tank Washer

#61659.....Flush tank washer 3/8" x 5" **#61962**......8" Rubber diaphragm



Micro Switch

#61631For flush tank



WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Submersible Sewage Ejector Pump

Handles tough, demanding tasks of effluent and sewage waste transfer materials up to 2" spherical diameter.

- Heavy-Duty cast iron housing Completely submersible Rated for continuous duty

 - Single Phase





Fullips up to 33	- Sell-Colitained power cold		-	8	
Item#	Volts	Hz	Нр	Cord	GPM @ 10
A) 61080	230	60	1	40'	150
B) 610800	230	60	2	20'	205

WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



MicroPT Pit and Lagoon Treatment

MicroPT's proprietary formula consists of stabilized natural and organic microorganisms designed to reduce pit and lagoon odors. Regular use aids in the digestion and liquefaction of manure solids along with a reduction in total nitrogen and ammonia content. Apply one gallon per 100,000 gallons of waste.

#MICROPT......2.5 gal. container



ASI Flush and Lagoon™

ASI Maintenace combines naturally-occurring bacteria to reduce organic solids, control odors and provide effective insect management. Water soluble packaging allow the product to be introduced through flush tanks, lift stations or directly into the lagoon.

#AS1002......1 lb. pack



No mixing or measuring, just toss it in your lagoon or pit and forget about it until the next treatment, AGRASPHERE utilizes a patented time-release technology that provides 24/7 continuous activation while being eco-friendly in a

AgraSphere

biodegradable sphere

#SPHERE......Pit Treatment #30500Lagoon Treatment (4 pk)



AgraSlat™

New slim profile allows placement through slat openings in deep pits. Contains proprietary blend of microbial insulates to liquefy solids and reduce pit crust.

#BA30150 AgraSlat™



ASI Pit Hammer Plus™

Pit Hammer Plus contains trillions of bacteria that safely digest and liquefy solids to reduce odor admissions in pits. The addition of citronella oil acts as an aid in controlling insect infestations.

#AS1000......2 gal container



ASI Pit Hammer™

Regular strength formulation containing bacteria that reduce odor admissions by liquifying pit solids. Contains citronella oil to help control insect populations.

#AS1001 5 Gal. bucket



ASI BioBlocks™

A blend of multiple bacterial spore selected to biologically digest and treat organic wastes in an easy-to-use timerelease cylinder. 1 block treats 100,000 gallons of waste. Drop into pit load outs, flush tanks and lift stations.

#AS1006 BioBlock (case of 4)



ASI Pit Slammer™

ASI Pit Slammers™ are designed to slip into the slatted floors of deep and shallow pit buildings to digest organic wastes natuarally and effectively.

#AS1007......ASI Pit Slammer



Al+Clear®

Al+Clear® is a powdered Aluminum Sulfate that reduces ammonia levels and inhibits pathogen growth in the litter throughout the bird's grow out period. Al+Clear® also improves the nitrogen content and binds up the phosphorous to reduce water runoff when litter is used for fertilizer.

#WY25213Al+ Clear, 50 lb. bag



MicroPuran®

MicroPuran® is a 100% soluble dry powder blend of enzymes, absorbents, oxidants, nutrients and selected anaerobic microbes designed to reduce ammonia emission, retain nitrogen in waste and aids in the digestion of solids. MicroPuran® helps your bottom line by improving your litter value, saving application and improving population of favorable bacteria.

#WHMIC...... MicroPuran, 1 lb.



Ultra Litter Treatment[™]

Ultra Litter Treatment™ is a blend of food grade organic acids and sodium salts blended with food grade buffering agents and YS-50® (Yucca schidigera extract). Lowering the pH of the poultry house floor or litter greatly improves the environment by reducing ammonia levels and by inhibiting pathogens that have an adverse effect on performance. ULT is a liquid that lowers the pH instantly. One five (5) gallon container of ULT mixed with 70 gallons of water will cover up to 20,000 square feet.

#ULT5GAL 5 gal. container



Poultry Litter Treatment - PLT

The Industry Leader in Ammonia Control **Delivery Available at Most Locations**

for an Additional Charge

#WYPLT0025......50 lb. bag




BURN-EASY INCINERATORS

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

COMPLETE UNITS



Item#	Model	Diameter	Door	Door Dimensions	Capacity
RK3102	Model 12 Afterburner Oil	2'x12"	N/A	N/A	N/A
RK3102-LP	Model 12 Afterburner LP	2'x12"	N/A	N/A	N/A
RK3102-NG	Model 12 Afterburner NG	2'x12"	N/A	N/A	N/A
RK3100	Model 20 Afterburner Oil	4'x20"	N/A	N/A	N/A
RK3100-LP	Model 20 Afterburner LP	4'x20"	N/A	N/A	N/A
RK3100-NG	Model 20 Afterburner NG	4'x20"	N/A	N/A	N/A
RK4280	Model 428 WO/Grate Oil	8'x42"	Single Door-Winched	31"x66"	1,200 lbs.
RK4280-LP	Model 428 WO/Grate LP	8'x42"	Single Door-Winched	31"x66"	1,200 lbs.
RK4280-NG	Model 428 WO/Grate NG	8'x42"	Single Door-Winched	31"x66"	1,200 lbs.
RK529	Model 529 Heat Lined Diesel	9'x52"	Single Door-Winched	43"x77"	2,500 lbs.



REPLACEMENT PARTS

#HS9074*	Motor 1/5 HP 3450 RPM 50/60 Hz Burn Easy Incinerator
#52359	New style heat probe for Burn Easy incinerator
#RK1205	Transformer Igniter Coil for Burn Easy Incinerator
#RK1642	
#523597	Fan Blower for Burn Easy Incinerator
#523598	Pump Fuel for Burn Easy Incinerator
#5235992	Gun Assembly For Incinerator
#RK1005	
#RK1006	
#RK1007	Nozzle 2GPH for Burn Easy Incinerator
#RK1206	Spring for 5235901 Transformer
#RK1209	Drive Coupler for Burn Easy Incinerator

*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#RK1226	Igniter for Burn Easy Incinerator
#RK1230	Tube Air Assembly for Incinerator
#RK1237	Shut Off Fuel for Burn Easy Incinerator
#RK1238	Probe Heat Plug for Burn Easy Incinerator
#RK1243B	Board Control for Control Box 523595 Burn Easy Incinerator
#RK1245	Box Only for Controls pre Drilled Bottom & Top
#RK1248	Decal Only for Burn Easy Controller
#RK3802	Grate for 500 LB Burn Easy Incinerator
#RK3803	Grate for 700 Lb Burn Easy 3 Per Set 22" X 24 1/2"
#RK3806	Grates for 1200LB Burn Easy Incinerator (Set of 5) 15" X 27"





Destructor Juniors

100 lbs total fill capacity (80 lb Recommended Burn Capacity)

• Size (H x L x W): 7'10" x 4' x 3' • Door Size: 17" x 17"

#02222JRWOB	Destructor JR- NO BURNER
#52350	Destructor Junior LP
#52350NG	Destructor Junior NG
#52350D	Destructor Junior Diesel
#52350-SBURN	Destructor Junior W/Secondary Burner LP
	Destructor Junior W/Secondary Burner NG
#52350D-SBURN	Destructor Junior W/Secondary Burner Diesel

Destructor Standard Door

1000 lbs total fill capacity (500 lb Recommended Burn Capacity)

• Size (H x L x W): 8'4" x 6' x 4 • Door Size: 17" x 24"

(
#52531-WOB	Destructor 500 Standard Door NO BURNERS
#02222DSLP	Destructor 500 Standard 24"x17" Door LP
#02222DSNG	
#52531D	
#52531-SBURN	Destructor 500 W/Secondary Burner Std Door LP
#52531NG-SBURN.	Destructor 500 W/Secondary Burner Std Door NG
#NIO22DSSCDSL	Destructor 500 Standard Door W/Secondary Burner Diesel

Destructor TC-275

275 lbs total fill capacity (138 lb Recommended Burn Capacity) • Size (H x L x W): 7'10" x 5'8" x 4'1" • Door Size: 14-1/2" x 24"

#52533 TC-275 LP #52533NG TC-275 NG #52533-SBURN...... TC-275 W/Secondary Burner LP #02222TC275SC TC- 275 W/Secondary Burner NG #52533D-SBURN TC-275 W/Secondary Burner Diesel

Destructor Hog Door

1000 lbs total fill capacity (500 lb Recommended Burn Capacity)

• Size (H x L x W): 8'4" x 6' x 4' • Door Size: 17" x 36"

DEED (II N II N VV). O I N O N	1 Door billo. 11 A CC
#52531HD	Destructor 500 Hog Door LP
#02222DSHOGDOOR	Destructor 500 Hog Door NG
#52531DSPEC	Destructor 500 36"x17" Hog Door Diesel
#52531-SBURN-HD	. Destructor 500 W/Secondary Burner & Hog Door LP
#52531NG-SBURNHD	Destructor 500 W/Secondary Burner & Hog Door NG
#02222DSHHOGDOOR	. Destructor 500 W/Second Burner & Hog Door Diesel
	_

Destructor HD500 Hog/ Sow

1000 lbs total fill capacity (500 lb Recommended Burn Capacity)


• Size (H x I, x W): 8'4" x 7' x 4' • Door Size: 4'4" x 20"


· DIZE (II A LI A VV). O T A I A T	Door bize. 44 X ZO
#525310	
#525310NG	Destructor HD500 54"x20" Door NG
#525310NG-SBURN	Destructor HD500 W/Secondary Burner NG
	Destructor HD500 W/Secondary Burner LP

LP Gas Incinerator

1) #NI6421-59	Tube Igniter
2) #NI8400-00	Regulator
	Block Ignitor Inlet
	Assembly
5) #NI6401-90	Shutter Replacement Kit
6) #NI6407-30	Gasket Flange
7) #NI6407-90	Mounting Flange Kit
8) #NI6406-05	Tube Blast LP & NG
9) #NI6404-90	Screw Input Adjustment
10) #NI6460-00	Igniter Assembly
11) #NI6413-09	Barrier Ground Kit
12) #NI6464-00	Motor
13) #NI6457-00	Ignitor Electrode
	Manifold

15) #NI6452-50	Gas Valve
16) #NI6416-90	. Inlet Ring & Screen Replacement
	Switch Terminal
18) #NI6410-00	Wheel Blower
19) #NI6400-80	Housing for Blower
20) #NI8429-03	Control Board Honeywell
21) #NI8408-42	Strip Terminal
22) #NI6458-50	Wire Boot Kit
23) #NI8408-76	Fuse
NS) #NI3200TC	Control Cal Incinerator
NS) #MKS2PIAC12	0 Relay






WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Becket Diesel Burner

1) #NIIDMDE07/DVII	Purpor Houging Aggs
	Burner Housing Assy.
2) #NIRWB3709	Air Shutter
3) #NIRWB5151501	Air Band
4) #NIRWB3493	Escutcheon Plate
#NIRWB5941	Adjusting Plate Assy.
5) #NIRWB5432	ADJ Mounting Flange
6) #NIRWB2139	Hole Plug
7) #NIRWB2456U	Motor 1/7 HP Becket
#NIRWB4189	Mounting Screws
9) #NIRWB2999U	Blower Wheel
10) #NIRWB2454	Coupler Driver for Pump
12) #NIRWB2256	Pump Nozzle Port Fitting
13) #NIRWB5636	Connector Tube Assy.
14) #NIRWB51771U	Transformer Fuel Oil model

15) #NIRWB31232	Hinge to Housing Gasket
17) #NIRWB5880	Low Firing Baffle
18) #NIRWB5780	Ignitor (electrode only)
19) #NIRWB2885	Pedestal Support Kit
20) #NIRWB5606	Extended Pedestal Kit
21) #NIRWB5770	Junction Box Kit
#NIRWB550274	Probe Wires
#NI101343-002	Ignition Control
#NIRWB5919	Probe Kit
#NIRWB7101U	Valve Oil Solenoid
#NIRWBAF65XPT	Tube Air Combination
#NIRWB5878	Trans Ignition Assembly
A Th	is product on expose you to shomic




WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Wayne Diesel Burner for Burn Easy and Valco Incinerators:

wayne biesei buin	iei ioi buili Lasy alli
1) #HS9074	Motor
2) #RK1202	Power Cord
3) #523597	Blower Fan
4) #RK1204	Fan & Burner Housing
5) #RK1205	Transformer
6) #RK1642	Controller (New Style)
NS) #RK1243B	Controller Board
7) #RK1235	Slot Cover Plate
8) #RK1207	Inner Air Band
9) #RK1208	Outer Air Band
10) #RK1209	Drive Coupler
11) #RK1210	Oil Line Assy.
12) #523598	Fuel Pump Suntec
12) #RK1211D	Fuel Pump Danfoss

16) #5235992	Gun Assy.
17-21) #RK1230	Air Tube Assy.
NS) #FD6H	6 Hr. Timer
20) #RK1216	Gasket
Part of 16) #RK1224	Hold Down Clamp
Part of 16) #RK1225	Flamelock
	Electrode Assy. w/Buss Bar
	Buss Bar
NS) #RK1005	After Burner Nozzle 1.10gph
NS) #RK1006	Main Burner Nozzle 2.25gph
NS) #RK1237	Fuel Oil Shut Off Valve
NS) #RK1238	Probe Heat Plug
ſ .	



WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

No Pre-Mix **Hose End** Sprayer

- No pre-mixing set metering dial for required dilution; concentrate & water will automatically be mixed at set rate.
- · Metering dial automatically be mixed at set rate. Metering dial selects from 16 mixing ratios; 1 teaspoon up to 10 tablespoons.
- · Sprays up to 100 gallons, remove the deflector for solid stream coverage up to 30'.
- Operates on water pressures ranging from 45-60psi. · Built-in anti-siphon device prevents back flow, unused
- chemicals can be returned to the container.

#HH13621115 No Pre-Mix Hose End Sprayer



HydroSprayer

Preset applicator with 1/2 oz. per gallon tip. Ideal for apply high volume saturation of Tek-Trol at low pressures. Saves on wastage and improves chemical performance.

#TEK-002Tek-Trol applicator, quart, liquid



1-Gallon Pump Sprayer

- Features durable, lightweight polyethylene tank which is non-corrosive to most fertilizers. herbicides and pesticides.
- Translucent poly tank allows easy viewing of liquid levels.
- Patent SureSpray® filter prevents most debris from clogging hose.
- · Funnel top for easy filling.
- Pressure relief valve to remove compressed air before opening to fill

#CH20075...... 1 gal. pump sprayer



Delivers disinfectant as thick, clinging foam to improve its effective power. Foam clings to vertical surfaces and promotes better coverage because operators can see where the disinfectant has been applied. Applicator connects to a regular garden hose, and its large, 48-oz. bottle is filled directly with disinfectant concentrate.

Dilution rate is Max 128:1 Min 12:1.

#HS483HydroFoamer



Flat-Back design fits snug against wall or gates and it makes hauling easier. Heavy polyethylene plastic resists damage from impact and warping. Heavy-duty wire handle with hanging notch. 14.75" diameter x 23" high, holds 5 gals. Black.

#P20FB-BLK20 Qt. Flat-Back Bucket



High-Pressure Foamer

Foamer attachement for use with high pressure sprayers; includes wide mouth, 64-oz tank. Constructed of corrosion-resistance stainless steel and plastic with five chemical mixture settings. Rated for 3625 psi and 5.2 gpm with max temperature rating of 176°F. Unique design reduces chemical consumption by up to 50% compared to other foamers.

#NPST732High-Pressure Foamer



Heavy duty, commercial grade boot scraper with durable powder coated steel frame and base. Features built in scraper on each sides. Poly brush mounts with extra stiff nylon bristles. Mounting screws and anchors included. No assembly required. Dimensions: 7.5"H x 9.5"W.

#KAHD1.....Commercial Model w/ base #KAHDRB1 Replacement Brush Set



EZ Disinfectant Pan

Covered foot pan reduces contamination of disinfectants. Includes 36" handle for ease of opening and closing. Metal pan measures 16" x 14" x 2" deep.



#IS9601-001 EZ Disinfectant Pan



Disinfection Mat

Our highest quality entrance mat. Constructed of foam core covered by a tough poly mesh with non-permeable bottom and sides to contain the disinfectant solution. The mat's extra capacity, of approximately 2 gallons, keeps solution fresher. The extra width prevents "walk-arounds" at entrance doors. We found the mats to hold solution better on uneven surfaces than other types we've used.

#459342434" x 24" x 1" deep



Black Disinfectant Mat

Thousands of rubber fingers cover the mat surface to dislodge debris from boot soles. Recessed mat holds up to one gallon solution.

#TM222......24" x 36"



Disinfection Mat

#80200024" x 32" Disinfection Mat



Rubber Disinfectant Pan & Tub

#HP3 3-gal. pan, 17-1/2" dia x 4-1/2" high #HP650 6.5-gal. tub, 18" dia. x 8" high

Respiratory Protection

- Dura-Mesh® outer shell retains its shape in moist conditions.
- · Soft foam nose cushion provides secure fit without metal straps.
- Double straps holds mask firmly.



2) #790130Dust & Mist Respirator 2300N95, Exhale valve quickly releases exhaled air, 10/box, Med/Large

7000 & 9000 Series **Reusable Masks**

Moldex designed the 7000 half mask and 9000 full face series to be the most user friendly reusable respirators on the market. Featuring fewer parts, minimal maintenance, and a wider field of vision. Ultra-lightweight, durable, and economical, providing maximum comfort with extended use.



Item#	OEM#	Description
#797112	7112	Moldex 7000 Half Mask Medium for Pesticide, Organic Vapor use w/ N95 Prefilter Assy
#797002	7002	Moldex 7000 Half Mask Only
#797942	7942	Moldex 7000 Half Mask Medium w/ P100 HEPA Filter Assy.
#799002	9002	Moldex 9000 Full Mask Only
#797920	7920	Piggyback Adapter for P100 Filter pair
#797940	7940	Replacement P100 Filter pair
#378910	8910	N95 Particulate Filter (5 pair)
#377020	7020	N95 Filter Retainer pair
#377600	7600	Replacement Multi-Gas Smart Cartridge

Medical Style Dust Mask

• 50 per box

#470700 Medical Style Dust Mask



Nuisance Mask

Non-rated nuisance mask which reduces irritating effects of non-toxic particles such as dust, pollen and cut grass. Paper construction with adjustable nose piece and single strap.

#7901008......Nuisance mask, 50/ box



Particulate Respirators 3M disposable particulate respirators are designed to provide comfortable, reliable protection against certain organic particles. These face pieces feature adjustable nose-clips and dual head bands for a better seal and a secure fit. Carbon layer on R95 models help reduce nuisance levels of gas and vapors. Cool Flow™ Exhalation Valve reduces heat build-up inside the respirator for greater comfort.



Hair Nets

• Bag of 100

#4GL67..Hair Nets



Pre-Powdered Latex Gloves

• 100 per box

#002053.	Latex Lightly Powdered Medium
#002107	Latex Lightly Powdered Large
#003852	Latex Lightly Powdered XL

Short Sleeve Poplin Coveralls

- 5 oz Poplin fabric
- 65% Polyester / 35% Combed Cotton
- Two-way brass zipper
- Two set-in front pockets · Two chest pockets
- Two patch hip pockets

#CP40NV-RG-S	Small
#CP40NV-RG-M	Medium
#CP40NV-RG-L	Large
#CP40NV-RG-XL	Extra Large
#CP40NV-RG-XXL	2X large
#CP40NV-RG-3XL	3X large
#CP40NV-RG-4XL	4X large



Mircomax® NS **Disposable Coveralls**

- Breathable
- · Open wrist & ankle

364153-EA	L - each
364153	L - case/25
364154-EA	XL - each
364154	XL -case/25
364155-EA	2XL - each
364155	2XL - case/25
364156-EA	3XL - each
364156	3XL - case/25
364157-EA	4XL - each
364157	4XL - case/25
364158-EA	5XL - each
364158	5XL - case/25



Foam Ear Plugs

- · Disposable foam ear plugs, Pura-Fit® NRR3
- · 200 pairs per box
- Uncorded



Constructed of EVA expanded rubber, the Chorelite boot is not only durable but the lightest boot we have found for use in poultry and swine houses. The Chorelite weights



less than 10 ounces vs a standard rubber boot at over 2 lbs. Its one-piece molded design has no seams to leak and because it is unlined the Chorelite can be cleaned and disinfected inside and out. Men's sizes only.

#M688-8	Size 8
#M688-9	Size 9
#M688-10	Size 10
#M688-11	Size 11
#M688-12	Size 12
#M688-13	Size 13



reinforced steel toe. Good general purpose farm boot where extra protection is desired.

Servus® Northern

15" high. Navy. TDT plastic compounds for increased durability cushioned center sole.

Series - Ladies

#75109-6	Size 6
#75109-7	Size 7
#75109-8	Size 8
#75109-9	Size 9
#75109-10	Size 10
#75109-11	Size 11
#75109-12	Size 12
#75109-13	Size 13

#75126-5.....Size 5 **#75126-6**......Size 6

#75126-7.....Size 7

#75126-8.....Size 8 #**75126-9**......Size 9 #75126-10......Size 10 #**75126-11**.....Size 11

Tinglev Airgo™ Lightweight **Knee Boots**

#21154-6.....

#21154-7.....

Lightweight, yet durable, these boots are 100% waterproof and have outsoles for traction resistance in wet and conditions.

% e cleated and slip ad muddy	
	Size 6
	Size 7
	Size 8
	Size 9
	0: 10

Carring® Marthaus	
#21154-13	
#21154-12	
#21154-11	Size 1
#21154-10	Size 1
#21154-9	Size 9
#21154-8	Size

Servus® Northern Series - Mens

15" high. Olive. TDT plastic compounds for increased

Size 5
Size 6
Size 7
Size 8
Size 9
Size 10
Size 11
Size 12
Size 13



Plastic Covers

• 25 pairs per box

#79099	Plastic Covers, one size fits all
#429503	3 mil, elastic top
#429510	6 mil, elastic top



Tek-Trol Aerosol

A spot disinfectant for use on boots, clothing, vehicles and hand tools. Non-staining, quick drying and ideally suited for service personnel moving from location to location.

#TEK-001 17 oz. aerosol spray can



Disposable Boot Covers

Disposable Boot/Shoe Covers with laminated Fabric, has a PVC textured sole. They are waterproof (not submersible) with elastic bands and a seamless bottom

1) #TI52658...... White, 16 1/2" long, 18" tall, 50/box 2) #TI53474 Heavy Duty, gray, 19" long, 7 3/4" Tall, 100/box 3) #TI72388 ...Light Weight, white, 15 1/2 long, 6 1/2 tall, 150/box



Biosecurity Signs

18" octagon style stop signs are made of outdoor-grade, high-density .055 gauge polyethylene. Red sign and white letters are printed with fade resistant inks. 2" x 7" blank white space at bottom center of sign provides highly visible area to list farm name, contact information or other instructions.

#BIOSIGN2......18" Disease Prevention Area" stop sign, .055-gauge rigid poly



Bioshift® Pass-Through UVC Chamber

The BioShift® is an economically friendly tool to use alongside established bio-security protocols. It is designed to kill viruses in a recommended time of five minutes, while being an effective replacement for passthrough windows and doors, germicidal disinfecting sprays/fogs, chemical cleaners and un-secured access panels.

- 120/240 Volts
- 80W Operating power
- · 7W Standby power
- 0-999 second variable time setting
- 23-1/2' L x 29-3/4" W x 24" H


#0I24-0200..... BioShift UVC Chamber



EasyFix Luna

A range of floor products are designed to provide environmental enrichment for pigs. Made from high quality natural rubber, the products are pliable, durable and safe for pigs to bite on.

#LUNA50	Red, 0-4 weeks
	Yellow, 4-7 weeks
#LUNA117	Blue, 7-12 weeks
#LUNA142	Green. Finish/sows



#HS830Castration mate

♠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

50cc Pistol Grip Syringe

- · Rugged cast aluminum pistol grip with high impact plastic barrel.
- Adjustable settings from 1 to 5 cc.
- · Includes a set of replacement washers.

#1000.....50cc Pistol Grip Syringe




easier process · Comes with a hook for

hanging · Does not require a spring adjuster for 100cc bottle

or less

#206558	2cc
#206657	5cc



· Vaccinator Replacement

#2068002cc **#206855**5cc #351616......1/2cc



Vaccinator with Large Draw-Off

- · Ruggedly designed syringe
- · Includes a hook for hanging the vaccinator out of one's way
- · Universal needle cap fits all lure lock style needles
- · Does not require a spring adjuster
- Tubing is included

#213105......5cc



#213358	2ml Prima-Marc w/ both draw offs
#212153	2ml replacement barrel
#213457	5ml Prima-Marc w/ both draw offs

#211903.....5ml replacement barrel



Barrel with O-Ring

- · Vaccinator Replacement
- · Includes Barrel, Piston O-ring

#206404	2cc
#217409	5cc



Draw-Offs

Slip draw-offs spike in the top of the medicine bottle so the cap surrounds the top to prevent leaks. Hose not included.

#141859	Small	draw-off
#141804	Large	draw-off

#VAC-AL.....On-arm - large

#VAC-AM......On-arm - medium

#VAC-WL.....Waist - large

#VAC-WM......Waist - medium





Needle Nut & Piston O-Ring

· Vaccinator Replacement

#203151	. Needle Nut 2cc, 5cc, 6cc
#203304	Piston O-Ring 1cc, 2cc
#203502	Piston O-Ring 5cc, 6cc



Metal Needle Nut

#330840SS luer lock needle nut



Vac-Pacs



Marking Twist Sticks

- · Colors are durable for approximately four weeks on cattle and sheep and two weeks on swine.
- · Reliable in all temperatures, strong in color with high luminosity.
- 10 sticks in a box (buy the box and SAVE!)

#001155 Purple #001209 Black #001254 Orange #001308 Red

#001353 Green **#001407** Blue

#002503 Fluorescent pink



Prima-Marc Spray

· 24 cans per case

#211859 Red #211651 Blue #211705 Green #211750 Orange



Spray-On Livestock Markers

· 12 cans per box

#VAC-171	Green
#VAC-172	Red
#VAC-174	Blue
#VAC-173	Fluorescent orange
#VAC-178	Fluorescent Purple
#VAC-179	Fluorescent Green
#VAC-180	Black

Spray On Marking Concentrate

- · Spray On Marking Concentrate provides an extremely inexpensive animal marking product. Just mix with water in a spray bottle and begin marking.
- Marking Concentrate produces an extremely visible mark that will not rub off.
- 16 fluid oz. bottles









Tamper Proof Button



Back

Swine Shows, State and County Fairs, and Auctions will soon require 840 tags. Learn more about 840 and PIN tags by reading our blog article:




Destron Fearing

Official Swine ID - Frequently Asked Questions

USDA Premise ID (PIN) Ear Tags

- Tags include a tamper-proof button and visual panel to easily identify tagged animals
- Tags include the official US shield, the assigned alpha-numeric seven character PIN (Premises Identification Number), state abbreviation and an "Unlawful to Remove" notice.
- Constructed of high-grade polyurethane to resist damage.
- Data is laser imprinted and inked to for easily visibility.
- *25 per bag. See website for available colors.





Easily monitor your pigs to accomplish specific goals for your operation. Hog Slat offers \mathbb{D} using \mathbb{D} using tags from Destron Fearing, available in 2 sizes and the most popular colors. Blank tags or tags with printed management numbers are available to maximize flexibility when tagging your animals



Cattle

Cattle tags allow you to visually identify and track your herd. Hog Slat offers Duflex® visual ID cattle tags from Destron Fearing™, available in 3 sizes and the most popular colors. Blank tags or tags with printed management numbers are available to maximize flexibility when tagging your cattle.



Sheep & Goats

Hog Slat offers Duflex® visual ID goat and sheep tags from Destron Fearing™, available in the most popular colors. Blank tags or tags with printed management numbers are available to maximize flexibility when tagging your animals.



EZ-Knife™

Safely and quickly remove animal identification tags with the EZ $\text{Knife}^{\scriptscriptstyle{\text{TM}}}$

#DFAC7004..... EZ-KnifeTM



ProGrip™ 2

Use the $\mathsf{ProGrip^{TM}}$ 2 applicator to quickly and accurately attach animal ID tags to livestock.

#DFAC7066......ProGrip $^{\text{TM}}$ 2 **#DFAC7008**....replacement pins

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Super Mark™

The Super Mark^m Pen contains special ink to permanently mark Destron Fearing^m animal identification tags.

#DFAC7001Super MarkTM

AVAILABLE COLORS:



REAPER



CHICKEN REAPER HIGHLIGHTS:

- · Wooden Track
- Adjustable Speed Remote
- Dump Box or Bucket Tray
- 24 Volt Lithium Battery
- · Gearmotor Disengage Lever
- · Heavy-Duty Galvanized Steel
- · Adjustable Height

The Chicken Reaper ships with everything needed for the complete system (with the exception of the rail lumber.) All fasteners, bolts, nuts, etc are included!



WOOD TRACK

The truss brackets are secured to bottom of every truss with (2) GRK fasteners. A galvanized steel hanger bracket then attaches the 2 x 6 yellow pine (provided by the end user) rail to truss bracket. This simple and sturdy rail system drastically reduces the cost of installing a trolley system in your poultry house. And since the rail lumber is sourced locally, shipping the Chicken Reaper is very economical. For wider

economical. For wider houses a metal rolled tube corner enables you to install a circular track.



⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Hanger Bracket Kit, 8 Sets w/ Hardware
Kit Rolled Tube Corner
Tool-Less Bridge Kit, Double
End Stop Kit 2 Stops w/ Hardware
Trolley w/Bucket Tray
Trolley w/Dump Box

TWO TRAY OPTIONS:




BUCKET TRAY

A simple, flat, stable bucket tray that accommodates (10) 5 gallon buckets. A great option for tray dispersal, maintenance work, dead bird removal, and much more.



REMOTE

A robust, waterproof remote transmitter gives the operator full control of the trolley. Forward, reverse, stop and speed adjustment can all be controlled with the remote allowing you to keep your Chicken Reaper where you need it at all times.



DRIVE SYSTEM

A 24 volt gear driven motor provides plenty of power to transport up to 500 lbs. The gear box is equipped with a disengage lever, allowing the unit to easily be pushed in the event of a dead battery. The wheels are constructed of tough, easy rolling polyurethane.



This easy to use system utilizes a dump box with a heavy duty handle. Simply fill the tray, move to a suitable location, and dump. Ideal option for the removal of larger birds, turkeys, and supplemental feeding.



BRIDGE KIT


Dropping brood curtains takes seconds with this no tools required design. Simply remove the bridge and flip the stop tube in place on top of the rail.

The on-board 24 volt lithium battery and charger provide thousands of charge/- discharge cycles. A single charge lasts 4-5 days on average, depending on length of track.



BATTERY

304



· Heavy-Duty Plastic Tray: Holds 30 eggs, 11-1/2" x 11-1/2", priced each

Cardboard Egg Flats: Sold in bundles of 140

#52527 Plastic Trays #521105......Cardboard Egg Flats



Bostitch C Ring Pliers

#DP7..... for 11/16" Rings

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Hog Ring Pliers Kit

Pliers feature a spring-loaded magazine feed and onehand operation with rubber grips. Kit includes DeWalt P7 manual hog ring pliers and (1000) 11/16" galvanized hog rings.

#P7DW.....Pliers and 50 Rings

B) Pocket

• 4-1/2" long

• Cushion grip

• 3-adjustments

· 3.68 oz weight

• 1/2" capacity · Electronic coating


Channellock



Plastic-Coated Egg Basket

Sturdy wire basket with plastic coating to prevent damage to eggs. Plastic coating is not affected by detergents and prevents rust from marking eggs during washing. 8-5/8" high x 14-1/8" dia. Holds up to 15 dozen eggs.

#52511 Plastic-Coated Egg Basket



Egg Cleaning Brush and Sanding Bands

#52525...... Individual Replacement Sanding Band for Egg Cleaning Brush (each) #52524.....Egg Cleaning Brush for Sanding Bands (each)




- 4-1/2" long
- Single dip handle
- 1-5/6" to 4-1/2" capacity
- · Corrosion resistance
- black oxide finish
- · 1 lb. weight

A) #24978..... mini tongue and groove plier B) #12111 mini channellock

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Egg Scoop

39" metal handle with plastic scoop

#HSH105.....Egg Scoop



Tub O' Towels Heavy Duty Wipes

Nine powerful cleaners in one tough wipe. Cleaning solution is 100% biodegradable with pleasant citrus fragrance.

#TW90...... 90 count / (10" x 12" Wipe) #TW40......40 count/ (7" x 8" Wipe)



Tub O' Scrub **Heavy Duty Hand Cleaner**

Tub O' Scrub™ heavy duty hand cleaner removes grease, oil and tough grime from hands without the use of water. No petroleum distillates.

#TS18...... 10 oz bottle



Electro Sampson Hanging Scale

- · Switchable between pounds and kilograms
- · Includes carrying pouch, handle and 9v battery
- · LCD display

#ES10.....Electronic scale



Jiffy Way Egg Grading Scale

- · Gravity-operated scale
- Vintage metal design
- · Weighs in both grams and ounces


#525201..... Gravity scale



Scale Shackle

· Metal with rubberized clamp

#BDSHKLfor hanging scales



#MFB-10......Plastic Migration Fence #MFB-2......Wall Hanger #MFI-D Drinker Line Insert #MFI-F.....Feed Line Insert





Migration Fence Stand


- Can permanently attach to migration fence
- · High visibility
- · Economical alternative to more expensive methods
- Can be attached back-to-back or staggered








. Migration Fence Stand



Migration Fence

A) #HSMF1Coated, 1" spacing, 16" x 12' **#HSMF12** Coated, 1/2" spacing, 16" x 12' B) #8010820100 Peck board painted flat metal




A-Frame Migration Fence

- 12' long x 12" high
- 1/2" spacing



#17320-12A-Frame Migration Fence



- · Painted finish

#HSH062Migration Fence Stand, Rod Style

⚠WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Dial Thermometer with 36" probe

Ideal for compost piles.

#T300-36......Dial thermometer



Plasson Migration Fence

- · Open design maintains proper airflow.
- Two connector lengths create gaps for feeding and drinking lines

#DI02353163 24"x16"	fence w/ 2 short connectors
#DI02353161	Short connector
#DI02353162	Long connector



Eureka Migration Equipment

Stand supports wire fence, folds flat for storage. Hoop connects wire panels and allows a clear path for feeder travel.

#HB8520	Eureka stand
#HB8521	Standard hoop kit
#HB8522	Wide hoop ki t

Paper Feeder **Trays**








Item#	Description	Dimensions	Wt. Each	# Per Bundle
1) #521102-B-BUNDLE	Large Disposable Paper	21" x 12-3/4" x 1-3/4"	.21 lbs	100
2) #521102-BUNDLE	Small Disposable Paper	19-1/2" x 11 3/8" x 1-3/4"	.19 lbs	100
3) #HSFTC-01	Cardboard Oversized	44" X 34" X 1.75"	-	1
4) #521194	Paper inserts for feed lids	16" x 22"	_	400
	-	_		

Pur-Clear Feeder Tray

Disposable, clear plastic feeder trays attract chicks to feed faster. May reduce feed loss from Darkling beetles.





Item#	Dimensions	Wt./lb	Thickness
HS797	14.28" x 22.28" x 2"	1.0	.160



Item#	Dimensions	Wt./lb	Thickness
521102-BPL	13" x 21" x 1-3/4"	.4	.036



Item#	Dimensions	Wt./lb	Thickness
52110A	13" x 21" x 2"	.40	.031




#52116	.Brooder Guard	12" x 250'
#52115	.Brooder Guard	15" x 250'
#52117	Brooder Guard	18" x 250'



Economy

feed capacity. High-density green polyethylene pan is excellent for starting chicks and young poultry. Stackable design for easy storage with patented lock-on base

#52105.....Feather Feeder





Brooder Guard

Feeder Paper

• Gray

· Composed of recycled paper

#521180	3′ x 750′
#521189	1' x 750'



Water Line Paper

- 1' x 2500'
- · Speciality tissue grade








Tong-Stik


Tong Stik is the heavy-weight pick-up tool designed rugged enough for farm use!

#HS549-36	Tong Stik 36" long
#HS549-30	
1) #608050	1/8" x 3/4" roll pin
2) #HS549-52	Rod Linkage - 30"
#HS549-15	
3) #HS549-17	Trigger Tong Stik
4) #HS549-18	Jaw Movable Tong Stik
5) #HS549-54	Frame 30" Tong Stik
#HS549-20	•
6) #608051	3/16" x 3/4" roll pin
7) #HS549-19	Spring
8) HS549-14	1 0
NA) #HS549-9	Rivet



Go to www.hogslat.com to view a demo video!

*This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Fowl Catchers/Chicken Hooks

A) #52122	Fowl Catcher, 48-3/4" long, , 4-1/2" plastic red handle
	Heavy duty rooster/turkey hook, 53" long

MARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



• Rubber Hand Grip

#G2928.....Pick-Up Sticks

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Unger Nifty Grabber

- Aluminum construction
- · Jaws include 14 rubber finger grippers.
- 36" long
- 4-1/2" wide jaws

#979-2532.....

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- · Aluminum construction
- · Replaceable pads
- · Ergonomically-designed trigger and soft-grip handle

#AI32S	G4 Dot Reacher - 32" Long
#AI40S	
#AIMD	Metal Replacement Disc

⚠ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



- · All plastic construction
- · Spring loaded handle

#52063	Chicken Picker (Plastic)
#IS1010	Replacement Spring
#AMT27308	Replacement Jaw
#IS1012	Replacement Handle



Trash Gator

- · Aluminum shaft
- High impact plastic handle
- · Rubber coated jaws

.......Trash Gator - 33" Long #AI3340Trash Gator - 40" Long

🚹 WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Gorilla Tape

Gorilla Tape offers over-the-top results with its heavyduty, double-thick duct tape. Made to stick to rough, uneven, unforgiving surfaces like wood, stone, stucco, plaster, brick and more.

#6025002	White, 1.88" x 30 yd. roll
#106425	Black Wide, 3" x 25 yd. roll
#6027003	Clear, 1.88" x 27' roll
#105629	Black 30 yd. roll
#6010902	Camo, 1.88" x 9 yd. roll
#6004002	Blaze orange, 1.88"x 35 yd. roll
#6025302	White wide, 3" x 25 yd. roll



Gorilla Tape Patch and Seal

Gorilla Waterproof Patch & Seal Tape instantly seals out water, air, and moisture. With an extra thick adhesive layer and UV resistant backing this tape conforms to form a permanent bond indoors and out. At 4" wide use it to patch holes, cracks, gaps and tears, even underwater. Excellent for Home, Auto, Marine, Camping, RVs, Outdoors, and more!

#4612502	Waterproof 4" X 10' Roll	
# TOTAGOA	waterproof i is to item	



Gorilla Glue

The product that started it all, Gorilla Glue, is known for its industrial holding power and versatility, regardless of the substrate. Easily bonds wood, stone, metal, ceramic, foam, glass and more!

#50002	Gorilla	Glue	2	oz.	Tube
#50004	Gorilla	Glue	4	oz.	Tube
#50008	Gorilla	Glue	8	oz.	Tube





Flex Tape

Powerful adhesive with a thick, flexible rubberized backing that conforms to virtually any shape and surface, even underwater. Gets stronger with time and pressure. UV resistant, VOC- free, withstands extreme temperature and weather conditions

#3330347	4" wide x 5', black
#7189640	
#9319377	4" wide x 5, white





do? Reach for Rescue Tape!

Feed Line

- 950 psi Tensile Strength
- · Waterproof & Airtight

• 1" x 12' Roll	
#RT1001	
#RT1002	
#RT1004	Clear
#RT1005	
#RT1006	Blue
#RT 1007	Green
#RT1008	Orange



In less than one minute you can tighten your fence wire with this simple wire tightening clip. Jake's Wire Tighteners™ work together with a turning tool to give leverage when applied to your fence.

#JWT001	
	5/16" Heavy Duty, 15ct
#JWT003	Handle Wire Tightener

▲ WARNING:

This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Shocker Line Charger

Low impedance model delivers an effective jolt even in the presence of litter and debris. 120 volts with .10 joule output. 2-year warranty.

#ኮ፫ ይለ	Line charge
#DE-0U	Lille Charde



Shocker Line Charger

Delivers an non-pulsing continous voltage charge. 120 Volts.

	C		



Stop Roost Spinner

The Stop Roost Spinner is designed for retrofit applications allowing the electricity to be disconnected from the shocker wires. This eliminates the problem of stray voltage at the nipples.

#ISSRS-2222" rod for shocker wire





WARNING: This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



AeroKroil

#AEROKROIL......16 oz. Spray Can



Chain & Gear Oil

#4F979Gear oil, 32 oz., SAE 80W-90 #4ZF30.....Synthetic oil, 32 oz., SAE 140 **#HS450** SAE 80W-90, 15 oz., for auger gear heads



WD-40® **Smart Straw**

#60008...... WD-40 11 oz. Smart Straw



Fluid Film

#60007.....Fluid Film, 11-3/4 oz. aerosol can



PB Blaster

#4LRF8 PB Blaster 11 oz. Aerosol Can #4LRF9PB Blaster 1 gal. Liquid Can



Liquid Wrench

#HE556650 Liquid Wrench, 11 oz. aerosol can #6349988.....Silicone spray, 11 oz. aerosol #8461675 ... White lithium grease, 10.25 oz aerosol #G3897763 White lithium grease, 8 oz. tube



O-Ring Silicone Lubricant

#1RGZ6....2 oz. squeeze bottle for medicator repair



Permatex

#HH20220547 8 oz. Anti-Seize Lubricant



Loctite

#4KM46...... 8 oz. Anti-Seize Silver Lubricant



Erickson natural rubber tarp straps. Subtract 3" from total length to calculate rubber end-to-end measurement.

SAVE WHEN YOU BUY 10 OR MORE.

#06711	
#06712	18"
#06713	24"
#06714	34"
#06715	











#DRY0005



Interstate Batteries

Item#	Туре	Description
DRY0035	AAA	Alkaline, 4-pack card
DRY0030	AA	Alkaline, 4-pack card
DRY0020	D	1.5 V, Alkaline, 2-Pack
DRY0015	С	1.5 V, 2-Pack
DRY0005	9V	Carded (1 battery)

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov





Item#	Туре	Description
DRY-0075	AAA	Alkaline, 24-pack box
DRY0074	AA	Alkaline, 600-pack tray (30 pkgs)
DRY-0070	AA	Alkaline, 24-pack
DRY-0080	С	Alkaline, 12-pack
DRY-0085	D	Alkaline, 12-pack
DRY0110	AAA	Alkaline, 600-pack tray
DRY0196	9V	Alkaline,12-pack box

🚹 WARNING:

This product can expose you to chemicals, including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov



Non-toxic and has the same density as air, so that it is possible to observe true air movements. The smoke has a particle size of 3– 2.5 microns. The smoke cartridges produce a generous amount of smoke, which is emitted at a constant rate to help with the identification of flow patterns. Smoke color is white and they are packaged 10 per box.

Item#	Burn Time	Smoke Volume	Size
#REG102		150 cu. ft.	1.25" x .55"
#REG103		600 cu. ft.	1.259" x .708"



RAE Ammonia Detection Kits

Ammonia levels above 25ppm can affect chick performance and have affects on bird health. Now you can know exactly what your ammonia levels are! Each tube can measure ammonia levels in multiple houses when used properly to save money.

#AIR71040Hand Pump Only (includes case) #AIR01500 Ammonia Tubes 5-100ppm (10 pack)



Portable Infrared Thermometers

#RAYMT4	Portable Infrared
#RW-5002	Economy Infrared
#RW-5004	Infrared w/Laser & Case



Digital 4-in-1 Meter

Measure air flow, humidity, temperature and light in one meter.

#LM8000ADigital 4-In-1 Meter



Kestrel Wind Meters

Durable and waterproof, Kestrel handheld measuring devices are excellent tools to check ventilation in tunnel houses. Each meter includes a hard slide-on case, lanyard, and battery. All models feature a replaceable impeller. The 2000 and 3000 models feature a backlit display for taking readings in dim light.

#KESTREL1000	Kestrel 1000, Blue
#KESTREL2000	Kestrel 2000, Green
#KESTREL3000	Kestrel 3000, Red
#KESTREL0801	Impeller Replacement



Heat Seeker Mid-Range Infrared Thermometer

- 8:1 Distance-to-spot (D:S) ratio
- Rugged, ergonomic design for general purposes
- Wide measurement range
- ±2% Basic accuracy
- · Backlit LCD display
- Switchable on/off laser pointer
- °F or °C selectable
- CE, RoHs, WEEE approved

#IRT207 Mid-Range Infrared Thermometer



Wide Range Infrared Thermometer

- Wide measurement range of -40° to 1076°F (-40° to 580°C)
- Accuracy of ±3°F (2°C) or ±5°F (3°C), depending on temperature
- · Large (1.6 in. diagonal) backlit LCD
- Includes Star Burst Laser and carrying case
- 12:1 Ratio

#IRT657 Wide Range Infrared Thermometer



Infrared Thermometer Energy Audit Scanner

- Light/sound alerts for temperature differences
- 0.5 seconds response time
- Star Burst laser targeting system
- Large backlit LCD
- Automatic temperature hold upon trigger release
- · Auto-power off after 60 seconds of inactivity
- 8:1 Ratio

#IRTC50Infrared Thermometer



Non Contact Laser Tachometer

- Measure fan blade RPM's, compare efficiency and
- easily check fan belt and pulley condition
- Jumbo 5-digit LCD display
- Auto ranging
- Wide measuring range
- Laser precision
- Memory: Min/Max/Last
- Includes reflective tape and case

#LT2234CNon Contact Laser Tachometer

Agita 10 WG

Water-soluble spot spray for the control of Darkling beetles and house flies. Apply with standard liquid spray applicator around the outside perimeter of animal housing. Average residual of 6 weeks.



#062584 2.2 lbs

Zetagard Insecticide

Contains: Zetacypermethrin and is synergized with Piperonyl Butoxide

When to use it: ZetaGard LBT is an advanced dust treatment for control of darkling beetles (lesser mealworm) in poultry litter in chicken broiler and turkey growout houses. This potent formulation provides

excellent control of hard to kill darkling beetles including those resistant to other pesticides including certain pyrethroids.

How to use it: Recommended application rate of 50 lbs. per 20,000 sq. ft. Sold in 12.5 lb. bags. 4 bags per pail.

#YTX33.....Zetagard Dust (Y-TEX)



Bifen I/T Insecticide

Used to prevent and control termites, fire ants, and many other insects that cause structural damage. This 1 gallon container has 7.9 % bifenthrin as its active ingredient. Use as directed.

#52499...... Bifen I/T Bifenthrin 7.9% 1 gal. Jug



Taurus SC

TAURUS® SC is a water-based suspension concentrate of 9.1% Fipronil that controls a wide variety of insect pests. Taurus SC is a non-repellent insecticide/ termiticide that is undetectable to target pests, allowing them to touch, ingest and spread the insecticide throughout the entire colony.

#099740	78	ΟZ	bottle
#376019	20	ΟZ	bottle




- · Non-staining on most surfaces
- Kills returning insects
- · Foam trapping spray
- Up to 25' jet spray

kills on contact.



Country Vet Flying Insect and Air Freshening Kit



#01-006 30-day metered air freshener kit #01-008 Dispenser only





Country Vet Refills

Refill cans for Country Vet automatic dispensers.

# 01-001 C	lean 'N Fresh air freshenei
#01-005	Fly spray
#01-33-4701CVCA	Dutch Apple Spice

Enforcer Wasp & Yellow Jacket Foam

- Fast-acting, blanketing foam traps and kills on contact.
- · Water-based formula is non-staining.
- Jet blast up to 22 feet.
- For outdoor use only. 16 oz can.

#FHW16Enforcer Wasp & Yellow Jacket Foam



No Natz Spray

- Repels Gnats & Biting Flies Botanical
- Pleasant Fragrance
- Contains NO DEET

#NN40Z4 oz. size

Prozap® LD-44Z **Insect Fogger**

- LD-44Z Insect Fogger quickly knocks-down and kills flying and crawling insects.
- Contains 0.5% Pyrethrin and 4% PBO.
- · Controls flies, mosquitoes, wasps, gnats, lady Asian beetles, roaches, spiders, plus 19 other flying and crawling insects.
- · For use in barns, milk rooms, parlors, stables, kennels and other buildings.



20 oz can

Prozap® LD-44T Fly Spray

Refills for the ProMist'r Metered Dispenser.

- Contains 1% Pyrethrins, 2% PBO and 3% 264.
- 6.5 oz can lasts up to 30 days in the Pro-Mist'r Metered Dispenser.
- · Covers 6,000 cubic feet of space.

#0073010......6.5 oz can



ProMist'r II Dispenser

Prozap®

- For use with Prozap® LD-44TTM Metered Insecticide
- · Features power switch display, 24 hour or day only operation and three spray interval selection: 7.5, 15 or 30 minute intervals
- · When set at 30 minute intervals will provide up to 30 days of coverage per refill.
- · Uses (2) "D" size batteries. Not Included

#CT89500 ProMist'r Dispenser only #CT89500KIT......Kit includes Dispenser and LD-44T Fly Spray



WWW.HOGSLAT.COM





Annihilator™ Polyzone®

Broad-spectrum premise spray provides residual insect control for up to 90 days. Uses technology that binds active ingredient to surface and slowly releases over time to achieve extended control.

- Active ingredient 4.74% deltamenthrin
- .06% treatment rate is 10,666 sq. ft.
- 1 pt. bottle

#BAY82020.....Annihilator™ Polyzone®



CyLence Pour-On

The Bayer Cylence Pour-On Insecticide is for direct animal use on beef cattle, and lactating and non lactating dairy cattle. Active ingredient 1% cyfluthrin, a pyrethroid, controls horn flies, face flies, biting lice and sucking lice.

#BAY713590 1 Pint



Tempo® 1% Dust Insecticide

- Provides effective pest control and easy application
- Requires no mixing equipment; non-corrosive, little to no odor
- · Available in 40 lb. bucket containing four 10 lb. sleeves
- 0.5 to 1 lb. treats 1,000 sq. ft. facility

OuickBavt® **Spot Spray**

indoors or out.

#TEMPODUSTTempo 1% Dust Insecticide



Tempo® SC Ultra **Premise Spray**

- Fifth-generation pyrethroid containing 11.8% beta-cyfluthrin
- · Strong insecticidal activity in a stable, suspension-concentrated liquid
- Available in 240 ml container
- 8 to 16 ml per 1 gal. of water treats 1,000 sq. ft. facility

#TEMPOBOTTLE...... Tempo SC Ultra Premise Spray



QuickBayt® Fly Bait

- · Scatter bait formula in 5 lb. pail
- · Remains effective for up to four weeks
- 6 oz. treats 1,000 sq. ft.

#BAY066399 5 lb. pail **#BAY8731627**......35 lb. bulk pail



#BAY81147923......3 oz. in a 24 oz. bottle

and you're ready to attract



OuickBavt® **Spot Spray**

- · Simply mix with water and spray where needed
- · Treats places conventional granular baits can't reach
- Provides up to six weeks of protection indoors
- · An effective spot size is 4 sq. ft.
- 1 lb. container treats 1,000 sq. ft. of fly-resting areas

#BAY08968805QuickBayt® Spot Spray



Credo®

Specifically formulated for the poultry industry to control Darkling beetles in the larvae and adult stages. Use in rotation with Tempo to prevent build-up of chemical resistance by insects. Credo® SC is the original formulation containing 42.8% Imidacloprid.

#BAY80511249......30 oz. bottle



Tempo® SC Ultra

For smaller applications and single dose needs.

#BAY8069425432 ml bottle



ProZap Insectrin X Concentrate

- Contains 10% Permethrin
- · Mix with water or mineral oil
- · For use as a dilution spray, spot treatment, or in a back rubbing devices.

#103751032 Oz.



ready-to-use poultry insecticide dust. Controls darkling beetles, northern fowl mites, chicken mites and lice. Can be used for banded applications. No withholding period from

last application to slaughter. Coverage is 100 sq. ft./ 1.4 to 4 oz. Active ingredient is tetrachlorvinphos 6.0%. **#56208**......4) 10 lb. sleeves



36.8% active ingredient for fast knockdown and longlasting 90 day residual treatment in and around animal housing.

#41008...... 1.25 gal container

LEVEL UP YOUR FLY CONTROL



Understand the three levels of fly activity for more effective control

Flies on hog or poultry farms are more than a nuisance; they carry diseases that can pose a severe health hazard to people and animals. Fly control is a basic component of biosecurity in hog and poultry houses.

Given the housefly's seven-day life cycle and the almost perfect environment conditions livestock and poultry facilities provid

Scan to read the full article



IN, ON & AROUND

Pyronyl™ Crop Spray

A broad-spectrum insecticide for use in dairy, livestock and poultry operations, Pyronyl™ Crop Spray is an insecticide formulated for surface spraying, misting systems and on-animal uses



#100208915 Spray Crop Gallon



Golden Malrin® Fly Bait

The standard in fly baits for over 30 years, Golden Malrin® bait attracts and controls nuisance flies right down to the last grain of bait. The Golden Malrin® Fly Bait two-phase action knocks out nuisance flies quickly and effectively. First, Muscamone® fly attractant draws flies in. Then, as they feed on the sugar-based bait, the active ingredient methomyl delivers the final blow, killing flies after ingestion. Golden Malrin® bait can be applied directly from the container or placed into a bait station such as the Starbar® Fly Bait Station. Cannot ship to New York or Indiana.



#SB8040	40 lb
#100527078	10 lb can

OuikStrike® **Fly Abatement Strips**

The QuikStrike® Fly Abatement Strip is specially designed to control nuisance flies. Flies are instinctively drawn to its curved design created to facilitate fly feeding. QuikStrike® Fly Abatement Strip has a large exposed surface area for flies to feed on and a unique active ingredient that kills flies in seconds. A triple-action attractant draws flies to the strip where they feed on a sugar-based active ingredient coating. The QuikStrike® Fly Abatement Strips are ideal for use wherever nuisance flies are a problem.



Starbar® Cyanarox™ Insecticidal Bait

For controlling house flies, it is both highly attractive and highly effective,



QuikStrike® Fly Bait

Granular bait that controls house flies quickly and stands up to pyrethrin resistance using the active ingredient dinotefuran

#100508298..





MEDIUM-LEVEL

Starbar® **Fly Bait Station**

Scatter baits are an effective and economical fly control method for areas with high fly populations. Flies



are drawn in by the powerful attractants and die rapidly after feeding on the bait. The Starbar® Fly Bait Station makes the use of scatter baits easy by reducing the associated mess and exposure concerns due to spreading the bait over the open ground where children, pets and livestock may come in contact. Simply use one ounce of product per bait station.

#3006166......Fly Bait Station for Scatter Baits Starbar

Bite Free™ Stable Fly Trap

Scientifically proven to help effectively trap stable flies, Bite Free™ Stable Fly Traps contain no insecticides

and are economical and easy to use. Bite Free™ Stable Fly Traps hold more flies than other sticky traps with no fly trap odor. Its compact size offers a 360° trapping surface that holds several thousand flies. When the trap is full just throw it away. Bite Free™ Stable Fly Traps have a special weatherproof adhesive that won't melt or wash away

#3005363 Bite Free Stable Fly Trap Starbar





FlyRelief™ Trap

Recommended for perimeter use, FlyRelief™ trap catches thousands of flies. Insecticidefree, FlyRelief™ trap disposable fly traps come with built-in attractant and are excellent for use around pets, in the yard, kennel and garbage containers. Giant FlyRelief™ trap catches twice as many flies as the FlyRelief™ trap.

#100503132Standard Fly Relief Fly Trap Starbar #100504346...... Giant Fly Relief Fly Trap Starbar

Fly Trap Attractant Refill

An exclusive formula that contains four different attractants flies can't resist in a water soluble pouch format. It can be used with Fly Terminator® Pro, Captivator® Fly Trap and other reusable water-based traps. Each package contains eight 30 gm. water soluble pouches.

#57102 Fly Trap Attractant Refill



Milk Jugg™ Trap

Turn ordinary plastic jugs into effective, insecticide-free fly traps and catch over 35,000 flies economically with an exclusive attractant flies can't resist. It's easy to use, just add water and the attractant to a one-gallon milk jug and pop on the specially designed reusable top.

#3002613......Milk Jugg Fly Trap Starbar



Trap 'n Toss™ Fly Trap

This handy, disposable fly trap can be hung up or set down wherever flies are a problem. Trap 'n Toss™ Fly Trap includes a special attractant that contains multiple feeding stimulants plus a fly sex attractant. Just squeeze it in and add water. Trap 'n Toss™ Fly Trap holds thousands of flies and can be simply thrown away when full.

#14624Trap'n Toss Fly Trap Starbar



Captivator® Fly Trap

Captivator® Fly Trap, the heavy-duty, reusable and economical plastic jar comes complete with 1 tube of attractant. Just squeeze attractant into a jar and add water. Captivator® Fly Trap's one-way entry system keeps flies in the trap and its 2-quart capacity means minimal maintenance.

#14680 Captivator Fly Trap Starbar



HIGH-LEVEL



Lure Fly™ Trap

Lure-Fly™ trap is a super sticky fly paper that effectively attracts flies. It's a disposable fly ribbon that contains no insecticides. Easy to hang and even easier to use, Lure-Fly™ trap is economical fly control

#45200.....Lure Fly/Revenge Ribbons Starbar



Starbar® EZ Trap

EZ Trap® Fly Trap has a unique, compact design which offers a large trapping surface that can be used indoors and outdoors with no harmful chemicals. EZ Trap® Fly Trap is insecticide free and odor free.

#3004323 EZ Trap 2-Pack



Fly Stik™ Jr. Trap

Sticky fly trap sticks that can be used indoors or outdoors. Fly Stik™ Jr. fly trap at 12 inches contains no insecticides and is odor-free. Great for use in and around barns, stables, corrals and homes

#100503350 12" Single Stick Fly Trap Starbar



Pest Control



Rozol

Rozol Blue Tracking Powder is formulated with chlorophacinone, a multi-feed anticoagulant invented by Liphatech. Apply into rat burrows along the periphery of buildings, in patches along rodent runways, and in spaces between floors and walls.



Renegade

rodent activity

Renegade 20 gram mini blocks are an ideal maintenance rodenticide where crumbs and scatter are a concern. Formulated with difethialone (25 ppm), a second-generation anticoagulant. Renegade is formulated with mold inhibitors making the ideal bait for high moisture environments such as cool cells. Blue marker dye can be seen in droppings.

long time periods. It is a palatable, multiple-feed soft bait that effectively kills rats and mice. DoubleTap is

for consistent everyday use - during light to heavy



#LT875004 lb. bag

Soft Bait

FastDraw™ Soft Bait is a revolutionary concept in rodenticide technology from Liphatech®. It contains the active ingredient Difethialone, food-grade grains and oils, and has a unique no-wax formula. FastDraw™ pouches combine the bait integrity of miniblocks with the money-saving, targeted dosing, of place packs. It is effective even in areas of infestation where competing food sources exist. Why wait for rodents to accept OTHER baits? Draw a following of rodents with FastDraw™. .35 oz. pouch.



#LT82908	8 lb. pail,	367 pouches
#LT82916 1	6 lb. pail,	734 pouches

R Soft Bait

Revolver™ soft bait provides the most palatable formulation of the most widely-used active ingredient, Bromadiolone. It is the single-feed solution when rotating to a Bromadiolone rodenticide in your biosecurity rodent control program. Revolver™ contains no-wax promoting quick feeding & results, in a low-cost per placement .42 oz. pouch.



#LT87400	8 lb.	pail,	302	pouches
#LT87405	.16 lb.	pail,	604	pouches



Hombre™ contains difethialone, a singlefeed anticoagulant that is the newest active ingredient in the animal health industry. It is so advanced its lethal dose is lower than any other product on the market. With less active ingredient, more food quality grain and an attractive odor, Hombre™ is significantly more palpable than other baits.



Mini-Blocks - .75 oz

#LT82804	. 10 lb. pail, 225 mini-blocks
#LT82801	20 lb. pail, 450 mini-blocks

Pellet Place Packs - .9 oz

CHALL STREET

BootHill™ contains Bromadiolone, a singlefeed anticoagulant that has a long history of proven efficiency. Superior palatability helps assure greater acceptance while preventing bait shyness. Available in a variety of effective formulation – mini-blocks, paraffinized pellets, and pellet place packs. BootHill™ is a perfect partner with Hombre™ in your rodent control program; different chemistry helps assure a high degree of effectiveness over time.



Mini-Blocks - 1 oz.

#LT87315	10 lb. pail, 160 mini-blocks
#LT87360	20 lb. pail, 320 mini-blocks

Pellet Place Packs - 1.5 oz.

GUNSLINGER™

GunslingerTM is Liphatech's* newest rodenticide and is made with the active ingredient Bromethalin. GunslingerTM is an effective addition to a rodent control baiting program since it has a different mode of action. Plus, rodents stop feeding after eating the lethal dose, saving bait. More rats and mice can be controlled with less bait. Bromethalin disrupts oxidative phosphorylation in the central nervous system resulting in paralysis and death.



#LT839214 lb. pail, 130 mini-blocks



SOFT BAIT CANNON™ Soft Bait

Cannon™ by Liphatech is the world's first bromethalin soft bait and provides simple and effective control of rodents without mixing meal bait and pellets! Low cost 8 gram placement packs reduce waste and save you money. After consuming a lethal dose, rodents cease feeding which makes your baits last longer and the active ingredient, bromethalin, kills in 24–48 hours. The no-wax formulation does not melt in high temperatures and outperforms purple wax blocks. .28 oz pouch.



Aegis Bait Stations

- Bait placed in the feeding chamber cannot be touched by fingers or probes when the lid is fastened.
- Unique double-quartered locking barbs make the Aegis bait stations tamper resistant.
- · Clear-lidded option makes monitoring quick and easy.
- · Vertical and horizontal baiting rods in the Rat Station keep bait secure inside the station and away from moisture
- · Bait Stations can be attached to walls, posts or any permanent structure.
- · Stations can be used both indoors and outdoors.
- RP model can be positioned vertically and is perfect for tight placements such as on rafters for roof rats.





Aegis stations provide convenient placement flexibility for vertical or horizontal mounting. Design provides capacity for two block or soft-baits. Available in clear or black lid. Approximate Length 5-1/2", Width 4-3/8", Height (lid closed) 1-5/8".

#LT83810......Black lid **#LT83811**......Clear lid



Rat Station w/ Black Lid

Double-tunnel design improves rodenticide consumption. Heavy-duty polypropylene construction encourages rats to enter tunnel rather than chew through the plastic. Units contain bait trays making clean-out quick and easy. Length 13-9/16", Width 10-5/8" (including hinge), Height (lid closed) 3-1/2". Key lock.

#LT83812..... Black body and lid



Rat Station w/ Clear Lid

The clear lid, with transparent panel in cover, makes bait monitoring easy and efficient. Rotating hinge, won't crack or break when opened in cold weather Vertical and horizontal baiting rods secure bait inside station and away from moisture. The universal key opens all Aegis products. Length 13-9/16", Width 10-5/8" (including hinge), Height (lid closed) 3-1/2".

#LT83813.....Black body and clear lid



Rat Bait Cool White

Cool white box reduces inside temperatures to increase rodent activity. Mounts vertical or horizontal for greater flexibility. Key Lock to prevent access from children and non-target animals. Length 13-9/16", Width 10-5/8" (including hinge), Height (lid closed) 3-1/2".

#LT83814.....White cool box



Aegis®-RP Bait Station (Non-Locking)

Excellent choice when tamper-resistant rat bait placement is not required. Versatile, allows rats or mice to access station. Low profile permits flexible mounting in tight locations (vertical or horizontal). Rotating hinge outlasts break away living hinged bait stations. 12-7/8" long; 7-7/8" wide (including hinge); 4" high (lid closed).

#LT83861 Black body and lid



Aegis®-RP Bait Station (Locking)

The locking AEGIS-RP Bait Stations are ideal for use where tamper resistant placement of rodenticides is required. Versatile, allows rats or mice to access station. Low profile permits flexible mounting in tight locations (vertical or horizontal). Rotating hinge outlasts break away living hinged bait stations. 12-7/8" long; 7-7/8" wide (including hinge); 4" high (lid closed).

#LT83860..... Black body and lid



Tube Style Bait Station

Versatile bait station can be mounted sideways or even upside down to gates, fences and wall tops. See through openings allow rodents to see light and sense air movement. Includes J-shaped bait hook and hex key. 11" high x 15" long x 2-3/4" wide.

#LU670007Tube style bait station



Bait Station

The multi-catch mouse trap allows users to catch multiple mice without re-setting the trap. The zinc plated metal trap features two doors, one on each side, that contain a "see-saw" type floor, allowing mice to enter, but not exit. Mice on the inside of the trap help attract others nearby, allowing several to be caught in a short period of time. Clear plastic window on the top door allows easy confirmation of a catch.

#AGP420CLMulti-Catch Bait Station



Convenient steel spikes for anchoring bait stations penetrate the hardest ground.

#8312 10-inch Heavy Duty Tent Stake



This product can expose you to chemicals, including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Tomcat Bait Stations



Titan Weighted Bait Station

Ten pound, pre-installed brick holds bait station in place without stakes for faster cleaning and servicing. Perfect for use on concrete slabs such bin pads and building interiors. Holds eight one ounce blocks and includes a removable tray.

#M-33496......Weight bait station



Vertical Bait Station

The station can be placed horizontally or vertically for a smaller footprint. Removable tray holds eight one ounce blocks for fast easy bait replacement and cleaning. Rear mounting holes for securing to fence or post. 9" W x 9" D x 4" H

#M-33446.....Vertical bait station



Rat Station

Motomco's original Bait Station with keyless design. Features a "living hinge" that can be opened & closed over 100,000 times without breaking. Holds up to one pound of bait chunxs. Includes horizontal and vertical bait securing rods.

#M-33456..... Black body and lid



Low Profile Bait Station

The Tomcat LP (Low-Profile) Rat Bait Station has a maximum height of less than 3.5" and will fit in tight spaces or underneath locations where other stations won't fit. Includes Vertical or Horizontal bait rods and fits up to four, loz bait chunxs.

#M-33470 Black body and lid



Bullet Bait Station

The Bullet is an excellent, all-around station that features heavy-duty, durable construction for long-lasting use and a removable tray for easy cleaning. Single key design holds four, 1 oz bait chunxs or snap trap.

#M-33432..... Black body and lid



Tomcat Refillable Station

Tomcat Rat Killer II Refillable Bait Station contains one Tier 1 refillable rat sized bait station with 15, 30 gm Bromethalin bait blocks.

#M-22814Refillable station



Glue Trap

4-pack of glue cards is coated with a powerful adhesive covered with special release paper. Non-toxic and pesticide free and an also be used for cockroaches, scorpions, spiders or other insect pests. Glue traps are 7.75" long x 5.25" wide.

#M-32509.....Weight bait station



Glue Boards

Tomcat Glue Boards are one of the most widely used ways to control mice, insects or other household pests without the use of pesticides or toxins. Hypoallergenic and scented to attract rats and mice. Can also be used for snakes, cockroaches, scorpions, spiders, centipedes, or other insect pests Tomcat mice glue boards are 4.5° long x 3.25° wide.

#M-32418Vertical bait station



The Tomcat Reusable Rat Snap trap is a non-poisonous, pesticide free way to capture and remove rats or other rodent pests. Powerful snap trap can be easily set by hand or food. Patented interlocking teeth make it virtually impossible for rats to escape. Removable bait cup makes baiting traps easy and is compatible with many Tomcat Rat-sized Stations (Bullet, Rodent Station, Titan)


#M-33521 Or	ıe	pack
#M-33500 Tv	70	pack





The most powerful single-feed anticoagulant for maximum control

JAGUAR® is tougher on rats and with the strongest single-feeding anticoagulant available - brodifacoum. JAGUAR® is especially successful in cleaning out tough mouse infestations or where resistance is suspected. Get guaranteed success with JAGUAR® tasty blend of more than 16 human food-grade ingredients.





Agrid₃ The first and only rodenticide registered by the EPA for organic production

AGRID3 is the first and only rodenticide registered by the EPA for use in organic production. The highly palatable formulation uses the active ingredient cholecalciferol, an acute rodenticide capable of killing anticoagulant resistant rats and mice. AGRID3 has a unique mode of action that causes rats and mice to stop

feeding after consuming a lethal dose, reducing the total amount of bait consumed, thus saving money. This same mode of action also gives AGRID3 a substantially reduced risk of secondary poisoning... making it excellent all-around bait.

#M-23144 Agrid3 Organic Chunx, 1 oz., 4 lb. pail



A single-feed anticoagulant ideal for superior, long-term control of rats and mice

HAWK® can kill rats and mice in a single feeding with its powerful anticoagulant bromadiolone. Use HAWK® with confidence for unsurpassed control, even against warfarin-resistant "super rats". Rats and mice die in 4 to 5 days after eating just a single feed of HAWK®. A superior formulation makes HAWK® irresistible to rats and mice.



#M-31218	Hawk® Chunx, 1 oz., 18 lb. pail
#M-31155	Hawk® Pellet Place Packs

Designed to be used as a cleanout bait during a building's down cycle

ERAZE™ is a economical choice to provide fast cleanout of rodent populations when other food sources are not present, such as the down time in confinement buildings between groups. ERAZE™ powerful active ingredient, zinc phosphide, kills mice, rats and gophers in a single teaspoon size feeding.



#M-32545..... Eraze™ Loose Pellets, 5 lb. pail





The fastest acting rodenticide and no secondary poisoning

RAMPAGE® contains bromethalin, a non-anticoagulant, which is the key component in the fight against resistance. RAMPAGE® provides sure, fast control in one to two days. Rodents also feeding after eating a lethal dose of RAMPAGE® eat less bait so there is no secondary poisoning if pets consume dead rodents.



#M-22121......RAMPAGE® Pellet Place Packs, 15 gm, 121 ct pail #M-22249 RAMPAGE® Bait Chunx, 4 lb. pail



A multiple-feed anticoagulant for economical control of rats and mice

TOMCAT® is tougher than a barnyard cat for the control of rats and mice. TOMCAT® baits are manufactured with human food-grade ingredients and enhancers for a bait so palatable that rats and mice can't resist. Containing the anticoagulant dipacoinone, TOMCAT® is a multiple-feed bait that kills rats and mice in 4 to 6 days.



#M-32345.....Tomcat® Pellets Place Packs, 10 lb. pail #M-32446......Tomcat® Chunxs, 1 oz., 9 lb. pail



Rampage Meal Bait

Exclusive oat and grain bait formulated especially for livestock facilities with high rodent populations.

#M-22925......12 lb. pail



Tomcat[®] Liquid Concentrate

Each pouch mixes with one quart of water. Excellent way to supplement a rodent control program especially in hot, dry conditions.

#M08140		E	30x / 8
#M-32701	1.7	oz.	pouch



Hawk® Meal Bait

Highly palatable oat and grain formula effective when competing food sources are available.

#M-31111	50	lb.	pail
#M-31125	25	lb.	pail

Wormer

PWT and PWT2

Contains: Specially processed Sodium Hydrogen Sulfate 91.5 to 94.7%, Sodium sulfate 4.8 to 8%, and proprietary ingredients. (PWT2 also contains a blue coloring additive)

When to use it: Water acidifiers approved by the FDA used to keep water systems sanitized with a lower pH. Can also be used as a cleaner and descaler.

How to Mix: As a water acidifier mix 1 to 2 packs of PWT or 1 to 2 pounds PWT2 per 4 gal. stock solution once daily. As a cleaner or descaler mix 2 packs of PWT or 2 pounds of PWT2 to 4 gal. water in line for 8-24 hours and flush from systems.

#PWT	16 oz. Pk
#WLS-PWT2	40 lb. Pail





SaniDate 5.0® SaniDate 5.0® is a powerful and effective EPA- registered sanitizer/disinfectant. The highly stabilized 5% peroxyacetic acid (PAA) formulation is composed of organic acids and hydrogen peroxide developed for a wide variety of agricultural applications. It's extensive labeling and versatile composition makes it ideal for many poultry water treatments and biosecurity applications.

#BSS01



Valbazen

A broad spectrum oral drench effective for controlling tapeworms, stomach worms, intestinal worms, lungworms & mature liver fluke in sheep and cattle. Active ingredient: Albedazole

#LW58221.....One liter bottle

Water Supplements

Dry Cider Vinegar

Contains: 208 grams of Grower Select Dry Cider Vinegar is equivalent to the use of 3 gallons vinegar. When to use: Use as drinking water additive when the supplementation of vinegar is indicated. How to Mix: Mix one 208 gram pack per 6 gallons of stock solution. For full strength, mix one 208 packet per 3 gallons stock solution.



Oregain

SaniDate 5.0

Contains: Vegetable Fat product, natural flavors, citric acid, and propylene glycol.

When to use it: Oregain is a blend of essential oils that provide a flavoring agent to the water to encourage birds to drink and potentially eat more when administered. May help during stressful periods or can be given daily during the course of the flock. It is used most during the first 7 to 10 days after chick placement, during the 3 to 5 days during a feed type change, and the last days when finisher feed is given. One bottle treats between 20 to 40 gallons of stock solution.

How to Mix: For Broilers mix 1.18 to 1.69 ounces (35 to 50 ml) of Oregain to 1 gallon of water in stock solution. For Layers mix .84 to 1.69 ounces (25 to 50 ml) of Oregain to 1 gallon of water in stock solution.

#OREGAIN......Oregain Liquid Concentrate



ACTIVO® Liquid

Blend of selected secondary plant compounds and organic acids. Better growth due to synergistic effect on regulating the microflora of the gastrointestinal tract. Recommended for preventive use in poultry during stress periods. Injects using standard medicator ratio of 1:128. Packaged in 1.32 gal. container.



#EW001ACTIVO® Liquid

Perform-Max

Contains: Acetic Acid, Copper and Zinc Chelate, Lactic, Citric and Tannic Acids.

When to use it: Drug and Antibiotic Free programs. Does not require a withdrawal period. Helps clean water lines to improve and maintain water consumption. Shown to help improve feed conservation. Performs best when pulse dosed

How to Mix: Using label directions, Perform-Max will reduce pH to 3.5-2.8 (depending on initial pH of water)

#WY26432......Perform-Max




Supplement 4

Contains: Acetic Acid, Citric Acid, Copper Manganese, Iron, and Potassium.

When to use it: Supplement 4 is a nutritional supplement with a wide arrange of beneficial acids and minerals to aid in performance and feed conversion. In addition it serves as a water acidifier, chelating agent, helps keep water lines clean and free flowing, and is also used as an aid to treat mouth lesions from mold and reduce feed passage.

How to mix: One quart to two gallons of stock solution. Run for 3 to 5 days continuously and repeat as necessary.





Suppa Sol

Contains: Copper Sulfate, Manganese Sulfate, Cobalt Sulfate, and Hydrochloric Acid.

When to use it: Suppa Sol is a mineral supplement that is believed to aid performance and provide broilers and turkeys with 90% of their daily recommended Copper requirement. How to Mix: Add one quart to two gallons of stock solution.

Run for 3 to 5 days continuously and repeat as necessary.




Electrolytes + Vitamin C

Contains: Potassium Chloride, Sodium Chloride, Magnesium Chloride, Citric Acid, and Ascorbic Acid (vitamin C) (20,000mg)

When to use it: Electrolytes plus Vitamin C is a soluble electrolyte formula that provides high levels of potassium, ascorbic acid (vitamin c), and other essential minerals during extreme temperatures and other periods of stress to help maintain osmotic balance of bodily fluids and prevent dehydration.

continuously for 3 to 5 days. Repeat when necessary



THE SELECT

Poultry Pack

Contains: Vitamin A, Vitamin B3, Vitamin E, Vitamin B12, Riboflavin, Niacin, d-Calcium Pantothenic Acid, Menadione Sodium Bisulfate, Biotin, Folic Acid, Thiamine Hydrochloride, Pyridoxine Hydrochloride, Ascorbic Acid (Vit C), Potassium, Sodium, and magnesium.

When to use it: Poultry Pack is a broad spectrum multi-vitamin, mineral, and electrolyte supplement that is used to help ensure birds are receiving the necessary vitamins, minerals, and electrolytes for good health and performance. It can also be used when birds are under stress to help performance as well.

How to Mix: 1 pack per two gallons of water on a regular basis. Run 3 to 5 days continuously and repeat as necessary

#HW98400 Poultry Pack



Vitamin D3 & E Concentrate

Contains: Vitamin E (80,000 IU/lb), Vitamin D3 (16,000,000 IU/lb), polysorbate 80, potassium sorbate, n-propyl alcohol, propylene glycol, water, and polyethylene glycol monocleate. When use it: Vitamin D3 is an essential Vitamin for the absorption of Calcium which helps prevent numerous bone issues such as rickets. Vitamin E is an essential Vitamin to help support a healthy immune system.

How to Mix: Mix 2 ounces of Vitamin D3 & E per gallon of water in stock solution

#HED3Vitamin D3 & E Concentrate

Vitamin D3

Contains: Vitamin D3 (2,000,000 ICU/fluid ounce) When to use it: Use Vitamin D3 for thin egg shells in breeders, to reduce symptoms from mold and fungi, and to treat stiff, swollen joints, rickets, malformation of bones and soft beaks.

How to Mix: 1/2 ounce per gallon of stock solution for regular use and 1 ounce per gallon to treat more serious issues. Run for 5 to 10 days continuously and repeat if necessary.

#HW72700......Vitamin D3



Liquid Vitamin Starter

Contains: Vitamin A (125,000 IU), Vitamin D3 (58,75 IU), Folic Acid (1,725 MCG), Vitamin E (465 IU), Riboflavin (26MG), d-Pantothenic Acid (60MG), MSBC (135 MG), Thiamine (105 MG), Niacin (305 MG), Vitamin B12 (250 MCG), Biotin (1,560 MCG), Pyridoxine (105 MG) per Ounce of product.

When to use it: Liquid Starter Vitamin is a good well-rounded multivitamin to help ensure chicks get off to a good start by providing extra vitamins.

How to Mix: Mix 6 ounces of Liquid Starter Vitamins per gallon of stock solution. Run daily the first week of your flock.

#HWFP-BLLiquid Vitamin Starter



Dawelyte®

When to use it: Dawelyte® is a balanced electrolyte plus trace elements pack that is especially useful during heat stress or scours in poultry and livestock.

How to Mix: Mix 8 oz. with 128 gallons of drinking water and offer for 3 to 5 days.

#DL002 Dawelyte®



CocciAid®

9.6% oral solution for the treatment of coccidiosis in chickens, laying hens and turkeys. One gallon treats 800 gallons at a 0.012% level.

CocciAid is not an antibiotic and does not require a withdraw time to prevent residue in meat.

#091403 1 gallon bottle



Amprol

Amprol is for the treatment of coccidiosis in growing chickens, turkeys and laying hens. Follow the label exactly as instructed for hest results

#10601Soluble Powder per 10 oz. pack

Acidified Copper Sulfate

Contains: Copper Sulfate 86.5%, Sodium Bicarbonate, & Citric Acid.

When to use it: Copper Sulfate can be used as a water acidifier, as an aid to treat mouth lesions and it can also be used to reduce feed

How to Mix: Mix 1 pack per two gallons of stock solution.



#HW81600 Acidified Copper Sulfate

/IN-SOL

Vinegar (Acetic Acid)

Contains: Acetic Acid 8% (#HW72500) and 22% Concentrate (#HW72501 shown)

When to use it: Varies, but typically during feed changes and when loose or watery droppings are noticed. Vinegar serves as an astringent in tightening the gut and helps decrease the incidence of feed passage and healthier looking droppings. How to Mix: Varies, and depends on the severity of the

issue. It is best to start at a low dosage of around a pint to 4 gallons of water and work up from there, but monitor water consumption and if consumption decreases with an increase in mix concentration back down on mixture.



Vin-Sol

Contains: Mix of Sodium Acetate & Sodium Diacetate that makes Acetic Acid when mixed with water.

When to use it: Varies, but as with any other Acetic Acid product you can use it typically during feed changes and when loose or watery droppings are noticed. It serves as an astringent

in tightening the gut and helps decrease the incidence of feed passage and healthier looking droppings. Can also help non Dextrose based vitamins extend their half life in stock solution. Can also be used as a water line cleaner.

How to Mix: 1 heaping teaspoon with 1 gallon of water in stock solution run once daily. As a water line cleaner mix 4 scoops per gallon of stock solution and flush after.

#HW81900-12-5......Vin-Sol

Citric Acid

Contains: 100% Citric Acid

When to use it: Citric Acid is used to increase solubility in hard water conditions or when needed to help the solubility of some medications. It can also be used as a water acidifier and water line cleaner

How to Mix: When used to improve solubility, mix 1/2 pack to 1 pack per gallon of water in stock solution. When used to clean water lines, mix 3 to 4 packs per gallon of water in stock solution.

#HW83000



.Citric Acid

Line Cleaners

HydroLine 34

Hydroline 34 is a 34% peroxide-based cleaner ideal for cleaning water lines.

It can reduce and eliminate biofilm and bacteria buildup in your lines which can lead to bird health issues.

#SJC0002......1 gal jug

HydroLine 34

#37648.....

Proxy Clean

Contains: Buffered and Stabilized Hydrogen Peroxide 50% plus Silver Complex.

When to use it: Proxy Clean removes and prevents heavy soils and biofilms in drinking systems and is non corrosive. It should be left in the drinking system in between flocks for at least 12 hours for best results.

How to Mix: When used during flocks mix at no higher than 1.66 oz per gallon of stock solution. When used in between flocks, pump straight out of container directly in system and let sit for a minimum of 12 hours, and flush afterwards until water is flowing clean from flush points.


...Proxy Clean



CID 2000

Contains: Hydrogen Peroxide 20%; Acetic Acid 10%; Peracetic acid 5%

When to use it: A waterline cleaner that gives you the power of 02 and acidification combined. The H202 removes heavy soils and the peracetic acid removes scale/mineral build-up. It is equipment friendly and contains no heavy metals. Comes in a 2.6 gallon jug. Use as directed.



Siloxycide

Contains: Hydrogen Peroxide 5.00%; Silver 0.01% When to use it: Bactericide and Virucide* SILOXYCIDE DISINFECTANT is a patented combination of Hydrogen Peroxide plus Silver Nitrate, providing extended peroxide stability, along with previously unmatched efficacy, when compared to products containing only Hydrogen Peroxide

#061009......2.5 gal jug





Synergize

Contains: Alkyl dimethyl benzyl ammonium chloride 26.0% and

Glutaraldehyde 7.0%

When to use it: Formulated for industrial use in Animal Producing Facilities as well as the following equipment in these facilities: Waterers, Feeders, Hauling

Equipment, Loading Equipment, Farrowing Barns, Nurseries, Blocks, Creep Areas, and Chutes. Its unique formula penetrates and alters the structure of the cell membrane allowing itself to destroy the microorganism. Best when applied with low pressure sprayers. Contains some detergent additives and acts as a cleaner.

How to Mix: 1/2 ounce per gallon of water



Synergize Cool

Contains: Quaternay Ammonium 26.0%; Glutaraldehyde 7.00%

When to use it: Low-foaming version of Synergize™ Disinfectant. Recommended for use in cool cell systems, evaporative coolers, and other areas where low-foaming disinfecting and the control of mold, algae, and the spread of aerosol disease is a priority. Use as directed.

#24494.....Synergize Cool



Sani Kleen

Contains: Heavy Duty Quaternary Ammonium Chlorides When to use it: Sani Kleen is a heavy-duty disinfectant cleaner. It is useful on numerous gram positive and gram negative bacteria. It can also be used as a sanitizer and in shoe baths if cleaned daily.

How to Mix: 2 to 3 ounces per gallon of water for all general applications. Allow at least a 10-minute contact time before residue is removed.

#24792 Sani Kleen



BioCres™

Contains: Sodium hydroxide and Cresylic acid. Use the same When to use it as the Kleen Cres

How to Mix: Mix at 0.5% solution (1 gallon in 200 gallons of water) (2 ounces per 3 gallons of water) (5 mL/L).

#BIOCRES Cresvlic cleaner



Virkon® S

Contains: A balanced, stabilized blend of peroxygen compounds, surfactant, organic acids and an inorganic buffer system.

When to use it: Broad spectrum virucidal disinfectant for livestock disease prevention and control. Proven highly effective against 65 strains of virus in over 19 viral families, 400 strains of bacteria and over 100 strains of fungi including Avian Influenza (H5N1), Newcastle Disease, Classical Swine Fever (Hog Cholera) and Foot and Mouth Disease.

How to Mix: 1% is recommended for Poultry applications: 1.3 ounces of Virkon® S per gallon of water. If solution contacts metal surfaces or equipment, wash off residue with water after 10 minutes.

#361221......Virkon® S



Virocid Disinfectant

Contains: Alkyl dimethyl benzyl ammonium chloride 17.7%, didecyl dimethyl ammonium chloride 8.1%, glutaraldehyde 11.2%.

When to use it: A highly-concentrated and broad spectrum disinfectant effective against Viruses, Bacteria & Fungi.

How to Mix: To disinfect hard non-porous surfaces (livestock equipment, floors, walls, table tops, counter tops), apply a 0.25% (1:400 parts) solution to thoroughly wet surface. Spray the surface and let stand for 10 minutes. VIROCID is a concentrate that can be used with a mop, sprayers, sponge, or by soaking. Heavily soiled surfaces should be pre-cleaned prior to disinfection. All food contact surfaces must be thoroughly rinsed with potable water after disinfection.

#BV061 Virocid Disinfectant



Quad-A-Mone

Contains: Dimethyl benzyl ammonium chloride 10% and Dimethyl ethylbenzyl ammonium chloride 10% Usage: A 20% quad with a

powerful germicide action for use in poultry, and for general farm use. Fast acting. Effective in hard

#CVE51 1 Gal



Dyne O Might

Contains: Propionic Acid 25 - 50%; Polyoxyethylene-Polyoxypropylene Iodine Complex 0.42%; Phosphoric Acid 5 - 20% Why use it: Provides disinfection

in the presence of high organic matter, Litter pH adjustment, can inhibit dust and help control ammonia. Also proven efficacy against vegetative clostridium perfringens known to cause Gangrenous dermatitis.

#36730 5 G	al
#39832 1 G	lal



Universal **Barn Cleaner**

Contains: Foam Boosters and Chelating Agents When to use it: A general purpose cleaner and deodorizer.

How to use it: poultry, swine, farm animal housing mix at a rate of 1 part to 250 - 500 parts of water.

#D12568757.....Universal Barn Cleaner

Odor Control



4410506

1.75% Iodine

Use for sanitation of drinking water and general disinfection.

#SJC00011-gallon container

Barnstorm

Contains: Phosphoric Acid 10-35%: Dodecylbenzene Sulfonic Acid 5-35% When to use it: Heavy-duty,

concentrated cleaner and descaler. It has a unique blend of specially formulated acids and a high-foaming detergent designed to remove both organic and inorganic soils from surfaces prior to disinfection. The mixture penetrates through the "biofilm" left behind on walls, floors and crates.

#MS3595 Barnstorm



Odor Pro

Odor Eliminator is designed to remove odors from kennels, offices, vehicles use as a rinse additive in the washing machine. Anti-Bacterial Deodorizing Body Wash 1 Gallon. Designed to



Kenosan™

- · Unique formula based on new technologies
- · Sticky and long-lasting foam
- Extreme dirt penetrating capacity and excellent at breaking down Biofilms.
- · Very economical use at 1% concentration.
- Non corrosive
- · Contains Sodium Hydroxide and Ethanol
- · With Kenosan as part of your disinfection program your disinfectants used like Virocid will be more effective and able to penetrate the pathogens for eradication.

.....5.3 gal



Tek-Trol II Disinfectant is a synthetic detergent concentrate combined with high-powered 20.6% multiple chlorphenolic disinfectants. Dilution rate of 1 oz per gal of water.

#TEK-003-2 Gallon liquid



Tek-Trol Aerosol

A spot disinfectant for use on boots, clothing, vehicles and hand tools. Non-staining, quick drying and ideally suited for service personnel moving from location to location.

Cool Cell Treatments



Triple-C by Proxy Clean **Cool Cell Descaler**

Triple-C® is a proprietary blend of acids and surfactants designed to clean and remove scale and mineral buildup from cool cell pads. Why use it: Triple-C® provides a unique scrubbing action that effectively loosens and removes scale, mineral and heavy metal deposits from cool cell pads. How to Mix: Add 1 Qt to recirculation tank

#PCP05 1 quart



POWDER DESCAL

Cool-N-Klean Descaler

Contains: Surfactants and organic acids.

When to use it: Cool-N-Klean is a replacement for Agua Max. It is a cleaner and descaler for water lines and cool cell pad systems.

How to Mix: Apply Cool-N-Klean per manufacturer's recommendations which are listed on the product jug depending on the type of application.



DeVere Powder Descaler

Contains: Citric acid, a buffer and quaternary ammonium chloride

Why use it: When used according to directions, this product will remove all types of mineral scale without harming evaporative cooling pads. This product also decreases the need to clean headers and nozzles that can become plugged with minerals.

How to mix: Add product to reservoir tank to make 0.5% (by weight) solution (4 lbs. per 100 gals of water).

#MPD8 8 lb **#MPD100**......100 lb



FASTKLEEN

Use: To remove calcium or mineral deposits on cool cell pads.

How to Use: How to use: Dilute 1/2 oz with one gallon of water. Circulate through system for one hour. Flush with fresh water. For startup, shut pump off. Saturate pads with one gallon of Fast Kleen mixed with 25 gallons of water. Rinse pads with water.

#FASTKLEEN 1 gallon



SCI-62 Algaecide


Contains: Copper Sulfate/ Sulfuric Acid mix How to use: To control the growth of algae, add 1 to 2 ounces of SCI-62® to the storage tank at the start of the season and 1 to 2 ounces once per week during periods of use and after flushing the sump

#59129......1 gallon











Southland Organics strengthens natural defenses to grow resilient birds and businesses.

Mother Load

Mother Load is raw, unfiltered liquid apple cider vinegar infused with garlic. It is designed to boost your birds' overall health, aid in digestion, keep the GI tract healthy, tighten gut and provide bacteria that support poultry development. Apply 1/2 gallon per 5 gallon of water in medicator bucket set at 1:128.



Big ole Bird

Big ole Bird is a powerhouse of probiotics, organic acids and biologically active carbon to strengthen your birds' natural defense system from within. BoB decreases mortality, improves weight gain, feed conversion, gut health and resistance to pathogens and disease. Apply 4 oz. liquid per 1 gallon of stock solution for a medicator pump set at 1:128.



#B0B0P2-5......2.5 gal. container

Catalyst

Catalyst Poultry Vitamin is a highly absorbable powder packed with specially formulated, poultry-specific vitamins and minerals that maximize performance when used with Big ole Bird. It helps promote leg and bone development, heart, skin and blood health. Apply 100 CC (two scoops) to 5 gallons of stock solution for a medicator pump at set 1:128.



#CATALYSTPAIL32 oz. pail

Desecticide

Desecticide uses breakthrough technology to kill resistant darkling beetles, lesser mealworms, bed bugs. mites, fleas and ticks on poultry without the use of toxic chemicals. It is proven effective and safe to use, even when birds are present. Bugs do not build resistance, and it can be used at any point during grow out. No applicator license needed, so spray it yourself and save time. Apply 1 gallon with 10 gallons of water per 5,000 square feet.



#DESECT...... 1 gal. container

Hen Helper

Hen Helper improves overall health. fertility and nutrition in layer hens. According to studies, probiotics and organic acids work together to increase egg production, egg weight and quality in laying hens. Hen Helper also tightens the gut, which produces cleaner eggs, less feed passage and firmer shells through improved calcium and vitamin absorption. Apply 4 oz. liquid per 1 gallon of stock solution for a medicator pump set at 1:128.

#HH-2-5.....2.5 gal. container

Litter Life

Litter Life is designed to improve litter quality and strengthen poultry health. A mixture of biologically active carbon, organic acids and beneficial microbes helps dry and condition litter, defend against harmful bacteria and control ammonia. Birds grow in a healthier environment with less threat of disease, lower mortality and better performance. Apply one gallon of Litter Life with nine gallons of water per 2,000 square feet.



Cool Cell Treatments

FortiCool A UR | FortiCool D

PREVENTION IS PROTECTION

Choose Forticool Products

- Continuous 24/7 protection
- Improve cooling efficiency and pad life
- · Simple application
- · Will not damage cell pads
- For optimal performance, replace every 30 days



FortiCool A

Time released water treatment for evaporative cooling pads to prevent buildup of algae and fungi. Replace every

#21132291FortiCool A



A MORE EFFECTIVE WAY TO CLEAN AND PROTECT SURFACES.

SWASH™ is a carefully formulated liquid that boosts sanitation levels in poultry and swine houses. SWASH™ alters dust, soil and waste's ability to build up on surfaces, while inhibiting the formation of organic films. The product increases sanitation levels and cuts required cleaning time by up to 50 percent, leaving you with more time for other aspects of animal care.

* Swash products are not disinfectants nor are they being marketed as disinfectants

SWASH DUST-REPEL™

SWASHDUST-REPEL™ is soil releasing, non-acidic, and non-corrosive product that is applied to plastic, fiberglass, or galvanized steel fans, cowlings, shutters, louvers, and light traps to reduce the buildup of dust and organic matter. Treating with Swash reduces wash time and improves cleaning and disinfectant effectiveness.

#SWASH......3.5 gal.

SWASH HOUSE™

SWASHHOUSE™ can also serve as a sanitation tool for swine facilities. Fecal matter leftover after the cleaning process poses a serious health risk to piglets. Applying SWASH for Swine™ between groups ensures a cleaner, safer environment for pigs.

#SWASHH5.....5 gal.

FortiCool D-scaler

Time released water treatment for evaporative cooling pads to prevent buildup of scale and mineral deposits. Replace every 30 days.

#21132292 FortiCool D-scaler

SWASHCOOL-CELL™

SWASHCOOL-CELL™ balances the systems pH level, keeps minerals soluble, and disperses dirt and dust so as to not stick on the pads. It treats algae, mineral buildup, scaling and iron.

#SWASHCOOLCELL55 gal.

SWASH EQUIPMENTTM

For use on tractors, trucks, cars, mowers, combines and more. SWASHEQUIPMENT™ can be applied to all surfaces after cleaning your vehicles or equipment and is safe to apply on all painted surfaces and glass. No drying or rinsing required





Auger, Flexible6

A	
Acme	186
Actuators, Vent	159, 218
Aerotech	
Controls	158
Curtain Machine	
Fans 175-176	6, 181-182
Agitator Pump	149
Agri-Alert	162
Agrivent	
Air Inlets	
AirStorm	165-168
Alarm Systems	
Aluminum Sorting Panels	291
Ammonia Detectors	
Anchor, Bearing	
Anchor, Bolt	
Anchor, Plastic Flooring	102
AP	
Chain Disk System	
Controls	
Curtain Machine	
Fans	
Heaters	
Aqua Bowl	
AquaChief.	
AT Newell	
000	

Auger, Rigid	35
В	
Baffle, Sidewall	
Bait Stations	317-318
BarnTalk	
Barngard Doors	
Batten Strips	266
Battery, Alarm	162
Bayer	313
Bell Drinker	115,119
Belting, Egg	
Big Dutchman, Chain Feeders.	
Big Dutchman, Pan Feeders	
Big Foot Heaters	
Bin Flag	33
BinStik	34
BinTrac	
Biosecurity Products	
Blitz Stunner	
Boar Feeder	
Bolt-on-legs	
Bolts	
Booster Pumps	
Boots	
Boot Covers	
Boot Scrapers	299

Box Fans	189
Brace, Peck Board	306
Breeder House Replacement F	arts71-73
Brooders	
Brooder Curtain	210
Brooder Guard	307
Bubble Pack Insulation	263
Buckets, Rubber	299
Burch Coolers	74
Burn-Easy Incinerators	297
С	
Cable Adjusters	19
Cable & Clamps	
Carcass Carts	. 289-290
Carts, Feed	
Cast Iron T-bolts	102
Castration Mate	301
Catch Hooks	308
Cannonball	6
Caulk	267
Ceiling Inlets	196, 199
Chain	268
Charger, Shock Line	309
Chase Gates	77
Chemilizer	
Chick Starter	49
Chicken Reaper	304

Chimneys, Ventilation		Extended Anchor Bearing	9	Nests	
Chore Cart		F		PolyStorm	
Chore-Time, Curtain Machi				Sow Drop	
Chore-Time, Pan Feeders		Fans	10.4	Sprinkler System	
Circulation Fans		Belts		Windstorm	170-172
Cleaners, Line		Circulation		GroLocs	259
Compost Temp Probe		Motor		TT T	
Concrete Repair Products		Paddle		H-I	
Contact-O-Max	80-82	Shutters	190	H2PAD	203
Control Pans (Poultry)		Farrowing		Halo	28
GrowerSELECT		Crates		Hair Nets	
Cumberland		Feeders		Handi-Foam	
Roxell		Flooring		Hardware	
Coolair		Water Cups, Aqua Bowl		Heat Lamps & Bulbs	
Cool Cell		Feather Feeder	307	-	
Cool Cell Pumps		Feed		Heat Mats	
Cord Adjusters		Bins		Hercules Arm	
Cord Sets		Carts	36-37	High Pressure Spray Syst	ems 135-136
Coveralls	300	Creep		Hired Hand	
Creep Feeders		Feed Line, Poultry	18-19	Alarm	_
Creep Mats	259	Fill Systems	3-9	Controls	155
Cumberland		Motors	10-11	Curtain Machine	22
Chain Feeders	57	Scoops	36	Curt-O-Matic	218
Drinkers	110	Tube, Poultry	41	Fans	183
Fans		Paper & Trays, Poultry		Heaters	
Nests		Feeders, Swine		Hog Snare	
Pan Feeders		Feedfas		Hog Panel	
Turkey Feeders		Float Valves		_	
Cup Hook & Driver		Fluorescent Bulbs		Hood, Fan Transition	
Cup Waterers, Swine		Flush Systems		Hot Shot	
Curtains		Fly Bait		Humidifer	
Drops		Foggers Portable		Incinerators	297-298
Hardware		Fogger Systems		Inlets, Air	196-199
Machine		Free Access Stall		Insecticides	312-315
Cut & Weld Panels		FRP Panels		Insulation, Spray Foam	264
cut & Weld Fallels	99		200	7.7	
D		G		J-L	
Dimmer, Light	272_276	G-Logic Control Pan	1/1	Jake's Wire Tigheters	309
Disinfectants		Gasolec		JanAire	
Disinfectant Mat		Gate Rods		J-Bolts	
Doors & Hardware		Gator		Jitterball	
			140	Kestrel Wind Meters	
Dosatron		Gestation	22		
Drinker Hose		Drop Feeders		Kwik Start	
Drinker Systems, Poultry		Feed Trough		Lag Bolts	
Drop Rods		Stalls & Stanchions		Latches, Door	262
DuraDrive		Globe, Lights		LB White	
DynoFan	187	Gloves, Disposable		Furnaces	232-239
E		Grills, Trough		Brooders	242-244
		Gorilla Tape		Tube Heaters	254
Ear Plugs	300	GroBelts		LED Lights	274-27
Egg		Gro40 Brooder		Light for Control Pan	
Basket		GroTube	252	Linear Vent Actuator	
Belts		GrowerSELECT®		Link Belt	
Coolers		AirStorm		Lipatech	
Cleaning Brush	72	Classic Flood Pan Feeders	12-17	-	
Sanding Bands		Curtain Machine		Litter Treatments	
Scoop		Feed Systems	3-9	Loading Chutes	
Electric Heaters		Feed Line, Poultry		Load Out Door Guard	
Electrical Supplies		Grow-Disk Feed System		Lubing Drinkers	
	_	<i>y</i> -	_		014
EuroValve	130	Kwik Start Chick Feeders.	49	Lubricants	310

M-N		Pulley Alignment Kit	195	Switches, Electrical	
	200	Pumps		Switch Covers	
Manure Treatments		Agitator	149	Syringes	302
Masks, Face		Booster		T-U	
Mats, Rubber		Cool Cell			
Maximus		PVC Fencing		Tachometer	
Medicators		PVC Fittings	132	Tags, Premise & Visual	
Metal Repair Products		R		T-Bolts	
Micro Switches				TEGO Tunnel Doors	
MicroZone		Rat Bait		Tempshield	
Migration Fence		Relay, Electrical	281	Thermalarm	
MixRite		Ridge Vents		Thermometer, Hi-Lo	
Motomco	319	Rigid Auger Systems	35	Thermometer, InfraRed	
Motors	10 11	RIO Nipple, Swine		Thermostat	
Auger		Rooster Pan Feeders	48	Timers	
Egg Table		Rotem, Controls	151-153	Toggle, Switches	
Fan		Rotem, Dimmer	273	Tong Stik	
Multifan, Controls		Round Feeders, Swine	106	TriDEK	
Multifan, Fans		Roxell, Fill Systems	40	Tri-Ply	
Nedap		Roxell, Feed Pans	45-46	Trusscore panels	
Nests		Q		Tube Heaters	
Nest Pads		S		Turkey, Feeders	
Nipple Bar	120	Scale System Feed Bins, P	oultry 52	Turkey, Drinkers	
Nutritional Supplements,		Scraper System	294	Tunnel Doors	
Poultry	321-322	Sensaphone Alarm		Turnbuckles	
P-Q		Sensor Wire		Turbogrow Poultry Feeders.	
1 -Q		Sharp Shock Prods	293	U-Bolts	268
Paddle Sticks		Shenandoah Brooders		V-W	
Penning Equipment, Swine	99	_	247-248	V-W	200 272
	99	Shenandoah Brooders	247-248 62	Vanberg Coatings	
Penning Equipment, Swine	99	Shenandoah Brooders Shenandoah Nests	247-248 62 309	Vanberg Coatings V-Belts	194
Penning Equipment, Swine Photoletic Control Pit Fan	99 228	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger	247-248 	Vanberg Coatings V-Belts VCS Curtain Systems	194 217
Penning Equipment, Swine Photoletic Control Pit Fan Plugs	99 228 192 130	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan	247-248 62 309 190 197-198	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls	194 217 151-161
Penning Equipment, Swine Photoletic Control Pit Fan	99 228 192 130	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets	247-248 	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Ventilation Fans	194 217 151-161 165-191
Penning Equipment, Swine Photoletic Control Pit Fan Plugs	99 228 192 130 191	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Ca	247-248 	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Ventilation Fans Venturi Proportioner Valve	194 151-161 165-191 149
Penning Equipment, Swine Photoletic Control Pit Fan Plugs Pump Out Covers	99 192 130 191	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Ca		Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Ventilation Fans Venturi Proportioner Valve VFD Fan Control	194 151-161 165-191 149
Penning Equipment, Swine Photoletic Control Pit Fan Plugs Pump Out Covers Transitions	99 192 130 191 191 296	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Caslats, Poultry Smoke Sticks Soaker Systems	247-248 	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve	194 151-161 165-191 149 172
Penning Equipment, Swine Photoletic Control Pit Fan Plugs Pump Out Covers Transitions Treatments	99192130191191296307	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Caslats, Poultry Smoke Sticks	247-248 	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Ventilation Fans Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests	194 151-161 165-191 149 130 63-68
Penning Equipment, Swine Photoletic Control Pit Fan Plugs Pump Out Covers Transitions Treatments Plastic Feed Trays	9919213019119129630769	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Caslats, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters	247-248 	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests	194 151-161 165-191 149 130 63-68
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Castata, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve	247-248 62 309 190 197-198 attle91-93 69 311 127 278 255	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water	194 151-161 165-191 149 172 130 63-68
Penning Equipment, Swine Photoletic Control Pit Fan	991921301911912963076995-96	Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Caslats, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve Sort Panels	247-248 62 309 190 197-198 attle91-93 69 311 127 278 278 255 130	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets	194 151-161 165-191 149 130 63-68 101
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Castata, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve	247-248 62 309 190 197-198 attle91-93 69 	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters	
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Castata, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve Sort Panels Sow Drop SowMAX	247-248 62 309 190 197-198 attle91-93 69 311 127 278 255 130 291 23	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Hose	194 151-161 165-191 149 130 63-68 101 121 133-134
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders		Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Hose Meters & Regulators	
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Caslats, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve Sort Panels Sow Drop SowMAX Speed Controls Ventilation Sprayers		Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Water Brackets Filters Hose Meters & Regulators Nipples, Poultry	
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Castata, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve Sort Panels Sow Drop SowMAX Speed Controls Ventilation Sprayers Spray Markers	247-248 	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Filters Hose Meters & Regulators Nipples, Poultry Nipples, Swine	
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Caslats, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve Sort Panels Sow Drop SowMAX Speed Controls Ventilation Sprayers Spray Markers Stanchions	247-248 62 309 190 197-198 attle91-93 69 311 127 278 255 130 291 23 89 1160 299 302	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Hose Meters & Regulators Nipples, Poultry Nipples, Swine Treatments	
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Caslats, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve Sort Panels Sow Drop SowMAX Speed Controls Ventilation Sprayers Spray Markers Stanchions Starbar		Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Hose Meters & Regulators Nipples, Poultry Nipples, Swine Treatments WayPig Scales	
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Castata, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve Sort Panels Sow Drop SowMAX Speed Controls Ventilation Sprayers Spray Markers Stanchions Starbar Stenner		Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Hose Meters & Regulators Nipples, Poultry Nipples, Swine Treatments WayPig Scales Wedge Anchors	
Penning Equipment, Swine Photoletic Control Pit Fan		Shenandoah Brooders Shenandoah Nests Shocker, Line Charger Shutters, Fan Sidewall Inlets Slat, Concrete, Swine & Caslats, Poultry Smoke Sticks Soaker Systems Sockets, Light Solaria Heaters Solenoid Valve Sort Panels Sow Drop SowMAX Speed Controls Ventilation Sprayers Spray Markers Stanchions Starbar Stenner Stir Fans	247-248	Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Hose Meters & Regulators Nipples, Poultry Nipples, Swine Treatments WayPig Scales Wedge Anchors Wet/Dry Feeders, Swine	
Penning Equipment, Swine Photoletic Control		Shenandoah Brooders		Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Hose Meters & Regulators Nipples, Poultry Nipples, Swine Treatments WayPig Scales Wet/Dry Feeders, Swine Winches	
Penning Equipment, Swine Photoletic Control		Shenandoah Brooders		Vanberg Coatings V-Belts	
Penning Equipment, Swine Photoletic Control		Shenandoah Brooders		Vanberg Coatings V-Belts VCS Curtain Systems Ventilation Controls Venturi Proportioner Valve VFD Fan Control Volumetric water valve Wadeken Nests Wall Brackets Water Brackets Filters Hose Meters & Regulators Nipples, Poultry Nipples, Swine Treatments WayPig Scales Wet/Dry Feeders, Swine Winches	

Equipment Service Department

Hog Slat staffs skilled service technicians at certain store locations throughout the United States. Covering the regions around their assigned stores, Hog Slat service techs are available to repair or replace damaged equipment in your hog and poultry barns. Our service techs have years of experience servicing and maintaining all types and brands of production swine and poultry equipment. Request a service call or schedule a maintenance visit to your farm using the guide below.





Service Area	Store Location	Service Tech	Contact Phone Number
Alabama	Holly Pond	Justin McComb	(256) 796-6507
Alabama	Spruce Pine	Greg Lee	(256) 331-2817
Arkansas/E. Oklahoma	Spiro, OK	Lao Xiong	(479) 561-2930
Arkansas	Clarksville	James Prosser	(470) 238-2590
Arkansas/Missouri	Hindsville, AR	Keith Obenshain	(479) 789-4001
Arkansas/Missouri	Wheaton, MO	Bryan McCool	(417) 389-6373
Arkansas/Missouri	Berryville, AR	Mike Youngblood	(870) 350-6318
Arkansas/Missouri	After Hours & Weekend Service	•	(479) 789-4001
Delaware	Laurel	Eugene Hudson	(302) 875-0886
Delaware	Laurel	Jim Briddes	(302) 875-0886
Delaware	Laurel	Robert Short	(302) 875-0886
Delaware	Laurel	Harold Smith	(302) 875-0886
Delaware	Laurel	Lewis Hawley	(302) 875-0886
Georgia - North	Royston		(706) 245-6486
Tennessee - South	Calhoun, GA	Zach Stafford	(706) 624-4244
Georgia - Northeast	Royston	Cody Legg	(919) 581-7077
Georgia (Central)	Roberta	Michael Clay	(800) 856-6106
Tennessee and NW Georgia	Calhoun, GA	Bart Crawford	(706) 624-4244
Indiana	Flora	Rod Moudy	(574) 835-7019
Indiana	Flora	Cory Chilcutt	(765) 505-0419
Indiana	Flora	David Jeffery	(910) 379-6193
Iowa	Algona	Chris Richardson	(515) 341-3180
Iowa	Algona	Dave Samp	(515) 570-9895
Iowa	Algona	Jeff Spencer	(515) 571-8833
Iowa	Bloomfield	Derek Crow	(641) 799-0411
Iowa	Hartley	Chad LeClair	(712) 344-0525
Iowa	Iowa Falls	Clay Hoversten	(515) 368-3359
Iowa	Iowa Falls	Justin Jaenke	(515) 368-3359
Iowa	Iowa Falls	Mark Hargrave	(515) 368-3359
Iowa	Sioux Center	Dave VanDonkelaar	(712) 737-7081
Iowa - Southeast	Storm Lake After Hours & Weekend Service	Dennis Tramell	(712) 449-5521 (641) 208-7028
Kentucky	Mayfield Mayfield	Jamie McKinney	(641) 208-7028 (270) 804-7375
Louisiana	Dubach	Jamie McKinney Jeremy Lay	(318) 478-0281
Maryland	Pocomoke	Chad Grizzle	(410) 957-6800
Minnesota	Pipestone/ Redwood Falls	Todd Henrich	(507) 438-5989
Minnesota	Sauk Centre	Todd Stordahl	(320) 777-9477
Mississippi	Forest	Jowl Gonzales	(601) 469-4165
Mississippi	Forest	Jason Bagley	(601) 469-4165
Mississippi	Philadelphia	Trace Thrash	(601) 504-4719
North Carolina	Beulaville	Wayne Knowles	(910) 594-0413
North Carolina	Bethel/Goldsboro	Bill Effler	(910) 594-0413
North Carolina	Biscoe/Siler City	Tim Sheffield	(910) 594-0413
North Carolina	Clinton	Matt Phillips	(910) 594-0413
North Carolina	Clinton	Brian Hargrove	(910) 594-0413
North Carolina	Elizabethtown	Nathan Hester	(910) 594-0413
North Carolina	Goldsboro	Jeremy Lancaster	(910) 594-0413
North Carolina	Newton Grove	Mark Rose	(910) 594-0413
North Carolina	Newton Grove	William Bryan	(910) 594-0413
North Carolina	Rose Hill	Gregory Knowles	(910) 594-0413
North Carolina	Taylorsville/Yadkinville	Richard Deal	(910) 594-0413
North Carolina	After Hours & Weekend Service		(910) 509-2229
South Carolina	Hartsville	Nathan Hester	(910) 594-0413
Tennessee - Central	Shelbyville	Marvin Betts	(931) 703-2038
Texas	Marquez	Jeremy Hart	(903) 512-1341
Virginia	Bridgewater	Brent Foster	(540) 879-9901
Virginia	Bridgewater	Cory Guyer	(540) 879-9901
Virginia	Bridgewater	Tracy Horn	(540) 879-9901
Virginia	Harrisonburg	Chad Custer	(540) 879-9901
Virginia	Harrisonburg	Andrew Huffman	(540) 879-9901
West Virginia	Moorefield	David Naylor	(304)-538-2346







MIDWEST SWINE

30
22
69
36
30
13
14
52
34
61
79
98
93
81
51
20
59
32
)3

MIDWEST POULTRY

Arkansas - Missouri - Iowa - Minnesota - Nebraska - Oklahoma - Wisconsin				
Matt Holdeman	Midwest Sales Manager	515-890-4028		
Colby Elliott	IA, MN & WI	641-220-1220		
Dean Sowers	Sauk Center, MN	320-527-3298		
Chad Buhl	Nebraska	402-276-6453		
Bobby Cox	Spiro, OK	479-629-6983		
Mike Sears	AR/MO Regional Manager	479-435-4255		
Matt Goforth	Siloam Springs, AR	417-238-2229		
Monte Rhodes	MO, Cage-Free Layer Equipment.	660-620-0541		

EGG LAYER

Dane Schipper	Midwest Sales Manager	641-426-6849
Dave Nicks	Midwest US	712-540-9327
Aaron Moystner	OH, MI & IN	260-251-2390

EASTERN SHORE POULTRY

Jim Karsnitz	Regional Sales Manager	410-251-1687
Spencer Hill	Delaware/Maryland	302-258-8457
Adam Mariner	Maryland/Virginia	302-604-2050

SHENANDOAH AG SUPPLY

Sebastian Fannan	. VA	601-265-8209
Andrew Robyak	. WV/VA	717-756-2730

Sales Contacts for New Construction and Remodeling

Worry-Free, Hassle-Free Construction. Completed start to finish from the experts in building better farms!

NORTH CAROLINA SWINE

Fritz Richards	National Sales Manager	910-590-6366
Kenny Bass	North Carolina	910-590-9523
Michael Thornton	North Carolina	910-596-1212
Shelton Johnson	North Carolina	910-590-9025
Pat Usher	North Carolina	910-990-1413
Frankie Warren	North Carolina	. 919-738-0124

NORTH CAROLINA POULTRY

Vann Pierce	Regional Sales Manager	252-287-5002
Nick Best	Goldsboro, NC	910-750-6865
Chancey Walker	Beulaville, NC	910-590-6411
Robert Herman	Taylorsville, NC	828-302-5950
Jacob Caviness	Siler City, NC	910-571-9435
Chuck Sutton	NC/SC/DE/MD/VA Sales Manager	252-370-0807
Bryan Price	NC/SC	843-253-6146

SOUTHEAST POULTRY

Georgia - Tennessee - Alabama - Arkansas

Doug Scroggs	Sales Manager	706-244 5428	
Jacob Williams	Calhoun, GA	706-988-4416	
Madison Williams	Roberta, GA	919-920-7084	
Timmy Gee	Royston, GA	706-498-0950	
Paul Butcher	Shelbyville, TN	931-993-2305	
Daniel Welborn	Holly Pond, AL	256-460-9504	
Ricky Bryan	Ft. Smith, AR	479-222-4662	
Matt Goforth	Siloam Springs, AR	417-238-2229	
Mississippi - Louisiana - Texas			
Patrick Harrison	Sales Manager	601-443-1688	
Ricky Holmes	Forest, MS	601-507-0759	
Derin Bonner	Summit, MS	601-248-0200	
Wayne Jones	Texas	903-717-4642	
Western Kentucky - Tennessee			

Tyson Nightingale......Mayfield, KY......270-970-9835 INTERNATIONAL SALES

Jeff Smith	International	Swine,	Se Habla	Español	910-214-9569	9
Eric Soza	.International	Swine,	Se Habla	Español	910-305-3386	ડે
Gregg Jackson	International	Poultry			336-406-2348	2

CANADA - MITCHELL, ONTARIO

Jeff Earl	.Inside Sales	519-348-9483
Steve Poppe	.Swine	.519-301-7308

ORDERING INFORMATION

Monday-Friday 8:00am to 5:00pm C.S.T. • Fax your order 24 hours a day, 7 days a week. Hog Slat Midwest FAX @ 515-332-3126 • Hog Slat S. E. • FAX @ 910-594-0010 • Georgia Poultry FAX @ 706-245-0496.

Orders placed before 1:00pm will be shipped the same day. Please have item number ready when ordering. Shipping charges will be calculated based on the weight of your order and the distance it must travel.



METHODS OF PAYMENT

- Visa, MasterCard, Discover/Novus and John Deere Financial
- ullet C.O.D's are available by UPS with an additional charge of \$10.00 per package
- Pre-Payment Please call for freight cost
- Items too large for UPS will be shipped by motor freight
- Next-day and second-day air deliveries available at an additional charge
- · Freight charges are the customer's responsibility
- · Report any damaged merchandise to UPS upon delivery

- Due to manufacturer's updating prices, products and specifications, prices are subject to change without notice
- Some items in this circular may require some assembly or installation, which
 is available at an additional cost at your nearest Hog Slat parts and service
 department.
- · Items are subject to availability
- We reserve the right to limit quantities and correct printing errors.

These items were selected in advance based on warehouse availability. In the event we are out of any particular item, every item can be ordered for you at the advertised price unless specifically noted otherwise. RETURN POLICY: Please call for authorization to return merchandise. All items must be returned within 30 days from the date of purchase. Items must be returned in clean and saleable condition. Special order items are not returnable. All returns are subject to a restocking fee.



Swine Parts & Products Questions (866) 464-7528

Swine Parts & Products Questions (800) 949-4647

Equipment & Products Questions (866) 850-4446

ALABAMA	Hartley, IA877-728-2105
Chancellor, AL855-513-9919	Humboldt, IA800-294-4014
Holly Pond, AL 855-675-0505	Independence, IA319-332-1400
Ider, AL 888-394-7458	Iowa Falls, IA877-648-3560
Ozark, AL334-443-0240	Le Mars, IA 855-573-9366
Petrey, AL334-335-2294	Marcus, IA 888-376-2558
Spruce Pine, AL	Monticello, IA866-465-9100
ARKANSAS	Rock Rapids, IA888-472-4229
Berryville, AR 855-929-6283	Sac City, IA Coming Soon
Clarksville, AR877-206-9804	Sibley, IA Coming Soon
Hindsville, AR877-717-2031	Sioux Center, IA800-598-4187
Mansfield, AR479-269-2047	Storm Lake, IA866-697-1891
Siloam Springs, AR877-373-6655	Washington, IA866-368-7124
DELAWARE	KANSAS
Harrington, DE844-816-0589	Seneca, KS
Laurel, DE844-816-0590	KENTUCKY
FLORIDA	Mayfield, KY833-228-0438
Live Oak, FL866-416-8369	LOUISIANA
GEORGIA	Dubach, LA 318-777-1212
Bowdon, GA877-405-2867	MARYLAND
Calhoun, GA 866-667-8159	Pocomoke City, MD 844-816-0591
Douglas, GA 866-416-8371	MICHIGAN
Ellijay, GA866-417-1427	Three Rivers, MI269-273-7277
Glennville, GA866-417-1428	MINNESOTA
Lexington, GA866-417-1377	Blooming Prairie, MN866-705-1655
Lula, GA770-869-1113	Fairmont, MN
Moultrie, GA 866-697-4614	Mankato, MN 855-588-8733
Roberta, GA800-856-6106	Pipestone, MN877-562-4203
Royston, GA 866-850-4446	Redwood Falls, MN 866-929-1350
ILLINOIS	Sauk Centre, MN 844-388-7620
Newton, IL618-783-2200	Waseca, MN 507-835-8015
Pittsfield, IL 877-385-4144	Worthington, MN507-376-2200
Rochelle, IL866-285-7017	MISSOURI
INDIANA	Wheaton/Exeter,M0417-652-3080
Flora, IN866-960-3776	MISSISSIPPI
IOWA	Bay Springs, MS 866-568-7985
Algona, IA 888-838-6489	Brookhaven, MS 888-354-0398
Bloomfield, IA	Forest, MS 844-777-6761
Carroll, IA877-792-0590	Kokomo, MS601-731-3003
Charles City, IA 855-228-2700	Magee, MS 866-795-0604
Decatur City, IA 888-446-3940	Philadelphia, MS855-230-6306

Hartley, IA	877-728-2105
Humboldt, IA	800-294-4014
Independence, IA	
Iowa Falls, IA	877-648-3560
Le Mars, IA	855-573-9366
Marcus, IA	
Monticello, IA	
Rock Rapids, IA	
Sac City, IA	
Sibley, IA	Coming Soon
Sioux Center, IA	800-598-4187
Storm Lake, IA	
Washington, IA	
KANSAS	
Seneca, KS	785-336-0082
KENTUCKY	
Mayfield, KY	833-228-0438
LOUISIANA	
Dubach, LA	318-777-1212
MARYLAND	
Pocomoke City, MD	844-816-0591
MICHIGAN	
Three Rivers, MI	269-273-7277
MINNESOTA	
Blooming Prairie, MN	866-705-1655
Fairmont, MN	866-461-4448
Mankato, MN	855-588-8733
Pipestone, MN	
Redwood Falls, MN	
Sauk Centre, MN	
Waseca, MN	507-835-8015
Worthington, MN	507-376-2200
MISSOURI	
Wheaton/Exeter,MO	417-652-3080
MISSISSIPPI	
Bay Springs, MS	866-568-7985
Brookhaven, MS	888-354-0398
Forest, MS	844-777-6761
Kokomo, MS	601-731-3003
Magee, MS	866-795-0604

Waynesboro, MS	855-230-6307
NEBRASKA	
Richland, NE	402-563-4533
Columbus, NE	402-563-4533
NORTH CAROLINA	
Aulander, NC	866-901-0092
Bethel, NC	855-271-7781
Beulaville, NC	866-569-2741
Biscoe, NC	877-710-0288
Clinton, NC	866-831-9169
Elizabethtown, NC	
Goldsboro, NC	800-722-0646
Laurinburg, NC	910-405-7515
Newton Grove, NC	
Rose Hill, NC	800-779-4657
Siler City, NC	800-854-3425
Taylorsville, NC	844-594-7241
Yadkinville, NC	844-528-3518
OHIO	
Union City, OH	866-968-3895
OKLAHOMA	
Guymon, OK	877-732-7677
Spiro, OK	918-962-8036
SOUTH CAROLINA	
Hartsville, SC	844-677-2555
SOUTH DAKOTA	
Mitchell, SD	844-831-0457
TENNESSEE	
Shelbyville, TN	866-693-2175
TEXAS	
Marquez, TX	903-529-1175
Nacogdoches, TX	936-569-8770
Pittsburg, TX	844-320-5511
UTAH	
Beaver, UT	435-438-4055
VIRGINIA	
Bridgewater, VA	540-879-9901
Harrisonburg, VA	540-434-4423
WEST VIRGINIA	
Moorefield, WV	304-538-2346
HOG SLAT CANADA Mitchell, ON	
Mitchell, ON	519-348-8483









HOG SLAT, INC. PO Box 300 Newton Grove, NC 28366 IA: 866.464.7528

NC: 800.949.4647 GA: 866.850.4446

PARA ESPAÑOL LLAMENOS: 866-364-7528

VISIT US ONLINE @ HOGSLAT.COM



Codes inside to view

Use your phone's camera to scan QR product videos.



